

# **Engineered Polymer (EP) Branch Multi-port Tee**

Submittal Information Revision F: Feb 1, 2016

## **Project Information**

Job Name:

Location:	Part No. Ordered:
Engineer:	Date Submitted:
Contractor:	Submitted By:
Manufacturer's Representative:	Approved By:

#### **Technical Data**

Material of multi-port tee: Polysulfone GF120

Material of mounting clip: Chevron Phillips Marlex 9018 High-

density Polyethylene (HDPE), black

Material of screw: Black phosphate carbon steel

Maximum temperature (no pressure): 320°F (160°C)

Max. working temperature/pressure: 210°F at 150 psi (99°C at 10.3 bar)

Max. Multi-port Tee Flow for 34" Inlet: 13.2 gpm at 12 fps

8.8 gpm at 8 fps

Max. Multi-port Tee Flow for 1" Inlet: 21.8 gpm at 12 fps

14.5 gpm at 8 fps

## **Product Information and Application Use**

Engineered Polymer (EP) Branch Multi-port Tees feature an integrated ¾" or 1" ProPEX® inlet with 1/2" ProPEX branch outlets.1 Designed for commercial plumbing applications, they eliminate the need for multiple connections. These multi-port tees all come with EP Mounting Clips (F7051250) with Phillips self-tapping screws.



✓ Description	Part Number	Length	Height	Width	Weight
34" EP Branch Multi-port Tee, 7 outlets with mounting clips	Q2277550	8.66"	2.10"	1.77"	0.327 lbs.
¾" EP Branch Multi-port Tee, 8 outlets with mounting clips	Q2287550	9.50"	2.10"	1.77"	0.362 lbs.
1" EP Branch Multi-port Tee, 7 outlets with mounting clips	Q2271051	8.90"	2.10"	1.77"	0.330 lbs.
1" EP Branch Multi-port Tee, 8 outlets with mounting clips	Q2281051	9.80"	2.10"	1.77"	0.365 lbs.
1" EP Branch Multi-port Tee, 10 outlets with mounting clips	Q2101051	11.60"	2.10"	1.77"	0.437 lbs.
1" EP Branch Multi-port Tee, 12 outlets with mounting clips	Q2121051	13.40"	2.10"	1.77"	0.505 lbs.

## Installation

These multi-port tees feature mounting clips with self-tapping screws, which are appropriate for wood or metal studs. Simply attach the clips to the multi-port tee and fasten the clips to the mounting surface.

### Accessories

F7051250: EP Mounting Clip, 34" to 1"

#### Standards

CAN/CSA B137.5; ASTM F877; ASTM F1960

## Codes

IPC; UPC; NSPC; NPC of Canada

ANSI/NSF 14- and 61-certified; ICC ESR 1099; IAPMO 3946, cQAIus P321

#### **Related Applications Contact Information**

PEX-a Plumbing Systems Uponor, Inc. 5925 148th Street West Apple Valley, MN 55124 USA Phone: 800.321.4739

Fax: 952.891.2008 www.uponorpro.com Uponor Ltd.

2000 Argentia Rd., Plaza 1, Ste. 200 Mississauga, ON L5N 1W1 CANADA Phone: 888.994.7726

Fax: 800.638.9517 www.uponorpro.com

¹ProPEX® is a registered trademark of Uponor, Inc. ProPEX™ is a trademark of Uponor Ltd.