



# T&B®

## Liquidtight Flexible Metal Conduit Fittings T&B Catalog Number:

**UPC Number:** 5249  
78621005249  
**Status:** Active  
**Description:**

3 in. 45 degree malleable iron liquidtight connector

### Features

Ability to install quickly with low torque effort

### Application

Used where flexible metal raceway is installed in outdoor or indoor locations where exposed to continuous or intermittent moisture.

To positively bond conduit to box or enclosure.

### General

Trade Size (inches)	3
Material	Malleable Iron
Finish	Electro Zinc Plated/Chromate Coating

### Dimension Information

Dimension A (inches)	4 1/2
Dimension B (inches)	4 1/4
Dimension C (inches)	1

### Specifications

3dmodel Available on Website

### Accessories & Components

Wiremesh Grips for Liquidtight Fittings WMG-LT9

### Packaging

Package in Units	1
T&B Sold in UOM	Each
T&B Weight Per UOM	780 lbs. per 100

### Certifications

RoHS Compliance Yes

### Certifications



File Nbr:  
E 23018

**For further technical assistance, please contact us...**

Thomas & Betts - USA  
8155 T&B Blvd.  
Memphis, TN 38125  
www.tnb.com

T&B Technical Support  
MS 3B-50  
8155 T&B Blvd.  
Memphis, TN 38125

Hours: 7AM - 6PM CDT  
Monday-Friday  
Phone: (888) 862-3289  
Fax: (901) 252-1321  
Email:techsupport@tnb.com