



Blackburn[®]

Aluminum Lug T&B Catalog Number:

UPC Number: Status: Description: AL12 78378604728 Active

Aluminum Two-Hole Lug - Straight Long Barrel, Wire Range 4/0 ASCR, 4/0 Str., 1/2 Inch Bolt Size, Blind-End, Mechanical Dies: 840, K840, 845, TX, Hydraulic Dies: 840, B49EA, EEI, 11A, K840, 249, 76, CSA 24 **Features**

	Complete die and crimp information clearly indent-
	ed on each lug. Install with standard tools and dies.
	NEMA standard mounting holes. Use 1/2 inch
	mounting hardware for all sizes.
	Prefilled with oxide inhibitor.
	Extended barrel for additional crimping area or
	weather-seal for outdoor terminators.
General	
Style	AL
Material	Aluminum
Conductor Range - ASCR	4/0
Conductor Range - Stranded	4/0
Dimension Information	
Length (inches)	6 5/8
Width (inches)	1 1/4
T (inches)	9/32
Diameter Min. (inches)	0.522
Diameter Max. (inches)	0.563
Tooling	
Hydraulic Dies	840, B49EA, EEI, 11A, K840, 249, 76, CSA 24
Mechanical Dies	840, K840, 845, TX
Packaging	040, 1040, 043, 17
lackaging	
T&B Inner Pack	25
Package in Units	150
T&B Sold in UOM	Each
T&B Weight Per UOM	24.7 lbs. per 100
Notes	
	Hole Spacing 1 3/4 inches.
	Available tin-plated (add suffix P to catalog num-
	ber).
Certifications	
RoHS Compliance	Yes
· ·	

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com



Email:techsupport@tnb.com