



Rigid Conduit/IMC Fittings

Locknuts — Steel/Zinc Plated




| CAT. NO. | CONDUIT SIZE (IN.) | DIMENSIONS (IN.) | | STD. CTN. |
|-----------|--------------------|------------------|-------|-----------|
| | | A | B | |
| LN-100-SC | ¾ | — | — | 1,000 |
| LN-101-SC | ½ | .125 | 1.140 | 1,000 |
| LN-102 | ¾ | .140 | 1.420 | 1,000 |
| LN-103 | 1 | .170 | 1.770 | 500 |
| LN-104 | 1¼ | .170 | 2.281 | 200 |
| LN-105 | 1½ | .170 | 2.598 | 100 |
| LN-106 | 2 | .187 | 3.175 | 50 |
| LN-107 | 2½ | .375 | 3.562 | 30 |
| LN-108 | 3 | .375 | 4.250 | 25 |
| LN-109 | 3½ | .438 | 4.803 | 25 |
| LN-110 | 4 | .438 | 5.402 | 25 |
| LN-111 | 5 | .500 | 6.674 | 10 |
| LN-112 | 6 | .561 | 7.934 | 10 |

Sealing Locknuts — Steel/Zinc Plated



| CAT. NO. | CONDUIT SIZE (IN.) | DIMENSIONS (IN.) | | STD. CTN. |
|----------|--------------------|------------------|----------|-----------|
| | | A (MIN.) | B (MAX.) | |
| LS 101 | ½ | .26 | 1.12 | 1,000 |
| LS-102 | ¾ | .27 | 1.37 | 1,000 |
| LS-103 | 1 | .28 | 1.75 | 500 |
| LS-104 | 1¼ | .32 | 2.06 | 200 |
| LS-105 | 1½ | .32 | 2.37 | 100 |
| LS-106 | 2 | .32 | 2.87 | 50 |
| LS-107 | 2½ | .32 | 3.43 | 50 |
| LS-108 | 3 | .32 | 4.12 | 50 |
| LS-109 | 3½ | .32 | 4.62 | 50 |
| LS-110 | 4 | .32 | 5.18 | 25 |

Locknuts — Non-Metallic




| CAT. NO. | TRADE SIZE (IN.) | A DIA. (IN.) | B THD. (IN.) | STD. CTN. |
|----------|------------------|--------------|--------------|-----------|
| LN-501 | ½ | 1.3 | ½-14 | 100 |
| LN-502 | ¾ | 1.4 | ¾-14 | 100 |
| LN-503 | 1 | 1.7 | 1-11½ | 50 |

Material: Nylon 6/6.

Color: Gray.


Locknuts Die-Cast Zinc



| CAT. NO. | CONDUIT SIZE (IN.) | DIMENSIONS (IN.) | | STD. CTN. |
|----------|--------------------|------------------|-------|-----------|
| | | A | B | |
| LN-201 | ½ | .125 | 1.140 | 2,000 |
| LN-202 | ¾ | .140 | 1.420 | 1,000 |
| LN-203 | 1 | .170 | 1.770 | 1,000 |
| LN-204 | 1¼ | .170 | 2.281 | 500 |
| LN-205 | 1½ | .170 | 2.598 | 500 |
| LN-206 | 2 | .187 | 3.175 | 200 |
| LN-207 | 2½ | .375 | 3.562 | 100 |
| LN-208 | 3 | .375 | 4.250 | 100 |
| LN-209 | 3½ | .438 | 4.803 | 40 |
| LN-210 | 4 | .438 | 5.402 | 40 |


CSA File No. LR-12798.

Grounding Locknuts — Malleable Iron/Zinc Plated



| CAT. NO. | CONDUIT SIZE (IN.) | DIMENSIONS (IN.) | | STD. CTN. |
|----------|--------------------|------------------|----------|-----------|
| | | A (MIN.) | B (MAX.) | |
| LG-401 | ½ | .125 | 1.140 | 100 |
| LG-402 | ¾ | .140 | 1.420 | 100 |
| LG-403 | 1 | .170 | 1.770 | 50 |
| LG-404 | 1¼ | .170 | 2.281 | 50 |
| LG-405 | 1½ | .170 | 2.598 | 50 |
| LG-406 | 2 | .187 | 3.175 | 25 |
| LG-407 | 2½ | .375 | 3.562 | 10 |
| LG-408 | 3 | .375 | 4.250 | 10 |
| LG-409 | 3½ | .438 | 4.803 | 50 |
| LG 410 | 4 | .438 | 5.402 | 5 |

Thin Construction Locknuts — Steel/Zinc Plated



| CAT. NO. | CONDUIT SIZE (IN.) | UNIT QTY | STD. CTN. |
|----------|--------------------|----------|-----------|
| SPLN-107 | 2½ | 30 | 30 |
| SPLN-108 | 3 | 25 | 25 |
| SPLN-109 | 3½ | 25 | 25 |
| SPLN-110 | 4 | 25 | 25 |