



Liquidtight Flexible Cord & Cable Fittings
T&B Catalog Number:

UPC Number: 2922NM
Status: 78621079742
Description: Active

Liquidtight Strain Relief Connector, Straight, 1/2 Inch NPT Thread, Cable Range 0.500 Inch/12.7mm to 0.750 Inch/19.0mm, IP65 Rating, UV Resistant Polyamide 6.6 Body, Black

Features

- Extended range with superior strain relief.
- Reduced overall size, fits into tighter spaces.
- Gland nut designed to restrict cable bending.

Application

- Provide a means for passing a cord cable into an enclosure through a bulkhead
- Suitable for Ordinary, Wet or Dry locations.

General

Material: Nylon
Cord and Cable Types: S, SO, SV, ST, STD, SJ, SJO, SJT, SJTO, SVD

Dimension Information

Hub Size (inches): 1/2
Dimension A (inches): 1 13/32
Dimension B (inches): 2 5/32
Dimension C (inches): 5/8
Cord Range (inches): .500-.750
Throat Diameter (inches): 0.55

Specifications

3dmodel: Available on Website

Packaging

T&B Inner Pack: 25
Package in Units: 100
T&B Sold in UOM: Each
T&B Weight Per UOM: 5.5 lbs. per 100

Application Support

T&B Instruction Sheets: ta00927-tb2
Product Overview: Available on Website
Specifications: Available on Website
Portable Cord Selection Table: Available on Website

Certifications

RoHS Compliance: Yes

Certifications



File Nbr:
E 13938

For further technical assistance, please contact us...

Thomas & Betts - USA
8155 T&B Blvd.
Memphis, TN 38125
www.tnb.com

T&B Technical Support
MS 3B-50
8155 T&B Blvd.
Memphis, TN 38125

Hours: 7AM - 6PM CDT
Monday-Friday
Phone: (888) 862-3289
Fax: (901) 252-1321
Email: techsupport@tnb.com