



P-122SC



Product Description

Single gang electrical box for use with nonmetallic sheathed cable

Brand: flexBOX®
Catalog #: P-122SC

Carton Quantity: 24
Carton Weight: 9 lb.

Height: 3-3/4 in.
Width: 2-9/32 (5-1/2) in.
Depth: 1-3/4 in.
Volume: 23.5 cu. in.
Type of Installation: New Work
Wall Box
Number of Gangs: 1

UPC: 085339249146
UNSPSC: 39121309
Patents:
U.S. Patent No. 8,143,518
Country of Origin: United States of America

FEATURES

Molded-in splined device holes, offset gauge marks, leveling ribs, cover and pocket for additional cubic inch fill in shallow walls

APPLICATION

New work residential construction 2 HR fire resistive walls (shallow 1" x 2") & ceilings

STANDARDS

ANSI / UL 514C: File No. E30594



FIRE CLASSIFICATION

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 24 inches

Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes must be 4-½ feet from one another

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)

COLOR

Black

ADDITIONAL MATERIALS

Carbon steel fasteners

MATERIAL

Polyvinyl Chloride

MOUNTING

Angled mid nails with two optional bottom mount recessed buttons