

**NEW**

# Smart Cap™



## Closet Bolt Cover Cap and Base

Patent Pending



442-2W



440-2W

- Taller cap eliminates the need to cut brass bolts
- Cap screws onto base for a secure connection
- Base creates a tight seal that helps create a sanitary seal between cap base and china
- Can be installed on new and existing toilets
- Can be used with both 1/4" and 5/16" bolts, maximum length 2 1/2"
- Boss on base prevents spinning during installation or removal




Never cut brass bolts again. Bolts that are cut may become too short to reuse if additional flooring is added.



Base is installed between the bowl and nut.



Cap screws onto base for a secure connection.



Item No.	Description	Min. Qty.	Case Qty.	List Price
	BULK			
440-2W	Cover cap and base, white with 425-PB closet bolts, 2/bag	1	25	2.83 EA
442-2W	Cover cap and base, white, 2/bag	1	25	1.90 EA



Supply • Drainage • Support • Testing • Specialties • Tools • Access



# Sioux Chief Toilet Specialties

## Raise-A-Ring™ Flange Extension Ring



886-R

Build up existing flange when added subfloor, tile, etc. leaves flange at or below floor level. Ring is 7/16" thick, can be stacked if needed.

## Ringer™ Stainless Steel Ring



886-MR

Fits securely over damaged flanges. Perfect for repairs to damaged closet flanges, or new concrete floor installations.

## Plumb Perfect™ Closet Bolt



Dome Nut  
420



Combination nut and cap. Appliance white. Cannot be knocked off.



Open Nut  
425



For use with bolt caps. Fits 1/2" sockets.



## Wedge-It™ Multi-Purpose Stability Wedge



Scored for easy separation when needed.



Stiff polypro  
460-10



Soft PVC  
460-20



Ideal for leveling unsteady closet bowls.

For more information on these toilet specialties see our catalog.

DISTRIBUTED BY

tel: 1-800-821-3944  
fax: 1-800-758-5950  
www.siouxchief.com  
P.O. Box 397  
24110 South Peculiar Drive  
Peculiar, Missouri 64078 USA

**Sioux  
Chief**   
MANUFACTURING SINCE 1957