Snapbloc® Power Distribution Blocks
Modular Design - Dual Rated

RoHS Compliant

UL LISTED 45U4

TYPE
LDAU
LDBU

Features
- Modular design
- Easy to assemble
- UL listed 90˚ C 600 Volts
- Electro-tin plated 6061-T6 aluminum alloy
- Multiple conductor capability

Benefits
- Simplifies stocking. Combines any number of blocks with multiple conductor ranges into the specific configuration required for the job.
- Unique locking feature allows individual blocks to be combined quickly without special tools
- Ensures reliability
- Suitable for use with both copper and aluminum conductors in any combination
- Individual blocks supplied in a variety of configurations with one or two main cable ports and four, six, or twelve taps. All are range taking.

C

Fig. 1

Fig. 2

Catalog Number	Figure Number	Connector		Primary			Secondary			Ampere
		Primary	Secondary	Wire Range	Openings Per Pole	Hex Size	Wire Range	Openings Per Pole	Hex Size	Rating Per Pole
LDBU-112-350 LDAU-112-350	1 2			350kcmil-6 350kcmil-6	1 1	3/8	4-14 4-14	12 12	Slot	310 310
LDBU-112A-350 LDAU-112A-350	1 2			350kcmil-6 350kcmil-6	1 1	3/8	4-14 4-14	12 12	Slot	310 310
LDBU-16-350 LDAU-16-350	1 2			350kcmil-6 350kcmil-6	1 1	3/8	2/0-14 2/0-14	6 6	3/16	310 310
LDBU-16-500 LDAU-16-500	1 2			500kcmil-4 500kcmil-4	1 1	3/8	2/0-14 2/0-14	6 6	3/16	380 380
LDBU-26-350 LDAU-26-350	1 2			350kcmil-6 350kcmil-6	2 2	3/8	2/0-14 2/0-14	6 6	3/16	620 620
LDBU-212-4/0 LDAU-212-4/0	1 2			4/0-6 4/0-6	2 2	1/4	4-14 4-14	12 12	Slot	460 460
LDBU-212-500 LDAU-212-500	1 2			500kcmil-4 500kcmil-4	2 2	3/8	4-14 4-14	12 12	Slot	760 760
LDBU-26-500 LDAU-26-500	1 2			500kcmil-4 500kcmil-4	2 2	3/8	2/0-14 2/0-14	6 6	3/16	760 760
LDBU-24-500 LDAU-24-500	1 2			500kcmil-4 500kcmil-4	2 2	3/8	4/0-6 4/0-6	4 4	5/16	760 760
LDBU-11-500 LDAU-11-500	1 2			500kcmil-4 500kcmil-4	1 1	3/8	500kcmil-4 500kcmil-4	1 1	3/8	380 380
LDBU-22-350 LDAU-22-350	1 2			350kcmil-6 350kcmil-6	2 2	3/8	350kcmil-6 350kcmil-6	2 2	3/8	620 620
LDBU-22-500 LDAU-22-500	1 2			500kcmil-4 500kcmil-4	2 2	3/8	500kcmil-4 500kcmil-4	2 2	3/8	760 760

Side Panel can be ordered separately Cat. No. LDS-1

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Tested to UL 1953, UL File E112158







Dimensions

A	B	C	D=Dia.	E	F	G	H	J = Cover	K	L	M	N
3	5-1/2	3-7/16	.28 Slot	1-1/2	5/16	4-7/8	1/4	1/2	4.75	2.69	.38	1.50

4730 Madison Road, Cincinnati OH 45227-1426 | PH: 513.533.6200 | FAX: 513.871.4084 | www.ilsco.com
In Canada: 1050 Lakeshore Road East, Mississauga, Ontario, Canada L5E 1E4 | PH: 905.274.2341 | FAX: 905.274.8763

Snapbloc® Power Distribution Blocks

Modular Design - Dual Rated

RoHS Compliant

LISTED 45U4

TYPE
LDAU
LDBU

Features
- Modular design
- Easy to assemble
- UL listed 90˚ C 600 Volts
- Electro-tin plated 6061-T6 aluminum alloy
- Multiple conductor capability

Benefits
- Simplifies stocking. Combines any number of blocks with multiple conductor ranges into the specific configuration required for the job.
- Unique locking feature allows individual blocks to be combined quickly without special tools
- Ensures reliability
- Suitable for use with both copper and aluminum conductors in any combination
- Individual blocks supplied in a variety of configurations with one or two main cable ports and four, six, or twelve taps. All are range taking.

Fig. 1

Fig. 2

Catalog Number	Figure Number	Connector		Primary			Secondary			Ampere
		Primary	Secondary	Wire Range	Openings Per Pole	Hex Size	Wire Range	Openings Per Pole	Hex Size	Rating Per Pole
LDBU-112-350 LDAU-112-350	1 2			350kcmil-6 350kcmil-6	1 1	3/8	4-14 4-14	12 12	Slot	310 310
LDBU-112A-350 LDAU-112A-350	1 2			350kcmil-6 350kcmil-6	1 1	3/8	4-14 4-14	12 12	Slot	310 310
LDBU-16-350 LDAU-16-350	1 2			350kcmil-6 350kcmil-6	1 1	3/8	2/0-14 2/0-14	6 6	3/16	310 310
LDBU-16-500 LDAU-16-500	1 2			500kcmil-4 500kcmil-4	1 1	3/8	2/0-14 2/0-14	6 6	3/16	380 380
LDBU-26-350 LDAU-26-350	1 2			350kcmil-6 350kcmil-6	2 2	3/8	2/0-14 2/0-14	6 6	3/16	620 620
LDBU-212-4/0 LDAU-212-4/0	1 2			4/0-6 4/0-6	2 2	1/4	4-14 4-14	12 12	Slot	460 460
LDBU-212-500 LDAU-212-500	1 2			500kcmil-4 500kcmil-4	2 2	3/8	4-14 4-14	12 12	Slot	760 760
LDBU-26-500 LDAU-26-500	1 2			500kcmil-4 500kcmil-4	2 2	3/8	2/0-14 2/0-14	6 6	3/16	760 760
LDBU-24-500 LDAU-24-500	1 2			500kcmil-4 500kcmil-4	2 2	3/8	4/0-6 4/0-6	4 4	5/16	760 760
LDBU-11-500 LDAU-11-500	1 2			500kcmil-4 500kcmil-4	1 1	3/8	500kcmil-4 500kcmil-4	1 1	3/8	380 380
LDBU-22-350 LDAU-22-350	1 2			350kcmil-6 350kcmil-6	2 2	3/8	350kcmil-6 350kcmil-6	2 2	3/8	620 620
LDBU-22-500 LDAU-22-500	1 2			500kcmil-4 500kcmil-4	2 2	3/8	500kcmil-4 500kcmil-4	2 2	3/8	760 760

Side Panel can be ordered separately Cat. No. LDS-1

All wire sizes, unless noted otherwise, are American Wire Gauge (AWG)

Tested to UL 1953, UL File E112158







Dimensions

A	B	C	D=Dia.	E	F	G	H	J = Cover	K	L	M	N
3	5-1/2	3-7/16	.28 Slot	1-1/2	5/16	4-7/8	1/4	1/2	4.75	2.69	.38	1.50

F