

90° SNAP²IT[®] Cable Connectors

FLEX • AC • MC



38900ST



38900AST



40900ST



40900AST

Zinc die-cast. For AC, MC, HCF, MC Continuous corrugated aluminum cable, MCI-A cables (steel and aluminum), MC-PCS cable, AC90 and ACG90.

FEATURES AND BENEFITS

- Widest total cable ranges—accommodates cables from 14/2 to 10/3
- Widest variety of cables
- Super-secure installation—No pullout!
- Easy screwdriver removal from box; connector is reusable
- Fully assembled and ready to use

| CATALOG NUMBER | UPC/DCI/NAED MFG #018997 | TRADE SIZE | KO SIZE | UNIT PKG | STD PKG | DIM A | DIM B | DIM C | DIM D | CABLE RANGE |
|----------------|--------------------------|------------|---------|----------|---------|-------|-------|-------|-------|-------------|
| 38900ST | 04098 | 1/2 | 3/8 | 25 | 250 | 2.496 | 1.739 | .854 | 1.000 | .405 - .610 |
| 38900AST* | 04093 | 1/2 | 1/2 | 25 | 250 | 2.496 | 1.819 | .854 | 1.000 | .405 - .610 |
| 40900ST | 04099 | 3/4 | 3/4 | 25 | 250 | 2.496 | 1.739 | .854 | 1.000 | .405 - .610 |
| 40900AST* | 04092 | 1 | 1 | 25 | 250 | 2.496 | 1.819 | .854 | 1.000 | .405 - .610 |

*Insulated Throat.

Red-tinted inside.

Refer to chart on page E-29 for a list of cable types.

See page E-30 and E-31 for MCI-A cable ranges.

PATENT PENDING.

Easy, snap-in insertion;
Saves 1 minute
per connector
compared to 2-screw
connector

