Wall Light 64 Watt LED

Glare Free

Emergency Back-Up


480V Driver

		WLD64LED			
Design is Protect	ed by U.S. Patent No. 9,482,395	Lumens: 6,966 Lumens per Watt: 111 CCT: 4500K	WATTS: CRI: 83 DIMMING		
Ordering Information	on		Options		
CATALOG #	DESCRIPTION	VOLTS	ADD SUFFIX #	DESCRIPTION	
WLD64LED		120-277	PC	120V Photocontrol	
WLD04LED	64W LED Wall Light	120-277	PM	208-277V Photocontrol	

Performance

- 95% Efficient Reflector Targets the Light
- Eliminates Glare & Offensive Light
- Less Wasted Light
- More Footcandles on the Ground
- Creates a Smooth & Uniform Light Pattern


Dimensions and Specifications



Recommended Mounting Height - 18-20 ft.

EB 4

Note: Atlas uses only premium LED compatible photocontrols



FOOTCANDLES ON THE GROUND									
Mtg.	90°			45°		Avg. FCs			
Hgt.	5'	10'	15'	5'	10'	15'	450 SQ. FT.		
18'	9.6	5.8	4.2	9.5	6.1	3.6	6.5		
20'	6.8	4.8	3.4	6.6	5.2	3.4	5.0		



*The majority of Atlas Lighting Products are assembled in USA facilities by an American Workforce utilizing both Domestic and Foreign components