



## UL LQT FLEX METAL CONDUIT



IMAGE UNAVAILABLE

### FEATURES & BENEFITS

- UL BONDED STRIP 3/8" - 1-1/4" FOR GROUNDING
- UL LIQUIDTIGHT ALL SIZES; SUNLIGHT RESISTANT
- FLAME RETARDENT PVC JACKET - GREY
- HOT DIPPED ZINC GALVANIZED LOW CARBON STEEL CORE
- 80 DEG C TO -30 DEG DRY
- 60 DEG C WET; 70 DEG OIL RESISTANT




IMAGE UNAVAILABLE

### SPECIFICATIONS

Cat. Number	Trade Size	Shelf Qty.	Master Qty.
620130	3/8"	0	100
620160	3/8"	0	1000
620230	1/2"	0	100
620245	1/2"	0	500
620260	1/2"	0	1000
620330	3/4"	0	100
620345	3/4"	0	500
620360	3/4"	0	1000
620430	1"	0	100
620441	1"	0	400
620524	1-1/4"	0	50
620540	1-1/4"	0	200
620624	1-1/2"	0	50
620724	2"	0	50



620730	2"	0	100
620822	2-1/2"	0	25
620922	3"	0	25
622022	3-1/2"	0	25
621022	4"	0	25