

MICROLITER[®] SERIES

Cat.#

Job

Type



HUBBELL
Outdoor Lighting

Approvals

APPLICATIONS

- Signs, facades, small area illumination, flag poles and landscape accent

SPECIFICATIONS

- Die cast aluminum housing is rugged, yet lightweight and compact in size
- The die cast aluminum door hinges and is removable for service. Two Hubbell Gard[®] screw fasteners secure the lens door to a silicone gasket for positive seal
- 1/2" cast aluminum knuckle provides universal aiming (1/2 x 14 NPS)
- Rotatable optics. Medium base lamp included
- HPS offered in 120V NPF or Multitap HPF, PSMH is HPF Multitap
- Bronze Lektrocote[®] powder paint finish

LISTINGS

- Listed to UL1598 for use in wet locations


LISTINGS



PRODUCT IMAGE(S)



DIMENSIONS



| A | B | C | D | E | F |
|---------------------------------|---------------------------------|---------------------------------|---------------------------------|----------------------------------|---------------------------------|
| 4 ⁷ / ₈ " | 2 ¹ / ₂ " | 9 ¹ / ₄ " | 7 ³ / ₈ " | 12 ¹ / ₈ " | 9 ¹ / ₄ " |
| 124 mm | 64 mm | 235 mm | 187 mm | 308 mm | 235 mm |

ORDERING INFORMATION

| Catalog Number ¹ | Wattage | Photometry NEMA/IES H° x V° | Lamp Type | Voltage | Weight lbs. (kg) | EPA ft ² (m ²) | Ballast Type ² |
|--|--------------|-----------------------------------|-----------|-----------------|---------------------|--|---------------------------|
| Normal Power Factor, High Pressure Sodium | | | | | | | |
| MIC-0070S-651 | 70 | 5 (90°) x 6 (102°) | Coated | 120 NPF | 9 (4.1) | 0.71 (0.1) | RX |
| High Power Factor, High Pressure Sodium | | | | | | | |
| MIC-0150S-258³ | 150 | 5 (71°) x 3 (34°) | Clear | 120/208/240/277 | 14 (6.4) | 0.71 (0.1) | AL |
| High Power Factor, Pulse Start Metal Halide | | | | | | | |
| MIC-0070H-358³ | 70 | 5 (81°) x 4 (60°) | Clear | 120/208/240/277 | 11 (5) | 0.71 (0.1) | AL |
| MIC-0150P-338³ | 150 | 3 (32°) x 3 (36°) | Clear | 120/208/240/277 | 14 (6.4) | 0.71 (0.1) | PLA |
| MIC-0150P-358³ | 150 | 6 (103°) x 5 (81°) | Clear | 120/208/240/277 | 14 (6.4) | 0.71 (0.1) | PLA |
| Less Ballast - Medium Base Socket | | | | | | | |
| MIC-XXXXX-XXX | Less Ballast | Varies | 150 max | None | 6 (2.7) | 0.71 (0.1) | None |

¹ Lamp included

² Ballasts are Class H, -40°F starting (HPS), -20°F starting (PSMH)

³ Quad-Tap[®] luminaires are shipped wired for 277V, easily changed to other voltages in the field


ACCESSORIES - Order Separately

| Catalog Number | Description |
|---------------------------|--|
| MIC-GS-2 | Glare shield (360°) bronze |
| MIC-SPC-2 | Polycarbonate shield assembly |
| S-302-M51 | Pole-top slipfitter for 1/2" knuckle, slipfits 2 3/8" OD pipe, bronze finish |
| PBT-1 | Photocontrol, button type, 120V |
| TRN-XX¹ | Trunnion adaptor for 1/2" threaded knuckle mount |


¹ Specify color, eg. DB - Dark Bronze

REPLACEMENT PARTS

| Catalog Number | Description |
|----------------------|---------------------------|
| 264-0292-9903 | Lens |
| 800-2827-0100 | Bronze lens/door assembly |
| 207-5011-0264 | Bronze knuckle |



MIC-GS-2



MIC-SPC-2



S-302-M51



PBT-1



TRN-XX




HUBBELL
Outdoor Lighting

Hubbell Outdoor Lighting • 701 Millennium Boulevard • Greenville, SC 29607 • Phone: 864-678-1000


Due to our continued efforts to improve our products, product specifications are subject to change without notice.

© 2015 HUBBELL OUTDOOR LIGHTING, All Rights Reserved • For more information visit our website: www.hubbelloutdoor.com • Printed in USA

MIC-SPEC 8/16



**MICROLITER
MIC-0100H-32X
NARROW BEAM**



**MICROLITER
MIC-0100H-35X
MEDIUM BEAM**

PHOTOMETRIC REPORTS

| Catalog Number | Report # |
|----------------|--------------|
| MIC-0175H-35X | HP04770S.IES |
| MIC-0175H-33X | HP04771S.IES |
| MIC-0070H-35X | HP04774S.IES |
| MIC-0070H-32X | HP04775S.IES |
| MIC-0150S-25X | HP04910S.IES |



HUBBELL
Outdoor Lighting

Hubbell Outdoor Lighting • 701 Millennium Boulevard • Greenville, SC 29607 • Phone: 864-678-1000

Due to our continued efforts to improve our products, product specifications are subject to change without notice.

© 2015 HUBBELL OUTDOOR LIGHTING, All Rights Reserved • For more information visit our website: www.hubbelloutdoor.com • Printed in USA

MIC-SPEC 8/16