
CONVERSION KIT FLANGE KIT

## PRODUCT HIGHLIGHTS

- · Allows for mounting grid troffer into plaster and drywall ceilings
- Flange frame made of extruded aluminum with mitered corners
- Eliminates the need to special order flange troffers

**CONSTRUCTION** - Flange kit constructed of extruded aluminum. Corner brackets and angle inserts constructed of heavy gauge, galvanized steel.


**FINISH** - All metal parts treated after fabrication with rust-resistant, phosphatized solution. Finish coating of reflector surfaces is white, high reflectance polyester powder. Minimum reflectance factor of 92%.



## INSTALLATION INSTRUCTIONS

## FLANGE KITS (FK)


- 1. Cut opening according to chart below.
- 2. Slide corner brackets and angle inserts into side and end rails. Snap assembly together.
- Place flange kit assembly into ceiling opening. Thread wire through corner holes in side rails of kit and attach to ceiling structure. Secure kit assembly up against ceiling.
- 4. Lay grid troffer into flange kit assembly.
- Specify "MOR" Middle Of Run or "EOR" End Of Run for continuos row mounting. Example: FK14MOR



SEE TABLE FOR CUTOUT SIZE

## WALL WASH FLANGE KITS (FKNWW)

- 1. Cut opening according to chart below.
- 2. Slide corner brackets and angle inserts into side and end rails. Snap assembly together.
- 3. Place flange kit assembly into ceiling opening. Thread wire through corner holes in side rails of kit and attach to ceiling structure. Secure kit assembly up against ceiling.
- 4. Lay grid troffer into flange kit assembly.



| Single Fixture | e Flange Kits         |                      |                       |                      |
|----------------|-----------------------|----------------------|-----------------------|----------------------|
| Catalog No.    | Nominal Size          | Cutout Opening       | Outside Flange Dim's. | Maximum Fixture Size |
| FK-12          | 12 x 24               | 12 3/8" x 24 1/2"    | 13 3/8" x 25 1/2"     | 11 3/4" x 23 13/16"  |
| FK-14          | 12 x 48               | 12 3/8" x 48 1/2"    | 13 3/8" x 49 1/2"     | 11 3/4" x 47 13/16"  |
| FK-22          | 24 x 24               | 24 3/8" x 24 1/2"    | 25 3/8" x 25 1/2"     | 23 3/4" x 23 13/16"  |
| FK-24          | 24 x 48               | 24 3/8" x 48 1/2'    | 25 3/8" x 49 1/2"     | 23 3/4" x 47 13/16"  |
| FK-14 CR1      | 12 x 48 CR1           | 12 5/16" x 48 3/8"   | 13 5/16" x 49 3/8"    | 11 3/4" x 47 13/16"  |
| FK-22 CR1      | 24 x 24 CR1           | 24 5/16" x 24 3/8"   | 25 5/16" x 25 3/8"    | 23 3/4" x 23 13/16"  |
| FK-24 CR1      | 24 x 48 CR1           | 24 5/16" x 48 3/4"   | 25 5/16" x 49 3/8"    | 23 3/4" x 47 13/16"  |
| FK-22 CR2      | 24 x 24 CR2           | 23 3/4" x 23 3/4"    | 24 13/16" x 24 13/16" | 23 3/16" x 23 3/16"  |
| FK-24 CR2      | 24 x 48 CR2           | 23 3/4" x 47 3/4"    | 24 13/16" x 48 13/16" | 23 3/16" x 47 3/16"  |
| FK-MWW4        | 6 x 48 29/32 Metric   | 6 1/2" x 47 7/8"     | 7 9/16" x 48 15/16"   | 5 15/16" x 47 5/16"  |
| K-22 METRIC    | 24 x 24 Metric        | 23 15/16" x 24 1/16" | 25" x 25 7/16"        | 23 3/8" x 23 1/4"    |
| K-24 METRIC    | 24 x 48 Metric        | 24 1/16" x 47 7/8"   | 25 1/8" x 48 15/16"   | 23 1/2" x 47 5/16"   |
| FKMWW2         | 6 x 24 Micro Wallwash | 6 1/2" x 24 1/2"     | 7 9/16" x 25 1/2"     | 5 15/16" x 23 13/16" |
| FKMWW3         | 6 x 36 Micro Wallwash | 6 1/2" x 36 1/2"     | 7 9/16" x 37 1/2"     | 5 15/16" x 35 13/16" |
| FKMWW4         | 6 x 48 Micro Wallwash | 6 1/2" x 48 1/2"     | 7 9/16" x 49 1/2"     | 5 15/16" x 47 13/16" |
| FKNWW-12       | 12 x 24 Wallwash      | 10 1/8" x 23 13/16"  | 11 7/16" x 25 3/8"    | 9 3/4" x 23 7/16"    |
| FKNWW-14       | 12 x 48 Wallwash      | 10 1/8" x 47 13/16"  | 11 7/16" x 49 3/8"    | 9 3/4" x 47 7/16"    |



| Project Name | Fixture Type |  |
|--------------|--------------|--|
|              |              |  |