

FEATURES & SPECIFICATIONS

Embossed polarity line to indicate correct insertion position and electrical connection.

Rigid steel backplate provides maximum reinforcement between track connectors and track sections. (Excludes LTA2, LTA3.)

All components are available in white (WH) and black (DBL) finish. (Exceptions noted below.)

Commercial Track accessories, pendant accessories, and T-bar accessories are available.

Commercial Track accessories and connectors compatible with Lithonia Commercial (LT) single or (LT2) double-circuit track system. Also compatible with Nordic Aluminum Global Trac® (GES and GET) systems.

One-year limited warranty. Complete warranty terms located at:

www.acuitybrands.com/CustomerResources/Terms_and_conditions.aspx.

Note: Actual performance may differ as a result of end-user environment and application. Specifications subject to change without notice.

Catalog
Number







Notes







Type







Commercial Track - Connectors & Accessories

LT TRACK





One-Circuit


LTA1	LTA2	LTA3	LTA4	LTA5	LTA6
WH, DBL	WH, DBL	WH, DBL	WH, DBL	WH, DBL	WH, DBL
Live End	Linear Coupler	Floating Feed	Straight Connector	Adjustable "L" Connector	"T" Connector
Feed connector used to start a run. Includes one dead end.	Joins two track sections in a straight run. Not a feed point. Does not add to length.	Permits track to be wired anywhere along track length. Includes two dead ends.	Joins two track sections in a straight run. Includes two dead ends. May be used as a feed.	Joins two track sections to make a 90° angle. Includes two dead ends. May be used as a feed.	Joins three track sections at 90° angles. Includes three dead ends. May be used as a feed.
					



LTA7	LTA9	LTA91	LTA10	LTA11	LTA12
WH, DBL	WH, DBL	WH, DBL	WH, DBL		WH, DBL
"X" Connector	Surface Conduit Feed	Conduit Continuation Kit	Cord and Plug Feed	Concealed Feed	Replacement Dead End
Joins four track sections at 90° angles. Includes four dead ends. May be used as a feed.	Permits track to be connected to conduit (1/2" trade size conduit fitting). Includes one dead end.	Left and right conduit connector. Allows continuous run around obstructions.	Permits track to be connected to grounded outlet. 12-foot, 3-wire cord. Maximum 10 amps. Includes one dead end. Consult factory for use.	Permits direct conduit wiring from above track without outlet box. Use with LTA1, LTA4, LTA5, LTA6, LTA7.	Terminates straight run Replacement only. Included with feed connectors. (Set of 10)
					

LTA13	LTA15	LTA16	LTA17	LTA18	LTA19
WH, DBL	WH, DBL	WH, DBL	WH, DBL	WH, DBL	WH, DBL
Outlet Box Cover	Grounded Convenience Outlet	Pendant Chain Adaptor	Switch Module	Line Voltage Monopoint	Pendant Cord Adaptor
Used at any feed connection point (LTA1, LTA4, LTA5, LTA6, LTA7).	Provides an electrical outlet on the track. Consult factory for use.	Allows chain hung or swag fixtures to be attached to track. Maximum weight: 20 lbs. (9kg).	Allows independent switching of connected fixture.	Converts line voltage track fixture for direct wiring to an outlet box. For use with 120V fixture.	Allows cord hung fixtures to be mounted on track. Maximum weight: 20 lbs. (9kg).
					




TRACK Accessories



LTA20	LTA21	LTA30	LTA33
WH, DBL	WH, DBL	WH, DBL	
Track Mounting Clips Optional track mounting method. (Set of 3)	Low Voltage Monopoint Converts low voltage track fixture for direct wiring to outlet an box. Not compatible with LTH Series MR16 Track Heads.	Threaded Rod Mounting Clips Allows support of track by 1/4" threaded rod. (Set of 3)	Track Reinforcement Plate Slides between track lengths for extra rigidity when pendant mounting.
			

LTA31 12	LTA31 18	LTA31 24	LTA31 36
WH, DBL	WH, DBL	WH, DBL	WH, DBL
12" Extension Wand Mounts to track, drops head 12".	18" Extension Wand Mounts to track, drops head 18".	24" Extension Wand Mounts to track, drops head 24".	36" Extension Wand Mounts to track, drops head 36".
			

LTAP1 12	LTAP1 18	LTAP1 24	LTAP1 36	LTAP1 48	LTAP2
WH, DBL	WH, DBL	WH, DBL	WH, DBL	WH, DBL	WH, DBL
Stem Kit Canopy and 12" stem for use on hard ceilings. Requires LTAP2 to be used as a feed.	Stem Kit Canopy and 18" stem for use on hard ceilings. Requires LTAP2 to be used as a feed.	Stem Kit Canopy and 24" stem for use on hard ceilings. Requires LTAP2 to be used as a feed.	Stem Kit Canopy and 36" stem for use on hard ceilings. Requires LTAP2 to be used as a feed.	Stem Kit Canopy and 48" stem for use on hard ceilings. Requires LTAP2 to be used as a feed.	Stem Feed Kit For use with stem kit. Required for track to be wired through stem. One required for each live feed.
					

TRACK Accessories

LTAT20	LTAT21	LTAT22	LTAT23	LTAT25	LTAT32
WH, DBL	WH, DBL	WH, DBL	WH, DBL		
T-bar Mounting Clips Offsets track from 1" Tbar, 1/4" drop. (Set of 3)	T-bar Mounting Clips Offsets track from 1" Tbar, 1/2" drop. (Set of 3)	T-bar Mounting Clips Offsets track from 1/2" Tbar, 1/4" drop. (Set of 3)	T-bar Mounting Clips Offsets track from 1/2" Tbar, 1/2" drop. (Set of 3)	T-bar Junction Box Replacement only.	T-bar Earthquake Clips Provides added structural support for 1" Tbar. (Set of 3)
					

LTATP1 12	LTATP1 18	LTATP1 24	LTATP1 36	LTATP1 48	LTAT1
WH, DBL	WH, DBL	WH, DBL	WH, DBL	WH, DBL	WH, DBL
T-bar Stem Kit Canopy and 12" stem. Requires LTAP2 to be a feed.	T-bar Stem Kit Canopy and 18" stem. Requires LTAP2 to be a feed.	T-bar Stem Kit Canopy and 24" stem. Requires LTAP2 to be a feed.	T-bar Stem Kit Canopy and 36" stem. Requires LTAP2 to be a feed.	T-bar Stem Kit Canopy and 48" stem. Requires LTAP2 to be a feed.	T-bar Feed Kit Outlet box for grid ceilings. For use with LTA1, LTA4, LTA5, LTA6, LTA7. Includes outlet box, cover and mounting hardware.
					

ORDERING INFORMATION

All configurations of this product are considered "standard" and have short lead times.

Example: LTA1 WH

Catalog Number												Finish ⁵
LTA1	LTA5	LTA9	LTA12	LTA17 ²	LTA21 ³	LTA31 24	LTAP1 12 ⁴	LTAP1 48 ⁴	LTAT21	LTAT32 ¹	LTATP1 36 ⁴	WH White DBL Black
LTA2	LTA6	LTA91	LTA13	LTA18 ²	LTA30	LTA31 36	LTAP1 18 ⁴	LTAP2	LTAT22	LTATP1 12 ⁴	LTATP1 48 ⁴	
LTA3	LTA7	LTA10	LTA15	LTA19	LTA31 12	LTA31 48	LTAP1 24 ³	LTAT1	LTAT23	LTATP1 18 ⁴		
LTA4	LTA8	LTA11 ¹	LTA16	LTA20	LTA31 18	LTA33 ¹	LTAP1 36 ⁴	LTAT20	LTAT25 ¹	LTATP1 24 ⁴		

Notes

1. Not available in finishes.
2. Not available for use with LTD CPWW 20.
3. Not compatible with LTH Series MR16 track heads.
4. Two stems required for 2' or 4' track. Three stems required for 8' track. Four stems required for 12' track. Can be field-cut and threaded.
5. When white track is used, white components are recommended. When other finishes are specified, black components are recommended.