



LUXEFLOW

Filtered water at the speed of your faucet.

- American-made quality and performance.
- Highest quality carbon block filtration available.
- Meets or exceeds all compliances.
- Hassle-free and low maintenance.
- Quick and easy installation – no tools required.
- Comes complete with everything you need.
- No separate dispenser needed.
- No drilling any holes in your sink or countertop.

Chlorine and its byproducts are known carcinogens. Drinking them is not recommended. The New York State Department of Health and President's Cancer Panel recommend water filtration to reduce or eliminate our exposure to these substances.*

REMOVES CHLORAMINE, CHLORINE, THMS, VOCS, PESTICIDES, LEAD, CYSTS, RUST, DIRT, SEDIMENT, & MORE.¹

High capacity, high flow, in-line filter that installs directly to your faucet.

**SAVE \$500
PER YEAR**

The **LUXE FLOW** replaces over 15,000 plastic water bottles, saving you \$500+ every year and preventing plastic waste.

**READY IN
5 MINUTES**

The **LUXE FLOW** is an in-line filter that installs directly at any kitchen, bathroom, or wet bar in just 5 minutes.

**ADVANCED
FILTRATION**

The **LUXE FLOW** removes chloramine, chlorine, pharmaceutical residues, lead, cysts, and more.¹ Perfect for drinking, cooking, watering live plants, and washing produce.

GO TO WWW.LOCKESUPPLY.COM TO FIND A LOCATION NEAR YOU.

TECHNICAL INFORMATION

LUXE FLOW FILTRATION

MODEL #: LF-2 <E1100>

SYSTEM SPECIFICATIONS

OPERATION TEMPERATURE: Maximum 100° F (37.8° C) / Minimum 40° F (4.4° C)

OPERATION PRESSURE: Maximum for warranty 75 psi (5.17 Bar) / Minimum 40 psi (2.76 Bar)

Fully Compliant
with California
No-Lead Standards.



1.) Not to be installed on well water of unknown quality. 2.) Do not use for filtering salt-softened water – either sodium chloride or potassium chloride. 3.) Do not use with water that is microbiologically unsafe or of unknown quality without adequate disinfection before or after the system. 4.) Replace your filter annually or as needed (do not exceed 1 year). 5.) Install in cold water supply only. 6.) Install in compliance with all local and state regulations.

MODEL

LF-2 <E1100>

REPLACEMENT FILTER ITEM

LF-2-R <E1101>

FILTER SPECIFICATION

ITEM #: LF-2-R <E1101>

DESCRIPTION: Carbon Block (1 Micron)

PURPOSE: Advanced filter for chlorine, chloramine reduction, lead, cysts, VOCs & more.

FEATURES & BENEFITS: Increased surface area, enhanced adsorption, excellent performance.

CONSTRUCTION: Activated carbon block.

SERVICE LIFE: 1 year†

MAX. FLOW: 2.5 GPM / 9.46 LPM

MAX. PRESSURE: 125 PSIG / 8.6 Bar

TEMP. RANGE: 40-100° F / 4.4-37.8° C

MICRON RATING: >99% @ 1 micron

CHLORINE REDUCTION: >95% 10,000 gallons @ 2 GPM

LEAD REDUCTION: >90% 2,500 gallons @ 2 GPM

CYST REDUCTION: >99.99%

The **LUXE FLOW** unit comes complete fully assembled. The unit comes with everything you need for a proper installation: connections, white and blue tubing (2.5 ft. each), and mounting bracket.

This filtration system DOESN'T NEED a faucet or dispenser. The **LUXE FLOW** offers full bed depth filtration and superior performance compared to the limited capacities of common in-line filters. The **LUXE FLOW** can be used in-line where greater filter capacity, longevity, and flow rate is required. It can also be used in situations where a separate dispenser for filtered water is not available or desirable, or where a separate hole in the counter or sink is not available or desirable. The **LUXE FLOW** will provide filtered water directly to the cold side of your kitchen faucet without any reduction of flow rate and can be installed in bathrooms, beverage centers and many applications.

FILTER SERVICE LIFE: 10,000 GALLONS (OR UP TO 1 YEAR)*

REPLACE YOUR FILTERS ANNUALLY OR AS NEEDED.

DO NOT EXCEED 1 YEAR.

**Filter service life is based on local water conditions and usage. Fine sediment, micro-plastics or certain water conditions may prematurely reduce flow rate and service life due to the filter's advanced ability to capture contaminants.*

† These substances may or may not be in your water. Please ensure this is the correct system for your needs. Please see included instructions for proper installation and usage.

ACTUAL UNIT SIZE: 4" x 16" (allow 4" clearance for filter replacement)

SHIPPING CARTON: 6" x 6" x 18"

SHIPPING WEIGHT: 6 lbs.



Above: **LUXE FLOW** included parts and assembled items. White bracket included (not pictured).



Independently lab-tested to meet or exceed NSF/ANSI Standard 42 & 53 for reduction of chlorine, taste, odor, lead, and cysts.



GO TO WWW.LOCKESUPPLY.COM TO FIND A LOCATION NEAR YOU.