## Product data sheet Characteristics

# HOM2100 MINIATURE CIRCUIT BREAKER 120/240V 100A

Product availability: Stock - Normally stocked in distribution facility





Price\*: 168.00 USD



#### Main

Product	Miniature circuit-breaker	
Range	Homeline	
Line Rated Current	100 A	
Certifications	UL listed	
System Voltage	120/240 V AC	
Mounting Type	Plug-in	
Number of Poles	2P	
Short Circuit Current Rating	10 kA	
Number of Spaces	2	
Circuit Breaker Type	Standard	
Ratings	HACR rated	-
Electrical Connection	Box lugs	
Wire Size	AWG 4AWG 2/0 for 1 cable(s) (aluminium/copper)	-
Height	3.13 in	•
Width	2 in	T - C
Depth	2.98 in	ž.

### Environment

Ambient air temperature for operation 104 °F (40 °C)

#### Ordering and shipping details

Ordering and shipping del	talis	<u>.v</u>
Category	00146 - HOM 40-50A 1P, 70-110A 2P	 ation
Discount Schedule	DE3D	
GTIN	00785901065753	qocni
Nbr. of units in pkg.	1	T
Package weight(Lbs)	0.9500000000000007	
Returnability	Υ	sc ai

Country of origin	MX	
Offer Sustainability		
Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1323 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	
Contractual warranty		
Warranty period	Lifetime	