# VACUUM GAUGES

PERFORMANCE THAT CAN BE MEASURED



# VG100A & VG200 VACROMETER DIGITAL VACUUM GAUGES VG100A & VG200:

- Advanced sensor design with self-heated thermistor bridge and automatic temperature compensation
- Field cleanable sensor designed to withstand 400 Psi of positive pressure
- Brass T adapter (AVT45), hanging hook (VGXH) and carrying case (VGXC) included with VG200, VG100A
- Calibrated to strict NIST standards for best-in-class accuracy and reliability
- Designed and manufactured in the USA with U.S. and globally sourced components

# VG200, VG201:

- Continual digital readout of evacuation process on large, easy to read 5 digit LCD display
- User selectable units: Microns, Torr, in/Hg or mBar

## **VG100A, VG101:**

 Vacuum level indication at Atm (Atmosphere), 5000, 2000, 1000, 500, 250, 100, 50 & 25 microns









Model	VG200	VG201	VG100A	VG101	
Sensor Type	Self - heated thermistor bridge [with integral temperature compensation from 32 to 122° F (0 to 50° C)]				
Field Cleanable Sensor	Yes				
Accuracy	+/- 10% Of Reading		+/- 10% Value Of Lighted LED		
Display Type	5 Digit LCD		9 High Intensity LEDs		
Display Auto-Off	After 5 Minutes Of Operation				
Operating Vacuum Range	Atmospheric pres	ssure to 0 microns	Atmospheric	pressure to 25 microns	
Maximum Working Pressure	400 Psig				
Operating Temp Range	Compensated (accuracy as stated): 32°F - 122°F (0°C - 50°C) Non-compensated: Add +/- 0.5% error for every °C outside compensated range				
Storage Temperature	-22° F to 185° F (-30° C to 85° C)				
Operating & Storage Humidity	0 - 95%, Non-condensing				
Power Source	One 9V Alkaline Battery (ANSI 1604AC – IEC 6LR61), included				
Battery Life	20 hr continuous use		18 hr continuous use		
Battery Indicator	Battery symbol with 3 segment Power Level Bar Graph		Symbol for 500 Microns Glows		
Weight (Excluding Battery)	5.5 oz (156 g)		4.8 oz (136 g)		
Dimensions	2.7" dia. by 1.6" Dp x 5" H (68 mm Dia. x 40 mm Dp x 124 H)				
Mechanical Connection	Standard 1/4" female SAE refrigerant hose w/core depressor	1/8" NPT thread connection	Standard 1/4" female SAE refrigerant hose w/ core depressor	1/8″ NPT thread connection	

## **GAUGE ADAPTERS**

The AVT45/48/87 are premium built brass adapters. The AVT45 is included for use with the VG100A & VG200 (purchased separately for VG201 & VG101) and has a 1/4" SAE male to 1/4" SAE male to 1/4" SAE swivel female tee.





<b>VACUUM GAUGE ACCESSORIES &amp;</b>	SPARE PARTS FOR VG200.	. VG201. 100A. VG101
	0.7 7 0 . 0 1 0	,

AVT44	1/4" SAE female hex nut x 1/4" SAE male x 1/4" SAE male w/cap & core
AVT45	1/4" SAE female knurl nut x 1/4" SAE male x 1/4" SAE male w/cap & core
AVT87	1/4" SAE male x 1/2-20" SAE female x 1/2-20" SAE male tee adapter
VGXC	Carrying case for VG Series (Included with VG100A & VG200)
VGXH	Hanging hook for VG Series (Included with VG100A & VG200)

