



Cartridge Filter Housings



Drinking Water Systems



3/4" Filter Housings



H34

Wrench	O-Ring	Bracket
WR200	ORVH	BRK-1020

- 3/4" inlet/outlet housing with wrench and pressure relief
- Clear sump
- Whole house applications
- Accepts a wide range of 2-1/2" x 10" cartridges
- Maximum pressure: 100 psi
- Maximum temperature: 100°F



VH34

Wrench	O-Ring	Bracket
WR300	ORVH	BRK-VIH

- Valve-in-head 3/4" inlet/outlet housing with wrench
- Turning the valve closes both inlet & outlet and relieves the pressure simultaneously, making cartridge change-out simple & quick
- Accepts a wide range of 2-1/2" x 10" cartridges
- Maximum pressure: 100 psi
- Maximum temperature: 100°F



HL34

Wrench	O-Ring	Bracket
WR400	OR3420	BRK-1020

- 3/4" inlet/outlet housing with wrench and pressure relief
- White sump
- Accepts a wide range of 2-1/2" x 20" cartridges
- Maximum pressure: 100 psi
- Maximum temperature: 100°F



HOT34

Wrench	O-Ring	Bracket
WR400	OR3420	BRK-1020

- 3/4" inlet/outlet hot water housing with wrench and pressure relief
- Maximum pressure: 100 psi
- Maximum temperature: 200°F

1" High Flow Filter Housings



HJ10-1

Wrench	O-Ring	Bracket
WR500	ORBB	BRK-J

- 1" inlet/outlet housing with wrench and pressure relief
- White sump
- Suitable for high flow applications
- Accepts a wide range of 4-1/2" x 10" cartridges
- Maximum pressure: 100 psi
- Maximum temperature: 100°F



HJ20-1

Wrench	O-Ring	Bracket
WR500	ORBB	BRK-J

- 1" inlet/outlet housing with wrench and pressure relief
- White sump
- Suitable for high flow applications
- Accepts a wide range of 4-1/2" x 20" cartridges
- Maximum pressure: 100 psi
- Maximum temperature: 100°F

1/4" Point of Use Housings



USH05

Wrench	O-Ring	Bracket
WR200	ORVH	BRK-1020

- 1/4" inlet/outlet housing with mounting bracket and wrench
- Ideal for single faucet installations
- Accepts 2-1/2" x 5" cartridges
- Maximum pressure: 100 psi
- Maximum temperature: 100°F



USH10

Wrench	O-Ring	Bracket
WR200	ORVH	BRK-1020

- 1/4" inlet/outlet housing with mounting bracket and wrench
- Ideal for single faucet installations
- Accepts 2-1/2" x 10" cartridges
- Maximum pressure: 100 psi
- Maximum temperature: 100°F

Drinking Water Systems

Reverse Osmosis Systems

Pump Model R.O. Systems



DWSB-TFC-50

5 Stage Reverse Osmosis System

- Stages: 5 Micron Sediment, GAC, Carbon Block, R.O. Membrane, and Carbon Polisher
- Complete System (as shown above)
- 50 gpd membrane



DWSB-50-PermPump

4 Stage Reverse Osmosis System

- Permeate Pump for higher line pressure and increased volume output
- Complete System (as shown above)
- 50 gpd membrane



QCRO-50

5 Stage Reverse Osmosis System

- Sanitary Quick Change Cartridges. Eliminates the mess associated with standard filter housings.
- Stainless steel bracket is strong and won't corrode
- Color coded filters makes for easy replacement
- All fittings are quick connect



RO-LSV

Leak Detector Stop Valve

- 1/4" quick connect
- Helps protect against accidental leaks from under the sink installations



DWSB-50-PUMP

5 Stage Reverse Osmosis System

- Quiet booster pump increases water pressure to improve water quality and quantity
- Complete System (as shown above)
- Great output

Drinking Water Systems



CRS-3

- Sanitary Quick Change Cartridges.
- Reduces bacteria, virus, and VOC's
- Does not reduce TDS
- No storage tank or drain needed
- All fittings are quick connect



NRS-1

Nitrate Reduction System

- Auto Shut-off water meter
- Complete system including: faucet, meter, and installation fittings
- No drain or storage tank needed



ARS-1

Arsenic Reduction System

- Auto Shut-off water meter
- Complete system including: faucet, meter, and installation fittings
- No drain or storage tank needed
- Non-leaching material for safe disposal

STERLING
WATER TREATMENT

12630 US Highway 33 N.
Churubusco, IN 46723
www.sterlingwatertreatment.com