



ADVANTAGES FOR YOU:

- Compact, handy, light. Drive unit with short tubular arms only 1.6 kg (3.5 lbs)
- Dividable tubular arms for individual adjustment of leverage to accomodate different force demands of different pressfitting systems
- Secure seating of pressing tongs through locking pins
- Final-lock-positioning enables visual check of perfectly pressed joint (completely closed pressing tong)

REMS Eco-Press Drive Unit

Manual radial press for producing pressing joints of plastic and multi-layer composite tubes Ø 10-26 mm, Ø 3/8- 1". For operation with REMS pressing tongs. Drive unit with final-lock-positioning and dividable tubular arms. In skin package.

REMS PRESSING TONGS, STANDARD

ADVANTAGES FOR YOU:

- High-compression pressing tongs in forged and specially hardened steel
- Pressing contours of REMS pressing tongs are system-specific and correspond with the respective pressfitting system. Thus perfect system conformity, safe press jointing
- Pressing jaws of pressing tongs manufactured on NC production centres ensure high-precision machining of pressing contour. Hence far closer tolerances compared to as cast pressing contour
- Drive through REMS Power-Press E, REMS Power-Press ACC, REMS Akku-Press, REMS Akku-Press ACC and suitable drive units of other makes. All pressing tongs marked with* also fit into the REMS Eco-Press drive unit



YOGAPIPE ACR:	PART #:
H 12 (1/4")*	570300
U 14 (3/8")*	570760
U 16 (1/2")*	570765
U 18 (5/8")*	570770
U 20 (3/4")*	570775
U 25 (7/8")*	570780
U 32 (1 1/8")	570785

REMS PRESSING TONGS, MINI

ADVANTAGES FOR YOU:

- High-compression pressing tongs in forged and specially hardened steel
- Pressing contours of REMS pressing tongs are system-specific and correspond with the respective pressfitting system. Thus perfect system-conformity, safe press jointing
- Pressing jaws of pressing tongs manufactured on CNC production centres ensure high-precision machining of pressing contour.
Hence far closer tolerances compared to as cast pressing contour
- Drive through REMS Mini-Press ACC, REMS Mini-Press 22 V ACC



YOGAPIPE ACR:	PART #:
H 12 (1/4")*	570300
U 14 (3/8")*	570760
U 16 (1/2")*	570765
U 18 (5/8")*	570770
U 20 (3/4")*	570775
U 25 (7/8")*	570780
U 32 (1 1/8")	570785

ADVANTAGES FOR YOU:

- Electro-mechanic drive unit with maintenance-free reduction gear with safety slipping clutch and feed system with trapezoidal gear spindle n. Only 4.7 kg (10.3 lbs)
- Proven universal motor 110 V, 50-60 Hz, 450 W (0.61 HP)
- The pressing jaws remain closed until switched into reverse
- Force protected

REMS POWER-PRESS ACC BASIC-PACK

Electric radial press for producing pressing joints of all common pressfitting systems Ø 10-108 (110) mm, Ø 3/8- 4". Drive unit. In sturdy steel case.



ADVANTAGES FOR YOU:

- Powerful electro-hydraulic drive unit n Only 4.7 kg (10.3 lbs)
- Swivelling pressing tongs seat (360°)
- Proven universal motor 110 V, 50-60 Hz, 450 W (0.61 HP)
- Automatic-Circuit-Control (ACC): Automatic retraction after completion of pressing operation

REMS POWER-PRESS ACC BASIC-PACK

Electro-hydraulic radial press for producing pressing joints of all common pressfitting systems Ø 10-108 (110) mm, Ø 3/8 - 4". Drive unit with automatic circuit control. In sturdy steel case.



ADVANTAGES FOR YOU:

- Electro-hydraulic drive unit n Only 4.3 kg (9.5 lbs)
- Optimum weight distribution for single-hand operation n Swivelling pressing tongs seat (360°)
- Acoustic signal after successful completion of pressing operation enables confirmation of a perfectly pressed joint (completely closed pressing tong)

REMS AKKU-PRESS LI-ION BASIC-PACK

Cordless radial press with automatic circuit control for producing pipe pressing joints Ø 10-108 (110) mm, Ø 3/8-4". Swivelling pressing tongs seat with automatic locking. Electro-hydraulic drive with powerful battery motor 14.4 V, 380 W (0.52 HP), robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch. Battery Li-Ion 14.4 V, 3.0 Ah, rapid charger Li-Ion/Ni-Cd 110 V, 50-60 Hz, 65 W. In sturdy steel case.



ADVANTAGES FOR YOU:

- Electro-hydraulic drive unit n Only 4.3 kg (9.5 lbs)
- Optimum weight distribution for single-hand operation
- Swivelling pressing tongs seat (360°)
- Automatic-Circuit-Control (ACC): Automatic retraction after completion of pressing operation (Automatic Circuit Control)

REMS AKKU-PRESS LI-ION BASIC-PACK

Cordless radial press with automatic circuit control for producing pipe pressing joints Ø 10-108 (110) mm, Ø 3/8-4". Swivelling pressing tongs seat with automatic locking. Electro-hydraulic drive with powerful battery motor 14.4 V, 380 W (0.52 HP), robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system. Safety tip switch. Battery Li-Ion 14.4 V, 3.0 Ah, rapid charger Li-Ion/Ni-Cd 110 V, 50-60 Hz, 65 W. In sturdy steel case.



ADVANTAGES FOR YOU:

- Universal, handy cordless tool with automatic circuit control for producing pipe pressing joints for all common pressfitting systems
- Super light and handy. Drive unit with battery Li-Ion only 2.4 kg (5.3 lbs)
- Optimum weight distribution for single-hand operation
- Ergonomically designed housing
- Secure seating of pressing tongs by automatic locking
- Swivelling pressing tongs seat for REMS pressing tongs Mini
- Enormous thrust and pressing force for fast and perfect press jointing



REMS Mini-Press ACC Li-Ion Basic-Pack

Cordless radial press with automatic circuit control for producing pipe pressing joints Ø 10–40 mm, Ø 3/8 – 1 1/4". For operating with REMS pressing tongs Mini. Swivelling pressing tongs seat with automatic locking. Electro-hydraulic drive with powerful battery motor 380 W (0.52 HP), robust planetary gear, eccentric reciprocating pump and compact high power hydraulic system, safety tip switch. Integrated LED work light. Battery Li-Ion 14.4 V, 1.5 Ah, rapid charger Li-Ion/Ni-Cd 110 V, 50–60 Hz, 65 W. In sturdy steel case.

ACCESSORIES FOR BATTERY PRESSES:	PART #:
Battery Li-Ion 14.4 V, 1.5 Ah	571545
Battery Li-Ion 14.4 V, 1.4 Ah	571555
Rapid charger 110 V, 50–60 Hz, 65 W	571560