



VAPCO PART NO.

SEAL

AC/REFRIGERATION SERVICE XPRESS INJECT

Cat. No.	Size	
XPS-SS	Up to 1.5 Tons	XPS-125T 61-125 Tons
XPS-5T	1.5-5 Tons	XPS-250T 126-250 Tons
XPS-15T	6-15 Tons	XPS-5XL 1.5-5 Tons
XPS-30T	16-30 Tons	Large Leak Version
XPS-60T	31-60 Tons	XPS-5XL 1.5-5 Tons

DESCRIPTION

SEAL is the fastest acting refrigerant sealer on the market proven to permanently seal leaks without hardening system lines or valves. Unlike other products, Xpress Seal is able to from seals faster by traveling with refrigerant gas instead of oil. This specially formulated epoxy reacts to water and air when in contact with the atmosphere at a leak. The product's formula is the safest choice on the market, and does not contain harmful chemicals that can lead to blindness.

APPLICATIONS

Seal Xpress Inject is able to permanently seal small holes in A/C condensers, evaporators, fittings, and metal inline sets. Perfect for split systems, heat pumps, microchannel coils, packaged units, and mini splits. After injecting the Xpress Seal formula, leave the system charged and running for one day to ensure that the seal has properly formed.

FEATURES AND BENEFITS

- Fastest acting leak seal on the market
- Formulated for a permanent seal
- Compatible with all Refrigerants except ammonia
- Safest choice on the market

LABEL INFORMATION

SEAL is the ideal solution for sealing small holes in A/C condensers, evaporators, fittings, and metal inline sets. Xpress Seal is safe to use, and designed to prevent accidental release under pressure or if hooked up incorrectly. This product is compatible with all refrigerants except ammonia.

Directions using Vapco's Direct Inject Gun : If hose is bent or kinked, do not use! Turn the A/C system on and verify the unit is running. With the CO2 cartridge in the gun, connect the Xpress Inject to the Direct Inject Gun. Connect the other end to the low-side service port. Briefly pull the trigger. The direct Inject Gun will meter just enough CO2 to empty tube. The sealer has now been injected into the system. Disconnect the empty tube from the low-side port. Install service port cap. Run the A/C unit at least one hour after installing Xpress Inject. 12+ uses per CO2 cartridge. **For traditional methods using refrigerants to install Xpress Inject use the following instructions:** 1. Turn the a/c system on and verify the unit is running. Connect Xpress Inject to the low-side service port of the system. (This is generally the large line). 2. Connect the manifold refrigerant hose to the refrigerant supply tank. Verify the high and low side valves on the manifold are closed before proceeding. Purge the low pressure hose when connecting to Xpress Inject. 3. Open low-side valve and watch for the tube to clear. (This will ONLY take a few seconds!) Turn off low-side manifold valve as soon as the tube is clear. Turn off refrigerant gas. Verify the system is charged to manufacturer's specifications! Disconnect low-side hose from Xpress Inject. Install service port cap. Run the a/c unit at least one hour after installing Xpress Inject. (Do not bend or kink hose!)

Dangers: Read and understand the product's label and Safety Data Sheet. May be fatal if swallowed and enters airways. Highly flammable liquid and vapor. May cause skin irritation. Toxic to aquatic life. **DO NOT** use in any manner for which it was not designed. Always wear PPE (Personal Protective Equipment) when servicing HVAC equipment.



- Fastest acting leak seal on the market
- Formulated for a permanent seal
- Compatible with all Refrigerants except ammonia
- Safest choice on the market

CONTAINS

CONTAINS (CAS#) : Ethyl alcohol (54-17-5), Toluene (108-88-3), Silane, ethenyltriethoxy (78-08-0)



WARNING: This product can expose you to Ethyl Alcohol, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

First Aid Measures

Inhalation: If symptoms occur, go to open air and ventilate suspected area. **Immediately call a POISON CENTER or doctor/physician.** **Skin contact:** Wash skin with soap and water. If irritation persists, seek medical attention. **Eye Contact:** Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. **Immediately call a POISON CENTER or doctor/physician.** **Ingestion:** Do NOT induce vomiting. **Immediately call a POISON CENTER or doctor/physician.**

Precautions

Do NOT handle or use this product until all safety precautions have been read and understood. Keep away from heat/sparks/open flame/hot surfaces – NO SMOKING! Do not breathe dust/fume/gas/mist/vapors/spray. Wash hands and arms thoroughly after handling. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/clothing/face/eye protection.

Storage

Keep temperatures below 52°C/125°F. Store in a dry/cool/well ventilated place. Store locked up. Store away from incompatible products.

In Case of Fire

Use dry chemical powder, alcohol-resistant foam or carbon dioxide.

Disposal

Dispose of contents in accordance with local/regional/national regulations. Brass components can be recycled.

Incompatible Products

Heat sources and oxidizers