


## **Premium UL 181B-FX Listed Duct Tape**



Backing: Printed Polyethylene Coated Cloth

Adhesive: Rubber

Liner: N/A

Colors: Metallic, Black, Silver

Specifications: UL 181B-FX Listed

Standard Sizes: 48mm x 55M, 72mm x 55M

## **Applications**

 A superior closure system for use on UL Listed flexible, non-metallic air duct • Challenging bonding, protecting, bundling, and repair applications

## Features Benefits

High Strength PE Coated Cloth Backing	<ul><li>Tough and durable</li><li>Conformable to wrap ducts for an effective seal</li></ul>		
Aggressive Natural Rubber Adhesive	<ul> <li>Excellent bond to sheet metal and other surfaces</li> <li>High strength to withstand vertical pull from the weight of the duct system</li> <li>Resistant to moisture and mold growth</li> </ul>		
UL 181B-FX Listed	<ul> <li>Meets code requirements and can contribute toward requirements for EA Credit 1 (Optimize Energy Performance) under LEED®</li> </ul>		
Low VOC Content	Can contribute toward satisfying EQ Credit 4.1  (Low Emitting Materials) under LEED®		

## **Typical Test Values**

	Standard UOM	Metric UOM	Test Method
Total Thickness	14.0 mils	0.356 mm	ASTM D-1000
Adhesion to Steel	45 oz/in	4.92 N/cm	PSTC-101
Tensile Strength	29 lb/in	50.79 N/cm	ASTM D-1000
Smoke Developed	15		ASTM E-84
Flame Spread	15		ASTM E-84
Operating Temperature	40 to 200 °F	4 to 93 °C	
VOC Content	<1 g/L		

Recommended Storage Conditions: 32-90 °F at 50% RH  $\pm 2\%$  Standard Shelf Life (at 25C): 36 months from date of manufacture.

The information presented herein was prepared at BERRY PLASTICS CORPORATION (25 Forge Parkway Franklin, MA 02038) by qualified technical personnel. To Berry Plastics' knowledge it is true and accurate. However, the information and recommendations are furnished for these products with the understanding that the purchaser or user, as the case may be, will independently determine that the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.

