

AC OPAL SERIES

4", 6" & 8" Surface or Recessed Mount

The Opal Series LED fixture is designed to surface mount over a standard junction box or is suitable for use with a recessed housing by Nora or others. The Opal produces even illumination with no diode image, from bright to dim. The low profile unit is cULus wet listed and produces 650 to 2000 lumens at 90+ CRI. Available in three finishes the Opal is an excellent energy efficient lighting solution for laundry rooms, closets, pantries, hallways and showers in residential and commercial retrofit or new construction applications.

FEATURES

- 4" Series - 650lm / 10.5W or T24 Series - 850lm / 13W
- 6" Series - 1050lm / 16W
- 8" Series - 2000lm / 32W
- 2700K, 3000K, 4000K or 5000K at 90+ CRI
- Nora designed, precision molded lens provides optimal lumen output and even distribution
- White polymer lens diffuser eliminates diode image, even when dimmed
- Surface mounted or retrofit into an existing recessed housing with torsion spring kit (ordered separately)
- Surface mounts to most standard junction boxes
- White, Natural Metal and Bronze finishes
- Suitable for use in closets when installed in accordance to NEC Section 410.16 (C)(1)
- T24 series can be used to comply with 2016 Title 24 Part requirements
- 5-Year limited warranty
- ENERGY STAR® certified



NLOPAC-R4509
4" AC Opal Series



NLOPAC-R6509
6" AC Opal Series



24 NLOPAC-R6T24
6" AC Opal T24 Series



24 NLOPAC-R4T24
4" AC Opal T24 Series



24 NLOPAC-R8T24
8" AC Opal T24 Series



AC OPAL SERIES 4", 6" & 8" SURFACE MOUNT

SIZE / LUMENS / WATTAGE	COLOR TEMP	FINISH
NLOPAC-R4509 4" / 650lm / 10.5W	27A 2700K	BZ Bronze
NLOPAC-R6509 6" / 1050lm / 15W	30A 3000K	NM Natural Metal
	40A 4000K	W White
	50A 5000K (White finish only)	
24 NLOPAC-R4T24 4" / 850lm / 13W	27 2700K	
24 NLOPAC-R6T24 6" / 1050lm / 16W	30 3000K	
24 NLOPAC-R8T24 8" / 2000lm / 32W	40 4000K	
	50 5000K (8" only)	

Example: **NLOPAC-R4T2430W** - 4" T24 AC Opal LED, 850lm / 13W, 3000K, White finish

OPTIONAL ACCESSORIES

- NLOPAC-56RECKIT** 6" Opal can be mounted on 5" or 6" recessed housing using optional torsion spring kit.
- NLOPAC-4BKT-2** Universal bracket for mounting 4" and 6" Opal to 3" or 4" junction boxes. Universal bracket is included with R4509 series.

OPAL W/ MOTION SENSOR

7" Surface or Recessed Mount

The AC Opal Motion Sensor LED Series is designed to surface mount over a standard junction box. The low profile luminaire produces even illumination and integral PIR sensor activates when motion is detected. After 3 minutes of no motion, the fixture automatically turns off.

FEATURES

- Surface mounts to most standard junction boxes
- 1000lm / 15W LED luminaire
- 3000K or 4000K at 90+ CRI
- PIR (passive infrared) motion sensor for easy on/off operation
- PIR sensor can detect motion up to 16' diameter pattern at 8' mounting height
- White finish
- Surface mounted or retrofit into an existing recessed housing with torsion spring kit (ordered separately)
- cETLus Listed for Wet Locations
- Suitable for use in closets when installed in accordance to NEC Section 410.16 (C)(1)
- 5-Year limited warranty
- ENERGY STAR® certified



AC OPAL SERIES 7" SURFACE MOUNT WITH MOTION SENSOR

SIZE / LUMENS / WATTAGE	COLOR TEMP	FINISH
NLOPAC-R7MS 7" / 1000lm / 15W	30 3000K	W White
	40 4000K	

Example: **NLOPAC-R7MS30W** - 7" AC Opal w/ PIR, 1000lm / 15W, 3000K, White finish

OPTIONAL ACCESSORIES

NLOPAC-56RECKIT 6" Opal can be mounted on 5" or 6" recessed housing using optional torsion spring kit.

