60 x 32 x 72 inches

SOAKER MODEL #2603CTW WHIRLPOOL MODEL #2603CTWWP



## **AQUATIC ADVANTAGE**

- National distribution
- 6 manufacturing facilities
- Private fleet
- Centralized customer service
- Field support

#### COLOR AND TRIM OPTIONS

Stock	Upgraded	Premium
Almond (C) White (C)	Linen/Biscuit (C) Bone (C)	Black (NA) Mexican Sand (NA) Sand Bar (NA) Sterling Silver (NA)

C = color matched trimNA = not applicable\* color not available for whirlpool models

## **FEATURES**

- Tub-shower
- Textured tile finish
- Ergonomic backrest
- Installed acrylic grab bar
- Slip-resistant textured bottom
- Left or right hand drain
- AcrylX™ applied acrylic surface
- Lifetime limited warranty

## Whirlpool Features:

- .75hp pump
- 4 directional hydrotherapy jets
- Advanced safety suction system
- Pneumatic on/off control

## **OPTIONS**

- Removable access panel (whirlpool models)
- Grab bar reinforcement
- Factory installed assisted care grab bars
- Dome (East zone only)
- Designer drain, waste & overflow
- Shower Door Series LO516











# 2603CTWWP


60 x 32 x 72 inches











FEATURES Ibs

Dimensional Tolerance ± %". Dimensions needed for site preparation should be measured from the unit. Aquatic assumes no responsibility for preparatory work.


			-	•				
Model #	Material	Wall Finish	Jets	Motor	Controls	Drain	Net Wt.	Pkg. Wt.
Soaker #2603CTW	AcrylX™	Textured Tile	0	_	_	LH or RH	129	134
Whirlpool #2603CTWWP	AcrylX™	Textured Tile	4	0.75 HP	Pneumatic	LH or RH	179	184

#### **DIMENSIONS**

Specifications	inches
Width: Overall / Net	60
Depth: Overall / Net	33 1/4 / 32
Height: Overall / Net	73 1/4 / 72
Enclosure Opening	56
Skirt Height	17
Drain Rough-In (from Back Wall)	15
Drain Rough-In (from Side Wall)	2 1/2
Drain: Diameter / Clearance	2 / 3/4

## FRAMING DIMENSIONS inches

Туре	<b>D</b> Depth	<b>W</b> Width	<b>H</b> Height	А	В	С
Alcove	33 1/4	60 1/8	=	Box Out	2 1/2	15



## SUMP DATA

Top of Drain to Bottom of Overflow	Capacity to Overflow gal	Min. Operating Capacity gal	WIDTH @	centerline	DEPTH @ centerline	
			Тор	Bottom	Тор	Bottom
12 1/4	50	45	53	43 <b>½</b>	22 <b>½</b>	20 ½