INTERCEPTORS


800 Series

Grease Interceptors, Series 800 - 801

Product Description: Recommended for removing, then retaining fat, oil, and grease from wastewater in kitchen and restaurant areas where food is prepared. The 800 series grease interceptor is constructed of coated fabricated steel with no-hub connections and separate flow control; a non-removable one-piece baffle; diamond plate, and non-skid cover.

Features and Benefits:

- Slip-resistant diamond plate cover
- Designed to be installed in above-the-floor installations or recessed where space is limited
- Constructed of fabricated steel.
- Regularly furnished with no-hub inlet and outlet, threaded available
- Low type grease interceptor is designed to be installed under the sink or in an area where space is limited
- Conforms to PDI Grease Interceptor Standard PDI-G101
- IAPMO Listed, File No. 2697 and C-3878
- Figure Numbers 800-Y & 800-T series, CSA Certified.





Flow Control for Series 800-801



FIG. NO.	GPM FLOW RATE	GREASE CAP LBS	А	В	С	D (LENGTH)	E (HEIGHT)	F (WIDTH)	G (Plug Size)
800-Y02-04	4	8	02"	6 7/8"	2 3/4"	12 1/4"	9 5/8"	13"	1 1/2"
800-Y02-07	7	14	02"	7 3/4"	3 1/4"	13 5/8"	11"	14 1/2"	1 1/2"
800-Y02-10	10	20	02"	8 3/4"	3 5/8"	15"	12 3/8"	15 3/4"	1 1/2"
800-Y02-15	15	30	02"	11 1/4"	3 1/2"	17 3/8"	14 3/4"	18 1/4"	1 1/2"
800-Y03-20	20	40	03"	12 3/4"	4"	19 3/8"	16 3/4"	20 1/4 "	1 1/2"
800-Y03-25	25	50	03"	14 1/4"	4 1/8"	21"	18 3/8"	21 3/4"	1 1/2"
800-Y03-35	35	70	03"	14 1/2"	4 1/2"	22 3/8"	19"	23 1/4"	1 1/2"
800-Y03-50	50	100	03"	14 1/2"	5 1/4"	31 5/8"	19 3/4"	23 1/4"	1 1/2"
LOW TYPE									
801-Y03-20	20	40	03"	7"	3 3/4"	39 1/2 "	10 1/2"	20 3/4"	1 1/2"
801-Y03-35	35	70	03"	7"	4 3/4"	52 1/4"	11 3/4"	26 3/4"	1 1/2"
801-Y03-50	50	100	03"	10"	5 15/16"	50 1/4"	15 15/16"	26 3/4"	1 1/2"
800-T02-04	4	8	02"	6 7/8"	2 3/4"	12 1/4"	9 5/8"	13"	1 1/2"
800-T02-07	7	14	02"	7 3/4"	3 1/4"	13 5/8"	11"	14 1/2"	1 1/2"
800-T02-10	10	20	02"	8 3/4"	3 5/8"	15"	12 3/8"	15 3/4"	1 1/2"
800-T02-15	15	30	02"	11 1/4"	3 1/2"	17 3/8"	14 3/4"	18 1/4"	1 1/2"
800-T03-20	20	40	03"	12 3/4"	4"	19 3/8"	16 3/4"	20 1/4"	1 1/2"
800-T03-25	25	50	03"	14 1/4"	4 1/8"	21"	18 3/8"	21 3/4"	1 1/2"
800-T03-35	35	70	03"	14 1/2"	4 1/2"	22 3/8"	19"	23 1/4"	1 1/2"
800-T03-50	50	100	03"	14 1/2"	5 1/4"	31 5/8"	19 3/4"	23 1/4"	1 1/2"
LOW TYPE									
801-T03-20	20	40	03"	7"	3 3/4"	39 1/2"	10 1/2"	20 3/4"	1 1/2"
801-T03-35	35	70	03"	7"	4 3/4"	52 1/4"	11 3/4"	26 3/4"	1 1/2"
801-T03-50	50	100	03"	10"	5 15/16"	50 1/4"	15 15/16"	26 3/4"	1 1/2"

NOTE: Dimensional data is subject to manufacturing tolerances and change without notice.











