

Regal® XL Flushometers 180-1.5 XL

▶ Code Number

3082442

► Flush Cycle

☐ 3.5 gpf/13.2 lpf

▶ Specifications

Quiet, Exposed, Diaphragm Type, Chrome Plated Urinal Flushometer with the following features:

- ADA Compliant Metal Oscillating Non-Hold-Open Handle
- 1" I.P.S. Screwdriver Bak-Chek® Angle Stop
- Control Stop Plug
- Sweat Solder Adapter with Cover Tube
- Cast Wall Flange with Set Screw
- Vacuum Breaker Flush Connection
- Spud Coupling Wall and Spud Flange for 11/4" Top Spud
- Non-Hold-Open Handle and No External Volume Adjustment to Ensure Water Conservation
- Low Consumption flush accuracy controlled by Para-FloTM Technology
- Diaphragm, Handle Packing and Vacuum Breaker Molded from PERMEX® Rubber Compound for Chloramine Resistance

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance with the applicable sections of ASSE 1037 and ANSI/ASME 112.19.2.


Accessories (Sold Separately)

See Accessories Section of the Sloan catalog for available accessories

▶ Fixtures

Consult factory for matching Sloan brand fixture options.





▶ Disclaimer

All information contained within this document subject to change without notice.

► Compliance & Certifications



Made In The





This space for Architect/Engineer Approval