

## **Protect the most expensive equipment in your home.**




highest SCCR THERMALLY PROTECTED SURGE PROTECTION DEVICE

**Surge Protection For:** Air Conditioners, Ductless Systems, Furnaces, Heat Pumps, Appliances, Motors and More.

## **Surge Device Overview**

The 5-2-1® Thermally Protected Surge Protection device is designed to protect HVAC equipment and other high end appliances from damaging electrical surges produced by proximity lightning strikes and other power line transients.

Engineered using the latest in Thermally Protected Metal Oxide Varistor (MOV) technology and independently tested to ensure superior protection and reliability for your customers.



## Surge Protection Highlights:

- Patented thermally protected MOV
- Type 1 or 2 installations A/C disconnect Junction box Electrical box
- NEMA 4X enclosure Outdoor / Indoor use
- Diagnostic indicator
  Green LED (ON) Device active
  Green LED (OFF) Replace device

Maximum Surge Current: 100,000 Amps

Service Voltage (VAC): 120/240 (Single - Split Phase), 50 or 60 Hz

Nominal Discharge Current Rating: 20kA

Maximum Continuous Operating Voltage (MCOV): 150VAC L-N 300VAC L-L

Voltage Protection Rating (VPR): 600VAC L-N/G 1200VAC L-L

**Operating Temperature:** 14 °F (-10 °C) to 122 °F (50 °C)

Approvals: UL 1449 4th Edition, ANSI, cUL

Warranty: 3 years and a Connected Equipment warranty up to \$10,000







www.five-two-one.com

MKG-LTTPSPD-0918B