STER Products

Blue Monster Power Deuce Brushing Tool Two Bruhes in One!

Clean fittings and tubing fast! The Power-Deuce is a multl-function brushing tool that prepares the inside of copper fittings and outside of copper tubing without having to change tools. Plus, if your drill quits, you can use it as a hand tool. It's fast and easy - saves time and money.

The Power-Deuce is a self-cleaning brush with rustproof, stainless steel bristles for plumbing and HVAC projects. A heavy-duty ABS housing is impact resistant and protects bristles so they retain their shape and prolongs brush life.



ROSE Clean-Fit Products

Cat #	Description	Std. Pkg.	Wgt./Pkg.	
	Counter/Shelf Display	ota r tig.	inguir kg.	
62820	1/2 I.D. (5/8" O.D.)	12	2.0 lbs.	
62830	3/4" I.D. (7/8" O.D.)	12	2.4 lbs.	
62840	1" I.D. (1-1/8" O.D.)	12	3.0 lbs.	
Power Pack with Quik Change Chuck Adapter				
62850	1/2 I.D. (5/8" O.D.) 3/4" I.D. (7/8" O.D.) 1" I.D. (1-1/8" O.D.)	6	1.2 lbs.	
Individua	ally Packaged on Blister (Card		
62821	1/2 I.D. (5/8" O.D.)	12	2.0 lbs.	
62831	3/4" I.D. (7/8" O.D.)	12	2.4 lbs.	
62841	1" I.D. (1-1/8" O.D.)	12	3.0 lbs.	

Blue Monster 1-Step Weatherproof PVC Cement Blue and Clear Formulas

Blue Monster 1-Step PVC cement is a self-priming PVC pipe glue that requires no additional primer. Blue Monster's 1-step joining process



simplifies installations by reducing labor and offers faster curing times before pressure testing. Ideal for under-the-sink jobs and home remodels. Use on all classes of rigid and flexible PVC pressure pipe, including Sch. 80, up to 6" in dia. and 8" dia. on nonpressure rigid and flexible PVC pipe.

Cat #	Description	Std. Pkg.	Wgt./Pkg.
Blue PVC	Cement		
76030	1/4 pint / 4 fl. oz. / 118 ml	24	10 lbs.
76032	1/2 pint / 8 fl. oz. / 237 ml	24	16 lbs.
76034	1 pint / 16 fl. oz. / 473 ml	12	15 lbs.
76036	1 quart / 32 fl. oz. / .95 liter	12	28 lbs.
Clear PV	C Cement		
76031	1/4 pint / 4 fl. oz. / 118 ml	24	10 lbs.
76033	1/2 pint / 8 fl. oz. / 237 ml	24	16 lbs.
76035	1 pint / 16 fl. oz. / 473 ml	12	15 lbs.
76037	1 quart / 32 fl. oz. / .95 liter	12	28 lbs.
			\frown

Medium Body - Low VOC

Blue Monster 1-Step PVC cement emits less than 510 grams per liter VOC when tested according to SCAQMD method 316 A.



*Use without primer where acceptable by local code.

BLUE MONSTER Products

Cat #

PSI rating:

Blue Monster® PTFE Thread Seal Tape - Mini-Monster Contractor Grade

Rugged, general purpose tape in a monstrous 1429" roll!

Ideal for hundreds of applications.

Blue Monster is a higher-guality PTFE sealing tape that is easier to apply. Blue Monster has not been stretched during the manufacturing process, so it is thicker and creates a more effective seal with less tape, and no need for pipe dope. Use Blue Monster on threads made from galvanized steel,



iron, brass, copper, aluminum, stainless steel, polyethylene, polypropylene, PVC, CPVC, ABS, fiberglass and more.

Specifications:

Composition:	99.6% PTFE < 0.4% Pigment
Color:	Blue
Thickness:	0.0035" +/-10% (0.0889 mm +/-10%)

Blue Monster Industrial Grade Thread Sealant

BLUE MONSTER Industrial Grade Pipe Thread Compound is a slow-drying, soft-setting,

non-hardening pipe thread compound. Specially formulated with superb "sticking" characteristics, BLUE MONSTER applies evenly and quickly to threads. Recommended for onsite or assembly line work, BLUE MONSTER is lead-free, non-toxic and will not harden or separate in the can.



70660	1/2" x 260"	144	720	5.5 lbs.	L
70661	1/2" x 520"	144	720	7.5 lbs.	L
70662	3/4" x 260"	100	500	5.0 lbs.	L
70663	3/4" x 520"	100	500	7.0 lbs.	L
70664	1" x 260"	120	600	8.0 lbs.	L
70665	1" x 520"	120	600	11.0 lbs.	L
70885	1/2" x 1429"	45	270	5.5 lbs.	L
70886	3/4" x 1429"	27	162	5.0 lbs.	L
70887	1" x 1429"	27	162	5.75 lbs.	L
70888	2" x 1429"	27	162	11.40 lbs.	L
Doneity	0.8a/cm ³				

Density: 0.8g/cm³ Elongation: 100%

Description



10,000 PSI (69,000 kPa) water and oil

Temperature range: -450°F to +500°F (-268°C to +260°C) PTFE is completely stable up to +500°F or +260°C. Decomposition is slow up to +750°F or +400°C. Decomposition will occur on contact with naked flames. 115N/mm² Tensile strength:

Gal#	Description	SIU. PKy.	wyu/rky.
76007	2 fl. oz. Squeeze Tube	24	4 lbs.
76009	1/4 pint / 4 fl. oz. / 118 ml	24	15 lbs.
76011	1/2 pint / 8 fl. oz. / 237 ml	24	23 lbs.
76015	1 pint / 16 fl. oz. / 473 ml	12	22 lbs.
76019	1 quart / 32 fl. oz. / .95 liter	12	48 lbs.
Meets Mil. Spec. TT-S-1732 Brushable from -50°F (-45°C) to +400 Pressure ratings: Gases up to 3,000 PSI Liquids up to 6,000 PSI		(211 kg/cm ²)	(NSF.)
	LIQUIOS UD TO 6.000 PSU	422 K0/Cm ²)	

Not recommended for use on oxygen systems. Use Clean-Fit 3-wrap Oxygen PTFE Tape.

(NSF.)
pw/dwv/sw Standard 14

Standard 61

Cat #	Description	Std. Pkg.	Wgt./Pkg.
76000	2 fl. oz. Squeeze Tube	24	4 lbs.
76001	1/4 pint / 4 fl. oz. / 118 ml	24	15 lbs.
76003	1/2 pint / 8 fl. oz. / 237 ml	24	23 lbs.
76005	1 pint / 16 fl. oz. / 473 ml	12	22 lbs.
76017	1 quart / 32 fl. oz. / .95 liter	12	48 lbs.

Meets Mil. Spec. TT-S-1732

Brushable from -50°F (-45°C) to +400°F (204°C) Pressure ratings: Gases up to 3,000 PSI (211 kg/cm²)



ANSI o/ww/w LC7-2009 ndard 6^{*}

Liquids up to 10,000 PSI (703.1 kg/cm²) Not recommended for use on oxygen systems. Use Clean-Fit 3-wrap Oxygen PTFE Tape.

Description	Std. Pkg.	Wgt./Pkg.
1/4 pint / 4 fl. oz. / 118 ml	24	18 lbs (8.2 kg)
1/2 pint / 8 fl. oz. / 237 ml	24	26 lbs (11.8 kg)
1 pint / 16 fl. oz. / 473 ml	12	25 lbs (11.3 kg)
1 quart / 32 fl. oz. / .95 liter	12	50 lbs (22.7 kg)
	1/4 pint / 4 fl. oz. / 118 ml 1/2 pint / 8 fl. oz. / 237 ml 1 pint / 16 fl. oz. / 473 ml	1/4 pint / 4 fl. oz. / 118 ml 24 1/2 pint / 8 fl. oz. / 237 ml 24 1 pint / 16 fl. oz. / 473 ml 12

Approved for use on all metal threaded connections, FlowGuard Gold®, Blazemaster®, and Corzan® pipe and fittings. Meets Mil. Spec. TT-S-1732 **Brushable from** -15°F (-20°C) to +400°F (204°C) Pressure ratings: Gases up to 5.000 PSI (351.5 kg/cm²) Liquids up to 10,000 PSI (703.1 kg/cm²)



The Mill-Rose Co. | Clean-Fit Products | 800.321.3598 | info@cleanfit.com | cleanfit.com

Blue Monster Industrial Grade Thread Sealant with PTFE

Formulated for extra lubrication on metal pipe threads, BLUE MONSTER Industrial Grade Thread Sealant with PTFE is a slow-drying, soft-setting, non-hardening pipe thread compound. BLUE

MONSTER has a high bulk density, which means there are more solids in the formulation. Recommended for on-site or assembly line work. It is leadfree, non-toxic and will not harden or separate in the can.



Blue Monster Stay-Soft Thread Sealant with PTFE

Blue Monster Stay-Soft PTFE enriched pipe thread compound does not harden and allows for pre-fab application to threads weeks before system assembly and pressurization. Stay-Soft is non-seizing and allows for easy disassembly of any threaded connection years



Clean-Fit Products



BLUE MONSTER Products

Std. Pkg.

12

12

Wgt./Pkg

9.4 lbs.

15.2 lbs.

Blue Monster[®] Copper Anti-Seize Sealant

Copper anti-seize lubricant for use on all metal pipe and fittings.

Mill-Rose Blue Monster Copper Anti-Seize is a specially formulated copper-based thread sealant for high temperature up to 1800°F (982°C) and high pressure environments. Blue Monster Copper Anti-Seize lubricant will not bleed, separate, or settle. Prevents pressure leakage and seizing resulting from high



16 oz. / 1.00 lb. / .454 kg Contains no grit. Prevents rust and corrosion.

10 oz. / .625 lb. / .283 kg

Copper anti-seize lubricant for use on all metal pipe and fittings.

• Temperature Range Use: Gases: -0°F (-17°C) to 1800°F (982°C) Liquids: -0°F (-17°C) to 1800°F (982°C) Brushable to: 10°F (-12°C) Pour Point: 32°F (0°C)

Description

Cat #

76024

76026

temperature, freezing, heavy loads, corrosion, and vibration.

Blue Monster® Nickel Anti-Seize Sealant

Pure nickel anti-seize compound for use on stainless steel pipe and fittings.

Blue Monster Nickel Anti-Seize is an extreme service anti-seize lubricant and thread sealant for use in a high temperature environment (up to 2600°F /1427°C). For use in applications where copper, lead, moly-disulfide, chlorides, and fluorides cannot be tolerated. Blue Monster Nickel

Anti-Seize lubricant is chemically inert and can be used with most chemicals that are unstable with copper-type compounds. Provides

Blue Monster Contractor Grade Abrasives

2" Width - 33% wider than traditional plumbers' rolls and 100% waterproof.

Blue Monster premium open mesh and Ultra-Flex® abrasive cloth are revolutionary, high-performance abrasives that are tough! Blue Monster outlasts all others in the most demanding conditions, wet or dry. Blue Monster's wide design provides more surface-to-surface coverage making it easier and faster to prep large-diameter tube and fittings.



- 21 x 21 Mesh Has larger holes than other open mesh products. This feature prevents "loading" and allows contractors to rinse the mesh clean. Resists clogging even when used on softer materials.
- · Premium blended 165 grit white Aluminum Oxide cuts and scores surfaces faster for more effective cleaning and deburring.

Blue Monster Six-in-One Brush

Blue Monster Six-in-One Brush cleans the inside diameter of 1/2" and 3/4" fittings and outside diameter of 1/2" and 3/4" tubing. The deburing plate reams and deburs the I.D. of tubing, has a b-tank gas key (square opening on plate), and also serves as a bottle opener.



Cat #	Description	Std. Pkg.	Wgt./Pkg.
76020	8 oz. / .500 lb. / .277 kg	12	10 lbs.
76022	16 oz. / 1.00 lb. / .454 kg	12	19 lbs.

excellent resistance to chemical oxidation and/or corrosion. Prevents rusting, seizing, welding, or galling. Not for use on potable water systems.

- High temperature lubricant and thread sealant for use on stainless steel, PVC, CPVC, nylon, polypropylene, plastics and all metals.
- Temperature Range Use: Gases: -0°F (-17°C) to 2600°F (1427°C) Liquids: -0°F (-17°C) to 2600°F (1427°C) Brushable to: 10°F (-12°C) Pour Point: 32°F (0°C)

Cat #	Description	Std. Pkg.	Wgt./Pkg.
Blue Mo	onster Open Mesh		
70151	2" x 8" mini strips (10)	12	1.85 lbs.
70152	2" x 5 yard roll	12	6.20 lbs.
70154	2" x 10 yard roll	12	10.50 lbs.
70156	2" x 25 yard roll	12	22.00 lbs.
Blue Mo	onster Ultra-Flex		
70171	2" x 8" mini strips (10)	12	1.85 lbs
70172	2" x 5 yard roll	12	5.00 lbs.
70174	2" x 10 yard roll	12	8.75 lbs.
70176	2" x 25 yard roll	12	20.00 lbs.



- Super flexible Ultra-Flex® backing conforms to tight work areas and Blue Monster will not crack or tear during use.
- · Premium 150 grit cuts and scores surfaces faster for more effective cleaning and deburring.

Cat #	Description	Std. Pkg.	Wgt./Pkg.
70255	1/2" x 3/4" ID Brush/Deburrer	10	3.50 lbs.
70269	1/2" x 3/4" Replacement Kit	6	.60 lbs.
70271	Adapter Kit (Deburring plate)	6	.50 lbs.

The Mill-Rose Co. | Clean-Fit Products | 800.321.3598 | info@cleanfit.com | cleanfit.com

BLUE MONSTER Products

Blue Monster Heavy-Duty Citrus Scrubbing Towels Description Clean hands, tools, equipment, and hard surface 77095 75 10" x 12" Towels 20 320 57 lbs. areas with these convenient scrubbing towels. Keep hands, tools and hard surfaces clean from ... BLUE MONSTER scrubbing towels are pre-moistened, Adhesives Asphalt · Heavy Soil heavy-duty cleaning towels dispensed from a handy, • Flux Grease • Grime flip-top container. They are saturated with a safe, • Paint • Pipe Dope Oils & Inks effective cleaning solution combined with a tough, dual-• Tar Lubricants Caulk textured towel to loosen, dissolve and absorb dirt and Pipe Cements Urethanes & More grease leaving your hands clean. One side is rough for scrubbing and the other side is smooth. These towels require no water and leave hands feeling conditioned Free Hand & Nail Brush Attractive floor display and clean with no left-over residue. included in each container! grabs consumer's attention.

Blue Monster Advantage Closet Bolts

Our bolt's patented broach-tip design gives the installer the direction of the foot underneath the flange. Each kit includes 2 solid brass bolts, 2 solid brass hex nuts, 2 solid brass open-ended acorn hex nuts, 4 stainless steel washers and 2 nylon tinnerman nuts. Not only does our bolt provide foot direction but also provides a true hold-back and break-off eliminating the need for a hacksaw.

Blue Monster[®] Compression Seal Tape

Stops problem leaks under pressure without turning off the water source!

Blue Monster[®] Compression Seal Tape features selffusing layers that form a waterproof compression seal. Seal leaks while under pressure - up to 150 PSI on any type of rigid piping material, from galvanized and cast iron to copper and all types of plastics and rubber.

Blue Monster Compression Seal Tape contains no adhesive and is ideal for crisis and long-term applications. This tape seals by compression, so pulling the tape as tight as possible forms a chemical reaction that fuses the layers of tape into a mass of silicone.

Elongation:



Specifications: Thickness: 0.045" Tear Resistance: ~ 12 lbf/in UV Resistance: Highly UV r

Highly UV resistant >325%

9	Cat #	Description	Std. Pkg.	Wgt./Pkg.	
	73065 73070	5/16" x 2-1/4" 5/16" x 3-1/2"	100 100	16 lbs. 22 lbs.	And strengthere
	Indicates foot	t direction	Raised knobs on underside prevents movement after installation.		

	Cat #	Descripti	on	Std. Pkg.	Master Pkg.	Wgt./Pkg.	
	76084	1" x 12"	Strip/Pack	20	80	.35 lbs.	
	76085 1" x 12-1		oot Rolls	10	40	3.5 lbs.	
	76086	2" x 12-1	oot Rolls	6	24	4.0 lbs.	
1	Adhesion(Fusion):		Standard requirement: "Tape shall not unwind more than 1.0 inch after 3 minutes with an attached load of 600g. Result: <1 inch				
1	Temperature range: Thermal Stability:		-90°C to +260°C / -130°F to 500°F				
1			-900°C to +260°C / -130° to 500°F continuous				
1	Tensile strength:		~ 1200 PSI throughout temperature range				
A	Acid/Alkaline/Chlorine: Self-Extinguising:		No negative effect from brief exposure to acids, alkaline or chlorine and can withstand submersion up to 3 days.				
5			UL standard 94 rating V-O. Tested to IEEE 383 and IEEE 1202 for flammability, self-extinguishes and will not propagate a flame.				
S	Standards Cor	mpliance:	MIL-I-46852 Monster Con	, ASTM D214 npression Se	-59163, ASTM 8, ASTM D3767 al Tape specific ards not include	' Blue cations meet	

Blue Monster® Drain Banger

Professional strength, odorless drain opener

Blue Monster Drain Banger devours hair, grease, soap and oils that slow and plug drain lines in less than 60 seconds! Blue Monster Drain Banger is a hot water activated non-acid drain cleaner designed to be used by professional contractors



Cat #	Description	Std. Pkg.	Wgt./Pkg.
76055	1 lb. (453 g)	24	26 lbs.
76057	2 lbs. (907 g)	12	26 lbs.
76059	6 lbs. (2722 g)	4	24 lbs.

only. It is odorless and will not harm plumbing fixtures, porcelain or septic systems.

- Devoirs hair, grease, soap, oils and other organic materials that slow and plug drain lines in less than 60 seconds!
- For professional contractors only!
 Non-Acid