
## Nashua PRODUCTS РΕ PROFESSIONALS CHOICE



## **Multi-Purpose Duct Tape**



Backing:	PE Coated Cloth		
Adhesive:	Rubber		
Liner:	N/A		
Colors:	Silver, Black		
Specification	s: Tested in accordance with UL 723		
Standard Siz	es: 48mm x 55m, 72mm x 55m		

## **Applications**

- General repair
- General purpose construction uses
  - Floor and aisle marking

- Bundling, patching, and mending •
- Seaming and hanging polyethylene sheeting •

Features	Benefits
PE-Coated Cloth Backing	<ul> <li>Conforms well to irregular surfaces</li> </ul>
	<ul> <li>Resists twisting and curling</li> </ul>
Natural Rubber Adhesive	<ul> <li>High adhesion and holding power for both rough and smooth surfaces</li> </ul>
Low VOC Content	<ul> <li>Can contribute toward satisfying EQ Credit 4.1 (Low Emitting Materials) under LEED®</li> </ul>

Typical Test Values					
	Standard UOM	Metric UOM	Test Method		
Total Thickness	10.0 mils	0.254 mm	ASTM D-1000		
Adhesion to Steel	75 oz/in	8.21 N/cm	PSTC-101		
Tensile Strength	24 lb/in	42.03 N/cm	ASTM D-1000		
Elongation	21%		ASTM D-1000		
Operating Temperature	40 to 200 °F	4 to 93 °C			
VOC Content	<1 g/L				

Recommended Storage Conditions: 32-90 °F at 50% RH ± 2%

Standard Shelf Life (at 25C): 36 months from date of manufacture. the product is suitable for the intended use, and that such use complies with all applicable federal, state and local laws and regulations. The data are typical values submitted only for the user's information and consideration, and do not constitute a warranty of any kind (including but not limited to a warranty of merchantability or of fitness for a particular purpose), or a representation for which BERRY PLASTICS assumes any legal responsibility.



25 Forge Pkwy Franklin, MA 02038 1-800-343-7875 Fax 1-800-328-4822 www.berryplastics.com 9/30/15