


EASY 3 COLORS
SELECTOR
3500K • 4000K • 5000K



NOMINAL LUMENS	DELIVERED LUMENS	WATTAGE
4000L/5000L/6000L	5850	45
	5895	45
	5940	45
	5054	38
	5092	38
	5130	38
	4624	34
	4658	34
	4692	34

Based on 4000K, 85+ CRI. Actual wattage may vary +/- 5%

FEATURES

The OWVS LED Vapor Tight is a wet location luminaire designed to withstand exposure to harsh weather and areas where water might be a hazard. Qualifies as emergency lighting, which lights a safe path of egress for evacuation. Shallow, lightweight design permits quick, easy installation. A wide beam spread and excellent glare control make it perfect for a number of egress lighting applications. Complies with building and safety codes to safely light parking garages, schools, car washes, corridors, hallways, stairways, food processing, cold storage, and other industrial facilities.

LUMENS	4000L/5000L/6000L
CCT	35K/40K/50K
CRI	85+
COLOR QUALITY	3 Step MacAdam Ellipse
LENGTH	4' or 8'
MOUNTING	Surface
DIMMING & CONTROL	0-10V Flicker Free 10% Dimming Standard (DIM10)
EMERGENCY	10W - Up to 1000L output
LIFETIME	L70 at 100,000 Hours
PHOTOMETRIC TESTS	In Accordance with IES LM79-08, LM80 and TM-30, TM-21



MAINTENANCE

Two-piece, snap-together design for fast, easy installation. Simple two-piece design consists of housing and optical assembly to streamline installation process.

OPTICS

Frosted lens is easy to install with clips that secure lens to housing and ensure vapor-tight operation. Frosted lens prevents discoloration and allows for maximum glare control.

MOUNTING

Suitable for suspension by V-hook or surface mounting. All required hardware is included (less chain, cable).

CONSTRUCTION

One-piece, durable fiberglass housing. Continuous one-piece gasket provides airtight seal, keeping out condensation, humidity, dirt, and dust. Latches securely attach to the housing, keeping the housing and lens securely in place.

DRIVER ELECTRICAL INFORMATION

Powered by high-quality constant-current power LED drivers rated for 50 to 60Hz at 120/277V input. Available in 347V, produce less than 20% THD, and have a power factor of .90 to 1.00.

DIMMING & DRIVER INFORMATION

DIM10 - Flicker Free 10% Dimming Standard (DIM10) 0-10V dimming on either MVOLT 120, 277 or 347V.

WARRANTY

Five-year warranty for parts and components. (Labor not included).

LISTINGS

UL/C-UL listed to US and Canadian standard
IP65 Rated
ANSI/UL 8750
ANSI/UL 1598
DLC listed

Example: **4-OWVS1-LED-4000L/5000L/6000L-DIM10-MVOLT-35K/40K/50K-85**

