SIEMENS

Data sheet US2:52PP2W2A




Figure similar

30mm Command/52, Chrome Finish Heavy Duty, Watertight/Oiltight Complete Metal Unit Push-Pull Operator Non-Illuminated Mushroom Head Cap Small 1 3/4" (44.5 mm) Plastic, Red 2 Position Maintained, Pull-to-Release with 1 N.O. - 1 N.C. Heavy Duty Contacts, A600/P600 UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

Enclosure		
Number of command points	1	
Delivery state		
● as a kit	No	
Actuator		
Material of the actuating element	plastic	
Number of contact modules	1	
Type of unlocking device	pull-to-unlatch mechanism	
Number of switching positions	2	
Front ring		
Product component front ring	Yes	
Design of the front ring	standard	
Material of the front ring	metal	
General technical data		
Product function		
• positive opening	Yes	

Product component	
• Light source	No
Insulation voltage	
• rated value	600 V
Surge voltage resistance rated value	4 kV
Protection class IP	IP66
• of the terminal	IP20
Thermal current	10 A

1
1
60 A
30 A
15 A
12 A

Connections/ Terminals	
Type of electrical connection	screw-type terminals
Tightening torque of the screws in the bracket	20 N·m
Tightening torque [lbf·in]	
with screw-type terminals	8 lbf·in

Ambient conditions	
Ambient temperature	
 during operation 	-35 +70 °C
during storage	-40 +85 °C

Installation/ mounting/ dimensions	
Shape of the installation opening	round

Certificates/ approvals

Further information

Ambient conditions

Information- and Downloadcenter (Catalogs, Brochures,...)

www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52PP2W2A

Cax online generator

 $\underline{\text{http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en\&mlfb=US2:52PP2W2A} \\$

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/US2:52PP2W2A

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52PP2W2A&lang=en

last modified: 12/18/2019