## **SIEMENS**

Data sheet US2:52SA2BAB

Metal, selector switch Maintained, short lever position, B Cam 3 position Operator only white insert Non-Illuminated UL file E22655 in Vol. 6 (7) Sec. 13 (2)



Figure similar

Design of the product	Actuator round	
Enclosure		
Number of command points	1	
Delivery state		
● as a kit	No	
Actuator		
Design of the operating mechanism	selector switch	
Material of the actuating element	plastic	
Type of unlocking device	rotate-to-unlatch mechanism	
Number of switching positions	3	
Front ring		
Product component front ring	Yes	
Design of the front ring	standard	
Material of the front ring	metal	
Color of the front ring	chrome	
Holder		

Material of the holder	Metal	
General technical data		
Product component		
• Light source	No	
Degree of pollution	1	
Protection class IP	IP66	
Operating frequency maximum	600 1/h	
Ambient conditions		
Ambient temperature		
<ul><li>during operation</li></ul>	-35 +70 °C	
during storage	-40 +85 °C	
Installation/ mounting/ dimensions		
Shape of the installation opening	round	
Certificates/ approvals		

## Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

www.siemens.com/sirius/catalogs

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SA2BAB

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52SA2BAB

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/US2:52SA2BAB

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) <a href="http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=US2:52SA2BAB&lang=en">http://www.automation.siemens.com/bilddb/cax\_de.aspx?mlfb=US2:52SA2BAB&lang=en</a>

last modified: 11/13/2019