DULE

LED











CERTIFICATIONS

- cULus
- RoHS
- IECC

- New York state
- UL/cUL Listed for Wet
- UL/cUL Listed for Damp Location
- California Title 24
- Washington state
- LM79/LM80

UNIQUELY ENGINEERED FOR NEW AND EXISTING CONSTRUCTION

The RL631 is the newest, most efficient, and advanced LED retrofit modules from ELITE Lighting. It's unique design delivers color quality above a 90 CRI rating. The color matching has never been so close, with a binning as low as 3 MacAdams ellipses. The RL631 LED retrofits meet all new mandatory California Title 24 requirements.

The Elite RL631 LED Module has been engineered for new constructions to meet Title-24's "No Edison Socket" mandate. The Elite RL631 LED system works in our dedicated (LD6IC-AT and LD6RIC-AT) housings and our existing 6" Incandescent housings (B6IC-AT, EZ6IC-AT, B26IC-AT, B26RIC-AT) but is also suitable for using in most 6" Incandescent recessed downlight housings in the market.

INPUT VOLT.	INPUT FREQ.	THD	POWER FACTOR	INPUT POWER	LUMENS
120	50/60Hz	<20%	>0.9	15W(+/-5%)	950

FEATURES

- Over 950 usable lumens are directed from the luminaire to the work surface
- Greater light output than a 26W CFL or a 65W BR30 while consuming less than 15W of power
- Rated at 90+ CRI to meet California Title-24 strict compliance standards
- Life tested to ensure light output up to 50,000 hours of operation to L70
- Glare reducing cut-off angle of 55 degrees
- High performance optic hides LED chip image but still delivers an even beam of light
- Elite's highly selective LED chips produce zero ultraviolet and virtually no infrared light
- Tested to LM-79 and LM-80 standards
- · UL listed for safety

7.4"

DURABILITY

Our die-cast system pulls the heat from the LED chip, allowing the continued cool operation for years. Our LED driver is rated for 50 to 60 Hz at 120V input, and produces less than 20% THD, has a power factor between 0.90 and 1.00 and is thermal protected for additional safety.

DIMMABLE

The Elite LED Module is dimmable down to 15% of initial light output with compatible dimmers. Consult factory for complete list of compatible dimming systems.

OUR WORD

The Elite LED lighting system carries a five-year carefree warranty for parts and components. (Labor not included)

INSTALLATION

Ez connector to use with special High efficacy housing or Edison base adapter for retrofitting into existing 6" incandescent housings.

- Utilizes industry standard V springs, installs in most 6" incandescent downlights.
- Insert V springs into can and press trim to ceiling.

Elite's innovative LED retrofit downlight modules deliver the brightest, most beautiful and most energy efficient ambient lighting to replace any lamp type on your existing fixture.

Example: RL635-950L-DIMTR-120-30K-90-W-WH

T	YPE	LUMEN SERIES	CCT	CRI	FINISH	OPTION
1.7	L631 Baffle)	□ 950L-DIMTR-120	□ 27K /30K /35K /40K /50K	90	□ W-WH	GU24SA GU24 SOCKET ADAPTER

Ordering Guide for Compatible Housing					
.IC - New Construction	Non-IC New Construction	IC - For Remodel	Non-IC For Remodel		
LD6IC-AT	LD6-AT		LDCD AT		
LDOIO AI	LD0-A1	LD6RIC-AT	LD6R-AT		
HLD6IC-AT	HLD6-AT	HLD6RIC-AT	HLD6R-AT		

*RECOMMENDED DIMMERS FOR ELITE RL631 LED SYSTEM

LUTKUN DIMIMEKS				
INCANDESCENT				
Diva DVCL-153P Skylark CTCL-153P Nova N-600 NovaT NT-600 Skylark S-600 Ariadni AY-600P Nova NTLV-600 Nova NLV-600	Maestro MRF2-6ND NovaT NTELV-600 Diva DVELV-300P Skylark SELV-300P Nova NELV-450 Skylark S-1000 Decora 06633-766 Decorra 6674 Toggle Dimmer TGI06-1LW	No No Di Le	o i\	

LUTRON CONTROL SYSTEM MAGNETIC LOW VOLTAGE

NovaNLV-600 NovaT NTLV-600 Diva DVLV-600P Leviton Dimmer 6613-PL

LED

RETROFIT

MODULE