



Above Ground Pedestal Connectors & Covers T&B Catalog Number:

CSB 4-4

UPC Number: 78378671492

Status: Active

Description:

Aluminum Multi-Tap Encapsulated Cable Blocks - two-way configuration, wire range 4-14, screw size slotted, length 2 1/16", width 1 5/8", height 1 5/16", outlets 4

tions. Clear PVC Insulation. Safe and time saving instal tion with no taping required. Style Aluminum Cable Blocks Material Aluminum Conductor Range 14-Apr Outlets 4 Screw Type Slotted Dimension Information Length (inches) 2 1/16 Width (inches) 1 5/8 Height (inches) 1 5/8 Certifications Standards Compliant Meets or Exceeds ANSI C119.4 specifications. Use	Ji TO , Odilets 4	
number of outlets available in one-way configurations. Clear PVC Insulation. Safe and time saving instal tion with no taping required. General Style Aluminum Cable Blocks Material Aluminum Conductor Range 14-Apr Outlets 4 Screw Type Slotted Dimension Information Length (inches) 2 1/16 Width (inches) 1 5/8 Height (inches) 1 5/8 Certifications Standards Compliant Meets or Exceeds ANSI C119.4 specifications. Use	Features	
tion with no taping required. General Style Aluminum Cable Blocks Material Aluminum Conductor Range 14-Apr Outlets 4 Screw Type Slotted Dimension Information Length (inches) 2 1/16 Width (inches) 1 5/8 Height (inches) 1 5/8 Certifications Standards Compliant Meets or Exceeds ANSI C119.4 specifications. Ut		number of outlets available in one-way configura-
Style Aluminum Cable Blocks Material Aluminum Conductor Range 14-Apr Outlets 4 Screw Type Slotted Dimension Information Length (inches) 2 1/16 Width (inches) 1 5/8 Height (inches) 1 5/8 Certifications Standards Compliant Meets or Exceeds ANSI C119.4 specifications. Use		Clear PVC Insulation. Safe and time saving installa-
Style Aluminum Cable Blocks Material Aluminum Conductor Range 14-Apr Outlets 4 Screw Type Slotted Dimension Information Length (inches) 2 1/16 Width (inches) 1 5/8 Height (inches) 1 5/8 Certifications Standards Compliant Meets or Exceeds ANSI C119.4 specifications. Use		tion with no taping required.
Material Aluminum Conductor Range 14-Apr Outlets 4 Screw Type Slotted Dimension Information Length (inches) 2 1/16 Width (inches) 1 5/8 Height (inches) 1 5/8 Certifications Standards Compliant Meets or Exceeds ANSI C119.4 specifications. Ut	General	
Conductor Range 14-Apr Outlets 4 Screw Type Slotted Dimension Information Length (inches) 2 1/16 Width (inches) 1 5/8 Height (inches) 1 5/8 Certifications Standards Compliant Meets or Exceeds ANSI C119.4 specifications. Ut	Style	Aluminum Cable Blocks
Outlets 4 Screw Type Slotted Dimension Information Length (inches) 2 1/16 Width (inches) 1 5/8 Height (inches) 1 5/8 Certifications Standards Compliant Meets or Exceeds ANSI C119.4 specifications. Use	Material	Aluminum
Screw Type Slotted Dimension Information Length (inches) 2 1/16 Width (inches) 1 5/8 Height (inches) 1 5/8 Certifications Standards Compliant Meets or Exceeds ANSI C119.4 specifications. Use	Conductor Range	14-Apr
Dimension Information Length (inches) 2 1/16 Width (inches) 1 5/8 Height (inches) 1 5/8 Certifications Standards Compliant Meets or Exceeds ANSI C119.4 specifications. Ut	Outlets	4
Length (inches) 2 1/16 Width (inches) 1 5/8 Height (inches) 1 5/8 Certifications Standards Compliant Meets or Exceeds ANSI C119.4 specifications. Ut	Screw Type	Slotted
Width (inches) 1 5/8 Height (inches) 1 5/8 Certifications Standards Compliant Meets or Exceeds ANSI C119.4 specifications. Ut	Dimension Information	
Height (inches) 1 5/8 Certifications Standards Compliant Meets or Exceeds ANSI C119.4 specifications. Ut	Length (inches)	2 1/16
Certifications Standards Compliant Meets or Exceeds ANSI C119.4 specifications. Ul	Width (inches)	1 5/8
Standards Compliant Meets or Exceeds ANSI C119.4 specifications. Ul	Height (inches)	1 5/8
·	Certifications	
Listed.	Standards Compliant	Meets or Exceeds ANSI C119.4 specifications. UL Listed.

For further technical assistance, please contact us...

T&B Technical Support MS 3B-50 8155 T&B Blvd. Memphis, TN 38125 Hours: 7AM - 6PM CDT Monday-Friday Phone: (888) 862-3289 Fax: (901) 252-1321 Email:techsupport@tnb.com

Thomas & Betts - USA 8155 T&B Blvd. Memphis, TN 38125 www.tnb.com