



Search Parameters:

[e-Catalog](#) > [Switches & Disconnects](#) > [Disconnect & Safety Switches](#)

Switches & Disconnects, Disconnect & Safety Switches

Product #: TH3363R

Short Description: 100A 3P HD SS N3R 600V FUSIBLE SW.

[Print This Page](#)

[Email This Page](#)

SPECIFICATIONS

| | |
|--------------------|-------------------|
| Category | Heavy Duty |
| Voltage | 600 AC |
| Amperage | 100 A |
| Poles | 3 |
| Wires | 3 |
| Fusing | Fusible |
| Enclosure | NEMA 3R (Outdoor) |
| Options | None |
| Height | 22.05 in |
| Depth | 4.86 in |
| Width | 9.33 in |
| Weight | 19.0 lb |
| Wire Range (Cu/Al) | 10-1/0 |
| 250 Vdc | 40 hp |
| GSA Compliance | Yes |
| CSA Certified | Yes |
| UL Listed | Yes |
| GO Schedule | 131 |
| List Price | \$1058 |



[View Larger](#)

Publications/Resources

[TH3363R](#)

Additional Resources for Heavy Duty

[Application and Technical](#)

[Brochures](#)

[Drawings-Outline and Dimensional](#)

[BIM Files](#)

[Buy Log :2-11](#)

- Designed for commercial and industrial applications where safety, high performance and continuity of service are essential.
- Listed to UL standard 98 enclosed and dead front switches.
- Suitable for use as service equipment when installed in accordance with the National Electrical Code.
- Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches.
- Meets or exceeds NEMA KS1 standard for enclosed switches - type HD.
- Fusible and non-fusible switches available (consult BuyLog for interrupt ratings).
- Quick-make, quick-break mechanism.
- 60/75°C conductor rating.
- Full cover interlocks.
- NEMA type 4X enclosure grade 304 stainless steel (catalog numbers with SS suffix).

