

Search Parameters:
[e-Catalog](#) > [Switches & Disconnects](#) > [Disconnect & Safety Switches](#)
Switches & Disconnects, Disconnect & Safety Switches

Product #: TG3223R

Short Description: 100A 2P GD SS N3R 240V FUSIBLE SW.

 [Print This Page](#)
 [Email This Page](#)
SPECIFICATIONS

Category	General Duty
Voltage	240 AC
Amperage	100 A
Poles	2
Wires	3
Fusing	Fusible
Enclosure	NEMA 3R (Outdoor)
Options	None
Height	21.05 in
Depth	5.04 in
Width	9.32 in
Weight	17.0 lb
Wire Range (Cu/Al)	10-1/0
240 Vac, NEC Std, 1-ph	7 hp
240 Vac, NEC Std, 3-ph	15 hp
240 Vac, Time Delay, 1-ph	15 hp
240 Vac, Time Delay, 3-ph	30 hp
250 Vdc	20 hp
GSA Compliance	Yes
CSA Certified	Yes
UL Listed	Yes
GO Schedule	131A
List Price	\$313


 [View Larger](#)
Publications/Resources
[TG3223R](#)
Additional Resources for General Duty
[Application and Technical](#)
[Brochures](#)
[Drawings-Outline and Dimensional](#)
[BIM Files](#)
[Buy Log :2-6](#)

- Designed for residential and light commercial applications where duty is not severe.
- Listed to UL standard 98 enclosed and dead front switches.
- Suitable for use as service equipment when installed in accordance with the National Electrical Code.
- Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches.
- Meets or exceeds NEMA KS1 standard for enclosed switches - type GD.
- Fusible and non-fusible switches available (consult BuyLog for interrupt ratings).
- Quick-make, quick-break mechanism (30-200 amp).
- 60/75°C conductor rating.