



[home](#)

[products](#)

[services](#)

[markets](#)

[resources](#)

[your business](#)

[Buy Online!](#) | [My Cart](#)

**Search Parameters:**

[e-Catalog](#) > [Switches & Disconnects](#) > [Disconnect & Safety Switches](#)

**Switches & Disconnects, Disconnect & Safety Switches**

Product #: TG3221R

Short Description: 30A 2P GD SS N3R 240V SAFETY SWITCH

[Print This Page](#)

[Email This Page](#)

**SPECIFICATIONS**

|                           |                   |
|---------------------------|-------------------|
| Category                  | General Duty      |
| Voltage                   | 240 AC            |
| Amperage                  | 30 A              |
| Poles                     | 2                 |
| Wires                     | 3                 |
| Fusing                    | Fusible           |
| Enclosure                 | NEMA 3R (Outdoor) |
| Options                   | None              |
| Height                    | 9.78 in           |
| Depth                     | 3.31 in           |
| Width                     | 6.38 in           |
| Weight                    | 6.0 lb            |
| Wire Range (Cu/Al)        | 14-8 CU;12-8 AL   |
| 240 Vac, NEC Std, 1-ph    | 1 hp              |
| 240 Vac, NEC Std, 3-ph    | 3 hp              |
| 240 Vac, Time Delay, 1-ph | 3 hp              |
| 240 Vac, Time Delay, 3-ph | 7 hp              |
| 600 Vdc                   | 5 hp              |
| GSA Compliance            | Yes               |
| CSA Certified             | Yes               |
| UL Listed                 | Yes               |
| GO Schedule               | 131A              |
| List Price                | \$124             |



[View Larger](#)

**Publications/Resources**

[TG3221R](#)

**Additional Resources for General Duty**

[Application and Technical](#)

[Brochures](#)

[Drawings-Outline and Dimensional](#)

[BIM Files](#)

[Buy Log :2-6](#)

- Designed for residential and light commercial applications where duty is not severe.
- Listed to UL standard 98 enclosed and dead front switches.
- Suitable for use as service equipment when installed in accordance with the National Electrical Code.
- Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches.
- Meets or exceeds NEMA KS1 standard for enclosed switches - type GD.
- Fusible and non-fusible switches available (consult BuyLog for interrupt ratings).
- Quick-make, quick-break mechanism (30-200 amp).
- 60/75°C conductor rating.

