



**Search Parameters:**

[e-Catalog](#) > [Switches & Disconnects](#) > [Disconnect & Safety Switches](#)

**Switches & Disconnects, Disconnect & Safety Switches**

Product #: TG3222

Short Description: 60A 2P GD SS N1 240V FUSIBLE SW

[Print This Page](#)

[Email This Page](#)

**SPECIFICATIONS**

Category	General Duty
Voltage	240 AC
Amperage	60 A
Poles	2
Wires	3
Fusing	Fusible
Enclosure	NEMA 1 (Indoor)
Options	None
Height	13.84 in
Depth	4.0 in
Width	8.38 in
Weight	10.0 lb
Wire Range (Cu/Al)	12-2
240 Vac, NEC Std, 1-ph	3 hp
240 Vac, NEC Std, 3-ph	7 hp
240 Vac, Time Delay, 1-ph	10 hp
240 Vac, Time Delay, 3-ph	15 hp
250 Vdc	3 hp
600 Vdc	10 hp
GSA Compliance	Yes
CSA Certified	Yes
UL Listed	Yes
GO Schedule	131A
List Price	\$135



[View Larger](#)

**Publications/Resources**

[TG3222](#)

**Additional Resources for General Duty**

[Application and Technical](#)

[Brochures](#)

[Drawings-Outline and Dimensional](#)

[BIM Files](#)

[Buy Log :2-6](#)

- Designed for residential and light commercial applications where duty is not severe.
- Listed to UL standard 98 enclosed and dead front switches.
- Suitable for use as service equipment when installed in accordance with the National Electrical Code.
- Certified to CSA standard 22.2 no. 4-04 enclosed and dead front switches.
- Meets or exceeds NEMA KS1 standard for enclosed switches - type GD.
- Fusible and non-fusible switches available (consult BuyLog for interrupt ratings).
- Quick-make, quick-break mechanism (30-200 amp).
- 60/75°C conductor rating.

