

Simple Remote Control (without operation Mode)

Job Name: \_\_\_\_\_  
 Location: \_\_\_\_\_  
 Engineer: \_\_\_\_\_  
 Submitted to: \_\_\_\_\_  
 Submitted by: \_\_\_\_\_  
 Reference: \_\_\_\_\_

Date: \_\_\_\_\_  
 Approval: \_\_\_\_\_  
 Construction: \_\_\_\_\_  
 Unit #: \_\_\_\_\_  
 Drawing #: \_\_\_\_\_



**General Features**

This is a stylish 2-wire Remote control without Mode change capability. It offers built-in temperature sensor for better comfort. In addition, it offers temperature set point adjustment in 1°F increments.

**Features**

- Built in room temperature sensor in the remote.
- Operation Mode without options control.
- Temperature adjustment in 1°F increments.
- Vertical louver adjustment for all indoor units.
- Temperature set point range limitation without central controller.
- Control, Start/Stop, operation mode, temperature setting and test operation.
- Stylish design & operation button.
- Backlight large LCD screen.
- Max. 16 indoor units can be connected to one remote.

**Electrical**

Power Supply DC (V) ..... 12  
 Max Power consumption (W) ..... 0.3  
 Remote control Wire Size (AWG) ..... 22 to 16  
 Wire Type ..... Non-polar 2 core shielded twisted pair cable

**Temperature**

Operating Temperature Range °F (°C) ..... 32 - 114 (0 ~ 46)  
 Storage Temperature Range °F (°C) ..... 4 - 158 (-20 ~ 70)  
 Humidity range (%) ..... 0 – 95 (no condensation)

**Weight and Dimensions**

Weight oz.(g) ..... 4 (120)  
 Dim.Net (HxWxD) in(mm) ..... 4-3/4 x 2-15/16 x 3/4  
 (120 x 75 x 19)

**Connections**

Maximum Indoor units connected to one Remote Group ..... 16  
 Maximum remotes under one Group..... 4

- This remote controller is compatible with all VRF A\*\*\*TLAV1 indoor units.
- This remote controller is not compatible with all VRF A\*\*\*RLAV/ VRF TLAV indoor units.

## Simple Remote Control (without operation Mode)

### Functions

Item			
Model name		UTY-RSRY	UTY-RHRY
Control	ON/OFF	●	●
	Operation mode setting	●	-
	Fan speed setting	●	●
	Room temp. setting	●	●
	Vertical louver position setting	●	●
	Room temp. set point limitation	●	●
	Test Operation	●	●
Display	Room temp.	●	●
	Error	●	●
	Defrosting	●	●
	R.C. Prohibition	●	●
	Cooling/Heating priority	●	●
	Filter sign	●	●
	Address display	●	●
	Backlight	●	●

● Supported function

### Dimensions

Unit: in (mm)

