

Global leaders in flexible couplings,
drainage & plumbing systems



ICON Pushfit

Internal Pushfit Connector - 4" & 6" Sewer Pipe and DWV



Simple, fast
pushfit
connection



Benefits

- Internal Pushfit connection - no tools required
- Can be installed in 30 seconds or less
- Install in sheared off pipe where standard couplings cannot be used
- No need to expose external surface of pipe
- Can be removed and re-used
- Watertight connection on any pipe material
- Connects pipes of differing or irregular outside diameters
- Pipe stop indicates that the product is properly installed, when it is flush to the pipe end
- Internal lip ensures smooth transition
- Rigid ABS Body provides excellent shear resistance
- Ideal for the connection of plastic (SDR 35, Sch 40), Cast Iron and Copper. Does not work for SDR-26
- 4.3 PSI test pressure

Product Code	Nominal Dia. (inch)	Box Qty	Description
IC44P	4	6	Connects two pipes having an I.D. range of: 3.90"-4.06"
IC66P	6	6	Connects two pipes having an I.D. range of: 5.83"-6.02"



Material	ABS & EPDM Rubber
Test Pressure	4.3 PSI



Step 1
Clean and measure pipe I.D.



Step 2
Lubricate gasket O.D. with soap & water solution



Step 3
Push in place up to the pipe stop



Step 4
Lubricate gasket and install 2nd pipe

Ensure that the tapered edge on the rubber sleeve does not fold back when inserting into the pipe.

