

Fuse terminal Screw terminal for G fuse link 5x 20 mm and 5x 25 mm with LED 24 V



Figure similar

| Model   |                    |
|---|--------------------|
| Product brand name                                  | ALPHA              |
| Type of light source / as fault indicator           | LED                |
| Design of the fuse link                             | glass fuse 5x25 mm |
| Design of fuse holder                               | pluggable          |
| General technical data                              |                    |
| Insulation material                                 | thermoplastic      |
| Terminal contact spacing                            | 10 mm              |
| Supply voltage                                      |                    |
| Type of voltage / for supply of the fault indicator | AC/DC              |
| Protection class                                    |                    |
| Combustibility class acc. to UL 94                  | Other              |
| Main circuit  |                    |
| Operating voltage / rated value                     | 250 V              |
| Operating current / rated value                     | 6.3 A              |

## Appearance

|       |               |
|-------|---------------|
| Color | miscellaneous |
|-------|---------------|

## Product details

|   |    |
|---|----|
| Product component / required / connection plate | No |
|---|----|

## Number

|                           |   |
|---------------------------|---|
| Number of terminal levels | 1 |
|---------------------------|---|

## Connections

|  |  |
|--|--|
| Connectable conductor cross-section / stranded |  |
|--|--|

|           |                     |
|-----------|---------------------|
| • maximum | 1.5 mm <sup>2</sup> |
|-----------|---------------------|

|                                     |  |
|-------------------------------------|--|
| Connectable conductor cross-section |  |
|-------------------------------------|--|

|         |  |
|---------|--|
| • solid |  |
|---------|--|

|           |                   |
|-----------|-------------------|
| — minimum | 1 mm <sup>2</sup> |
|-----------|-------------------|

|           |                   |
|-----------|-------------------|
| — maximum | 1 mm <sup>2</sup> |
|-----------|-------------------|

|                   |  |
|-------------------|--|
| • finely stranded |  |
|-------------------|--|

|                                      |                      |
|--------------------------------------|----------------------|
| — with core end processing / minimum | 0.75 mm <sup>2</sup> |
|--------------------------------------|----------------------|

|                                      |                     |
|--------------------------------------|---------------------|
| — with core end processing / maximum | 1.5 mm <sup>2</sup> |
|--------------------------------------|---------------------|

|                               |  |
|-------------------------------|--|
| Type of electrical connection |  |
|-------------------------------|--|

|     |                     |
|-----|---------------------|
| • 1 | screw-type terminal |
|-----|---------------------|

|     |                     |
|-----|---------------------|
| • 2 | screw-type terminal |
|-----|---------------------|

|                            |         |
|----------------------------|---------|
| Position / of the terminal | lateral |
|----------------------------|---------|

## Mechanical Design

|   |       |
|---|-------|
| Height / with lowest-profile installation | 42 mm |
|---|-------|

|        |       |
|--------|-------|
| Length | 57 mm |
|--------|-------|

|               |                |
|---------------|----------------|
| Mounting type | DIN rail 35 mm |
|---------------|----------------|

|                                   |             |
|-----------------------------------|-------------|
| Material / of the insulating body | Thermoplast |
|-----------------------------------|-------------|

|                                 |                                  |              |
|---------------------------------|----------------------------------|--------------|
| <b>General Product Approval</b> | <b>Declaration of Conformity</b> | <b>other</b> |
|---------------------------------|----------------------------------|--------------|



[Environmental Confirmations](#)

## Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=8WA1011-1SF13>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/8WA1011-1SF13>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=8WA1011-1SF13](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=8WA1011-1SF13)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>