

Aluminum Dual Rated Ground Clamps

Types GC and GCL

- Manufactured from high strength aluminum alloy
- Designed to connect aluminum or copper ground conductors to copper water pipe, galvanized pipe, or steel conduit
- Plated for corrosion protection and low contact resistance
- Standards: UL 467
- GCL lay-in feature

CATALOG NUMBER	WATER PIPE RANGE	CONDUCTOR RANGE	CLAMP SCREW MATERIAL	CONDUCTOR GROOVE SCREW MATERIAL	CONNECTOR BODY PLATING
GC-1	1/2" - 1"	14 Sol. - 1/0 Str.	Tin Plated Steel	Tin Plated Aluminum	Tin
GCL-2*	1 1/4" - 2"	6 Sol. - 250 kcmil	Stainless Steel	Stainless Steel	Tin
GC-4	2 1/2" - 4"	6 Sol. - 250 kcmil	Zinc Plated Steel	Tin Plated Aluminum	Clear

*cULus listed



Cast Copper Tanker Static Ground Clamp

Type TSGC

- Manufactured from high strength cast copper alloy
- Ribbed design provides multiple contacts with the tank car
- Pointed wing screw design penetrates surface finishes to ensure a positive grounding contact
- Accommodates flexible rubber sheathed cable

CATALOG NUMBER	COPPER CONDUCTOR RANGE	HEX SIZE
TSGC-030	#6 - #2 AWG	3/8

