

Cual-Aid #11C

- Use with compression lugs and splices
- Recommended for aluminum to aluminum, aluminum to copper, conduit threads, and bolted applications
- Non-melting, non-petroleum base compound with suspended zinc particles
- Has little or no effect on rubber or other insulating materials



CATALOG NUMBER	UNIT PACKAGING	CARTON QTY.
4OZNO11C	4 oz. Squeeze Tube	12
1/2PTNO11C	8 oz. Squeeze Bottle	12
PTNO11C	1 pint Can	1
QTN011C	1 quart Can	1
GALNO11C	1 gal. Can	1
5GALNO11C	5 gal. Can	1
55GALNO11C	55 gal. Drum	1

Cual-Aid #12C

- Recommended for aluminum to aluminum and aluminum to copper compression applications
- Non-melting, non-petroleum base compound with suspended zinc particles and abrasive grit
- Abrasive grit breaks down surface oxides improving conductivity
- Not for use on threads or bolted applications
- Has little or no effect on rubber or other insulating materials

CATALOG NUMBER	UNIT PACKAGING	CARTON QTY.
1/2PTNO12C	8 oz. Squeeze Bottle	12
PTNO12C	1 pint Can	1
QTN012C	1 quart Can	1
GALNO12C	1 gal. Can	1
5GALNO12C	5 gal. Can	1
55GALNO12C	55 gal. Drum	1