



Home (/) ► Products By Type (/products-by-type/) ► PVC (/products-by-type/pvc) ► Sewer Pipe

## SEWER PIPE

Basic uses include sewer line from septic to house, down spouts from guttering, foundation drainage, and leach fields.

- ▼ D-2729 Belled End 10 ft.
- ▼ D-3034. Belled End 10 ft.
- ▼ D-3034. Belled End 20 ft.
- ▼ D-3034. Gasket Joint

---

### Sewer & Drain D-2729

#### Standard Compliances:

- ASTM D-2729, standard for sewer pipe

PVC Cell Classification 12454 for ASTM D-2729

Manufactured from PVC Type 1 Grade 1

### D-2729 BELLED END 10 FT.

Nominal Size	Item Number	Outside Diameter	Min. Wall Thickness	Inside Diameter (Value)	Wt/100'	Ft/Pallet	Perforation
3"	205000	3.250	0.070	3.110	46	810	n/a

Nominal Size	Item Number	Outside Diameter	Min. Wall Thickness	Inside Diameter (Value)	Wt/100'	Ft/Pallet	Perforation
3"	205001	3.250	0.070	3.110	46	810	2-hole. 1/2"
4"	205002	4.215	0.075	4.065	64	500	n/a
4"	205005	4.215	0.075	4.065	64	500	3-hole. 1/2"
4"	205103	4.215	0.075	4.065	64	500	2-hole. 5/8"
6"	205105	6.275	0.100	6.075	128	280	n/a
6"	205007	6.275	0.100	6.075	128	280	3-hole. 1/2"

Swipe to see more...

---

## SDR 35 Sewer

### Standard Compliances:

- ASTM D-3034, standard for Type PSM sewer pipe

PVC Cell Classification 12454 for ASTM D-3034 (Pipe stiffness 46 PSI)

Manufactured from PVC Type 1 Grade 1

## D-3034. BELLED END 10 FT.

Nominal Size	Item Number	Outside Diameter	Min. Wall Thickness	Inside Diameter (Value)	Wt/100'	Ft/Pallet	Perforation
3"	203000	3.250	0.093	3.057	59	810	n/a
4"	203001	4.215	0.120	3.965	99	500	n/a
4"	203002	4.215	0.120	3.965	99	500	2-hole. 5/8"
4"	203003	4.215	0.120	3.965	99	500	n/a
6"	203006	6.275	0.180	5.901	220	280	n/a
6"	203007	6.275	0.180	5.901	220	280	3-hole. 1/2"
6"	203008	6.275	0.180	5.901	220	280	n/a

Swipe to see more...

\* 203000 and 203008 is white instead of green pipe

## D-3034. BELLED END 20 FT.


Nominal Size	Item Number	Outside Diameter	Min. Wall Thickness	Inside Diameter (Value)	Wt/100'	Ft/Pallet
4"	203010	4.215	0.120	3.965	99	1,000
4"	203011	4.215	0.120	3.965	99	1,000
6"	203012	6.275	0.180	5.901	220	560
6"	203013	6.275	0.180	5.901	220	560
8"	203014	8.400	0.240	7.901	393	280

Swipe to see more...

\* 203010 and 203014 is white instead of green pipe


Pipe Drains, Underdrains and French Drains – Perforated pipe shall be placed with the perforations down and the pipe sections shall be joined securely with the appropriate coupling.

2 Hole Perforation




2 Rows of 1/2" holes, 120° a part at 4-8 o'clock positions  
2 Rows of 5/8" holes, 120° a part at 4-8 o'clock positions

3 Hole Perforation



3 Rows of 1/2" holes, 60° a part at 4-6-8 o'clock position



### SDR 35 Sewer Gasket Joint

#### Standard Compliances:

- Joint meets ASTM D-3212, standard for pressure using flexible elastomeric seals
- Gasket meets ASTM F-477, made from an elastomeric ring

## D-3034. GASKET JOINT

Nominal Size	Item Number	Outside Diameter	Min. Wall Thickness	Inside Diameter (Value)	Length	Wt/100'	Ft/Pallet
4"	339000	4.215	0.120	3.965	14'	104	840
4"	339003	4.215	0.120	3.965	20'	104	1,200
6"	339001	6.275	0.180	5.901	14'	230	392
8"	339002	8.400	0.240	7.901	14'	411	210

Swipe to see more...

### INDUSTRY ORGANIZATION AFFILIATIONS & BUYING GROUP MEMBERSHIPS



North Carolina Office 800-438-9020 (tel:8004389020)  
Florida Office 877-335-9770 (tel:8773359770)  
Oklahoma Office 877-300-8625 (tel:8773008625)



(<https://www.linkedin.com/company/silver-line-plastics-llc/>)

© 1962 - 2020 Silver-Line Plastics LLC | plastics