E26 5" Trim Series


DESCRIPTION

Frost dome glass lens trim with reflector and self-flange in the 5" trim family for use in recessed downlighting. Compatible for use in Halo and other housings.

| Catalog # | Туре |
|-------------|------|
| Project | |
| Comments | Date |
| Prepared by | |

SPECIFICATION FEATURES

- · Low profile dome frost glass lens
- Wet location showerlight
- · Torsion spring retention
- Non-conductive "Dead Front" plastic (polymer) trim ring and glass lens
- · Socket supporting internal reflector
- Self-flanged trim ring sized to hide gaps caused by construction tolerances



| Housings | | Max Lamp Compatibility | | |
|--------------------------|---------|---------------------------|--|--|
| H5ICAT | H5RICAT | 2014/ 4.10, 2014/ DA D200 | | |
| E5ICAT | E5RICAT | 29W A19, 39W PAR30S | | |
| H25ICAT | = | 29W A19 | | |
| H5ICATNB E5ICATNB | | 29W A19, 39W PAR30S | | |
| H25ICATNB | | 29W A19 | | |
| H5T H5RT E5TAT E5RTAT | | 60W A19, 50W PAR30S | | |
| H5TNB E5TATNB | | 60W A19, 50W PAR30S | | |

Compatible with Halogen, Incandescent, LED* or CFL* lamps.



5150WH Frost Lens with Reflector, White Plastic Trim



5150SN Frost Lens with Reflector, Satin Nickel Plastic Trim



5150TBZFrost Lens with Reflector,
Tuscan Bronze Plastic Trim

5150

5-Inch Frost Glass Lens, Self-flange



ORDERING INFORMATION

SAMPLE NUMBER: 5130WH

Dimensions: A: 4-1/2" [114mm] H: 5-4/5" [148mm] OD: 6-5/8" [168mm]

| Trim | | Finish | | |
|------|--|--|--|--|
| | 5150 = 5"Frost dome glass lens, self-flange | WH=Matte White plastic trim, self-flange SN=Satin Nickel plastic trim, self-flange TBZ=Tuscan Bronze plastic trim, self-flange | | |

HALO HOUSING COMPATIBILITY

| Trim # | Style | H5ICAT | H5RICAT | E5ICAT | E5RICAT | H25ICAT | H5ICATNB | E5ICATNB | H25ICATNB |
|--------|-------------|--------|---------|--------|---------|---------|----------|----------|-----------|
| | | • | • | • | • | • | • | • | • |
| 5150 | Showerlight | H5T | H5RT | E5TAT | E5RTAT | H5TNB | E5TATNB | | |
| | | • | • | • | • | • | • | | |

*UL1993 listed LED & CFL equivalent lamps permitted. Consult lamp manufacturer for conditions of use. Cooper Lighting Solutions does not warranty the lamp.

For use in other's housings, refer to U.L. Classification list at www.cooperlighting.com.



LISTED

For use in Halo listed housings.



Select trims are classified for use in others housings. See www.cooperlighting.com.

