



Selector Switch
22 mm
Three position maintained
Multiple Legends
For use with enclosures with lift-off covers



Image is representative and may not depict the actual product.

General technical data:	
Weight	0.4 lb.
Height x Width x Depth	3.5 x 1.75 x 4.5 in
Finger-safe	Yes
Environmental ratings	NEMA 1
Maximum altitude	(no data)
Ambient storage temperature	(-30 to 65)°C / (-22 to 149)°F
Ambient operating temperature	(-20 to 40)°C / (-4 to 104)°F
Humidity (% non-condensing)	(no data)
Country of origin	Mexico
Actuator:	
Type	Short lever
Material	Plastic
Illumination	None
Switching positions	3 maintained positions
Mechanical service life (switching cycles)	1,000,000
Contact Block:	
Number of NC contacts	0
Number of NO contacts	2
Thermal current	10A
Contact material	Silver alloy
Mechanical service life (switching cycles)	10,000,000
Electrical endurance (switching cycles)	10,000,000
Legend:	
Material	Synthetic paper label with adhesive back
Inscriptions	HAND/OFF/AUTO, REV/OFF/FOR, HIGH/OFF/LOW, LOCAL/OFF/REMOTE
Background color / foreground color	Black / White
Dimensions	17 mm wide x 12 mm high
Mounting/wiring:	
Mounting type	Bracket for use with enclosures with lift-off covers
Mounting torque	25 - 30 lb. in.
Wire connection type / torque	Screw-type terminals / 7 lb. in. - 8 lb. in.
Solid & stranded conductors	2 x (18 - 16 AWG) 75°C CU
Included	Wires, mounting screws, plugged hole for additional device

