






**Circuit
Breaker
Lighting
Panel
Type P1**



**Circuit
Breaker
Lighting or
Distribution
Panel Types
P2/P3**



**Circuit
Breaker
Distribution
Panel Type
P4/P5**

Scan to connect
online to the
most up-to-
date version of
this Section of
SPEEDFAX.



contents

Features, Reference Guide & General Specifications	11-2 – 11-5
Factory Assembled Panelboard Coding System	11-6
Unassembled Panelboards - General info & Kits	11-7 – 11-14
Legacy Original P1-S1-S2-SE Kits available	11-15
15A-125A Branch Breakers for Panelboards	11-16 – 11-19
Spare Parts, GB kits, Fillers for Revised P1 panels	11-20 – 11-23
Type P1	11-24 – 11-41
General Specifications	11-24
Main Lug and Main Breaker Configuration Info	11-25 – 11-28
Modifications and Additions	11-29 – 11-30
Enclosure Dimensions - Type 1, 3R and 3R/12	11-31
General P1-P2-P3 Enclosure and Accessory Info	11-32 – 11-41
Type P2	11-42 – 11-54
Specifications	11-42
Enclosure Selection/ Dimensions	11-43 – 11-44
Main Breaker and Subfeed Breakers	11-45
Branch Breakers	11-46
Main Lug and Main Breaker	11-47
Modifications and Additions	11-48 – 11-53
Enclosure Dimensions	11-54
Type P3	11-55 – 11-65
Specifications	11-55
Enclosure Selection/ Dimensions	11-56
Alternate Main, Branch and Subfeed Breakers	11-57 – 11-58
Main Lug and Main Breaker	11-59 – 11-60
Modifications and Additions	11-61 – 11-64
Enclosure Dimensions	11-65
3VA Breaker Reference Info used in Panelboards P1 thru P5	11-66 – 11-84
Type P4	11-85 – 11-98
Specifications	11-85
Enclosure Selection	11-85 – 11-87
Main Lug and Main Breaker	11-88
Main Switch and Alternate Main Breakers	11-89
Branch Devices – Circuit Breaker and Switch	11-90 – 11-92
Modifications and Additions	11-93 – 11-97
Enclosure Dimensions	11-98
Type P5	11-99 – 11-112
Specifications	11-99
Enclosure Selection	11-100
Main Lug and Main Breaker	11-101
Alternate Main Breaker and Main Switch	11-102
Branch Breakers	11-103 – 11-104
Branch Switches	11-105
Modifications and Additions	11-106 – 11-111
Enclosure Dimensions	11-112
Column Type Panelboards	11-113 – 11-116
Telephone and Equipment Cabinets	11-117
Panelboard Modifications and Additions	11-118 – 11-120
Enclosures—Relay Cabinets, NEMA 4X	11-118
Remote Switches—ASCO, LEN	11-118
Enclosure, Door, & Trim Modifications	11-119
Circuit Breaker Accessories & Panel Skirts	11-120
Coordination Panels	11-121 – 11-128

Panelboards

Introduction

General

This generation of panelboards from Siemens offers the high level of engineering and innovation you've come to expect from the leader in power distribution technology. The "P Series" line of panelboards offers a stepped approach to power distribution.

Additional strength has been added to an already rugged and durable panelboard family. Engineered specifically to provide maximum flexibility, the new designs simplify wiring and reduce material requirements making them easier to install and less costly than competitive products. At the heart of the product line is the extensive research and technology found among Siemens circuit protection devices – both fusible switches and molded case circuit breakers.

The line is anchored by the innovative P1. Featuring the industry's most flexible designs, the P1 virtually eliminates common errors, such as feed direction, and main lug versus main breaker. Increasing distribution is simplified by the ability to add feed-thru lugs. The Revised P1 design introduced in January 2015 has added Extended Circuits up to 66 and has available smaller Enclosures with no Subfeed option for added flexibility

Subsequent steps in the P Series offer increased capacity and more design options:

- The highly flexible P2 provides options to fit the most demanding specifications.

- Sized more like a lighting panel, the P3 packs the power of a distribution panel in a space-saving, highly flexible design.
- The P4 is a mid-sized distribution panel that allows both fusible and circuit breaker branch and main devices.
- The powerful P5 anchors the high end of the series. With larger fusible and circuit breaker branch and main devices, the venerable P5 delivers maximum power and flexibility to larger distribution systems.

Siemens also offers a number of specialty panels, like column panels, SEM3 (Embedded Micro Metering Module™), Disaggregation Panels (which are California Title-24 compliant), and others. Don't see a panel to meet your requirements? Ask your Siemens representative about our custom capabilities.

Features Overview

P Series lighting panel features include Fas-Latch trim, which is popular among installers; the jacking screw system, that permits adjustments even after wiring has been installed; our exclusive split neutral, and more. Many panelboards have the capability of mixing and matching breakers of different sizes and ratings – or changing from main lug to main breaker, or adding subfeed breakers without changing the box size. Other models accept a wide range of fuse types, including Siemens exclusive Vacu-Break® technology.

Key Panelboard Features

	P1	P2	P3	P4	P5
Power Panelboard Applications	—	•	•	•	•
Convertible From Top Feed To Bottom Feed Or Vice Versa	•	—	—	—	—
Change From Main Lug To Main Breaker Or Add Subfeed Without Changing Enclosure Size [Ⓢ]	•	—	—	—	—
Space-Saving, Horizontally Mounted Main Breaker	Up To 250 Amps	Up To 250 Amps	Up To 400 Amps	•	•
Short-Circuit Rating Label Giving Performance Level	•	•	•	•	•
Standard Aluminum Ground Assembly	•	•	•	•	•
Blank End-Walls Standard [Ⓢ]	•	•	•	•	•
Bolted Current-Carrying Parts	•	•	•	•	•
Split Neutral	•	—	•	—	—
Connection Accessible From Front	•	•	•	•	•
Screw-Type Mechanical Lugs	•	•	•	•	•
Time-Reducing Wing Nuts To Secure Interior Without Tools	•	•	•	—	—
Flush Lock, Concealed Door Hinges/Trim Screws	•	•	•	—	—
Symmetrical Interior Mounting Studs To Eliminate Upside-Down Mounting of Box	•	•	•	•	•
Interior Height Adjustment For Flush Applications	•	•	•	—	—
Mix and Match Fusible Switch Circuit Breaker Capability	—	—	—	•	•
Standard Depth and Width of Enclosure	5.75" x 20"	5.75" x 20"	7.75" x 24"	10.00" x 32"	12.75" x 38"
Accepts Vacu-Break Fusible Switch with Wide Range of Fuse Types	—	—	—	•	•
Optional Compression Lugs	•	•	•	•	•

• Standard

Ⓢ KO's available on P1 and P2 – 5.75" Deep x 20" Wide boxes and P3 7.75" deep X 24" wide boxes.

Ⓢ For Revised P1, only when Subfeed Space is selected, Interior Part Number ends with "T". When "N" is at end there is no Subfeed Space available

Panelboards

General Specifications

General

Service Entrance Equipment

When a panelboard is used as service entrance equipment, it must be located near the point of entrance of building supply conductors. The National Electrical Code prior to 2020 allowed a maximum of six service disconnects in the same panelboard. The 2020 NEC now restricts panelboards to one service disconnect in a panelboard enclosure. Adoption of this code vary by a state or local jurisdiction. Consult the local code authorities to determine if this has been adopted in the area where the panel is to be installed and configure the panel accordingly. Also, panels must include a connector for bonding and grounding the neutral conductor.

UL67 requires Service Entrance Barriers for all Panels used for Service Entrance. Siemens includes these barriers in all Factory assembled panels, marked as Service Entrance, and also has available Field Installable kits when needed.

Integrated Equipment Short Circuit Rating

The term “Integrated Equipment Short Circuit Rating” refers to the application of series connected circuit breakers in a combination that allows some breakers to have lower individual interrupting ratings than the available fault current. This is permitted as long as the series combination has been tested and certified by UL.

Standards

NEC: 2020 (where accepted)

NEMA: PB1.1

UL: 67, 50 and 50E. Listed by Underwriter’s Laboratories, Inc., under “Panelboards” File #E2269, and #E4016. Meets Federal Specification W-P-115c.

Wire Connectors


Standard wire connectors in Siemens panels are suitable for copper or aluminum cables rated 60/75 degree. Copper main lugs are a price-added option for most panel types and some Circuit Breakers (check with Siemens sales for availability). It should be noted that most copper lugs will only accept copper cables. Some applications, 100% rated devices in particular, require that the cable and connectors be rated 90 degree but are sized to the 75 degree tables.

Standard ground connectors are also suitable for copper or aluminum wire. Ground connector assemblies (EGK, ICK) have (6) 1/0 max. and (15) #6 max. connections. The 1/0 holes are capable of connecting up (3) #10 max. wires. The #6 holes can accept up to (2) #12 max. wires. Copper ground assemblies (ECGK, ICKG) are rated for copper wire only and have the same wiring capacity as the Al/Cu connectors.

Standard neutrals, like standard main lugs, are also rated for copper or aluminum wire. The neutral cross bar material follows the selection bus. Copper neutral lugs are rated for copper cable only and available as a price added option.

Lug Data


Space Required for Mounting of Double Panels




Use two or more panelboards with feed-thru or subfeed lugs when:

1. More circuit mounting space is required than is provided in the largest box size

Feed-Thru Lugs



Subfeed Lugs or Double Lug



Feed-thru lugs are mounted at the opposite end of the main bus from the main lugs or main breaker and are used to connect two or more panelboards to the incoming feeder. The feeder cables are brought into Panelboard 1 and connected to the main lugs or main breaker. Cables interconnecting the two panelboards are connected to the feed-thru lugs in Panelboard 1 and are carried over the main lugs in Panelboard 2. This arrangement could be reversed with the main lugs located at the top and the feed-thru lugs at the bottom of the panel.

Subfeed lugs are mounted directly beside the main incoming lugs and are used to connect two or more panelboards to the incoming feeder. The feeder cables are brought into Panelboard 1 and connected to the main lugs. Another set of cables that are the same size are connected to the subfeed lugs of Panelboard 1 and are carried over the main lugs of Panelboard 2.

Note: P1 panelboards do not have subfeed lugs available. If this configuration is needed, move to a P2 or P3 panelboard.

Note: For Panelboards, Siemens uses this Document for the Operations and Maintenance manual: ANSI/NEMA PB 1.1-2013 [General Instructions for Proper Installation, Operation, and Maintenance of Panelboards Rated 600 Volts and Less (O&M Manual)]

** The PDF of this document can be downloaded (at no cost) for printing at this location:

<https://www.nema.org/standards/view/Panelboards> (ref. Material # 11-1056-01)

Panelboards

General Specifications

General

Bussing Sequence

Interiors are designed to accommodate top or bottom feed. Regardless of which is specified, the uppermost pole is always on "A" phase; the second pole down is always on "B" phase, and the third pole down is always on "C" phase (assuming 3Ø panel).

As standard, branch breakers shall be mounted at the top of the panel with "spaces" at the bottom, regardless of the direction panel is fed.

All breakers have bolted connections except plug-in type. The panel design provides bracing up to 200,000A IR UL short circuit rating. Case-hardened, high performance, thread rolling screws are used on branch bus.



Circuit Breaker Lighting
Panel Type P1



Circuit Breaker Lighting or
Distribution Panel Types P2/P3



Circuit Breaker Distribution
Panel Type P4/P5



Fusible Switch Distribution
Panel Type P4/P5

Panelboard Ratings (Updated June 2014 with release of Revised P1 design)

Description	P1 Revised	P2	P3	P4	P5
Max. Voltage	480V AC Max. [®] 600Y/347V AC [®]	600V AC Max. 250V DC Max.	600V AC Max. 250V DC Max.	600V AC Max. 250V DC Max.	600V AC Max. 250V DC Max.
System	1-Phase, 2-wire 1-Phase, 3-wire 3-Phase, 3-wire 3-Phase, 4-wire	1-Phase, 2-wire 1-Phase, 3-wire 3-Phase, 3-wire 3-Phase, 4-wire	1-Phase, 2-wire 1-Phase, 3-wire 3-Phase, 4-wire 3-Phase, 3-wire	1-Phase, 3-wire 3-Phase, 4-wire 3-Phase, 3-wire	1-Phase, 3-wire 3-Phase, 4-wire 3-Phase, 3-wire
Mains					
Main Lugs	125A-400A	125A-600A	250A-800A	400A-1200A	800A-1200A
Main Breaker	100A-400A	100A-600A	225A-800A [®]	400A-800A	800A-1200A
Main Switch (Vacu-Break)	—	—	—	—	200A-1200A
Molded Case Switch[®]	150A-400A	150A-600A	150A-800A	400A-800A	400A-800A
Circuits	18, 30, 42, 54, 66 (250A) 30, 42, 54, 66 (400A)	18, 30, 42, 54, 66 78, 90 ^①	(unit space 9"- 45")	—	—
Branch Ratings	15-125A	15-400A	15-400A	15-800A MCCB 30-200A Fusible	15-1200A MCCB 30-1200 Fusible
Branch Disconnect Devices (see detailed tables for UL type codes)	BL/BQD series [®] , BT series, xGB series [®] , 3VA41 series, AFCI/GFCI series	BL/BQD series [®] , BT series, xGB series, 3VA41 series, QR series, AFCI/GFCI series, ED series, 3VA52/61/62 series [®]	BL/BQD series [®] , BT series, xGB series, 3VA41 series, QR series, AFCI/GFCI series, ED series, 3VA52/61/62 series [®]	All 15-600A MCCBs, VL MG at 800A and 30-200A VB switches, 3VA52/61/62 series, 3VA53/63 series [®] , 3VA54/64 series [®]	All 15-1200A MCCBs, 30-600A VB switches and 400-1200A HCP switches, 3VA52/61/62 series, 3VA53/63 series [®] , 3VA54/64 series [®]
Subfeed Circuit Breakers^{②③} (see detailed tables for UL type codes)	BL/BQD series [®] , xGB series [®] , 3VA41 series, QR series, FD series, 3VA52/61/62 series	FD series, JD series, 3VA53/63 series	FD series, JD series, 3VA53/63 series	—	—
Enclosure Heights Inches – (mm)	26, 32, 38, 44, 50, 56 @250A (660, 813, 965, 1118, 1270, 1422) 56, 62, 68, 74 @400A (1422, 1575, 1727, 1880)	26, 32, 38, 44, 50, 56, 62, 68, 74 (660, 813, 965, 1118, 1270, 1422, 1524, 1575, 1727, 1880)	56, 68, 80 (24" W) (1422, 1727, 2032) (68"H & 80"H in 30"W Type 1 only)	60, 75, 90 (1524, 1905, 2286)	60, 75, 90 (1524, 1905, 2286)
Standard Trims	Fas-Latch – 1 Piece Surface or Flush	Fas-Latch – 1 Piece Surface or Flush	Fas-Latch – 1 Piece Surface or Flush	Four Piece ^④ Surface or Flush	Four Piece ^④ Surface or Flush

① Functional pricing is based on circuits shown. However, the panel can be figured with less circuits.

② P1 can have max. 1 subfeed breaker when Subfeed Space is available. P2 and P3 can have up to (2) FD subfeed breakers.

③ JD and FD breakers are mounted vertical. Limitations apply.

④ Trim ring provided for flush applications.

⑤ A maximum of (4) QR/3VA52/3VA62 breakers may be mounted in a P2 Panel and are single mounted.

⑥ A maximum of (6) QR/3VA52/3VA62 breakers may be mounted in a P3 panel in 24" wide enclosure. Up to 12 can be installed with 30" wide enclosure.

⑦ P1 panels with xGB/3VA41 are limited to interiors for xGB/3VA41 breakers only.

⑧ Factory assembled P1 has capability of 600Y/347V AC system when the proper breakers are selected.

⑨ BQD6 is not UL Listed. Only for CUL and CSA panels.

⑩ New breakers being introduced in 2021.

Panelboards

General Specifications

General

Typical Panelboard Modifications

Description	Lighting and Distribution Panelboards			Distribution Panelboards	
	P1	P2	P3	P4	P5
Box					
Type 1	Standard (20"W x 5.75"D)	Standard (20"W x 5.75"D)	Standard (24"W x 7.75"D)	Standard (32" W x 10.0" D)	Standard (38" W x 12.75" D)
Type 1 Enclosure with Hood	●	●	●	●	●
Type 1 w/Gasket between box and front	●	●	●	—	—
Type 2 Enclosure - Drip Tight (this is not available)	—	—	—	—	—
Type 3R/12	●	●	●	●	●
Type 4, 4X (size varies by type/material)	●	●	●	●	●
Wider Box (check w/factory for custom options not shown)	● (24"W)	● (24"W)	● (30"W Type 1)	● (custom)	● (custom)
Deeper Box (check w/factory for custom options not shown)	● (7.75"D)	● (7.75"D)	● (custom)	● (custom)	● (custom)
Front – NEMA Type 1 only					
Front with Door	Standard	Standard	Standard	●	●
4-piece Front	—	—	—	Standard	Standard
4-piece Front w/Hinged Gutter Covers	—	—	—	●	●
Hinged-to-Box Front/Screw-to-Box Front	●	●	(H-to-B only)	(see Door-in-Door)	(see Door-in-Door)
Door-in-Door Front	●	●	●	●	●
Common Front (custom - multi section applications)	● (custom)	● (custom)	● (custom)	—	—
Special Locks	● (custom)	● (custom)	● (custom)	● (custom)	● (custom)
Nameplate (mounting provisions provided as Std - P1/P2/P3) - Nameplate text is configured in COMPAS with limitations.	●	●	●	●	●
Interior					
Aluminum Equipment Ground Bar	Standard	Standard	Standard	Standard	Standard
Copper Equipment Ground Bar	●	●	●	●	●
Insulated Equipment Ground (CU or AL)	●	●	●	●	●
Subfeed Lugs (see page 11-48 or 11-61)	—	●	●	●	●
Feed-Thru Lugs	●	●	●	●	●
Split Bus	—	●	●	●	●
Compression Lugs	●	●	●	●	●
Copper Lugs	●	●	●	●	●
200% Neutral	●	●	●	400 - 600A	400 - 600A
Temperature Rated - Aluminum 1 (tin plated)	Standard	Standard	Standard	Standard	Standard
Temperature Rated - Copper 1	●	●	●	●	●
750 Ampere / in. - Aluminum (tin plated)	—	●	●	●	●
1000 Ampere / in. - Copper	—	●	●	●	●
Copper Plating	Tin	Tin Std./ Silver Opt.	Tin Std./ Silver Opt.	Silver	Silver
Remote Control Switches	External Mounted	●	●	●	●
Time Clocks	External Mounted	●	●	●	●
Circuit Breaker Shunt Trips	●	●	●	●	●
R, J and T Fuse Clips	—	—	—	●	●

All aluminum bus is tin-plated. ● Available as an option. — Not Available

UL Fuse Classes^①

Class	Amperes	Volts	Interrupting Ratings (kA)	I^2t , I_i	Circuits
H	1-600	250 and 600V or less AC	10	—	Less than 10,000A Available
K5 ^②	1-600	250 and 600V or less AC	100	I_t – RK5 up to 100A, I_i – RK5 up to 100A	Feeder circuits
J	1-600	600V or less	200	I_t – Low, I_i – Low	Feeder circuits (motor load small %)
RK1	1/10-600	600V or less and 250V or less	200	I_t – Slightly > J, I_i – Slightly > J	Feeder circuits (motor load small %)
RK5	1/10-600	600V or less and 250V or less	200	I_t – > RK-1, I_i – > RK-1	Motor starting currents a factor
T	1-800, 1-1200	300 and 600V or less AC	To 200	I_t – Low, I_i – Low	Non-Motor loads
L	601-1200	600V or less	200	I_t – Low, I_i – Low	Mains, feeder circuits

① Per UL 67.

② Fuses do not prohibit the use of Class H type fuse in switch.

Panelboards

Factory Assembled

Selection

11
PANELBOARDS

Catalog Numbering System

Type of Panel P1, P2, P3, P4, P5

Voltage and System*

C = 208Y/120 3Ø 4 W Wye AC - All (X for UPB)

E = 480Y/277 3Ø 4 W Wye AC - All

8 = 480Y/277 3Ø 4 W Wye - P1 w/ GB/3VA41 Branch Only

D = 240 3Ø 3 W Delta AC - All

F = 480 3Ø 3 W Delta AC - All

G = 600 3Ø 3 W Delta AC - P2, P3, P4, P5

I = 347 3Ø 3 W Delta AC - All

B = 240/120 3Ø 4 W Delta BØ High Leg AC - P2, P3, P4, P5

Q = 240/120 3Ø 4 W Delta CØ High Leg AC - P2, P3, P4, P5

A = 120/240 1Ø 3 W AC - All

H = 120 1Ø 2 W Grounded Neutral AC - P2, P3, P4, P5

J = 240 1Ø 2 W No Neutral AC - All

Y = 125 1Ø 2 W Grounded Neutral AC - P2, P3, P4, P5

Z = No Longer Available

K = 220/127 3Ø 4 W Wye AC - All

M = 380/220 3Ø 4 W Wye AC - All

R = 415/240 3Ø 4 W Wye AC - All

S = 440/250 3Ø 4 W Wye AC - All

L = 600/347 3Ø 4 W Wye AC - All

T = 230 3Ø 3 W Delta AC - All

W = 380 3Ø 3 W Delta AC - P2, P3, P4, P5

1 = 24V DC 1-Pole Branch Only - P2, P3, P4, P5

2 = 24V DC 2-Pole Branch Only - P2, P3, P4, P5

3 = 48V DC 1-Pole Branch Only - P2, P3, P4, P5

4 = 48V DC 2-Pole Branch Only - P2, P3, P4, P5

5 = 125V DC 1-Pole Branch Only - P2, P3, P4, P5

N = 125V DC 2-Pole Branch Only - P2, P3, P4, P5

O = 125/250V DC 2-Pole Branch Only - P2, P3, P4, P5

P = 125/250V DC 2 & 3-Pole Branch - P2, P3, P4, P5

U = 120V AC 3Ø3W - All

V = 240V 3Ø3W Grounded B Phase - P2, P3, P4, P5

*For any voltage system not listed, check with sales for availability.

Circuits or

P1 – 18, 30, 42, 54, 66

P2 – 18, 30, 42, 54, 66, 78, 90

Enclosure Height^①

P3 – 56, 68, 80 (62" & 74" now custom)

P4, P5 – 60, 75, 90

Main Lug (ML), Main Breaker

(See Main Breaker Table coding below), Main Switch (MS)

Amperage
100–400A = P1^② 250–800A = P3

100–600A = P2 400–1200A = P4, P5

Bus Code^③
Bus Material
Bus Plating

P1

P2

P3

P4

P5

A Temp rated Al.
B 750A/sq. in. Al.
C Temp rated Cu.
E Temp rated Cu.
F Temp rated Cu.
G 1000A/sq. in. Cu.
H 1000A/sq. in. Cu.

Tin-Plated
Tin-Plated
Tin-Plated
Silver-Plated
Tin-Plated
Tin-Plated
Silver-Plated

•
n/a
n/a
n/a
n/a
n/a
n/a

•
n/a
optional
•
•
optional

•
n/a
optional
•
•
optional

•
n/a
n/a
optional
optional
•

•
n/a
•
n/a
optional
•

• Indicates default for this bus type.

Feed Location T = Top B = Bottom

Mounting

S = Surface F = Flush. Extends 1 1/2" beyond the base box dimensions on P1, P2, P3; and 2" on P4, P5 panels.

Subfeed Space Indicator (for P1 only)

T = Subfeed Space Included

N^④ = No Subfeed Space

Main Breaker Type Coding

Code	Breaker	Code	Breaker	Code	Breaker	Code	Breaker	Code	Breaker	Code	Breaker	3VA ref	Code	Breaker	3VA ref
BL	BL	CJ	CJD6	L6	LD6	HN	HNDD6	M5	HMG	V1	SEAB	3VA41	W2	MDAE	3VA61
BH	BLH	6H	HHJD6	LX	LXD6	HT	HNXD6	M2	HMX	V2	MEAB	125A	W3	HDAE	150A
BR	BLR	H9	HHJXD6	LH	LXD6H	HX	HNXD6H	M8	HMY	V3	HEAB	max	W4	CDAE	max
HB	HBL	H6	HJD6	S1	SCLD6	ND	ND6	M6	LMG	V4	SEAS	3VA51	W5	LDAE	
BQ	BQD	H5	HJXD6	S2	SHLD6	NX	NXD6	M3	LMX	V5	MEAS	150A	WA	MFAE	3VA62
B6	BQD6 ^⑤	H7	HJXD6H	SL	SLD6	NT	NXD6H	M9	LMY	V6	HEAS	max	WB	HFAE	250A
CE	CED6	J6	JD6	QJ	QJ2	SR	SCND6	M4	NMG	VA	MFAS	3VA52	WC	CFAE	max
E4	ED4	JD	JXD2	Q2	QJ2H	ST	SCND6H	M1	NMX	VB	HFAS	250A	WD	LF AE	
E6	ED6	JX	JXD6	QH	QJH2	AD	SHND6	M7	NMY	VC	CFAS	max	WE	MJAE	3VA63
H4	HED4	JH	JXD6H	C9	CMD6	SD	SHND6H	N8	HNG	VE	MJAS	3VA53	WF	HJAE	400A
HA	HLED6	SC	SCJD6	CH	CMD6H	SN	SHND6	N2	HNX	VF	HJAS	400A	WG	CJAE	max
CF	CFD6	SX	SHJD6	HM	HMD6	AY	SND6H	N5	HNH	VG	CJAS	max	WH	LJAE	
FD	FD6	SY	SHJD6H	HR	HMXD6	JA	HJG	N9	LNG	VJ	MLAS	3VA54	WJ	MLAE	3VA64
FX	FXD6	SJ	SJD6	HS	HMXD6H	J7	HJX	N3	LNH	VK	HLAS	600A	WK	HLAE	600A
HF	HFD6	SH	SJD6H	MD	MD6	J5	HJY	N6	LNH	VL	CLAS	max	WL	CLAE	max
H2	HFXD6	CL	CLD6	MX	MXD6	J9	LJG	N7	NNG	VN	MMAS	3VA55	WM	LLAE	
H1	HFFD6	HH	HHLDD6	MH	HMXD6H	J3	LJX	N1	NNX	VO	HMAS	800A	WN	MMAE	3VA65
H3	HFFXD6	XH	HHLXD6	SO	SCMD6	J8	LJY	N4	NNY	VP	CMAS	max	WO	HMAE	800A
G2	HGB	HL	HLDD6	SO	SCMD6H	L3	LLX	QR	QR2	VV	MNAS	3VA56	WP	CMAE	max
G3	LGB	HO	HLXD6	S5	SHMD6	J2	NJG	Q4	QRH2	VW	HNAS	1200A	WR	MMNAE	3VA66
NB	NGB	HP	HLXD6H	S6	SHMD6H	J1	NJX	Q5	HOR2	VX	CNAS	max	WS	HMNAE	1000A
G4	NGB2			SM	SMD6	J4	NJY	Q6	HOR2H				WT	CMNAE	max
G5	HGB2			AX	SMD6H	L2	HLX	Q7	QR2-MCS				WV	MNAE	3VA67
G6	LGB2			CN	CND6	L7	NLX						WW	HNAE	1200A
				C6	CND6H								WX	CNAE	max

① P3, P4, P5 enclosure height tables found on page 11-56, 11-85 and 11-100. These show the amount of unit space available.

② P1 Bus is either 250A max or 400A max.

③ Standard bussing in P1, P2 and P3 panels is tin-plated for aluminum and copper. Standard bus is temperature

rated to the maximum amperage in the panel.

④ Not available for Revised P1 xGB interiors.

⑤ BQD6 is not UL Listed. Only for CUL and CSA panels

Panelboards

Unassembled

Reference


Type P1 unassembled panelboards are completely convertible from main lug to main breaker and vice-versa. Additionally, feed-thru lugs up to 400 ampere or subfeed circuit breakers up to 250 ampere can be added without increasing the box height for Revised P1 with "T" suffix, see the chart.

1. When BL / BQD or GB Main Breaker is chosen as back-fed in unit space, the Main Breaker will use 2 or 3 positions of unit space and will reduce usable branch circuit space.
2. List catalog number and price of interior, box and front.
3. Select main lug kit or main breaker kit from appropriate tables.

Note: Main/Subfeed Breaker mounting kits may be ordered with or without breakers included, see page 11-13 and 11-14 for selection.

4. List required branch circuit breakers and filler plates to cover any unused positions.
5. Select any modifications or accessories.

Note: Revised P1 was introduced in 2015. All original P1 devices do not include the "Subfeed Space" Indicator. All original P1 included the Subfeed Space as standard.



Note: Standard bussing in P1 panels is tin plated for aluminum and copper. Standard bus is temperature rated to the maximum amperage in the panel.

Revised P1 Branch Breaker reference

Revised P1 Branch Breakers in unit Space have a full range of capabilities. [Ⓢ]	Voltage reference	Breaker frame series (kA range)			
		BL	BQD	xGB	3VA41
Only P18... series can accept both xGB and 3VA41 mixed in unit space. See Branch Breaker charts for more info.	120/240V	10-65k	65k	100k	65-150k
	240V	10-65k	65k	100k	65-150k
	480Y/277V	—	14k	25-65k	25-65k
	480V	—	—	—	25-65k
	600Y/347V [Ⓢ]	—	—	14k	14-25k
P1, Revised P1 interior type					
P1X = 208Y/120, 3-Phase 4-Wire		x	x	na	na
P1A = 120/240V, 1-Phase 3-Wire		x	x	na	na
P1E = 480Y/277V, 3-Phase 4-Wire (BL/BQD only) [Ⓢ]		x	x	na	na
P18 = 480Y/277V, 3-Phase 4-Wire (xGB/3VA41 only) [Ⓢ]		na	na	x	x

[Ⓢ] xGB interiors changed to "8" code when 3VA41 capability was added in 2020. Main breaker code "7" will no longer be available.
[Ⓢ] P1 panels use either 250A rated bus or 400A rated bus, regardless of the Main Breaker installed (or) MLO Amp

rating chosen. Panels with 250A bus can have up to 250A Main Breaker or Main Lugs. Panels with 400A bus can have up to 400A Main Breaker or Main Lugs.
[Ⓢ] Consult sales office for availability of CSA.

[Ⓢ] 600V options are not available in a UPB panel – see factory assembled section.
[Ⓢ] See Speedfax for additional information.
[Ⓢ] Previous P17... series only accepted xGB series Branch Breakers – you cannot add 3VA41.

Panelboards

Features / Benefits

Reference

The standard Siemens P1 panelboard has some unique features that make it easier to design for an engineer, easier to reconfigure in the field for a contractor, and easier to upgrade and maintain for the Owner.


- The P1 is the smallest panel in the Siemens lineup, with bus sizes up to 400A.
- What makes it different is the split neutral design and the open ended bus. In the Siemens panel, instead of the common single neutral bus on one end, we have a neutral bus on both sides that is cross-bussed.

- This makes branch wiring simpler and cleaner – the lead lengths for line and neutral can now be made nearly the same, creating more room and a neater installation.
- It also allows access to both ends of the bus as a standard feature – this provides the flexibility to make changes in the field, even if it wasn't part of the original configuration.

New Revised P1 introduced in 2015 has extended circuits up to 66 available and also non-feed thru versions are available, without the Subfeed Space, in a 6" smaller enclosure.

- In 2020 we introduced 3VA Main and Branch breakers as well as BT twin and BSPD Surge Products.


MAIN BREAKER or SUB-FEED BREAKER



MAIN LUGS or FEED-THROUGH LUGS



INTEGRAL BUS MOUNTED SPD



The following can be done to a standard P1 panelboard **in the field** with no modifications:

- Change from top fed to bottom fed
- Add feed-through lugs[Ⓢ]
- Add an Integral bus-mounted SPD[Ⓢ] (or new Branch Mounted BSPD)
- Add a sub feed breaker up to 250 amps[Ⓢ]
- Change from Main Lugs to Main Breaker
- Change from Main Breaker to Main Lugs
- Panel may have up to two ground assemblies. Options are: (a) standard aluminum, (b) optional copper, or (c) optional insulated/isolated aluminum or copper. Mounting provisions in opposing corners of the box are standard. Any of these options may be added after installation.

[Ⓢ] Only when Subfeed Space is selected/available.

Panelboards

New Revised P1 Unassembled Panelboards

Introduction


To better serve the needs of customers, Authorized Siemens Unassembled Panelboard Distributors offer product flexibility, quicker job turn-around, and affordable pricing. All Siemens unassembled panelboards are fully backed for high quality, trouble-free operation and are labeled as Suitable for use as Service Entrance Equipment.

Flexibility and ease of assembly:

Customer oriented design creates installation convenience. For all of its one-of-a-kind features, the P1 panelboard is also designed to be extremely user friendly. For instance, field convertible main breaker and main lug kits, (through 400 amps), will allow you to switch from main lug to main breaker, and vice versa with no change in box size or additional cabling. Plus, lay-in construction (for 250 A CU) and/or removable lugs make wiring the main and neutral lugs easier and faster.

To further speed wiring, as well as reduce clutter, the P1 panel also features a split neutral design and branch neutral connections which are closer to the breakers than competitors. Additionally, field addable sub-fed breakers (up to 250 amps) or feed through lug kits can be field installed without utilizing any of your feeder breaker positions or increasing your box height. Furthermore, the unique design allows the panel to be inverted in the field and keep its labeling legible.

- 1) Completely symmetrical Type 1 boxes may be mounted with either end up. There are two pre-punched equipment ground connector locations for contractor friendly installation.
- 2) Box comes pre-punched for optional, field installable door-in-door or hinged style trims. There are also two pre-punched ground connector locations. The panel box will accept both standard ground connector (EGK and ECGK) assemblies and insulated ground connector kits (IGK and ICGK).
- 3) Interior mounting is completely symmetrical allowing it to be changed from top to bottom feed by simply rotating the interior.
- 4) Choose either a Main Breaker kit or Main Lug kit with which to terminate your incoming cables. Main lug kits are contractor friendly lugs through 350 kcmil (250 amp panel), (1) 600 kcmil or (2) 250 kcmil connectors for 400 amp panels. No line connectors in the P1 panel require multiple wires under one screw. Main Breaker kits (250 amps and below) are horizontally mounted allowing field convertible top or bottom feeds to be performed easily. MLO kits and
- Main Breaker Kits are interchangeable and can be changed/added in the field without making changes to the enclosure or interior.
- 5) Branch neutral connections are near the breaker connections to speed wiring and reduce clutter. The standard P1 neutral is rated for 100% of the panel's ampacity and will accept copper or aluminum wire. Optional 200% and 2/0 neutral kits are also available. (2/0 max. Neutral strips are now standard on all xGB/3VA41 Interiors.)
- 6) The panel includes space to add (1) sub-feed breaker (max 250 amps), feed-thru lugs or one TPS3 (SPD) kit. (Branch mounted BSPDs are also available for Surge Protection Flexibility.)
- 7) Siemens standard trim has hidden hinges and mounting hardware for added safety. The rounded door corners not only enhance the panel's appearance but also help to eliminate injuries caused from sharp corners.
- 8) Semi-flush lock comes standard. Easily identified locked position denoted by keyway being horizontal when door has been locked.





Panelboards

Revised P1 Panelboard 250 & 400A

Reference

Invertability and Flexibility!

All FT and NFT are invertable in field – Top-feed or Bottom-feed

FT
Feed-Thru Style Panel
 (Catalog Number ends with "T")^①
**NFT**
Non-Feed-Thru Style Panel
 (Catalog Number ends with "N")^②


① 66 circuits only for Factory Assembly.

② Not available for UPB..

Panelboards


Revised P1 Panelboard 250A and 400A

Reference

Revised P1 Panelboard 250A and 400A

FT


250A Configurations Feed-Thru Style Panel




NFT configurations below are
6" shorter than FT with same circuit count

FT


400A Configurations Feed-Thru Style Panel

**NFT**

250A Configurations Feed-Thru Style Panel

**NFT**

400A Configurations Feed-Thru Style Panel



Panelboards

Distributor Stock – Type P1 Panelboards

Selection

11
PANELBOARDS

Configuring An Unassembled Panel

400A Max. — 20" Wide x 5.75" Deep

- Choose the appropriate Interior from the table below.
- Choose the Main Device: Main Lugs from page 11-13, Main Breaker Kit from pages 11-13 to 11-14 and Main Breakers needed for strap kits separately from Section 7.
- Choose Branch Breakers: BL, BQD, xGB, 3VA41 (or) AFCI/GFCI from tables on pages 11-16 thru 11-19 or Section 7.
- Choose Feed-Thru Lugs or Subfeed Breaker Kit from pages 11-13 to 11-14 and Subfeed Breaker for Strap kits from Section 7 (250A max.).

Type P1 Unassembled Panelboards (Revised P1 introduced 2014)

Amps	Max. # of Poles	Revised P1 Interior Catalog Number ³	Box Size	Type 1 Enclosure	Type 3R/12 Enclosure ¹	Type 1 Front Surface	Type1 Front Flush
------	-----------------	---	----------	------------------	-----------------------------------	----------------------	-------------------

Convertible Mains — 1-Phase, 3-Wire 120/240V (BL/BQD Branch Breakers only)

250	18	P1A18MC250AT ²	32	B32	WP32	S32B	F32B
	30	P1A30MC250AT	38	B38	WP38	S38B	F38B
	42	P1A42MC250AT	44	B44	WP44	S44B	F44B
	54	P1A54MC250AT	50	B50	WP50	S50B	F50B
400	18	—	—	—	—	—	—
	30	P1A30MC400AT	62	B62	WP62	S62B	F62B
	42	P1A42MC400AT	68	B68	WP68	S68B	F68B
	54	P1A54MC400AT	74	B74	WP74	S74B	F74B
250	18	P1A18MC250CT ²	32	B32	WP32	S32B	F32B
	30	P1A30MC250CT	38	B38	WP38	S38B	F38B
	42	P1A42MC250CT	44	B44	WP44	S44B	F44B
	54	P1A54MC250CT	50	B50	WP50	S50B	F50B
400	18	—	—	—	—	—	—
	30	P1A30MC400CT	62	B62	WP62	S62B	F62B
	42	P1A42MC400CT	68	B68	WP68	S68B	F68B
	54	P1A54MC400CT	74	B74	WP74	S74B	F74B

Convertible Mains — 3-Phase, 4-Wire 208Y/120V (BL/BQD Branch Breakers only)

250	18	P1X18MC250AT ²	32	B32	WP32	S32B	F32B
	30	P1X30MC250AT	38	B38	WP38	S38B	F38B
	42	P1X42MC250AT	44	B44	WP44	S44B	F44B
	54	P1X54MC250AT	50	B50	WP50	S50B	F50B
400	18	—	—	—	—	—	—
	30	P1X30MC400AT	62	B62	WP62	S62B	F62B
	42	P1X42MC400AT	68	B68	WP68	S68B	F68B
	54	P1X54MC400AT	74	B74	WP74	S74B	F74B
250	18	P1X18MC250CT ²	32	B32	WP32	S32B	F32B
	30	P1X30MC250CT	38	B38	WP38	S38B	F38B
	42	P1X42MC250CT	44	B44	WP44	S44B	F44B
	54	P1X54MC250CT	50	B50	WP50	S50B	F50B
400	18	—	—	—	—	—	—
	30	P1X30MC400CT	62	B62	WP62	S62B	F62B
	42	P1X42MC400CT	68	B68	WP68	S68B	F68B
	54	P1X54MC400CT	74	B74	WP74	S74B	F74B

Convertible Mains — 3-Phase, 4-Wire 480Y/277V (BL/BQD Branch Breakers only)

250	18	P1E18MC250AT ²	32	B32	WP32	S32B	F32B
	30	P1E30MC250AT	38	B38	WP38	S38B	F38B
	42	P1E42MC250AT	44	B44	WP44	S44B	F44B
	54	P1E54MC250AT	50	B50	WP50	S50B	F50B
400	18	—	—	—	—	—	—
	30	P1E30MC400AT	62	B62	WP62	S62B	F62B
	42	P1E42MC400AT	68	B68	WP68	S68B	F68B
	54	P1E54MC400AT	74	B74	WP74	S74B	F74B
250	18	P1E18MC250CT ²	32	B32	WP32	S32B	F32B
	30	P1E30MC250CT	38	B38	WP38	S38B	F38B
	42	P1E42MC250CT	44	B44	WP44	S44B	F44B
	54	P1E54MC250CT	50	B50	WP50	S50B	F50B
400	18	—	—	—	—	—	—
	30	P1E30MC400CT	62	B62	WP62	S62B	F62B
	42	P1E42MC400CT	68	B68	WP68	S68B	F68B
	54	P1E54MC400CT	74	B74	WP74	S74B	F74B

Interiors for xGB/3VA41 Breakers — 3-Phase, 4-Wire 480Y/277V

250	18	P1818MC250AT ²	32	B32	WP32	S32B	F32B
	30	P1830MC250AT	38	B38	WP38	S38B	F38B
	42	P1842MC250AT	44	B44	WP44	S44B	F44B
	54	P1854MC250AT	50	B50	WP50	S50B	F50B
400	18	—	—	—	—	—	—
	30	P1830MC400AT	62	B62	WP62	S62B	F62B
	42	P1842MC400AT	68	B68	WP68	S68B	F68B
	54	P1854MC400AT	74	B74	WP74	S74B	F74B
250	18	P1818MC250CT ²	32	B32	WP32	S32B	F32B
	30	P1830MC250CT	38	B38	WP38	S38B	F38B
	42	P1842MC250CT	44	B44	WP44	S44B	F44B
	54	P1854MC250CT	50	B50	WP50	S50B	F50B
400	18	—	—	—	—	—	—
	30	P1830MC400CT	62	B62	WP62	S62B	F62B
	42	P1842MC400CT	68	B68	WP68	S68B	F68B
	54	P1854MC400CT	74	B74	WP74	S74B	F74B

¹ Front included in NEMA 3R and 3R/12 Box.

² The Revised P1 (18 circuit 250A only) is limited to 100A per connection (200A per pair) when installing BL/BQD or xGB Branch Breakers across from one another. 3VA41 does not

have this restriction. All other configurations allow 125A per connection max. (250A per pair max.)

³ Original P1 is similar Part Number - Remove "T" up to 42 circuits only.



42 circuit with Back-fed Main

54 circuit 400A

Panelboards

Distributor Stock – Type P1 Panelboards

Selection

Lug Kits — Main or Feed Thru

Amp Rating	Mat.	Wire Range (includes Neutral)	Service	Revised P1 Catalog No.®
250	AL	(1) #6 AWG-350 kcmil (CU or AL)	1 Phase	MLKA1A
			3 Phase	MLKA3A
	CU	(1) #6 AWG-350 kcmil (CU)	1 Phase	MLKC1A
			3 Phase	MLKC3A
400	AL	(2) 1/0 - 250 kcmil or (1) #2 AWG-600 kcmil	1 Phase	4MLKA1A
			3 Phase	4MLKA3A
	CU	(1) 1/0 - 600 kcmil CU cable only	1 Phase	4MLKC1A
			3 Phase	4MLKC3A
400	AL	(1) AL 1/0-750 kcmil (2) AL/CU 250kcmil max. [max.(1) 600 kcmil CU wire]	1 Phase	4MLKA1B
			3 Phase	4MLKA3B



MBKQJ3A



MBKFD3A

11
 PANELBOARDS

Main and Subfeed Strap Kits for Revised P1® (after neutral updates – April 2020)

Group	Amps	Kit Catalog #	Description	Replaces	Comments
250A RP1 Main Strap Kits	125A max	MBKVA41A	RP1 1PH Main/SF kit BL/BQD/GB/3VA4 - Includes filler #DFFPVA41A	MBKBL1A ^① MBKBC1NBA ^①	New kits allow use of all 4 breaker types with included adapter.
		MBKVA41B	RP1 3PH Main/SF kit BL/BQD/GB/3VA4 - Includes filler #DFFPVA41A	MBKBL3A ^① MBKBC3NBA ^①	
		MBKED1A MBKED3A	RP1 1PH Main/SF kit ED - 125A max RP1 3PH Main/SF kit ED - 125A max	none	Includes DF Filler #DFFPVA41A replacing #DFFPED01
	225A max	MBKQR1A MBKQR3A	RP1 1PH Main/SF kit QR - 225A max RP1 3PH Main/SF kit QR - 225A max	none	Includes DF Filler # MBKQRFK
		MBKFD1A MBKFD3A	RP1 1PH Main/SF kit FD - 250A max RP1 3PH Main/SF kit FD - 250A max	none	Includes DF Filler # DFFPVA01
	250A max	MBKVA5262A MBKVA5262B	RP1 1PH Main/SF kit 3VA52/62 - 250A max RP1 3PH Main/SF kit 3VA52/62 - 250A max	none	Includes DF Filler # DFFPVA5262A
400A RP1 Main Strap Kits	400A max	MBKVA5363A	RP1 400A 3VA Main Strap kit, 1ph or 3ph, includes: MBKVA5363JD (Large) Filler	none	These new 400A kits include both small and large filler plates.
		MBKJD3B	RP1 400A JD Strap kit 1ph/3ph 2-fillers, includes: DFFPJD02 (Large) and DFFPJD01 (Small) Filler	MBKJD1A ^① MBKJD3A ^①	
		MBKVA5363JD	RP1 400A JD to 3VA53/63 Retrofit kit 1ph/3ph - This kit will allow 3VA53/63 in old 400A RP1 only with small Deadfront opening - no access to breaker adjustments without removing DF.	none	(to be available 2021)

Neutral Kits for Revised P1® (after neutral updates – April 2020)

Group	Amps	Kit Catalog #	Description	Replaces ^①	Circuits / details
1/0 Neutral Kits	250A & 400A	LNLK5X12A	RP1 1/0 NEUTRAL LUG KIT [(5x)1/0 + (12x) #6] - short 1/0 replacement neutral strip (17POS) (5.80" long)	na	2 strips per pack - replacement parts
		LNLK7X18A	RP1 1/0 NEUTRAL LUG KIT [(7x)1/0 + (18x) #6] - long 1/0 replacement neutral strip (25POS) (8.14" Long)	na	
2/0 Neutral Kits	250A & 400A	LNLK4X11B	RP1 & P3 2/0 NEUTRAL LUG KIT (15POS) - [(4x)2/0 + (11x) #6] - 2/0 max neutral strips (6.17" Long)	LNLK30A LNLK42A LNLK54A Revised P1 only	2 strips per pack - replacement parts
		LNLK6X17B	RP1 & P3 2/0 NEUTRAL LUG KIT (23POS) - [(5x)2/0 + (17x) #6] - 2/0 max neutral strips (8.67" Long)		
		LNLK7X20B	RP1 & P3 2/0 NEUTRAL LUG KIT (27POS) - [(7x)2/0 + (20x) #6] - 2/0 max neutral strips (9.92" Long)		
Copper Neutral Kits	250A	CNLK42B	RP1 CU NEUTRAL LUG KIT, 42B - 2 short & 2 long strips (17 & 25 pos) contains: CU neutral strips and CU riser extension, plus all hardware to replace standard neutrals. CU strips are 1/0 max. and require CU cable.	CNLK30A CNLK42A CNLK54A Revised P1 only	250A - 18, 30, 42
	250A & 400A	CNLK54B	RP1 CU NEUTRAL LUG KIT, 54B - 4 long strips (25 pos) contains: CU neutral strips and CU riser extension, plus all hardware to replace standard neutrals. CU strips are 1/0 max. and require CU cable.		all 400A - 30, 54, 66 250A - 54, 66
200% Neutral Kits	250A	2NLK42B	RP1 250A 200% NEUTRAL LUG KITS. Contains: CU neutral strips (2 short & 2 long strips (17 & 25 pos)), CU neutral extensions and an additional AL Line Lug (350kcmil), plus all hardware to replace standard neutrals. CU strips are 1/0 max. and require CU cable. (200% neutral kits require CU neutrals)	2NLK30A 2NLK42A 2NLK54A Revised P1 only	250A - 18, 30, 42
		2NLK54B	RP1 250A 200% NEUTRAL LUG KITS. Contains: CU neutral strips (4 long strips (25 pos)), CU neutral extensions and an additional AL Line Lug (350kcmil), plus all hardware to replace standard neutrals. CU strips are 1/0 max. and require CU cable. (200% neutral kits require CU neutrals)		250A - 54, 66
	400A	42NLK54B	RP1 400A 200% NEUTRAL LUG KIT contains: CU neutral strips (4 long strips (25 pos)), CU neutral extensions and an additional AL Line Lugs (600kcmil and 300kcmil), plus all hardware to replace standard neutrals. CU strips are 1/0 max. and require CU cable. (200% neutral kits require CU neutrals)	42NLK30A 42NLK42A 42NLK54A Revised P1 only	all 400A - 30, 54, 66

① Parts will no longer be available after inventory is depleted. OK to use up inventory.

② Revised P1 kits cannot be used with original P1. See page 11-15.

Panelboards

Warehouse Stock/Unassembled – Type P1 Panelboards

Selection

 11
 PANELBOARDS

Main Breaker Mounting Kits with Breakers for P1 Panels (250A and lower can be used as subfeed kits also)

Frame size Reference	Revised P1 Catalog No.	Description	Max IR (kA) at		
			240V	480V	600V
ED 3-ph 125A Max.	MBKED3100A	Kit w/3-pole ED4 100A breaker	65	18	—
	MBKED3125A	Kit w/3-pole ED4 125A breaker	65	18	—
QR 1-ph 225A Max.	MBKQR1125A	Kit w/2-pole QR2 125A breaker	10	—	—
	MBKQR1150A	Kit w/2-pole QR2 150A breaker	10	—	—
	MBKQR1175A	Kit w/2-pole QR2 175A breaker	10	—	—
	MBKQR1200A	Kit w/2-pole QR2 200A breaker	10	—	—
	MBKQR1225A	Kit w/2-pole QR2 225A breaker	10	—	—
HQR 1-ph 225A Max.	MBKQR1125H	A Kit w/2-pole HQR2 125A breaker	65	—	—
	MBKQR1150H	A Kit w/2-pole HQR2 150A breaker	65	—	—
	MBKQR1175H	A Kit w/2-pole HQR2 175A breaker	65	—	—
	MBKQR1200H	A Kit w/2-pole HQR2 200A breaker	65	—	—
	MBKQR1225H	A Kit w/2-pole HQR2 225A breaker	65	—	—
QR2 3-ph 225A Max.	MBKQR3125A	Kit w/3-pole QR2 125A breaker	10	—	—
	MBKQR3150A	Kit w/3-pole QR2 150A breaker	10	—	—
	MBKQR3175A	Kit w/3-pole QR2 175A breaker	10	—	—
	MBKQR3200A	Kit w/3-pole QR2 200A breaker	10	—	—
	MBKQR3225A	Kit w/3-pole QR2 225A breaker	10	—	—
HQR2 3-ph 225A Max.	MBKQR3125H	A Kit w/3-pole HQR2 125A breaker	65	—	—
	MBKQR3150H	A Kit w/3-pole HQR2 150A breaker	65	—	—
	MBKQR3175H	A Kit w/3-pole HQR2 175A breaker	65	—	—
	MBKQR3200H	A Kit w/3-pole HQR2 200A breaker	65	—	—
	MBKQR3225H	A Kit w/3-pole HQR2 225A breaker	65	—	—
3VA52 3-ph 250A Max.	MBKVAM3150A	RP1 150A MB kit, 35kA 3ph 3VA52	85	35	18
	MBKVAM3200A	RP1 200A MB kit, 35kA 3ph 3VA52	85	35	18
	MBKVAM3225A	RP1 225A MB kit, 35kA 3ph 3VA52	85	35	18
	MBKVAM3250A	RP1 250A MB kit, 35kA 3ph 3VA52	85	35	18
	MBKVAH3200A	RP1 200A MB kit, 65kA 3ph 3VA52	100	65	25
	MBKVAH3250A	RP1 250A MB kit, 65kA 3ph 3VA52	100	65	25
FD 3-ph 250A Max.	MBKFD3150A	Kit w/3-pole FXD6 150A breaker	65	35	22
	MBKFD3175A	Kit w/3-pole FXD6 175A breaker	65	35	22
	MBKFD3200A	Kit w/3-pole FXD6 200A breaker	65	35	22
	MBKFD3225A	Kit w/3-pole FXD6 225A breaker	65	35	22
	MBKFD3250A	Kit w/3-pole FXD6 250A breaker	65	35	22
3VA53 3-ph 400A Max.	MBKVAM1300A	RP1 300A MB kit, 35kA 1ph 3VA53	85	35	18
	MBKVAM1400A	RP1 400A MB kit, 35kA 1ph 3VA53	85	35	18
	MBKVAM3300A	RP1 300A MB kit, 35kA 3ph 3VA53	85	35	18
	MBKVAM3400A	RP1 400A MB kit, 35kA 3ph 3VA53	85	35	18
	MBKVAH3300A	RP1 300A MB kit, 65kA 3ph 3VA53	100	65	25
	MBKVAH3400A	RP1 400A MB kit, 65kA 3ph 3VA53	100	65	25
JD 1-ph 400A Max.	MBKJD1300A	Kit w/2-pole JXD6 300A breaker	65	35	—
	MBKJD1400A	Kit w/2-pole JXD6 400A breaker	65	35	—
	MBKJD12300A	Kit w/2-pole JXD2 300A breaker	65	—	—
	MBKJD12400A	Kit w/2-pole JXD2 400A breaker	65	—	—
JD 3-ph 400A Max.	MBKJD3300A	Kit w/3-pole JXD6 300A breaker	65	35	—
	MBKJD3400A	Kit w/3-pole JXD6 400A breaker	65	35	—
	MBKJD32300A	Kit w/3-pole JXD2 300A breaker	65	—	—
	MBKJD32400A	Kit w/3-pole JXD2 400A breaker	65	—	—

Branch Breakers Selection for P1

Selection Guide

1. Select breaker type.
2. Select required amperage.
3. Select number of poles.
4. Select branch breaker catalog numbers.
5. Select ground bar and filler plates. (See replacement parts & accessories on Page 11-13.)



300A Main installed.
These Revised P1 kits can now be used as top or bottom feed.

Panelboards

Panelboard Replacement, Modification, and Additions

Selection

S1/S2 Panels—All the original P1 panel kits for 250 amp and below panels will work for 250 amp maximum S1/S2 panels

(will not work for S1/S2 400A and above).

Note: Revised P1 kits will not work with S1/S2 or SE Panels.

Original P1 Kits

Original P1 Main or Subfeed Strap Kits without Breakers and MLO kits

S1/S2 Panels—All the original P1 panel kits for 250 amp and below panels will work for 250 amp maximum S1/S2 panels (will not work for S1/S2 400A and above).

Note: Revised P1 kits will not work with S1/S2 or SE Panels.

Strap kits for Original P1 product only - Breaker kits not available				
Original P1 Catalog No.	Description of breaker type to order	Phase	Amps Max.	Available for Subfeed
MBKBL1	2-pole BL/BLH/HBL 15A-100A	1	100A	yes
MBKBL3	3-pole BL/BLH/HBL 15A-100A	3	100A	yes
MBKBC3	3-pole BQD 15A-100A	3	100A	yes
MBKNB1	2-pole NGB/LGB/HGB 15A-125A	1	125A	yes
MBKNB3	3-pole NGB/LGB/HGB 15A-125A	3	125A	yes
MBKED1	2-pole ED4/HED4 50A-125A	1	125A	yes
MBKED3	3-pole ED4/HED4 50A-125A	3	125A	yes
MBKQR1	2-pole QR(H)2/HQR2(H) 125A-225A	1	225A	yes
MBKQR3	3-pole QR(H)2/HQR2(H) 125A-225A	3	225A	yes
MBKFD1	2-pole F(X)D6/HF(X)D6 70A-250A	1	250A	yes
MBKFD3	3-pole F(X)D6/HF(X)D6 70A-250A	3	250A	yes
MBKJD1	2-pole JXD2/J(X)D6/HJ(X)D6 200A-400A	1	400A	NO
MBKJD3	3-pole JXD2/J(X)D6/HJ(X)D6 200A-400A	3	400A	NO

Strap kits for 400/600A S1/S2 and all SE panels - breakers not included				
Catalog No.	Description of breaker type to order	Phase	Amps Max.	Available for Subfeed
SMBKED1	2-pole ED2, ED4, ED6, HED4, HHED6	1	125A	yes
SMBKED3	3-pole ED2, ED4, ED6, HED4, HHED6	3	125A	yes
SMBKFD1	2-pole FXD6, FD6, HFXD6, HFD6	1	250A	yes
SMBKFD3	3-pole FXD6, FD6, HFXD6, HFD6	3	250A	yes
SMBKJD1	2-pole JD6, JXD6, HJD6, HJXD6	1	400A	yes
SMBKJD3	3-pole JD6, JXD6, HJD6, HJXD6	3	400A	yes

MLO kits for Original P1 product only

* MLO Kits available for SE Panels - AL 250A only

Note: 400/600A S1/S2 MLO kits no longer available

Original P1 Cat No.	Description	Phase	Amps Max.	Available for P1 Feed-thru
MLKA1*	(1) #6 AWG- 350 kcmil (CU or AL)	1	250A	yes
MLKA3*		3		yes
MLKC1	(1) #6 AWG- 350 kcmil (CU)	1	250A	yes
MLKC3		3		yes
4MLKA1	(2) 1/0 - 250 kcmil or (1) #2 AWG-600 kcmil	1	400A	yes
4MLKA3		3		yes
4MLKC1	(2) 1/0 - 4/0 or (1) 1/0 - 600 kcmil	1	400A	yes
4MLKC3		3		yes

Other applications:

For P4/S4 and 10" deep SPP panels see page 11-92 for branch breaker mounting kits.

For P5/S5 and 12.75" deep SPP panels see page 11-106 for branch breaker mounting kits.

For P4/F1 and 10" deep FPP panels see page 11-92 for branch fusible switch mounting kits.

For P5/F2 and 12.75" deep FPP panels see page 11-106 for branch fusible switch mounting kits.

For Series 5, Series 6, CDP6 and VB 6 panels as well as FC20, FCI, FCII, SB1, SB2 and SB3 distribution switchboards, see page 12-32 for branch device mounting kits.

Panelboards

Warehouse Stock/Unassembled

Selection

 11
 PANELBOARDS


Branch Breakers Selection for P1

BL Family Circuit Breakers

Amp Ratings	1-Pole	2-Pole		3-Pole
	120V	240/120V	240V	240V
Type BL - 10,000A IR^①				
15	B115	B215	B215R	B315
20	B120	B220	B220R	B320
25	B125	B225	B225R	B325
30	B130	B230	B230R	B330
35	B135	B235	B235R	B335
40	B140	B240	B240R	B340
45	B145	B245	B245R	B345
50	B150	B250	B250R	B350
60	B160	B260	—	B360
70	B170	B270	—	B370
80	—	B280	—	B380
90	—	B290	—	B390
100	—	B2100	—	B3100
Type BLH — 22,000 IR^①				
15	B115H	B215H	—	B315H
20	B120H	B220H	—	B320H
25	B125H	B225H	—	B325H
30	B130H	B230H	—	B330H
35	B135H	B235H	—	B335H
40	B140H	B240H	—	B340H
45	B145H	B245H	—	B345H
50	B150H	B250H	—	B350H
60	B160H	B260H	—	B360H
70	B170H	B270H	—	B370H
80	—	B280H	—	B380H
90	—	B290H	—	B390H
100	—	B2100H	—	B3100H
Type HBL — 65,000A IR^①				
15	B115HH	B215HH	—	B315HH
20	B120HH	B220HH	—	B320HH
30	B130HH	B230HH	—	B330HH
40	B140HH	B240HH	—	B340HH
50	B150HH	B250HH	—	B350HH
60	—	B260HH	—	B360HH
70	—	B270HH	—	B370HH
80	—	B280HH	—	B380HH
90	—	B290HH	—	B390HH
100	—	B2100HH	—	B3100HH

BT Twin Family Circuit Breakers

The Space saver duplex breakers combine two independent 1/2" breaker poles in a common unit. This unit bolts into any location that would typically fit a 1-pole BL breaker and requires only 1" of panel space.



Replacement for 1-pole BL series (15A & 20A only)

Amp Ratings	Width	Circuits	BT (10k AIC)	BTH (22k AIC)	Details
Type BT and BTH					
15-15	1" pole	2	B1515	B1515H	Two 15A circuits
20-20	1" pole	2	B2020	B2020H	Two 20A circuits

BQD & GB Family Circuit Breakers

Amp Ratings	1-Pole	2-Pole	3-Pole
	277V	480Y/277V	480Y/277V
Type BQD^② – 14,000A IR @ 480/277V 65,000A IR @ 240V			
15	BQD115	BQD215	BQD315
20	BQD120	BQD220	BQD320
25	BQD125	BQD225	BQD325
30	BQD130	BQD230	BQD330
35	BQD135	BQD235	BQD335
40	BQD140	BQD240	BQD340
45	BQD145	BQD245	BQD345
50	BQD150	BQD250	BQD350
60	BQD160	BQD260	BQD360
70	BQD170	BQD270	BQD370
80	BQD180	BQD280	BQD380
90	BQD190	BQD290	BQD390
100	BQD1100	BQD2100	BQD3100
GB Family^②			
Type NGB - 25,000A IR @ 480/277V 100,000A IR @ 240V			
Type HGB - 35,000A IR @ 480/277V 100,000A IR @ 240V			
Type LGB - 65,000A IR @ 480/277V 100,000A IR @ 240V			
Type NGB/HGB/LGB - 14,000A IR @ 347V and 600Y/347V			
Amp Ratings	277V	480Y/277V	480Y/277V
15	xGB1B015B	xGB2B015B	xGB3B015B
20	xGB1B020B	xGB2B020B	xGB3B020B
25	xGB1B025B	xGB2B025B	xGB3B025B
30	xGB1B030B	xGB2B030B	xGB3B030B
35	xGB1B035B	xGB2B035B	xGB3B035B
40	xGB1B040B	xGB2B040B	xGB3B040B
45	xGB1B045B	xGB2B045B	xGB3B045B
50	xGB1B050B	xGB2B050B	xGB3B050B
60	xGB1B060B	xGB2B060B	xGB3B060B
70	xGB1B070B	xGB2B070B	xGB3B070B
80	xGB1B080B	xGB2B080B	xGB3B080B
90	xGB1B090B	xGB2B090B	xGB3B090B
100	xGB1B100B	xGB2B100B	xGB3B100B
110	xGB1B110B	xGB2B110B	xGB3B110B
125	xGB1B125B	xGB2B125B	xGB3B125B

Typical Cable Ranges by Breaker Type

UL Breaker Type	Amps	Connector Range for AL cable	Connector Range for CU cable
BL	15-20A	#12-#10 AWG	#14-#10 AWG
	25-35A	#8-#6 AWG	#8-#6 AWG
	10-50A	#8-#4 AWG	#8-#6 AWG
	55-70A	#8-#2 AWG	#8-#4 AWG
	80-100A	#2-#1/0 AWG	#4-#1/0 AWG
BQD	15-40A	#12-#6 AWG	#14-#6 AWG
	45-100A	#6-1/0 AWG	#8 - #1 AWG
xGB	15-30A	#12-#6 AWG	#14-#6 AWG
	35-125A	#4-2/0 AWG	#6-1/0 AWG
3VA41	15-125A	#14 AWG - 3/0	#14 AWG - 2/0

① To add Shunt trip to BL breakers (factory assembled only), See SpeedFax Breaker accessories section 7. One inch additional unit space required typically.

② To add Shunt trip or other accessories to BQD and GB family breakers, See SpeedFax Breaker accessories section 7. One inch additional unit space required typically for each.

Panelboards

Warehouse Stock/Unassembled

Selection

AFCI/GFCI

Electronic Circuit Breakers		1-Pole		2-Pole		Catalog Number
Trip Type	Breaker Type	Max IR (kA) at 120V	Amp Ratings Available	Max IR (kA) at 120/240	Amp Ratings Available	
Combination AFCI	BAF2	10	15	—	—	BA115AFC
		10	20	—	—	BA120AFC
	BAFH2	22	15	—	—	BA115AFCH
		22	20	—	—	BA120AFCH
	HBAF2	65	15	—	—	BA115AFCHH
		65	20	—	—	BA120AFCHH
	BAF	—	—	10	15	B215AFC
		—	—	10	20	B220AFC
	BAFH	—	—	22	15	B215AFCH
		—	—	22	20	B220AFCH
Dual Function AFCI/GFCI	BFGA2	10	15	—	—	B115DF
		10	20	—	—	B120DF
	BFGAH2	22	15	—	—	B115DFH
		22	20	—	—	B120DFH
	HBFGA2	65	15	—	—	B115DFHH
		65	20	—	—	B120DFHH
Switching Neutrals ¹	BLG 2-Wire/3-Wire Common Trip	10	15	—	—	BG215
		10	20	—	—	BG220
		—	—	10	30	BG330
GFCI Personnel Protection (5mA)	BLF2	10	15	—	—	BF115A
		10	20	—	—	BF120A
		10	30	—	—	BF130A
	BLF	—	—	10	15	BF215A
		—	—	10	20	BF220A
		—	—	10	30	BF230A
		—	—	10	40	BF240A
		—	—	10	50	BF250A
		—	—	10	60	BF260A
	BLHF2	22	15	—	—	BF115AH
		22	20	—	—	BF120AH
		22	30	—	—	BF130AH
	BLHF	—	—	22	15	BF215AH
		—	—	22	20	BF220AH
		—	—	22	30	BF230AH
		—	—	22	40	BF240AH
		—	—	22	50	BF250AH
		—	—	22	60	BF260AH
	HBLF2	65	15	—	—	BF115AHH
		65	20	—	—	BF120AHH
		65	30	—	—	BF130AHH
GFCI Ground Fault Equipment Protection (30mA)	BLE	10	15	—	—	BE1153
		10	20	—	—	BE1203
		10	30	—	—	BE130
		—	—	10	15	BE215
		—	—	10	20	BE220
		—	—	10	30	BE230
		—	—	10	40	BE240
		—	—	10	50	BE250
		—	—	10	60	BE260
	BLEH	22	15	—	—	BE115H2
		22	20	—	—	BE120H2
		22	30	—	—	BE130H2
		—	—	22	15	BE215H2
		—	—	22	20	BE220H2
		—	—	22	30	BE230H2
		—	—	22	40	BE240H2
		—	—	22	50	BE250H2
		—	—	22	60	BE260H2
		—	—	22	60	BE260H2

^① Built to order. Additional "circuit" is included for neutral (via pigtail) and is NOT connected to bus. 2-pole is one

phase and one neutral pigtail. 3-pole is two phase connections and one neutral pigtail.

^② Allow 8-10 weeks for delivery
^③ UL Listed as SWD (Switching Duty) Rated, suitable for 120V AC fluorescent lighting

Panelboards

Warehouse Stock/Unassembled

Selection

 11
 PANELBOARDS

3VA41 TMTU 125A max. - breakers w/AL lugs included

3VA41 1-Pole (1" wide)

		UL Type Code ==>	SEAB	MEAB	HEAB
		Panelboard MB codes ==>	V1	V2	V3
		120 VAC kAIC rating ==>	1-pole	1-pole	1-pole
		277 VAC kAIC rating ==>	65	85	150 ^①
		347 VAC kAIC rating ==>	25	35	65
		125 VDC kAIC rating ==>	14	18	25
			14 ^②	25 ^②	30 ^②
		IC family @ 277VAC ==>	25kA	35kA	65kA
amps	code	FTFM Trip included ==>	TM210	TM210	TM210
15	95	3VA41 1P breaker w/TM210 1 Pole 3VA41 with AL connectors included. For copper, use the following kits: 15A-40A use # 3VA9133-0JD10 45A-125A use # 3VA9133-0JD11 Note: No accessory pockets available	3VA4195-4ED14-0AA0	...-5ED...	...-6ED...
20	20		3VA4120-4ED14-0AA0	...-5ED...	...-6ED...
25	25		3VA4125-4ED14-0AA0	...-5ED...	...-6ED...
30	30		3VA4130-4ED14-0AA0	...-5ED...	...-6ED...
35	35		3VA4135-4ED14-0AA0	...-5ED...	...-6ED...
40	40		3VA4140-4ED14-0AA0	...-5ED...	...-6ED...
45	45		3VA4145-4ED14-0AA0	...-5ED...	...-6ED...
50	50		3VA4150-4ED14-0AA0	...-5ED...	...-6ED...
60	60		3VA4160-4ED14-0AA0	...-5ED...	...-6ED...
70	70		3VA4170-4ED14-0AA0	...-5ED...	...-6ED...
80	80		3VA4180-4ED14-0AA0	...-5ED...	...-6ED...
90	90		3VA4190-4ED14-0AA0	...-5ED...	...-6ED...
100	10		3VA4110-4ED14-0AA0	...-5ED...	...-6ED...
110	11		3VA4111-4ED14-0AA0	...-5ED...	...-6ED...
125	12		3VA4112-4ED14-0AA0	...-5ED...	...-6ED...

3VA41 1-Pole in 2-Pole Frame (2" wide)

		IC family @ 277VAC ==>	25kA	35kA	65kA
amps	code	FTFM Trip included ==>	TM210	TM210	TM210
15	95	3VA41 1P in 2-P Frame breaker w/TM210 1 Pole in 2-pole Frame 3VA41 with AL connectors included. For copper, use the following kits: 15A-40A use # 3VA9133-0JD10 45A-125A use # 3VA9133-0JD11 Note: Only 3 Left side Accessory pockets available	3VA4195-4ED54-0AA0	...-5ED...	...-6ED...
20	20		3VA4120-4ED54-0AA0	...-5ED...	...-6ED...
25	25		3VA4125-4ED54-0AA0	...-5ED...	...-6ED...
30	30		3VA4130-4ED54-0AA0	...-5ED...	...-6ED...
35	35		3VA4135-4ED54-0AA0	...-5ED...	...-6ED...
40	40		3VA4140-4ED54-0AA0	...-5ED...	...-6ED...
45	45		3VA4145-4ED54-0AA0	...-5ED...	...-6ED...
50	50		3VA4150-4ED54-0AA0	...-5ED...	...-6ED...
60	60		3VA4160-4ED54-0AA0	...-5ED...	...-6ED...
70	70		3VA4170-4ED54-0AA0	...-5ED...	...-6ED...
80	80		3VA4180-4ED54-0AA0	...-5ED...	...-6ED...
90	90		3VA4190-4ED54-0AA0	...-5ED...	...-6ED...
100	10		3VA4110-4ED54-0AA0	...-5ED...	...-6ED...
110	11		3VA4111-4ED54-0AA0	...-5ED...	...-6ED...
125	12		3VA4112-4ED54-0AA0	...-5ED...	...-6ED...

① Although some breakers have a kAIC rating above 100 kAIC – many panels are limited to 100 kAIC or less.

② DC Voltage panels are limited by various factors. These DC ratings apply to the Breaker only.

Panelboards

Warehouse Stock/Unassembled

Pricing

3VA41 TMTU 125A max. - breakers w/AL lugs included

3VA41 2-Pole & 3-Pole (2" & 3" wide)

		UL Type Code ==>	SEAB	MEAB	HEAB
		Panelboard MB codes ==>	V1 3-pole 2-pole	V2 3-p 2-p	V3 3-p 2-p
		240 VAC kAIC rating ==>	65 65	85 85	150 ^① 150 ^①
		480Y/277VAC kAIC rating ==>	25 25	35 35	65 65
		480 VAC kAIC rating ==>	25 25	35 35	65 65
		600Y/347VAC kAIC rating ==>	14 14	18 18	25 25
		600 VAC kAIC rating ==>	na na	na na	na na
		250 VDC kAIC rating ==>	na 50 ^②	na 85 ^②	na 100 ^②
		IC family @ 480VAC ==>	25kA	35kA	65kA
amps	code	FTAM Trip included ==>	TM210	TM210	TM210
15	95	3VA41 2P breaker w/TM210 2 Pole 3VA41 with AL connectors included. For copper, use the following kits: 15A-40A use # 3VA9133-0JD10 45A-125A use # 3VA9133-0JD11 Note: Only 3 Left side Accessory pockets available	3VA4195-4ED24-0AA0	...-5ED...	...-6ED...
20	20		3VA4120-4ED24-0AA0	...-5ED...	...-6ED...
25	25		3VA4125-4ED24-0AA0	...-5ED...	...-6ED...
30	30		3VA4130-4ED24-0AA0	...-5ED...	...-6ED...
35	35		3VA4135-4ED24-0AA0	...-5ED...	...-6ED...
40	40		3VA4140-4ED24-0AA0	...-5ED...	...-6ED...
45	45		3VA4145-4ED24-0AA0	...-5ED...	...-6ED...
50	50		3VA4150-4ED24-0AA0	...-5ED...	...-6ED...
60	60		3VA4160-4ED24-0AA0	...-5ED...	...-6ED...
70	70		3VA4170-4ED24-0AA0	...-5ED...	...-6ED...
80	80		3VA4180-4ED24-0AA0	...-5ED...	...-6ED...
90	90		3VA4190-4ED24-0AA0	...-5ED...	...-6ED...
100	10		3VA4110-4ED24-0AA0	...-5ED...	...-6ED...
110	11		3VA4111-4ED24-0AA0	...-5ED...	...-6ED...
125	12		3VA4112-4ED24-0AA0	...-5ED...	...-6ED...
amps	code	FTAM Trip included ==>	TM210	TM210	TM210
15	95	3VA41 3P breaker w/TM210 3 Pole 3VA41 with AL connectors included. For copper, use the following kits: 15A-40A use # 3VA9133-0JD10 45A-125A use # 3VA9133-0JD11 Note: 3 Left side and 3 right side Accessory pockets available	3VA4195-4ED34-0AA0	...-5ED...	...-6ED...
20	20		3VA4120-4ED34-0AA0	...-5ED...	...-6ED...
25	25		3VA4125-4ED34-0AA0	...-5ED...	...-6ED...
30	30		3VA4130-4ED34-0AA0	...-5ED...	...-6ED...
35	35		3VA4135-4ED34-0AA0	...-5ED...	...-6ED...
40	40		3VA4140-4ED34-0AA0	...-5ED...	...-6ED...
45	45		3VA4145-4ED34-0AA0	...-5ED...	...-6ED...
50	50		3VA4150-4ED34-0AA0	...-5ED...	...-6ED...
60	60		3VA4160-4ED34-0AA0	...-5ED...	...-6ED...
70	70		3VA4170-4ED34-0AA0	...-5ED...	...-6ED...
80	80		3VA4180-4ED34-0AA0	...-5ED...	...-6ED...
90	90		3VA4190-4ED34-0AA0	...-5ED...	...-6ED...
100	10		3VA4110-4ED34-0AA0	...-5ED...	...-6ED...
110	11		3VA4111-4ED34-0AA0	...-5ED...	...-6ED...
125	12		3VA4112-4ED34-0AA0	...-5ED...	...-6ED...
amps	code	Molded Case Switch			
100	10	3VA41 2P MCS 65 kA	HEAB only 65ka ==> 3VA4110-1BB24-0AA0		
100	10	3VA41 3P MCS 65 kA	HEAB only 65ka ==> 3VA4110-1BB34-0AA0		

① Although some breakers have a kAIC rating above 100 kAIC – many panels are limited to 100 kAIC or less.

② DC Voltage panels are limited by various factors. These DC ratings apply to the Breaker only.

Panelboards

Miscellaneous accessories

Selection

 11
 PANELBOARDS

Spare Parts Kits for Revised P1 Panels

Kit Number	Current Product					Old Product is no longer Manufactured, some kits are available				Product Description	Drawing # ref for part or kit
	P1 Revised	P2	P3	C1	C2	P1 Original	S1, S2, SE	qty/kit			
Note: Some kits apply to only specific enclosures used or configurations of the product listed											
Deadfront Parts											
NBK01A	X					X		1	Number Strips 1–60. Stick-on type; Use w/ P1 series Panels – includes 1/2" spacing numbers for BT twins	replaces NBK03	
NBK02A	X					X		1	Number Strips 61-120. Stick-on type; Use w/ P1 series Panels – includes 1/2" spacing numbers for BT twins	replaces NBK04-05	
NBK03A	X					X		1	Number Strips 121-240. Stick-on type; Use w/ P1 series Panels – includes 1/2" spacing numbers for BT twins	replaces NBK06-08	
P1DFS250AFT	X							1	P1 250A Deadfront Support - for Feed-thru interiors only (4 per interior) Part # 11-D-3323-01 (replaces # 11-D-3212-01)	11-D-3323	
P1DFS250ANFT	X							1	P1 250A Deadfront Support - for Non Feed-thru interiors only (4 per interior) Part # 11-D-3323-02 (replaces # 11-D-3212-02)	11-D-3323	
P1DFS400A	X							1	P1 400A Deadfront Support (new for 3VA) - for both FT and NFT interiors. (#11-D-3315-01 replaces # 11-D-3004-01) (4 per interior)	11-D-3315	
Filler Plates											
DFFP1A	X	X	X	X	X	X	X	1	DFFP1A Blank filler , 1 inch snap-in, replaced old QF3 and DFFP1 in Systems Products. Ref. old #12-1800-01 and 11-D-4554-01	11-D-4613-01	
DFFP01B	X			X		X		1	P1 Main or Subfeed 250A Blank Filler Plate (use for Original or Revised P1 - also replaces DFFP01A/11-D-4560-01/12-A-1801-01) (Installs Vertical for 400A Main w/small DF opening)	11-D-4612-01	
DFFP01C	X							1	P1 Main 400A Blank Filler Plate (use for Revised P1 400A with Large MB opening only)	11-D-4600-01	
DFFPVA41A	X							1	RP1 Main/Sub-feed, 3VA4/BL/BQD/ED/xGB filler (replaces DFFPED01 / 12-A-1802-01)	11-D-4604-01	
DFFPVA5262A	X							1	RP1 Main or Subfeed Filler 3VA52/61/62 – new filler for P1 150A-250A 3VA frame breakers	11-D-4617-01	
DFFPVA5363A	X	X	X					1	RP1 400A Main Filler 3VA53/63 (also used in P2/P3 applications) – for RP1 Deadfronts with Large MB opening only	11-D-4617-01	
MBKVA5363JD	X							1	RP1 400A Main only Filler 3VA53/63 – for Deadfronts with Small MB opening only (replacing a JD Main)	tbd - being developed	
DFFPED01 (replaced by DFFPVA41A)	X					X		1	P1 Main Filler 100-125A frames ED, BL/BQD or xGB (old filler used for Original or Revised P1 and other applications)	12-A-1802-61	
DFFPFD01	X	X	X			X	X	1	FD Main Filler Plate for 1-Ph and 3-Ph P1 Panels (use for Original or Revised P1 and other applications)(P2/P3 and S1/S2/SE)	12-A-1803-61	
DFFPJD01	X	X	X			X	X	1	JD Main Filler Plate for 1-Ph and 3-Ph P1 Panels – Small MB opening (use for Original or Revised P1 & other applications)(P2/P3 & S1/S2)	11-D-4522-61	
DFFPJD02	X					X		1	JD Main Filler Plate for 1-Ph and 3-Ph – for P1 Panels with Large MB Opening only.	11-D-4598-01	
DFFPQJ01	X					X		1	QJ Main Filler Plate for 3-Phase (3-pole) P1 Panels (use for Original or Revised P1 and other applications)	12-A-1804-61	
DFFPQJ02	X					X		1	QJ Main Filler Plate for 1-Phase (2-pole) P1 Panels (use for Original or Revised P1 and other applications)	12-A-1804-62	
MBKQRFK	X					X		1	P1/Revised P1 Filler for 1PH/3PH QR. Horizontal Mount only.	11-D-2643-01	
Service Entrance Barriers Kits (SEB)											
SEBKR1V1	X							1	SEB Kit for RP1 with FD, QJ or QR Horizontal Main	11-A-1148-01	
SEBKR1V2	X							1	SEB Kit for RP1 with ED Horizontal Main	11-A-1148-01	
SEBKR1V3	X							1	SEB Kit for RP1 with back-fed BL/BQD Main in Unit Space	11-A-1149-01	
SEBKR1V4	X							1	SEB Kit for RP1 with back-fed xGB Main in Unit Space	11-A-1149-01	
SEBKR1V5	X							1	SEB Kit for RP1 with BL/BQD/xGB Main - with steel breaker brackets	11-A-1165-01	
SEBKR1V6	X							1	SEB Kit for RP1 with BL/BQD/GB/3VA41 Main - with all plastic strap kit	11-A-1194-01	
SEBKR1V7	X							1	SEB Kit for RP1 with 3VA52/61/62 Horizontal Main	11-B-1060-01	
SEBKP1P2P3V1	X	X	X					1	SEB Kit for RP1 with RP1/P2/P3 with JD/LD or 3VA53/63 Vertical Main	11-A-1157-01	
Ground Bar & Bond Kits											
BK1A	X							1	Revised P1 Bonding Kit including Service Disconnect Label	11-A-2024-01	
ECGK	X	X	X			X		1	ECGK Copper Ground Bus Kit, Connection count: (6) of #14-1/0 and (15) of #14-6 Connections (21 Holes total). Some connections allow multiple wires.	11-A-2024-01	
EGK	X	X	X			X		1	ECGK Al/Cu Ground Bus Kit, Connection count: (6) of #14-1/0 and (15) of #14-6 Connections (21 Holes total). Some connections allow multiple wires.	11-A-2024-01	
ICGK	X	X	X			X		1	ICGK Insulated Copper Ground Bus Kit, Connection count: (6) of #14-1/0 and (15) of #14-6 Connections (21 Holes total). Some connections allow multiple wires.	11-A-2024-01	
IGK	X	X	X			X		1	IGK Insulated Al/Cu Ground Bus Kit, Connection count: (6) of #14-1/0 and (15) of #14-6 Connections (21 Holes total). Some connections allow multiple wires.	11-A-2024-01	

Panelboards

Miscellaneous accessories

Selection

Spare Parts Kits for Revised P1 Panels (cont.)

Kit Number	Current Product					Old Product is no longer Manufactured, some kits are available			Product Description	Drawing # ref for part or kit
	P1 Revised	P2	P3	C1	C2	P1 Original	S1, S2, SE	qty/ kit		
Note: Some kits apply to only specific enclosures used or configurations of the product listed										
General Hardware										
IMK1	X	X	X			X		1	Interior Mounting Kit with Adjustment Provisions for P1/P2/P3	11-A-2024-01
LPDC01	X	X	X	X	X	X	X	10	Panelboard Directory Card. 5.5"X5", for 1-90 circuits. Mates with pouch # 11-1824-01	12-1110
LPDC02	X	X	X	X	X	X	X	10	Panelboard Directory Vinyl Pouch, 6.3"x6.1". Mates with Directory Card #12-1110-01	11-1824
MCHK	X	X	X	X	X	X	X	1	MCHK - Metal Card Holder Kit - Field Installable	12-A-2098-00
LPJSPDNUT01	X	X	X	X	X	X	X	25	Replacement J-nuts for use with lighting panel fronts and deadfronts. Also used in miscellaneous other applications.	11-A-1820-61
LPTS01	X	X	X	X	X	X	X	25	Trim Screw, Lighting Panel Front, 0.547" Length, ¼-20 Machine Screw Thread (kit pending - not yet available) ref #11-A-1819-01	11-A-1819
P1CONACPHCU	X							6	RP1 A/C-Phase Replacement Copper Connectors, Kit of 6 pcs plus mounting hardware. Also can be used to replaced AL A/C-Phase Connectors.	11-D-2572-02
P1CONBPHAL	X							6	RP1 B-Phase Replacement Aluminum Connectors, Kit of 6 pcs plus mounting hardware	11-D-2573-01
P1CONBPHCU	X							6	RP1 B-Phase Replacement Copper Connectors, Kit of 6 pcs plus mounting hardware	11-D-2573-02
P1SCRWS	X					X		42	P1 Branch breaker mounting screws - pack of 42 screws, part #11-A-1505-03, 10-32 x 0.312" Hex Washer Head Screw - Do Not Substitute	11-A-2010-01
LP3RHP01	X	X	X			X		12	3R/12 Hinge Pin, 0.188" dia. Steel w/Zinc plate (kit pending, not yet available) ref # 11-1902-01	11-1902
ref 31-1905-01	X	X	X	X	X	X		1	NEMA 3R T-Handle with hardware, uses B363A key - does not include key (kit needed with all mounting hardware and keys - in process)	31-1905
LPKEY01A	X	X	X	X	X	X		4	Key for standard Panelboard Lock series 1-1895-0x. Siemens FAS-Latch and other various fronts use this standard key #B363A	B363A
LPKEY01B	X	X	X	X	X	X		25	Key for standard Panelboard Lock series 1-1895-0x. Siemens FAS-Latch and other various fronts use this standard key #B363A	B363A
LPLOCK01A	X	X	X	X	X	X		1	Siemens FAS-Latch Replacement Lock Kit with two B363A Keys, for 14 Gauge Steel, Lighting Panel Type 1 Fronts, various styles.	11-1895-61
LPLOCK02A	O	O	O	O	O	O		1	Siemens FAS-Latch Replacement Lock Kit with two B363A Keys, for 12 Gauge Steel, Lighting Panel Type 1 Fronts, various styles.	11-1895-62
LPLOCK03A	O	O	O	O	O	O		1	Siemens FAS-Latch Replacement Lock Kit with two B363A Keys, for 10 Gauge Steel, Lighting Panel Type 1 Fronts, various styles.	11-1895-63
XTP060	X	X	X	X	X	X	X	1	TUP61 Grey Touch-up Paint, 12 oz Spray Can	na
Misc. Parts for reference										
ref 11-A-1505-02	X					X		1	Screw: 10-32 x0.375" Slotted Hex Washer Head SEMS - Used in P1 for BL/BQD/xGB/ED Main breaker to bus strap mounting (not in unit space)	11-A-1502
ref 11-A-1508-04	X					X		1	Screw: 1/4-20 x0.50" Slotted Hex Washer Head SEMS - Used in P1 for QJ/QR/FD breaker to bus strap mounting - Also used for P1 Bus strap to Bus connections - BL/BQD/xGB/ED/FD	11-A-1508
ref 11-A-1508-08	X					X		1	Screw: 10-32 x0.875" Slotted Hex Washer Head SEMS - Used in P1 for FD breaker to bus strap mounting	11-A-1508
ref 11-A-1520-07	X					X		1	Screw: 5/16-18 X 0.750" IHWHSW, Indented Hex Washer-Head Screw, Thread Forming SEMS with captive Belleville washer. - Used for P1 Bus strap to Bus connections - JD - two per connection	11-A-1520
ref 11-1576-04	X					X		1	Screw: 10-24 X 0.437" ISHWHSW Indented Slotted Hex Washer Head. - Used for P1 250A and 400A Deadfront support to base-rail and deadfront to DF support (plus many other items) (kit pending, not yet available)	11-1576
ref 11-1615-07 ref 11-1618-05 ref 11-1586-05	X					X		1	One of each used for each phase: JD Breaker to Bus strap connection. Washer: Type A Plain 3/8" Narrow, .406"x.812"x.065" Washer: 3/8" Helical Spring Lock washer, .382"x.683"x.094" Screw: 3/8-16x1.00" HHMS, Hex Head Machine Screw	11-1615 11-1618 11-1586

Panelboards

Lighting panel ground bus information: P1, P2, P3

Selection

Lighting panel ground bus information: P1-P2-P3

Catalog Number	Description	Comments
EGK	Al Ground Bus 44 Connections	Type 1, 3R, 3R/12
ECGK	Cu Ground Bus 44 Connections	Type 1, 3R, 3R/12
IGK	Insulated Al Ground Bus	Type 1, 3R, 3R/12
ICGK	Insulated Cu Ground Bus	Type 1, 3R, 3R/12

EGK / ECGK / IGK / ICGK Installation Instructions:

Ground bus to be mounted in either left or right gutter with hardware provided. Applied torque ratings shall be 45-lbs-inch for three No. 10 AWG solid copper conductors in the large holes. For all other combinations of conductors, refer to the torque rating label on the panelboard.

Note: For IGK / ICGK, insure ground bar is attached to Glastic insulator with two screws before mounting insulator to enclosure. Ground Bar mounts thru side holes oriented as shown on picture below.

Construction notes:

- a) AL Ground bus kits can be used with either AL or CU Cable.
- b) CU Ground bus kits only accept CU Cable.

Wire size range of the EGK/ECGK/IGK/ICGK lug connections/holes:

(Note: The multiple combinations typically only apply when used as an equipment ground. If similar bar is used as a neutral bar, only one wire can be used in each hole.)

1. Connection count: (6) of #14-1/0 and (15) of #14-6 Connections (21 Holes total). (note: one Connection may be needed for incoming Ground Connection)
2. The Maximum wire size the standard ground accepts is: 1/0 in the Large Holes and #6 in the Smaller Holes.
3. Small Hole can accept:
(1-2 wires) #14-12; (1 wire) #10; (1 wire) #8-#6.
4. The Large Hole can accept:
(1-3 wires) #14-#10; (1 wire) #8; (1 wire) #6 - #4; (1 wire) #3-1/0.
5. Max. connections if largest wire size is used:
 $(6 \times 1) + (15 \times 1) = 21$
6. Max. connections if smallest wire size is used:
 $(6 \times 3) + (15 \times 2) = 48$
7. Request for Ground Lug greater than 1/0 in Size requires a Special Modification in COMPAS when Line Item is entered (specify number of connections needed greater than 1/0) or Manual Line for Custom Ground (specify number of connections needed greater than 1/0).

This chart is on labels for P1, P2 and P3 enclosures.


USE SIEMENS EQUIPMENT GROUND BUS
TYPES EGK, IGK, ECGK, ICGK

Torque required to secure wire sizes listed below:

Small Terminal	
(1-2 Wires)-#14-#12	20 lb-in
(1 Wire)-#10	20 lb-in
(1 Wire)-#8-#6	30 lb-in

Large Terminal	
(1-3 Wires)-#14-#10	35 lb-in
(1 Wire)-#8	40 lb-in
(1 Wire)-#6-#16	45 lb-in
(1 Wire)-#3-1/0	50 lb-in

Grd. bus location



Type 1, 3R and 3R/12 Enclosure



EGK / ECGK kit parts



IGK / ICGK kit parts

Panelboards

Panelboard Replacement, Modification, and Additions

Selection

Deadfront Filler Chart – P1, P2, P3, C1, C2

Ref.	Panel Type	Breaker Position	Breaker Type	Orientation	Catalog No.	Catalog Description / comments	Filler Plate Eng ref #	Filler Description
A1	P1 & RP1, P2, P3, C1, C2	1" Branch & Main ^①	BL/BQD/xGB/xGB2/ED ^② /3VA41	Horiz. or Vert.	DFFP1A^③	1" Branch circuit filler plate (used for BL/BQD/xGB/xGB2/ED/3VA41 blank positions) ^④	11-D-4613-01 replaces 11-D-4554-01	Blank Filler 1"
A2	P1 & RP1, C1	Main / Subfeed	blank MLO - no breaker	Horiz. or Vert.	DFFP01B	P1 Main Blank Filler Plate - 1 Piece (use for Original or Revised P1 - also replaces DFFP01A and 12-A-1801-01) (Vertical for 400A Main)	11-D-4612-01 (replaces 11-D-4560-01 & 12-A-1801-01)	P1 Main - Blank Filler Plate With standard small opening
B1	P1 & RP1	250A Main / 250A & 400A Subfeed (small opening)	3VA4/xGB BL/BQD/ED	Horiz.	DFFPVA41A	RP1 Main/Sub-feed 125A max. 3VA4/BL/BQD/ED/xGB filler (replaces DFFPED01 ref. 12-A-1802-01)	11-D-4604-01 replaces 12-A-1802-01	P1 125A Main Breaker Filler
B2	P1 & RP1		QJ 2-pole	Horiz.	DFFPQJ02	P1 QJ Main Filler Plate 2 pole - 1 pc.	12-A-1804-02	P1 QJ Main 2P Filler Plate
B3	P1 & RP1		QJ 3-pole	Horiz.	DFFPQJ01	P1 QJ Main Filler Plate 3 pole - 1 pc.	12-A-1804-01	P1 QJ Main 3P Filler Plate
B4	P1 & RP1		QR	Horiz.	MBKQRFK	P1/Revised P1 Filler for 1PH/3PH QR. Horizontal Mount only.	11-D-4563-01*	P1 QR Filler Plate
B5	P1 & RP1		FD	Horiz.	DFFPFD01	P1 FD Main Filler Plate - 1 Piece	12-A-1803-01	FD Filler Plate
B6	RP1		3VA52/61/62	Horiz.	DFFPVA5262A	RP1 SINGLE MNT 3VA52/61/62 FILLER 1 piece	11-D-4617-01	RP1 SINGLE MNT 3VA52/61/62 FILLER 1 piece
C1	P1 & RP1 400A only	400A Main (small opening)	JD	Vert.	DFFPJD01	P1 JD Main Filler Plate - 1 Piece	11-D-4522-01	Deadfront Filler 400 - 800A Breaker
C2	RP1 400A only		JD	Vert.	MBKVA5363JD	RP1 Deadfront Filler 400A Max. allows old 400A JD to be replaced with 3VA53/63 with small DF opening	tdb	RP1 400A JD to 3VA retrofit kit 1ph/3ph (filler only - launching Q4 FY20)
D1	RP1 400A only	400A Main (large opening)	blank MLO - no breaker	Vert.	DFFP01C	RP1 400A Main Blank Filler Plate - 1 Piece for large opening (use for Revised P1 400A with large MB opening only)	11-D-4600-01	RP1 400A Main w/ large opening - Blank Filler Plate for MLO
D2	RP1 400A only		JD	Vert.	DFFPJD02	RP1 400A w/JD Main - 1 Piece for large opening	11-D-4598-01	JD Filler - RP1 400A Main w/ large opening
D3	RP1 400A only		3VA53/63	Vert.	DFFPVA5363A	RP1 400A w/3VA53/63 Main - 1 Piece for large opening	11-D-4599-01	3VA53/63 Filler - RP1 400A Main w/ large opening
E1	P2 & P3	Branch	BL/BQD/ED/xGB/xGB2	n/a ^⑤	DFK1	BL, BQD, ED, xGB, xGB2, 3VA41 deadfront center strip kit for 1" pole breakers with mounting hardware	multiple parts 11-D-3018-01 thru ...-07	Center strips included (7 sizes) 3", 6", 9", 12", 15", 18", 21" (of branch height)
E2	P2 & P3	Branch	blank - no breaker	Horiz.	DFFP3	Deadfront filler, 3" steel blank filler plate (one each P2&P3)	11-D-3014-02 11-D-3035-02	P2 Blank Deadfront Plate 3" P3 Blank Cover Plate 2.97"
E3	P2 & P3	Branch	blank - no breaker	Horiz.	DFFP6	Deadfront filler, 6" steel blank filler plate (one each P2&P3)	11-D-3014-01 11-D-3035-01	P2 Blank Deadfront Plate 6" P3 Blank Cover Plate 5.97"
F1	P2 & P3	Main / Branch	3VA52/61/62	Horiz.	DFFPVA5262P2A	3VA52/61/62 FILLER for single mount P2/P3 applications. 1 piece	11-D-4610-01	P2/P3 SINGLE MNT 3VA52/61/62 FILLER 1PCE
F2	P2 & P3	Main / Branch	3VA52/61/62	Horiz.	DFFPVA5262P2B	3VA52/61/62 (single mount) blank plate with provision barrier (one set of parts for P2 or P3)	11-D-3340-01 11-D-4614-01	P2/P3 3VA52/62 BLANK PLATE/BARRIER 1PCE
F3	P2	Branch	QR	Horiz. or Vert.	BBKQRP1FK	P2 Filler for QR. Horiz. or vert. mount. Contains all cover plates necessary to change from QJ to QR both 2 and 3-pole breakers.	11-D-3282-01 11-D-4563-01* 11-D-4564-01	QR Deadfront Plate P1 QR Filler Plate P2 QR Deadfront Filler
F4	P3	Branch	QR	Horiz.	BBKQRP2FK	P3 Filler for QR. Dual mount horiz. Kit contains all cover plates necessary to change from QJ to QR both 2 and 3-pole breakers. For 1-phase panel, both breakers must change from QJ to QR, cannot have one of each installed.	11-D-4565-01 11-D-3283-01 11-D-3284-01 11-D-3288-01 12-6812-34	P3 QR Deadfront Filler P3 DUAL QJ Deadfront Plate P3 DUAL QJ Deadfront Plate P3 QR-QJ Combo Deadfront Plate Breaker Blank Filler
G1	P3	Branch	NEB/HEB	Horiz.	EBF1	EB Filler Plate	11-D-4529-01	EB Deadfront Filler
G2	P3	Branch	BL, BQD, ED, xGB or 3VA41	Horiz.	DFFP3AP01	Used for filling space in a P3 deadfront when a BL, BQD, ED, xGB or 3VA41 branch breaker is installed. Can be replaced in field if lost or damaged.	11-D-3033-01	P3 BL/BQD/ED/xGB/3VA41 adaptor plate 3" - 1 Piece per pack

① 1" Branch circuit filler plate (used for BL/BQD/xGB/xGB2/ED/3VA41 blank positions. Suitable for replacing QF3 and DFFP1 in P1-P5 Panelboards and Switchboards). Also used to fill void where a 2-pole breaker is installed in a 3-pole position in various applications.

② QF3/DFFP1 compatibility

a) DFFP1 fits tighter in the opening than the QF3 (small spring tabs are stronger on the sides, but otherwise almost identical). thus DFFP1 will not slide out of place without some force being applied).

b) In a P1-P2-P3 deadfront, a QF3 will slide out of position when the deadfront is removed from the panel. This makes it difficult to put the deadfront back on the panel.

c) Both the QF3 and DFFP1 are approved for use in all panelboards and switchboards. However, only QF3 is approved for use in residential products (load centers, meter combos, etc).

Panelboards

Circuit Breaker / Lighting and Distribution

General

Revised Type P1 - General Specifications

480V AC Maximum
600Y/347V AC Maximum (limited applications)
400 Ampere Max. Mains
250 Ampere Maximum Branch
UL Short Circuit Rating —
200,000 A. @ 240 Vac / 100,000 A. @
480/277 Vac. IR Maximum

Branch Breaker Symmetrical
Interrupting Capacity

Based on Underwriters' Test Procedure

Feed thru and subfeed lugs may result in lower interrupting ratings if not protected by a main device. Consult sales office.

Standards

NEC: 2020 (where accepted)

NEMA: PB1.1

UL: 67, 50 and 50E. Listed by Underwriter's Laboratories, Inc., under "Panelboards"

File #E2269, and #E4016.

Meets Federal Specification W-P-115c.

Service

1-phase 2-wire - 120 Vac, 240 Vac

1-phase 3-wire - 120/240 Vac

3-phase 3-wire - 480Y/277 (when derived from 3-phase 4-wire system), 480 Vac, 347 Vac, 240 Vac, 120 Vac

3-phase 4-wire - 208Y/120 Vac, 480Y/277 Vac, 600Y/347 Vac, 380/220 Vac (see complete list in table on page 11-6)

Panelboard Fronts and Doors

Standard panelboards are furnished with trim featuring concealed fasteners and hinges with a flush door lock. All are factory-assembled for ease of installation. Fronts are fabricated from code gauge steel and finished ANSI-61. See page 11-35 for optional fronts.

Main Breakers

BL, BLH, HBL, NGB, HGB, LGB, BQD, ED4, ED6, HED4, QR2, QRH2, HQR2, HQR2H, FXD6, FD6, HFD6, HFXD6, JXD6, JD6, HJXD6, HJD6, 3VA41/52/61/62/53/63. (All main breakers except 400 amp frame are mounted horizontal.)

Note: Revised P1 interiors with BL, BQD, GB or 3VA41 Type Mains can be Back-fed in unit space. See special Notes for unit space reduction.

Main Breaker Panel Connectors

Ampere Rating	Connectors Suitable for Cu or Al
100	(1)—#14 1/0 AWG
125	(1)—#4 1/0 AWG
225	(1)—#4 AWG-300 kcmil
250	(1)—#4/0 AWG-350 kcmil Al (1)—#6/0 AWG-350 kcmil Cu
400 ^①	(2)—#3/0 AWG-250 kcmil Al or (1)—#3/0 AWG-500 kcmil Al

Connector ranges indicated do not apply to all main breaker types. Refer to molded case circuit breaker standard pressure wire connector chart (Section 7) for the connector range of a specific frame.

Main Lug Connectors^②

125	(1)—#6 AWG-350 kcmil
250	(1)—#6 AWG-350 kcmil
400 std.	AL (2) 1/0-250 kcmil or (1) #2 AWG-600 kcmil
400 opt.	CU (2) 1/0-4/0 or (1) 110-600 kcmil
400 opt.	AL (1) AL 1/0-750 kcmil (2) AL/CU 250 kcmil max. [max. (1) 600 kcmil (1) wire]

Boxes

20" wide, 5.75" deep

- End walls are blank as standard.
- End walls with knockouts are available for 5.75" deep enclosures, if requested at time of order, and are available as a field installable kit.

Weight — Approximate

Total panelboard weight when filled with a normal quantity of breakers and accessories is:

- About 3 lbs. per inch of box height

Gauge Steel Boxes (Type 1)

Width	Height	Gauge Steel
20"	All	#16

Fronts — Surface, Flush (Type 1)

20"	All	#14
-----	-----	-----

Series Connected Short Circuit Ratings

The term "Series Connected Short Circuit Rating" refers to the application of series connected circuit breakers in a combination that allows some breakers to have lower individual interrupting ratings than the available fault current. This is permitted as long as the series combination has been tested and certified by UL.

See Circuit Breaker Section of this book. Series ratings must be specified on order at time of entry.

^① P1 400 amp main breaker panels have wire bending space available for 600 kcmil.

^② 400A main breaker is vertical mounted.

^③ Feed-thru lug wire bending space is 15.000" and neutral wire bending space is 15.880" on 400A panel.

^④ P1 panel limited to (1) subfeed 250 amperes max.

^⑤ See Branch Breaker Side Gutter Chart for Revised P1 Backfed Options.

^⑥ See complete list of MLO connectors on page 11-27.

For inches / millimeters conversion, see Application Data section.

Panelboards

Circuit Breaker / Lighting and Distribution

Selection

Shown with Standard Mains, Top Fed and Surface Trim
Catalog number is for aluminum main bus. For optional copper main bus change "A" in position 11 to "C".

Panels are top feed, surface mounted. For bottom feed, change "T" in position 12 to "B". For flush mounting, change "S" in position 13 to "F".

Replace fifth and sixth position in panelboard catalog number, with alternate main breaker code.

Note: Original P1 was produced until 2015 and in January the revised P1 was introduced. All interior numbers that end with "T" or "N" are the new Revised interiors. "T" at end of catalog number indicates there is a Subfeed area available. "N" at end of catalog number indicates there is no Subfeed area available.

Table P1-16 – Main Lugs Only (These are examples of configured panels - for reference only)

Main Lug Only			Revised P1 – Subfeed Space ^{①③}	Revised P1 – Subfeed Space ^{①③}	Revised P1 – Subfeed Space ^{①③④}
Max Panel Amp Rating	Max 1-Pole Circuits	Box Height (in.)	208Y/120V 3-Phase 4-Wire Catalog #	120/240V 1-Phase 3-Wire Catalog #	480Y/277V 3-Phase 4-Wire Catalog #
125	18	32	P1C18ML125ATST®	P1A18ML125ATST®	P1E18ML125ATST®
	30	38	P1C30ML125ATST	P1A30ML125ATST	P1E30ML125ATST
	42	44	P1C42ML125ATST	P1A42ML125ATST	P1E42ML125ATST
	54	50	P1C54ML125ATST	P1A54ML125ATST	P1E54ML125ATST
	66	56	P1C66ML125ATST	P1A66ML125ATST	P1E66ML125ATST
250	18	32	P1C18ML250ATST®	P1A18ML250ATST®	P1E18ML250ATST®
	30	38	P1C30ML250ATST	P1A30ML250ATST	P1E30ML250ATST
	42	44	P1C42ML250ATST	P1A42ML250ATST	P1E42ML250ATST
	54	50	P1C54ML250ATST	P1A54ML250ATST	P1E54ML250ATST
	66	56	P1C66ML250ATST	P1A66ML250ATST	P1E66ML250ATST
400	18	56	—	—	—
	30	62	P1C30ML400ATST	P1A30ML400ATST	P1E30ML400ATST
	42	68	P1C42ML400ATST	P1A42ML400ATST	P1E42ML400ATST
	54	74	P1C54ML400ATST	P1A54ML400ATST	P1E54ML400ATST
	66 ^②	74 ^②	P1C66ML400ATSN ^②	P1A66ML400ATSN ^②	P1E66ML400ATSN ^②

Table P1-17 – Main Circuit Breaker (These are examples of configured panels - for reference only)

100	18	32	P1C18BL100ATST®	P1A18BL100ATST®	P1E18V1100ATST®
	30	38	P1C30BL100ATST	P1A30BL100ATST	P1E30V1100ATST
	42	44	P1C42BL100ATST	P1A42BL100ATST	P1E42V1100ATST
	54	50	P1C54BL100ATST	P1A54BL100ATST	P1E54V1100ATST
	66	56	P1C66BL100ATST	P1A66BL100ATST	P1E66V1100ATST
125	18	32	P1C18V1125ATST®	—	P1E18V1125ATST®
	30	38	P1C30V1125ATST	—	P1E30V1125ATST
	42	44	P1C42V1125ATST	—	P1E42V1125ATST
	54	50	P1C54V1125ATST	—	P1E54V1125ATST
	66	56	P1C66V1125ATST	—	P1E66V1125ATST
225	18	32	P1C18QR225ATST®	P1A18QR225ATST®	P1E18VA225ATST®
	30	38	P1C30QR225ATST	P1A30QR225ATST	P1E30VA225ATST
	42	44	P1C42QR225ATST	P1A42QR225ATST	P1E42VA225ATST
	54	50	P1C54QR225ATST	P1A54QR225ATST	P1E54VA225ATST
	66	56	P1C66QR225ATST	P1A66QR225ATST	P1E66VA225ATST
250	18	32	P1C18VA250ATST®	P1A18VA250ATST®	P1E18VA250ATST®
	30	38	P1C30VA250ATST	P1A30VA250ATST	P1E30VA250ATST
	42	44	P1C42VA250ATST	P1A42VA250ATST	P1E42VA250ATST
	54	50	P1C54VA250ATST	P1A54VA250ATST	P1E54VA250ATST
	66	56	P1C66VA250ATST	P1A66VA250ATST	P1E66VA250ATST
400	18	56	—	—	—
	30	62	P1C30VE400ATST	P1A30VE400ATST	P1E30VE400ATST
	42	68	P1C42VE400ATST	P1A42VE400ATST	P1E42VE400ATST
	54	74	P1C54VE400ATST	P1A54VE400ATST	P1E54VE400ATST
	66 ^②	74 ^②	P1C66VE400ATSN ^②	P1A66VE400ATSN ^②	P1E66VE400ATSN ^②

Table P1-18 – Standard Enclosures

Box Height (in.)	Catalog Number				
	Type 1 Standard Trim				Type 3R/12 ^⑦
	Box ^⑤	Surface ^⑥	Flush ^⑥	Type 3R ^⑦	
26	B26	S26B	F26B	NR26	WP26
32	B32	S32B	F32B	NR32	WP32
38	B38	S38B	F38B	NR38	WP38
44	B44	S44B	F44B	NR44	WP44
50	B50	S50B	F50B	NR50	WP50
56	B56	S56B	F56B	NR56	WP56
62	B62	S62B	F62B	NR62	WP62
68	B68	S68B	F68B	NR68	WP68
74	B74	S74B	F74B	NR74	WP74

① For all products without subfeed space - change "T" at end to "N" and reduce box size by 6".

- ② No sub-feed space only for 400A 66 circuit.
- ③ BL/BQD/GB Type Mains are only available as Back-Fed. No kits are available for use in Main or Sub-feed space. (GB Type includes NGB, HGB and LGB Breakers). These breakers take up branch circuit space.
- ④ xGB interiors are not available as Non-Feed-Thru, without Subfeed Space.
- ⑤ 16 GA std., Optional 14 GA & 12 GA Enclosures only.
- ⑥ 14 Gauge Steel only.
- ⑦ 16 Gauge Can w/ 14 Gauge Front.
- ⑧ The Revised P1 (18 circuit 250A only) is limited to 100A per connection (200A per pair) when installing BL/BQD or xGB Branch Breakers across from one another. 3VA41 does not have this restriction. All other configurations allow 125A per connection max. (250A per pair max.)

Panelboards

Circuit Breaker / Lighting and Distribution

Selection

Table P1-3 – Main Breaker Panel Size Selector – Revised P1

RP1 Est. size/weights for AL MLO panels. - Add Main Breaker weights as needed. - Add 20% for CU Bus.		Max # of 1" Poles		Max # of Poles w/BT ^②		Dimensions in inches (mm)			MLO ^① Estimated Weight in Lbs. (kg) with Breakers
Type of RP1 interior ==>		BL/BQD or xGB/3VA41 ^③		BL/BQD only		Unit Space		Box Height B"(mm)	
Main Breaker Amp Rating / Type	Main Lug Amp Rating	FT #	NFT #	FT w/BT	NFT w/BT	FT A"	NFT A"		
250A max. Main Bus rating 100A max BL or BQD series 125A max xGB or 3VA41 Series or 225A max QR Series 250A max FD or 3VA52/62 Series	125A or 250A (all bus is 250A max.)	—	18	—	18 + 10	—	9	26 (661)	95 (43)
		18	30	18 + 10	30 + 20	9	15	32 (813)	110 (50)
		30	42	30 + 20	42 + 30	15	21	38 (965)	125 (57)
		42	54	42 + 30	54 + 30	21	27	44 (1118)	140 (64)
		54	66	54 + 30	66 + 30	27	33	50 (1270)	155 (71)
		66	—	66 + 30	—	33	—	56 (1423)	170 (78)
400A max. Main Bus rating 400A max JD Series or 400A max 3VA53/63 Series	400A	—	30	—	30 + 20	—	15	56 (1423)	172 (78)
	(all bus is 400A max.)	30	42	30 + 20	42 + 30	15	21	62 (1575)	190 (86)
		42	54	42 + 30	54 + 30	21	27	68 (1728)	208 (95)
		54	66	54 + 30	66 + 30	27	33	74 (1880)	226 (104)

① Estimated weights are for Aluminum bus MLO panels and vary by MB and installed Branches

② BT - twin style breakers are available in 15A and 20A only and provide two 1-pole circuits in 1" of unit space.

③ The maximum Qty. of BT twins allowed in a panel is restricted to the max. number of neutral positions and/or physical space available, whichever is lower. Values shown are recommended maximums.

④ BT twins can only be used in BL/BQD RP1 panels. The xGB series of interiors do not accept BL/BQD or BT style of breakers.




Table P1-4 – Main Breaker Selection

P1 Main Circuit Breakers & Subfeed					2-Pole and 3-Pole Max IR (kA) at ^①					Amp Ratings Available	Available for Sub-feed Horizontal mount only
Amp Rating	Trip Type	Breaker Family	Main Breaker Code	Breaker Type	240V	480V /277V	480V	600V /347V	600V		
100	Thermal Magnetic	BL	BL	BL	10	—	—	—	—	15-100	Single
			BH	BLH	22	—	—	—	—	15-100	Single
			HB	HBL	65	—	—	—	—	15-100	Single
		BQD	BQ	BQD ^⑤	65	14	—	10	—	15-100	Single
125	Thermal Magnetic	Sentron GB	NB	NGB	100	25	—	14	—	15-125	Single
			G2	HGB	100	35	—	14	—	15-125	Single
			G3	LGB	100	65	—	14	—	15-125	Single
		Sentron ED	E4	ED4	65	—	18	—	—	15-125	Single
			E6	ED6 ^⑥	65	—	25	—	18	20-125	Single
			H4	HED4	100	—	42	—	—	15-125	Single
		3VA41	V1	SEAB	65	—	—	—	14	15-125	Single
			V2	MEAB	85	—	35	—	18	15-125	Single
			V3	HEAB	100	—	65	—	25	15-125	Single
225	Thermal Magnetic	Sentron QR	QR	QR2	10	—	—	—	—	100-225	Single
			Q4	QRH2	25	—	—	—	—	100-225	Single
			Q5	HQR2	65	—	—	—	—	100-225	Single
			Q6	HQR2H	100	—	—	—	—	100-225	Single
250	Thermal Magnetic	Sentron FD	FX, FD	FXD6-A, FD6-A	65	—	35	—	22	70-250	Single
			HF	HFD6	100	—	65	—	25	70-250	Single
			H2	HFXD6	100	—	65	—	—	70-250	Single
250	Thermal Magnetic	3VA52 (W/TM230 trip)	VA	MFAS	85	—	35	—	18	100-250	Single
			VB	HFAE	100	—	65	—	25	100-250	Single
			VC	CFAS	200	—	100	—	35	100-250	Single
	Electronic (Solid state)	3VA62 (ETU350 LSI standard)	WA	MFAE	100	—	35	—	18	100-250	Single
			WB	HFAE	100	—	65	—	22	100-250	Single
			WC	CFAE	200	—	100	—	35	100-250	Single
			WD	LFAE	200	—	150	—	50	100-250	Single
400	Thermal Magnetic	Sentron JD	JX, J6	JXD6-A, JD6-A	65	—	35	—	25	200-400	n/a
			H5, H6	HJXD6-A, HJD6-A	100	—	65	—	35	200-400	n/a
			JD	JXD2	65	—	—	—	—	300-400	n/a
400	Thermal Magnetic	3VA53 (W/TM230 trip)	VE	MJAS	85	—	35	—	18	200-400	n/a
			VF	HJAS	100	—	65	—	25	200-400	n/a
			VG	CJAS	200	—	100	—	35	300-400	n/a
	Electronic (Solid state)	3VA63 (ETU350 LSI standard)	WE	MJAE	100	—	35	—	18	100-400	n/a
			WF	HJAE	100	—	65	—	22	100-400	n/a
			WG	CJAE	200	—	100	—	35	100-400	n/a
			WH	LJAE	200	—	150	—	50	100-400	n/a

① DC System Voltages are not available for RP1 series.

⑤ ED6 2-pole only available in 20A, 25A and 30A.

⑥ Approved for CSA and UL Listed.

See SpeedFAX section 7 for more details.

Panelboards

Circuit Breaker / Lighting and Distribution

Selection

11
PANELBOARDS

Table P1-5 - Line/Load Cable Connector Size Chart

Max Amp Rating	Main Lug	Amp Series	Connections suitable for Copper Cable	Connections suitable for Aluminum Cable
125	Aluminum body	125A max	(1) #6 AWG - 350 kcmil	(1) #6 AWG - 350 kcmil
	Copper body	125A max	(1) #6 AWG - 350 kcmil	not suitable
250	Aluminum body	250A max	(1) #6 AWG - 350 kcmil	(1) #6 AWG - 350 kcmil
	Copper body	250A max	(1) #6 AWG - 350 kcmil	not suitable
400 std.	Aluminum body	400A max	(2) 1/0 - 4/0 or (1) #2 AWG - 600kcmil	(2) 1/0 - 250 kcmil or (1) #2 AWG-600kcmil
	Copper body	400A max	(2) 1/0 - 4/0 or (1) 1/0 - 600kcmil	not suitable for AL
400 alt.	Aluminum body	400A max	(2) 1/0 - 250 kcmil or (1) 1/0 - 600kcmil	(2) 1/0 - 250 kcmil or (1) 1/0 - 750kcmil
Max Amp	Main Breaker Types	Series	Connections for Copper	Connections for Aluminum
100	BL, BLH, HBL	15-35A 40-50A 55-100A	#14-#6 AWG #8-#6 AWG #8 AWG - 2/0	#14-#6 AWG #8-#4 AWG #8 AWG - 2/0
	BQD	15-40A 45-100A	#14-#6 AWG #8-#1 AWG	#12-#6 AWG #6 AWG -1/0
125	NGB, HGB, LGB	15-30A 35-125A	#14-#6 AWG #8 AWG-1/0	#12-#6 AWG #8-2/0 AWG
	ED4 ED6, HED4	15-25A 30-100A 110-125A (1-P) 30-60A (1-P) 70-100A	#14-#10 AWG #10 AWG -1/0 #3 AWG-3/0 #10-#4 AWG #6 AWG- 1/0	#12-10 AWG #10 AWG -1/0 #1 AWG-2/0 #10-#4 AWG #6 AWG- 1/0
	3VA41	15-125A	#14 AWG - 3/0	#14 AWG - 3/0
	QR2, QRH2, HQR2, HQR2H	100-225A	#3 AWG-300 Kcmil	#3 AWG-300 Kcmil
250	FXD6, FD6, HFD6, HFXD6	70-250A	#6 AWG-350 Kcmil	#4 AWG-350 Kcmil
	3VA52 3VA62	100-250A 40-250A	#6 AWG-350 Kcmil	#6 AWG-350 Kcmil
	JD6, JXD6, HJD6, HJXD6	200-400A	(1)or(2) 3/0-500 Kcmil [dual port lug]	(1)or(2) 4/0-500 Kcmil [dual port lug]
400	3VA53 3VA63	200-400A 100-400A	(1)or(2) 2/0-600 kcmil [dual port lug]	(1)or(2) 2/0-600 kcmil [dual port lug]

Note: Main breakers use breaker connectors. For sizes, see breaker connector chart. 400A MLO Panels have wire bend space for 600kcmil CU & AL wire when using standard lugs. With optional 750kcmil AL/CU connectors, wire bend space is available for up to 750kcmil AL wire, but is still limited to 600kcmil CU wire.

Table P1-6 – Branch Circuit Breakers

Revised P1 Branch Circuit Breakers ^①				1-Pole					2-Pole and 3-Pole								
				Max IR (kA) at				Amp Ratings Available	Max IR (kA) at							Amp Ratings Available	
Amp Rating	Trip Type	Breaker Family	Breaker Type	120V	277V	347V	125V DC ^③		120/ 240V	240V	480Y/ 277V	480V	600Y/ 347V	600V	125/ 250V DC ^③		250V DC ^③
100	Thermal Magnetic	BL	BL, BT ^②	10	—	—	—	15-70 ^②	10	10	—	—	—	—	—	15-100 ^④	
			BLH, BTH ^②	22	—	—	—	15-70 ^②	22	22	—	—	—	—	—	15-100 ^④	
			HBL	65	—	—	—	15-50	65	65	—	—	—	—	—	15-100	
	Special ^② Application	BLG BL	BLG ^②	10	—	—	—	15-20	10	-	—	—	—	—	—	30	
			BL(HID) ^②	10	—	—	—	15-30	10	-	—	—	—	—	—	15-30	
	Thermal Magnetic	BQD BQD (CSA)	BQD ^⑤	65	14	—	14	15-100	—	65	14	—	—	—	14	—	15-100
	BQD6 ^⑤		65	—	—	14	15-70	—	65		—	10	—	14	—	15-70	
XX	Electronic and misc.	BL	AFCI/GFCI & Dual Function	X	—	—	—	see special table page 11-16	x	—	—	—	—	—	—	see special table page 11-16	
125	Thermal Magnetic	GB	NGB	100	25	14	14	15-125	—	100	25	—	14	—	14	—	15-125
			HGB	100	35	14	14	15-125	—	100	35	—	14	—	14	—	15-125
			LGB	100	65	14	14	15-125	—	100	65	—	14	—	14	—	15-125
		3VA41 ^③	SEAB	65	25	14	14		65	65	25	25	14	—	50	50	15-125
			MEAB	85	35	18	25		85	85	35	35	18	—	85	85	15-125
			HEAB	150	65	25	30		150	150	65	65	25	—	100	100	15-125

- ① Unit space is 1 inch per pole, except for Special Application with accessory included.
 - No branch kits available, unit space for all branch positions is twin mount.
 - Branch space is either for BL/BQD only (or) for xGB/3VA41 only. (after 3VA41 is made available).
 ② BLG: Two-pole breaker is one phase and neutral. Three pole is two phases and neutral
 - See SpeedFax Page 7-31 for additional info. Some are Built to order. Allow 2-3 weeks delivery.
 ③ DC Voltage Systems are not approved for use in P1 panels. Refer to P2/P3 panels if DC Voltage Systems are needed.

- ④ 110A-125A BL/BLH (2-pole only) available as Main or Subfeed only in Revised P1 panels.
 ⑤ Approved for CSA and UL Listed.
 ⑥ Approved for CSA but not UL Listed.
 ⑦ BT and BTH are only available in 15A and 20A with two 1-pole circuits in one inch of unit space.

Panelboards

Circuit Breaker / Lighting and Distribution

Selection

Table P1-13 – Main Breaker Gutter Dimensions Inches (mm)

Main Breaker	Gutter Space inches (mm)		Neutral Location to Endwall
	20" wide box	24" wide box	20" wide box
BL, BLH, HBL ^③	8.500 (215) ^③	10.500 (267) ^③	10.000 (254)
BQD ^②	7.750 (196) ^③	9.750 (248) ^③	10.000 (254)
NGB, HGB, LGB ^②	7.500 (190) ^③	9.500 (241) ^③	10.000 (254)
ED4, ED6, HED4	6.125 (156)	8.125 (206)	10.000 (254)
QR2, QRH2, HQR2, HQR2H	6.500 (165)	8.500 (216)	10.000 (254)
3VA41	7.250 (184)	9.250 (235)	10.000 (254)
3VA52	6.750 (171)	8.750 (222)	10.000 (254)
3VA61/62	6.250 (159)	8.250 (210)	10.000 (254)
3VA53/63	7.500 (190) /	14.750 (375) /	24.500 (622)
Double / Single Port	12.250 (305)	12.250 (305)	
FD6, FXD6, HFD6, HFXD6	5.250 (133)	7.250 (184)	10.500 (267)
JD6, JXD6 ^①	15.000 (381)	15.000 (381)	26.500 (674)

① JD frame mounted vertically.

② For Revised P1 with Back-fed Main option, use Side Gutter Wiring Spec Table P1-15.

③ These dimensions are for Revised P1 only. See Original P1 cut sheets for valid dimensions if needed (P1 production prior to January 2015).



Feed-Thru (FT)

Table P1-14 – Main Lug End Gutter Dimensions Inches (mm)

Amp Rating	End Gutter		Neutral Location - to Endwall	
	20" wide box	24" wide box	20" wide box	24" wide box
125	9.500 (242)	9.500 (242)	10.500 (267)	10.500 (267)
250	9.500 (242)	9.500 (242)	10.500 (267)	10.500 (267)
400	25.500 (648)	25.500 (648)	26.750 (680)	26.750 (680)

NOTE: Feed-thru lug and neutral wire bending space is 15.000" and 16.250" respectively on 400A panel.



Non-Feed-Thru (NFT)


Table P1-15 – Side Gutter Wiring Space Inches (mm) (Fig P1-1)

Reference Letter	Panel Width 20"	Panel Width 24" Optional
A ^②	6.375 (167)	8.375 (213)
B ^②	5.500 (140)	7.500 (191)
C ^②	5.000 (127)	7.000 (178)
D	6.125 (156)	8.125 (206)
E	6.500 (165)	8.500 (216)
F	5.250 (133)	7.250 (184)
G	6.750 (171)	8.750 (222)
H	6.250 (159)	8.250 (210)

① Subfeed mounting limit 1 per panel.

② For all Revised P1 panels using BL/BQD or xGB breakers as mains in back-fed position, use this chart for wiring space.

Fig P1-1



Example of Back-fed xGB Main breaker installed

Panelboards

Type P1 Panelboard Modifications and Additions

Selection

Panel Options

Enclosures

- Extra gutter to sides or ends of the can
- 24" wide boxes
- Hinged to box trim
- Door-in-door trims
- Screw to box trims
- Piano hinge trims
- Painted boxes (ANSI 61 Light Gray is standard color)
- Custom colors
- Increase gauge trims and boxes (See pages 12-13)
- Stainless steel trims (304 SS only) for Type 1 enclosures
- Type 1 enclosures (Std 16 Gage / Optional 14 or 12 Gage)
- Type 1 Standard are A60 Galvanealed non painted (Painted Type 1 use HRPO material)
- NEMA 3R/12 enclosures 16 Gauge Can w/ 14 Gauge front)
- NEMA 4 enclosures (14 Gauge only)

- NEMA 4X enclosures (14 Gauge only - 304SS Std, 316SS Optional)
- Special Keyed Locks (Keys are not supplied)
- Panel skirts
- Gaskets between trim and box

TEY TEU1 Cat 60 LL803 LL806	All fit FAS-Latch Front*
Yale 47 (NYC) National C413A Beck Lock 7-pin tumbler Southco 1 4 Fastener Corbin 1001 FAB7	Special non-FAS-Latch*

*See page 11-38 for more information.

Panel Modifications

- Main Bus
Standard main bus is tin-plated aluminum. For copper main bus, add from the table for each panel. Includes copper neutral cross bar. For copper neutral branch lugs, see miscellaneous.
- Compression lug for MLO^①
- Contactor mains - Mount in 23" enclosure ahead of panel.
 - Asco 920 through 225 amps^②
 - Asco 911 through 150 amps^③
 - Siemens LEN through 30 amps^③
- Branch and main breaker accessories
 - Handle blocks
 - Handle locks
- Feed-thru lugs^④
Cannot be used in conjunction with SPD/TVSS or subfeed breakers. Do not add height to the panel.

Feed-thru Lugs Amp Rating	Type	Connector CU/AL Range
250	AL/CU Mechanical	(1)-#6 AWG- 350 kcmil
	CU Mechanical	(1)-#6 AWG- 350 kcmil
	AL/CU Compression	(1)-#6 AWG- 350 kcmil
400	AL/CU AWG Mechanical	(2)-#1/0 - 250 kcmil or
		(1)-#2 AWG- 600 kcmil
	CU	(1)-1/0-600 kcmil (2)-1/0-4/0
	AL/CU Compression	(1) 400-600 kcmil AL (1) 400-500 kcmil CU

- 200% neutral^①

Note: Specify copper or aluminum cable.

^① Do not increase panel or enclosure size.

^② Accessories on 1" pole breakers (BL, BQD, xGB, ED) will take 1" unit space.

^③ External to the panel, supplied in a separate enclosure.

- Copper lugs, mechanical line and branch neutral^①
- Bus mounted SPD/TVSS and unit space mounted BSPD^②
- Service entrance labeling
- Factory installed and Field installable Service Entrance Barrier kits are now available as required by UL67
- Grounding of Panelboards
 - Ground Bars except for brazed to box are shipped with the panel interior.
 - Non-Insulated Equipment Ground Bar – standard
 - Copper Non-Insulated Ground Bar – optional
 - AL Insulated Equipment Ground Bar – optional
 - CU Insulated Equipment Ground Bar – optional
 - Ground Bar Brazed to Box (recommended for painted boxes)
- Shunt Trip on Main or Branch^③
BL, BLH, HBL, BQD, xGB as branch use
1" unit space for shunt trip.

QR2, QRH2, HQR2, HQR2H, ED2, ED4, ED6,
HED4, HED6, HHED6, FD6, FXD6, HFD6

HFXD6, JXD6, JD6, HJD6, HJXD6

- Remote control switches – 480V AC max. mounted in a 23" enclosure to be cable connected to the panel.
- Time Clocks – mounted in a 23" enclosure to be cable connected to the panel. Tork time clock can be supplied and mounted in panelboard cabinet.

Time Clock Information and Options

Time Clock (1- or 2-Pole, Single or Double Throw Contacts, 3-Pole Single Throw) 277V Maximum with Plain Dial

Options:

Astronomical Dial

An Omitting Device

Reserve Power or Carryover

Space and Mounting Provisions Only

Panelboards

Type P1 Panelboard Modifications and Additions

Selection

Compression Lugs

Table P1-19 – Lugs

Style	Amp Rating	Breaker Type	Compression Connectors	Box Height Addition
MLO	125	N/A	(1) #6 AWG - 350 kcmil	None
	250			
Main Breaker	400	N/A	(1) 400 - 600 kcmil AL (1) 400 - 500 kcmil CU	None
	125	ED4, ED6, HED4	(1) #14 AWG - 2/0	Box must go to 24" wide
	225	QR2, QRH2, HQR2, HQR2H	(1) #6 AWG - 350 kcmil CU or AL	Box must go to 24" wide
	250	FXD6, HFD6	(1) #6 AWG - 350 kcmil CU or AL	Box must go to 24" wide

Note: Standard compression lugs used for P1 panels are range taking lugs and require a particular crimping tool (tool is Hubbell/Anderson Versa Crimp VC6 -for 250A) to accommodate the range. Consult factory for information. 200% neutral not available with compression lugs. xGB breakers cannot accommodate compression lugs. (For 400A tool use Hubbell/Anderson Versa Crimp VC6FT/VC7FT - see instruction sheet for details.)

Enclosure Modifications

NEMA-4-Water Tight, Dust Tight, Steel Enclosure

(Actual NEMA-4 enclosure is larger than standard Type 1 enclosure. See chart below for reference to approximate actual size.)

Table P1-20

Standard Box Height (in inches)	Actual NEMA 4 Enclosure Size		
	H	W	D
32	32	20	8
38	42	30	8
44	48	36	8
56	60	36	10

Note: Larger NEMA 4 enclosures are not available.

Table P1-21 – NEMA Type 4X (Water Tight, Dust Tight and Corrosion Resistant)

Enclosure – Stainless Steel (304SS is standard)

Note: 316SS is optional - must be specified

Catalog Number	Size (inches)			Catalog Number	Size (inches)		
	H	W	D		H	W	D
B4X26	26	20	5.75	24B4X26	26	24	5.75
B4X32	32	20	5.75	24B4X32	32	24	5.75
B4X38	38	20	5.75	24B4X38	38	24	5.75
B4X44	44	20	5.75	24B4X44	44	24	5.75
B4X50	50	20	5.75	24B4X50	50	24	5.75
B4X56	56	20	5.75	24B4X56	56	24	5.75
B4X62	62	20	5.75	24B4X62	62	24	5.75
B4X68	68	20	5.75	24B4X68	68	24	5.75
B4X74	74	20	5.75	24B4X74	74	24	5.75

Enclosure – Non-metallic / Fiberglass

Catalog Number	Ref. Interior Height	Size (inches)			Custom order in COMPAS Reference Number
		H	W	D	
tbd	26	30	24	8	A30H2408GQRLP
tbd	32	36	30	8	A36H3008GQRLP
tbd	38	48	36	12	A48H3612GQRLP
tbd	44				
tbd	50	60	36	12	A60H3612GQRLP
tbd	56				
tbd	62	na	na	na	na
tbd	68	na	na	na	na
tbd	74	na	na	na	na

Remote Switch Modifications

Table P1-22 – Control Power Transformer

Size	VA Relay
0, 1	50
2	75
3	150
4	250

Table P1-24 – Remote Control Switch Modification

Description
Auxiliary Contacts (mounted, not wired)
2-Wire Control

Table P1-23 – Applications for a Remote Switch

Switch Type	Modification
920	Mounts in 23" relay cabinet as a main only
LEN	30A mounts in 23" relay cabinet as a main only

Gauge Steel of Boxes/Fronts, Surface and Flush (see pgs. 11-6 & 11-7)

Dimensions in Inches (mm)		Gauge Steel		
H	W	Box	Front/Door	Type
26-74 (660-1880)	20 (508)	16 ^①	14 ^②	Type 1
26-74 (660-1880)	20 (508)	16 ^②	16/14 ^②	Type 3R/12
32-60 (813-1524)	20-36 (508-914)	14 ^③	14 ^③	Type 4
26-74 (660-1879)	20 (508)	14 ^④	14 ^④	Type 4X
36-60 (914-1524)	30-36 (762-914)	N/A ^⑤	N/A ^⑤	Type 4X Non-Metallic

① 16 Gauge is Standard (14 Gauge & 12 Gauge are optional)

② 15 Gauge Steel Can with 14 Gauge Door or Similar Approved Construction

③ No Optional Gauge available

④ 304SS 14 Gauge Std., 316SS 14 Gauge optional

⑤ Sizes do not match Standard Enclosure Sizes - See Table P1-21 - material is non-metallic - No Gauge Specified.

⑥ FAS-Latch is 14 GA only. Screw-to-Box, Hinge-to-Box, Door-in-Door (14 GA Std./12 GA Std. or 10 GA Optional) STB/HTB/DND with Piano Hinge (14 GA Std./12 GA Optional) (14 GA Stainless 304 Optional)


Panelboards

Type P1 Enclosure Details

Dimensions

Type 1 Box


Box is symmetrical



(UL approved construction. 16 Gage Steel or equivalent alternate Construction.
14 or 12 Gage is available as an optional special order.)
G60 Galvanized is standard without paint.

Type 3R and 3R/12 Box

Note: 3R boxes 50" High and Larger include two "T" handles.



① Dimensions are interior of the box. Add 5/8" to width for absolute dimension. Add 1/8" to height for absolute dimension.

(UL approved construction. 16 Gage Steel Can with
14 Gage front or similar approved construction.)
A60 Galvannealed with ANSI 61 light gray paint is standard.

Dimensions shown in inches and millimeters [].

Panelboards

NEMA Enclosures

Introduction

Enclosures

NEMA Type 1

Primarily indoor use: Box and front needed for complete enclosure.



NEMA Type 3R

Outdoor use primarily to provide a degree of protection against rain, sleet, and damage from external ice formation.



NEMA Type 12 (Siemens 3R/12)

These enclosures for Lighting Panels are useable as Type 12 or Type 3R by adding the gasket shown around the door.



(Siemens 3R/12 panelboard products meet this requirement)

NEMA Type 4 or 4X

Indoor or outdoor use primarily to provide a degree of protection against splashing water, corrosion, windblown dust and rain, hose-directed water, and damage from external ice formation.



Note: NEMA Type 4 is painted steel. NEMA Type 4X is typically stainless or non-metallic.

Panelboards

NEMA Type 1 enclosure for P1, P2, P3

Reference

P1, P2, P3 panelboard standard Type 1 enclosure

Features:	Typical Standard P1 and P2 Type 1 enclosures are 20"W and 5.75"D - 16 GA A60 Galvanized steel or equivalent UL approved construction - Endwalls are blank as standard - Endwalls with Knockouts are available	Options - Painted enclosures [ANSI 61 gray] - 24" wide enclosures - 7.75" deep enclosure - 24" wide and 7.75" deep
	Typical Standard P3 Type 1 enclosures are 24"W and 7.75"D	Options - Painted enclosures [ANSI 61 gray]

Note: Contact customer support for special colors (RAL # required.)

Box Height Inches	P1, P2 and P3 Catalog Number								
	Type 1 Standard Enclosure								
	Standard P1/ P2 Galvanized 20" W	Option P1/P2, Painted 20" W	Option P1/P2, Galvanized w/ KOs 20" W	Option P1/P2, Galvanized 20" W	Option P1/P2, Painted 20" W	Option P1/P2, Galvanized 24" W	Option P1/ P2, Painted 24" W	Standard P3, Option P1/P2, Galvanized 24" W	Standard P3, Option P1/P2, Painted 24" W
	5.75" Depth	5.75" Depth	5.75" Depth	7.75" Depth	7.75" Depth	5.75" Depth	5.75" Depth	7.75" Depth	7.75" Depth
26	B26	B26P	B26K	Ref BD26 ^①	Ref BD26P ^①	24B26	24B26P	N/A	N/A
32	B32	B32P	B32K	BD32	BD32P	24B32	24B32P	24BD32 ^②	24BD32P ^②
38	B38	B38P	B38K	BD38	BD38P	24B38	24B38P	24BD38 ^②	24BD38P ^②
44	B44	B44P	B44K	BD44	BD44P	24B44	24B44P	24BD44 ^②	24BD44P ^②
50	B50	B50P	B50K	BD50	BD50P	24B50	24B50P	24BD50 ^②	24BD50P ^②
56	B56	B56P	B56K	BD56	BD56P	24B56	24B56P	24BD56 ^{②③}	24BD56P ^{②③}
68	B68	B68P	B68K	BD68	BD68P	24B68	24B68P	24BD68 ^{②③}	24BD68P ^{②③}
74	B74	B74P	B74K	BD74	BD74P	24B74	24B74P	24BD74 ^{②③}	24BD74P ^{②③}
80	N/A	N/A	N/A	N/A	N/A	N/A	N/A	24BD80 ^③	Ref 24BD80P ^{①③}

① Custom order in COMPAS

② P1/P2 only with adaptor (Contact Customer Service)

③ P3


* 24BD Series replace 24WD series

* For parts without catalog numbers yet, please contact Customer Service for ordering information.

For further information on P1, P2, and P3 lighting panels, please refer to: <http://w3.usa.siemens.com/powerdistribution/us/en/resources/Pages/DownloadCenter.aspx>

Type 1 Box

Box is symmetrical (P1/P2 std type 1 box shown for ref)



① Dimensions are interior of the box. Add 5/8" to overall depth for absolute dimension.
Add 1/8" to height and width for absolute dimension.

② Optional 7.75 in. [197].
③ Dimension is for P1 and P2.
④ Dimension is for P3.

Panelboards

Accessories Enclosures


Selection

11 Miscellaneous parts and accessories-enclosures


Catalog Number	Description	Comments
EWK1	End Wall Kit with Knockouts (20"W x 5.75" DP)	Type 1 Only
EWK2	End Wall Kit with Knockouts (24"W x 7.75" DP)	Type 1 Only
EWK3	End Wall Kit - open center space - ref B74FLR (20" W x 5.75" DP)	Type 1 Only
EWK1B	End Wall Kit without Knockouts (20" W x 5.75" DP)	Type 1 Only
EWK2B	End Wall Kit without Knockouts (24" W x 7.75" DP)	Type 1 Only

For further information regarding these parts, please follow the below to the literature section tab under lighting panels. usa.siemens.com/panelboards


EWK1 End Wall w/KOs (20"W X 5.75"D)



EWK2 End Wall w/KOs (20"W X 5.75"D)



Panel Skirts Standard Length



8, 9, 10, 11, 12, 14, 17, 18, 23, 24, 25, 25, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36, 37, 38, 39, 40, 41, 42, 43, 44

Notes:

- A) 4-sided skirts have standard Part Numbers (not catalog numbers).
- B) 3-sided skirts are ordered as Custom in COMPAS
- C) Order in COMPAS with interior when possible.
- D) If ordered separate from interior, use a manual line in COMPAS.
- E) Must note if Top Entry or Bottom Entry required.

Panelboards

Type 1 Standard Fronts for P1, P2

Selection

P1, P2 FAS-Latch standard fronts: Type 1

Standard Trim (FAS-Latch) Typical Dimensions. Hinges available as shown on right side only.
Typical 14 Gage Steel construction or UL approved equivalent. Stainless steel is not available.

Optional Fronts for FAS-Latch Series – see examples below for Suffix adders:

Suffix	Description	Example
M	Metal Card Holder	F44BM
WM	Welded-on Metal Card Holder	F44BWM

Options for FAS-Latch Series:

Metal Card Holder – Add


"M" suffix on all fronts

Welded Metal Card Holder – Contact Customer Support for availability




Front Height Inches	Flush FAS-Latch Fronts	
	20" Wide Flush Front Catalog No.	24" Wide Flush Front Catalog No.
26	F26B	24F26B
32	F32B	24F32B
38	F38B	24F38B
44	F44B	24F44B
50	F50B	24F50B
56	F56B	24F56B
62	F62B	24F62B
68	F68B	23F68B
74	F74B	24F74B

Front Height Inches	Surface FAS-Latch Fronts	
	20" Wide Surface Front Catalog No.	24" Wide Surface Front Catalog No.
26	S26B	24S26B
32	S32B	24S32B
38	S38B	24S38B
44	S44B	23S44B
50	S50B	24S50B
56	S56B	24S56B
62	S62B	24S62B
68	S68B	24S68B
74	S74B	24S74B



Box Size	Surface A	Flush A	# of Hinges
26	26	27.5	2
32	32	33.5	2
38	38	39.5	2
44	44	45.5	3
50	50	51.5	3



Box Size	Surface A	Flush A	# of Hinges
56	56	57.5	3
62	62	63.5	3
68	68	69.5	3
74	74	75.5	3

Standard Trim (FAS-Latch)

(14 Gage Standard – no options)
(UPB includes surface or flush versions of this style. Other special fronts below are not part of the UPB program).

Circuit Numbering			
P1 only Stick-on		P2 / P3 Push-in	
NBK01A	1-60	NBK3	1-42
NBK02A	61-120	NBK4	43-84
NBK03A	121-240	NBK5	85-126
		NBK6	127-168
		NBK7	169-210
		NBK8	211-252

Replacement Parts

Catalog No.	Market Facing Description	Pack Quantity
LPLOCK01A	Panel Trim Lock (14GA) W Key, B363A (FAS-Latch)	1
LPLOCK02A	Panel Trim Lock (12GA) W/O Key (Non FAS-Latch)	3
LPLOCK03A	Panel Trim Lock (10GA) W/O Key (Non FAS-Latch)	1
LPKEY01A	Key for Panel Trim Lock (FAS-Latch)	4
LPKEY01B	Key for Panel Trim Lock (FAS-Latch)	25
LPJSPDNUT01	J-Type Speed Nut For Panel Fronts	25
LPTS01	Trim Screw, Lighting Panel Front, 0.547" Length, ¼-20 Machine Screw Thread (kit pending - not yet available) ref #11-A-1819-01	25
LPDC01	Panelboard Directory Card 5.5 x 5 in	10
LPDC02	Directory Card Pouch, Vinyl w/adhesive back	10
MCHK	Metal Card Holder Kit, stick-on with double sided tape	1

Panelboards

Type 1 Optional Fronts for P1, P2

Selection

 PANELBOARDS
11

P1, P2 non FAS-Latch optional fronts

Options: For 24" wide fronts – Add "24" to start of part number: "F44H" becomes "24F44H" Note: 24" wide may require special order in COMPAS for some options.

For Metal Card Holder (stick-on) – Add "M" suffix to end of part number: "F44H" becomes "F44HM"

For Welded Metal Card Holder (special order in COMPAS) – Add "WM" suffix to end of part number: "F44H" becomes "F44HWM"

Front Height Inches	Screw to Box	
	20" W Flush	20" W Surface
	Catalog Number	
26	F26C	S26C
32	F32C	S32C
38	F38C	S38C
44	F44C	S44C
50	F50C	S50C
56	F56C	S56C
62	F62C	S62C
68	F68C	S68C
74	F74C	S74C




Figure 1: Standard Screw to Box Trim

Front Height Inches	Hinge to Box	
	20" W Flush	20" W Surface
	Catalog Number	
26	F26H	S26H
32	F32H	S32H
38	F38H	S38H
44	F44H	S44H
50	F50H	S50H
56	F56H	S56H
62	F62H	S62H
68	F68H	S68H
74	F74H	S74H




Figure 2: Standard Hinge to Box

Front Height Inches	Door-to-Door	
	20" W Flush	20" W Surface
	Catalog Number	
26	F26D	S26D
32	F32D	S32D
38	F38D	S38D
44	F44D	S44D
50	F50D	S50D
56	F56D	S56D
62	F62D	S62D
68	F68D	S68D
74	F74D	S74D




Figure 3: Standard Door in Door

Piano Hinge Options (Stainless 304 is available as option; all have piano hinges)

Front Height Inches	Screw to Box	
	20" W Flush	20" W Surface
	Catalog Number	
26	Ref F26CPH26 ^①	Ref S26CPH26 ^①
32	Ref F32CPH32 ^①	Ref S32CPH32 ^①
38	Ref F38CPH38 ^①	Ref S38CPH38 ^①
44	Ref F44CPH44 ^①	Ref S44CPH44 ^①
50	Ref F50CPH50 ^①	Ref S50CPH50 ^①
56	Ref F56CPH56 ^①	Ref S56CPH56 ^①
62	Ref F62CPH62 ^①	Ref S62CPH62 ^①
68	Ref F68CPH68 ^①	Ref S68CPH68 ^①
74	Ref F74CPH74 ^①	Ref S74CPH74 ^①




Figure 4: Screw to Box w/ Piano Hinge Door 1)

Front Height Inches	Hinge to Box	
	20" W Flush	20" W Surface
	Catalog Number	
26	Ref F26HPH26 ^①	Ref S26HPH26 ^①
32	Ref F32HPH32 ^①	Ref S32HPH32 ^①
38	Ref F38HPH38 ^①	Ref S38HPH38 ^①
44	Ref F44HPH44 ^①	Ref S44HPH44 ^①
50	Ref F50HPH50 ^①	Ref S50HPH50 ^①
56	Ref F56HPH56 ^①	Ref S56HPH56 ^①
62	Ref F62HPH62 ^①	Ref S62HPH62 ^①
68	Ref F68HPH68 ^①	Ref S68HPH68 ^①
74	Ref F74HPH74 ^①	Ref S74HPH74 ^①




Figure 5: Hinge in Box w/ Piano Hinge and Piano Hinge Door

Front Height Inches	Door-to-Door	
	20" W Flush	20" W Surface
	Catalog Number	
26	Ref F26DPH26 ^①	Ref S26DPH26 ^①
32	Ref F32DPH32 ^①	Ref S32DPH32 ^①
38	Ref F38DPH38 ^①	Ref S38DPH38 ^①
44	Ref F44DPH44 ^①	Ref S44DPH44 ^①
50	Ref F50DPH50 ^①	Ref S50DPH50 ^①
56	Ref F56DPH56 ^①	Ref S56DPH56 ^①
62	Ref F62DPH62 ^①	Ref S62DPH62 ^①
68	Ref F68DPH68 ^①	Ref S68DPH68 ^①
74	Ref F74DPH74 ^①	Ref S74DPH74 ^①




Figure 6: Door in Door w/ Piano Hinge both Doors

^① Custom order in COMPAS.

^② Stainless 304 is available as a special order for 20" W and 24" W only. Stainless 316 is not available. Flush stainless fronts are typically 1/2" wider and taller than standard flush fronts.

Panelboards

P3 Dead Front

Reference

P3 series fronts (will not work with P1/P2 interiors)

Note: The P3 Dead Front size is larger than P1/P2, so any fronts or Dead Front interfaces for P3 interiors have to be larger than those for P1/P2. If a P3 Front is used with a P1/P2 interior there is a gap that allows access to live parts, so this is not allowed or UL approved.

Front Height Inches	Standard FAS-Latch Front	
	24" W Flush Standard	24" W Surface Standard
	Catalog Number	Catalog Number
56	P3F56	P3S56
62	P3F62	P3S62
68	P3F68	P3S68
74	P3F74	P3S74
80	P3F80	P3S80


Note: Add "M" suffix for Metal Card Holder or "WM" suffix for Welded Metal Card Holder

Front Height Inches	Door-in-Door Front ^①	
	24" W Flush	24" W Surface
	Catalog Number	Catalog Number
56	P3F56D	P3S56D
62	P3F62D	P3S62D
68	P3F68D	P3S68D
74	P3F74D	P3S74D
80	P3F80D	P3S80D

Note: Add "M" suffix for Metal Card Holder. For Welded Metal Card Holder, contact Customer Support for availability.

Front Height Inches	Hinge-to-Box Front ^①	
	24" W Flush	24" W Surface
	Catalog Number	Catalog Number
56	P3F56H	P3S56H
62	P3F62H	P3S62H
68	P3F68H	P3S68H
74	P3F74H	P3S74H
80	P3F80H	P3S80H

Note: Add "M" suffix for Metal Card Holder.
Non-standard P3 series fronts options must be ordered as manual item on factory. For welded metal card holder, contact Customer Support for availability.



P3 Series Surface Front

24"W P3 Box Size	Surface	Flush	# of Hinges
	A	A	
56	56	57.5	3
62	62	63.5	3
68	68	69.5	3
74	74	75.5	3
80	80	81.5	3

^① Stainless 304 is available as a special order for 20" W and 24" W only.
Stainless 316 is not available. Flush stainless fronts are typically 1/2" wider and taller than standard flush fronts.

Panelboards

Type 1 Panel Locks for P1, P2, P3

Selection

P1-P3 panel locks for Type 1 fronts^{⑥⑦}

Push-In Panel Locks - Availability for Front/Door by Gauge ^①			Type 1 Front Styles available with material, lock and hinge options. ^③										
Front/Door Thickness	Replacement kit (where available) and Reference Material #	This lock is keyed for	FAS-Latch (16 Gauge)	STB (Screw-to-Bolt)	HTB (Hinged Front)	DND (Door-in-Door)	STB w/Piano Hinge Door	HTB w/Piano Hinge 2 places	DND w/Piano Hinge 2 places	STB 304 Stainless ^④ w/Piano Hinge Door 20" & 24" wide only	HTB 304 Stainless ^④ w/Piano Hinge Door 20" & 24" wide only	DND 304 Stainless ^④ w/Piano Hinge Door 20" & 24" wide only	Comments
0.178 max (16-14 GA)	Cat # LPLOCK01A ^① ref 11-1895-01	standard lock - keyed for B363A	std	std	std	std	std	std	std	std	std	std	
0.208 max (12 GA)	Cat # LPLOCK02A ^① ref 11-1895-02	standard lock - keyed for B363A	n/a	opt	opt	opt	opt	opt	opt	n/a	n/a	n/a	
0.238 max (10 GA)	Cat # LPLOCK03A ^① ref 11-1895-03	standard lock - keyed for B363A	n/a	opt	opt	opt	n/a	n/a	n/a	n/a	n/a	n/a	see note 2
Special keyed locks below: (Contact Customer Support if needed)													
Front/Door thickness	Ref. Material number ^②	This lock is keyed for ^⑤											
0.178 max (16-14 GA)	11-1896-01	Yale LL803 / GE 75 (Corbin TEY)	opt	opt	opt	opt	opt	opt	opt	opt	opt	opt	see note 2 and 6
0.178 max (16-14 GA)	11-1896-02	Yale LL806	opt	opt	opt	opt	opt	opt	opt	opt	opt	opt	see note 2 and 6
0.178 max (16-14 GA)	11-1896-03	Corbin TEU1	opt	opt	opt	opt	opt	opt	opt	opt	opt	opt	see note 2 and 6
0.178 max (16-14 GA)	11-1896-04	Corbin CAT 60	opt	opt	opt	opt	opt	opt	opt	opt	opt	opt	see note 2 and 6
0.178 max (16-14 GA)	11-1896-05	National C413A	opt	opt	opt	opt	opt	opt	opt	opt	opt	opt	see note 2 and 6
0.208 max (12 GA)	11-1896-06	Yale LL803 / GE 75 (Corbin TEY)	n/a	opt	opt	opt	opt	opt	n/a	n/a	n/a	n/a	see note 2 and 6
0.208 max (12 GA)	11-1896-07	Yale LL806	n/a	opt	opt	opt	opt	opt	n/a	n/a	n/a	n/a	see note 2 and 6
0.208 max (12 GA)	11-1896-08	Corbin TEU1	n/a	opt	opt	opt	opt	opt	n/a	n/a	n/a	n/a	see note 2 and 6
0.208 max (12 GA)	11-1896-09	Corbin CAT 60	n/a	opt	opt	opt	opt	opt	n/a	n/a	n/a	n/a	see note 2 and 6
0.208 max (12 GA)	11-1896-10	National C413A	n/a	opt	opt	opt	opt	opt	n/a	n/a	n/a	n/a	see note 2 and 6
0.238 max (10 GA)	11-1896-11	Yale LL803 / GE 75 (Corbin TEY)	n/a	opt	opt	opt	n/a	n/a	n/a	n/a	n/a	n/a	see note 2 and 6
0.238 max (10 GA)	11-1896-12	Yale LL806	n/a	opt	opt	opt	n/a	n/a	n/a	n/a	n/a	n/a	see note 2 and 6
0.238 max (10 GA)	11-1896-13	Corbin TEU1	n/a	opt	opt	opt	n/a	n/a	n/a	n/a	n/a	n/a	see note 2 and 6
0.238 max (10 GA)	11-1896-14	Corbin CAT 60	n/a	opt	opt	opt	n/a	n/a	n/a	n/a	n/a	n/a	see note 2 and 6
0.238 max (10 GA)	11-1896-15	National C413A	n/a	opt	opt	opt	n/a	n/a	n/a	n/a	n/a	n/a	see note 2 and 6

Replacement Parts

Catalog No.	Market Facing Description	Pack Quantity
LPKEY01A	Key #B363A for Panel Trim Lock (FAS-Latch)	4
LPKEY01B	Key #B363A for Panel Trim Lock (FAS-Latch)	25

Contacts for Special Keys

National C413A	Go to this website: http://compix.com/dist-csp.html ==> then lookup a distributor in your area to get keys. Or call 864-297-6655
Corbin TEU1 or CAT 60	Contact your local distributor for special keys
Yale LL803 / GE 75 (Corbin TEY)	Contact your local distributor for special keys

Locks not listed may require special door cutouts and are not field replaceable in standard fronts included in this table.

① Lock kits include one replacement lock with 2 keys #B363A

② Contact Customer Support for re-ordering special keyed locks as needed.

③ The lock options for Yale 511, BEST, Corbin 15751 and Corbin 15757 CANNOT be used in 12GA and 10GA fronts, or with any 304 stainless steel fronts.

④ Factory has final determination on whether combinations of non-standard features are available. Contact customer support for complex front configurations.

⑤ The factory does not stock keys for these locks. It's the customer's responsibility to obtain it from outside sources.

⑥ NEMA 3R/12, NEMA 4, NEMA 4X SS, NEMA 4X non-metallic enclosures cannot be used with the fas-latch lock assembly.

⑦ Consult Factory or Customer Support for any special lock requirements.

Panelboards

NEMA Type 3R and 3R/12 enclosure for P1, P2, P3

Reference

P1, P2, P3 panelboard standard Type 3R and 3R/12 enclosures

Type 3R/12 enclosures meet both NEMA 3R and NEMA 12 requirements

Features:	Typical Standard NEMA Type 3R and 3R/12 Enclosure	Options
	– P1 and P2 are 20"W x 5.75"D (min interior dimensions) – P3 is 24"W x 7.75"D (min. interior dimensions) – 16 GA Steel can with 14 GA steel door or similar UL approved construction – Standard is A60 galvanized ANSI 61 gray paint	– Custom paint available – Note 3R and 3R/12 are same steel enclosure. 3R/12 has gasketing added at factory. – Note Siemens 3R/12 meets NEMA Type 12 specifications


Note: Contact customer support for special colors (RAL # required.)

Box Height Inches	P1/P2 Catalog Number			P1/P2 Catalog Number			P3 Catalog Number	P3 Catalog Number
	Type 3R Standard Enclosure			Type 3R/12 Standard Enclosure			Type 3R Standard Enclosure	Type 3R/12 Standard Enclosure
	Galvanized 20" W	Galvanized 20" W	Galvanized 24" W	Galvanized 20" W	Galvanized 20" W	Galvanized 24" W	Galvanized 24" W	Galvanized 24" W
	5.75" Depth	7.75" Depth	5.75" Depth	5.75" Depth	7.75" Depth	5.75" Depth	7.75" Depth	7.75" Depth
26	NR26	Ref NRD26 ^①	24NR26	WP26	Ref WPD26 ^①	24WP26	N/A	N/A
32	NR32	NRD32	24NR32	WP32	WPD32	24WP32	N/A	N/A
38	NR38	NRD38	24NR38	WP38	WPD38	24WP38	N/A	N/A
44	NR44	NRD44	24NR44	WP44	WPD44	24WP44	N/A	N/A
50	NR50	NRD50	24NR50	WP50	WPD50	24WP50	N/A	N/A
56	NR56	NRD56	24NR56	WP56	WPD56	24WP56	24NRD56	24WPD56
62	NR62	NRD62	24NR62	WP62	WPD62	24WP62	24NRD62	24WPD62
68	NR68	NRD68	24NR68	WP68	WPD68	24WP68	24NRD68	24WPD68
74	NR74	NRD74	24NR74	WP74	WPD74	24WP74	24NRD74	24WPD74
80	N/A	N/A	N/A	N/A	N/A	N/A	24NRD80	24WPD80

① Custom order in COMPAS

Type 3R and 3R/12 Box

Note: 3R boxes 50" High and Larger include two "T" handles (ref # 31-1905-01).



(UL approved construction. 16 Gage Steel Can with 14 Gage front or similar approved construction.)
A60 Galvanized is standard without paint.

Dimensions shown in inches and millimeters [].

① Dimensions are interior of the box. Add 5/8" to width for absolute dimension. Add 1/8" to height for absolute dimension.

② Dimensions are for P1 and P2. (P1/P2 24" W x 7.75" D is special - contact factory)
③ Dimensions are for P3.

Panelboards

NEMA Type 4 and 4X Enclosures for P1,P2

Reference

P1/P2 NEMA 4 and NEMA 4X non-metallic enclosures

NEMA Type 4 enclosures below are special order and are larger than typical enclosure size needed. NEMA 4X enclosures are more appropriately sized.

NEMA 4

Ref. Type 1 Enclosure Height Inches	Actual Box Height Inches	P1 / P2 Catalog Number			
		24" W	30" W	36" W	36" W
		8" Depth	8" Depth	8" Depth	10" Depth
26*	30	Custom A36H24BLP* ^①	—	—	—
32	36	Custom A36H24BLP ^①	—	—	—
38	42	—	Custom A42H30BLP ^①	—	—
44	48	—	—	Custom A48H36BLP ^①	—
50, 56	60	—	—	—	Custom A60H36CLP ^①


Note that the parts listed in this table are buyout items; long lead times are associated with them. Must be entered as manual line in COMPAS.

*Type 4 26" height enclosures will be adjusted at the plant to use the 32" enclosure

NEMA 4X

Box Height Inches	P1 / P2 / P3 Catalog Number			
	304 SS Enclosure		316 SS Enclosure	
	20" W – P1 / P2	24" W – P3	20" W – P1 / P2	24" W – P3
	5.75" Depth	7.75" Depth	5.75" Depth	7.75" Depth
26	B4X26	N/A	Ref A6X30103883 ^①	N/A
32	B4X32	N/A	Ref A6X30065588 ^①	N/A
38	B4X38	N/A	Ref A6X30065589 ^①	N/A
44	B4X44	N/A	Ref A6X30069448 ^①	N/A
50	B4X50	N/A	Ref A6X30100668 ^①	N/A
56	B4X56	24BD4X56 ^②	Ref A6X30100669 ^①	N/A
62	B4X62	24BD4X62 ^②	N/A	Ref A6X30075982 ^{①②}
68	B4X68	24BD4X68 ^②	Ref A6X30100670 ^①	Ref A6X30075983 ^{①②}
74	B4X74	24BD4X74 ^②	Ref A6X30100701 ^①	Ref A6X30075984 ^{①②}
80	N/A	24BD4X80 ^②	N/A	Ref A6X30069449 ^{①②}

NEMA 4X Stainless Enclosures (Hasp for padlock included)



① Custom order in COMPAS

② Interface with the Deadfront is for P3 only, will not work with P1/P2

Panelboards

NEMA Type 4 and 4X Enclosures for P1,P2

Reference

NEMA 4X enclosures (continued)



NEMA 4X Non-Metallic Enclosures (Limited sizes are available)

Ref. Type 1 Enclosure Height Inches	Actual Box Height Inches	AxBxC Reference Inches	Catalog Number		
			24" W - P1 / P2	30" W - P1 / P2	36" W - P1 / P2 / P3
			8" Depth	8" Depth	12" Depth
26	30	30.25 x 30.25 x 8.00	Custom A30H2408GQRLP ^①	—	—
32	36	36.25 x 30.25 x 8.00	—	Custom A36H3008GQRLP ^①	—
38, 44	48	48.25 x 36.25 x 12.00	—	—	Custom A48H3612GQRLP ^①
50, 56	60	60.25 x 36.25 x 12.00	—	—	Custom A60H3612GQRLP ^{①②}

Hinged with Quick-Release Latches, Type 4X

NEMA 4X Non-Metallic Enclosures

Dimensions below for reference only - actual sizes vary by enclosure

Hinged with Quick-Release Latch Enclosures 36 X 30 or Smaller Drawing^③Hinged with Quick-Release Latch Enclosures 36 X 36 or Larger Drawing^④

① Custom order in COMPAS

② 60" enclosure can fit 56" P3 interior due to custom fit at plant.

③ ??There is a footnote# by the drawing but no actual footnote on the page 12 in the guide.

Panelboards

Type P2 Panelboards

General

Features

Flexibility is the hallmark of the P2 panel. This panel offers a wide array of factory-assembled options to meet almost all lighting panel applications. With this design, the ability to mix breaker frames in unit space up to 250 amps will also meet many distribution panel requirements in a much smaller package. Bussing options for the P2 vary from the typical temperature rated to 750 A/Si aluminum to 1000A/Si copper. Standard bussing in the P2 panel is tin-plated. Silver-plated copper is also offered as an option. Integrated time clocks, bus mounted contactors, as mains or sub mains, split bus, and subfeed lugs (up to 400 amp) are just a few of the options of this unique panel.

Like a lighting panel, P2 is set up around 18, 30, 42, 54, 66, 78, and 90 circuit configurations. It will also allow the user to configure the panel to the smallest possible size. The P2 panel starts with 9" of unit space (18 circuits of 1" pole breakers). Breakers mounted in unit space can be mixed and matched to meet customer requirements. All 1" pole breakers (BL, BQD, xGB, xGB2, ED frames) are mounted in 3" or 6" pole increments. Breaker frames, above 125 amps, are mounted in 6" single breaker mountings.

As an example of a minimum panel, (6) 20 amp 1-pole BL breakers (3" of unit space) and a 3-pole 225 amp QJ breaker (6" of unit space) equaling 9" of unit space can be configured in a P2 panel without any extra provisions or space required. FD 250 amp and JD 400 amp breakers are mounted as subfeed breakers outside of unit space.

Another unique feature of the P2 panel is that blank unit space can be added to allow for future expansions or modifications. Any expansions or modifications must be in 3" increments. BL, BQD, xGB, xGB2, and ED frame breakers have 3" or 6" pole kits, and can be mixed in unit space by these increments. Breakers of the same frame can cross from one mounting to another if contiguous. QR frame breakers are mounted in 6" increments for two- and three pole, single mounted units. Changes in the unit space length for BL, BQD, xGB, xGB2, or ED frame breakers require an addition deadfront, center strip kit. Check with sales or the factory for additional unit space kits.

Main Lug / Main Breaker

Enclosure – Standard Type 1 enclosure is 20" wide x 5.75" deep X. Box Height is determined by main device and unit space. See charts for box height.

Voltage – 600V AC max.
250V DC max.

Amperage – 600 amp max.

Short circuit rating – 200 KAIC max. symmetrical or equal to the lowest rated device installed unless a series rating is indicated. Panels with subfeed or feed-thru lugs without a main device, circuit breaker or fusible unit, are limited to a three-cycle rating. The three-cycle rating for the P2 panel is limited to 22 KAIC. Note that the main device may be mounted remote from the panel.

Bussing – The P2 panel has more options to meet market requirements. The standard bussing is temperature rated aluminum. The rating is per the requirements of UL 67 – the standard for panelboards. All aluminum bussing is tin-plated. Optional bussing for the P2 panel is: 750 A/Si aluminum, temperature rated copper, and 1000 A/Si copper. The copper bus option for this panel is tin-plated.

Weight – Approximate

Total panelboard weight when filled with a normal quantity of breakers and accessories is about 3 lbs. (1 kg) per inch (54g per mm) of box height.

Gauge Steel of Boxes/Fronts, Surface and Flush (see pgs. 11-6 & 11-7)

Dimensions in Inches (mm)		Gauge Steel		
H	W	Box	Front/Door	Type
26-74 (660-1880)	20 (508)	16 ^①	14 ^②	Type 1
26-74 (660-1880)	20 (508)	16 ^②	16/14 ^②	Type 3R/12
32-60 (813-1524)	20-36 (508-914)	14 ^③	14 ^③	Type 4
26-74 (660-1879)	20 (508)	14 ^④	14 ^④	Type 4X
36-60 (914-1524)	30-36 (762-914)	N/A ^⑤	N/A ^⑤	Type 4X Non-Metallic

① 16 Gauge is Standard (14 Gauge & 12 Gauge are optional)

② 15 Gauge Steel Can with 14 Gauge Door or Similar Approved Construction

③ No Optional Gauge available

④ 304SS 14 Gauge Std., 316SS 14 Gauge optional

⑤ Sizes do not match Standard Enclosure Sizes - See Table P1-21 - material is non-metallic - No Gauge Specified.

⑥ FAS-Latch is 14 GA only.

Screw-to-Box, Hinge-to-Box, Door-in-Door (14 GA Std./12 GA Std. or 10 GA Optional)
STB/HTB/DND with Piano Hinge (14 GA Std./12 GA Optional)

Panelboards

Type P2 Panelboards

Selection/Dimensions

Standard Circuit P2 Panels (Neutral Configurations for up to 54 circuits max.)

Table below shows minimum Box Size required for the Unit Space indicated with the Main Option at the top of each Column.

- Adding other options generally will add to the box Height when configured in COMPAS. Also, there may be cost adders with each option.

- The maximum number of 1" circuits supported is shown at the bottom of each column in brackets. [54p] = max 54 poles of 1" circuits supported (BL, BQD, ED, xGB, xGB2).
- Unit space is available in 9", 15", 21", 27", 33", 39", and 45" sizes.
- Within unit space listed, the neutral will support up to 54 circuits.

- When more than 54 circuits are required, COMPAS will configure with larger Extended Circuit Neutral - see Extended Circuit chart below for minimum box sizes.
- Box sizes available: 26", 32", 38", 44", 50", 62", 68", 74"

"B" Dimension Box Height	P2 Panels with Standard Line Lugs. Unit Space (starting with 9" and adding 6" increments) "A" Dimension														
	Main Lugs			Main Breakers											
	125A	250A	400A 600A	125A Horiz. BL, BQD, xGB, ED	125A Vert. ED ^①	125A Horiz. CED	225A Horiz. QR	225A Vert. QR ^①	250A Horiz. FD	250A Vert. FD ^①	250A Vert. CFD	400A Vert. JD	400A Vert. CJD	600A Vert. LD	600A Vert. CLD
26	9	—	—	9	—	—	—	—	—	—	—	—	—	—	—
32	15	9	—	15	9	9	—	—	—	—	—	—	—	—	—
38	21	15	9	21	15	15	15	9	9	—	—	—	—	—	—
44	27	21	15	27	21	21	21	15	15	9	—	—	—	—	—
50	33	27	21	33	27	27	27	21	21	15	9	9	—	—	—
56	39	33	27	39	33	33	33	27	27	21	15	15	—	9	—
62	45	39	33	45	39	39	39	33	33	27	21	21	9	15	9
68	45	45	39	45	45	45	45	39	39	33	27	27	15	21	15
74	45	45	45	45	45	45	45	45	45	39	33	33	21	27	21
	[54p]	[54p]	[54p]	[54p]	[54p]	[54p]	[54p]	[54p]	[54p]	[54p]	[54p]	[54p]	[42p]	[54p]	[42p]

Extended Circuit P2 Panels (Neutral Configurations for more than 54 circuits)

When COMPAS configuration has more than 54 circuits, the large neutral configuration is needed. Box size shown is the minimum available without any options.


- Unit space of 33", 39", and 45" are available.
- Unit space will be reduced by selecting some options such as Feed-thru lugs, Surge Protection Devices, and the other Subfeed options.
- In general, vertically mounted mains require 6" more box space than equivalent horizontally mounted mains.
- Neutral configuration supports a maximum of 90 1-pole breakers.

"B" Dimension Box Height	P2 Panels with Standard Line Lugs. Unit Space (starting with 9" and adding 6" increments) "A" Dimension														
	Main Lugs			Main Breakers											
	125A	250A	400A 600A	125A Horiz. BL, BQD, xGB, ED	125A Vert. ED ^①	125A Horiz. CED	225A Horiz. QR	225A Vert. QR ^①	250A Horiz. FD	250A Vert. FD ^①	250A Vert. CFD	400A Vert. JD	400A Vert. CJD	600A Vert. LD	600A Vert. CLD
56	33	—	—	33	—	—	33	—	—	—	n/a	—	n/a	n/a	n/a
62	39	33	33	39	33	33	39	33	—	—	n/a	—	n/a	n/a	n/a
68	45	39	39	45	39	39	45	39	33	—	n/a	—	n/a	n/a	n/a
74	45	45	45	45	45	45	45	45	39	33	n/a	33	n/a	n/a	n/a
	[90p]	[90p]	[90p]	[90p]	[90p]	[90p]	[90p]	[90p]	[78p]	[66p]	n/a	[66p]	n/a	n/a	n/a

① Note: The vertical main breaker application for ED, QJ, QR, and FD adds 6" of box height.


Main lug wire bending space diagram

Box depth = 5.75 in.
(146 mm)
Box width = 20 in.
(508 mm)
for 100-600A



Main breaker wire bending space diagram

Box depth = 5.75 in.
(146 mm)
Box width = 20 in.
(508 mm)
for 100-600A



Panelboards

Type P2 Panelboards

Selection/Dimensions

Standard Circuit P2 Panels

Main Breaker Wire Bending

Standard Circuits (up to 54 1" module branch poles)			
Panel Amps	Breaker Frames	C ^①	D ^①
100	BL	5.75	8.00
	BQD	5.13	8.00
125	xGB, xGB2	4.63	8.00
	ED (horiz.)	4.00	8.00
	ED (vert.)	6.56	11.13
225	QR (horiz.)	5.00	7.00
	QR (vert.)	10.06	16.69
250	FD (horiz.)	5.00	7.00
	FD (vert.)	13.25	22.72
400	JD	15.38	25.00
600	LD	15.38	23.00

Extended Circuit P2 Panels

Main Breaker Wire Bending

Extended Circuits (more than 54 1" module branch poles)			
Panel Amps	Breaker Frames	C ^①	D ^①
100	BL	5.75	6.56
	BQD	5.13	6.56
125	xGB, xGB2	4.63	6.56
	ED (horiz.)	4.00	6.56
	ED (vert.)	12.56	14.88
225	QR (horiz.)	5.00	6.44
	QR (vert.)	10.06	15.53
250	FD (horiz.)	5.00	5.63
	FD (vert.)	19.25	25.71
400	JD	15.38	23.75
600	LD (54p max)	N/A	N/A

Main Lug Connectors


Standard Circuits (up to 54 1" module branch poles)			
Panel Amps	Standard Connectors	C ^①	D ^①
125	(1) #14-2/0	6.62	8.19
250	(1) #6 AWG - 350 MCM	11.75	10.72
400	(1) #4 AWG - 600 MCM or (2) #6 - 250 MCM	14.00	13.09
600	(2) #4 AWG - 500 MCM	14.00	11.00

Main Lug Connectors

Extended Circuits (more than 54 1" module branch poles)			
Panel Amps	Standard Connectors	C ^①	D ^①
125	(1) #14-2/0	12.62	8.91
250	(1) #6 AWG - 350 MCM	17.75	13.69
400	(1) #4 AWG - 600 MCM or (2) #6 - 250 MCM	14.00	14.19
600	(2) #4 AWG - 500 MCM	14.00	14.23

Branch Breaker Side Gutters Inches (mm)

Reference Letter	Panel Width 20" (508)
A	5.750 (146)
B	5.125 (130)
C	4.000 (102)
D ^②	5.000 (127)
E	4.625 (117)



① Refer to diagrams at the bottom of page 11-43.
② Single branch mounting construction.

③ BQD6 is not UL Listed. Only for CUL and CSA panels.

Panelboards

Type P2 Panelboards

Selection

Main Breaker Selection^①

Amp Rating	Breaker Type	Max. Interrupting Rating (kA)			Ref. Type Code	Horizontal or Vertical	Available Trip Values
		240V	480V	600V			
100	BL	10	—	—	BL	H	15, 20, 25, 30, 35, 40, 50, 60, 70, 80, 90, 100
	HBL	65	—	—	HB	H	15, 20, 25, 30, 35, 40, 50, 60, 70, 80, 90, 100
	BQD	65	14	—	BQ	H	15, 20, 25, 30, 35, 40, 50, 60, 70, 80, 90, 100
	BLH	22	—	—	BH	H	15, 20, 25, 30, 35, 40, 50, 60, 70, 80, 90, 100
125	NGB	100	25	14	NB	H	50, 60, 70, 80, 90, 100, 110, 125
	HGB	100	35	14	G2	H	50, 60, 70, 80, 90, 100, 110, 125
	LGB	100	65	14	G3	H	50, 60, 70, 80, 90, 100, 110, 125
	ED4	65	18	—	E4	H/V	50, 60, 70, 80, 90, 100, 110, 125
	ED6 ^⑤	100	25	14	E6	H/V	60, 70, 80, 90, 100, 110, 125 (3-pole)
	HED4	100	42	—	H4	H/V	50, 60, 70, 80, 90, 100, 110, 125
	CED6 ^②	200	200	100	CE	H/V	50, 60, 70, 80, 90, 100, 110, 125
	NGB2	100	25	14	G4	H	50, 60, 70, 80, 90, 100, 110, 125
	HGB2	100	35	22	G5	H	50, 60, 70, 80, 90, 100, 110, 125
225	LGB2	100	65	25	G6	H	50, 60, 70, 80, 90, 100, 110, 125
	QR2	10	—	—	QR	H	100, 110, 125, 150, 175, 200, 225
	QRH2	25	—	—	Q4	H	100, 110, 125, 150, 175, 200, 225
	HQR2	65	—	—	Q5	H	100, 110, 125, 150, 175, 200, 225
	HQR2H	100	—	—	Q6	H	100, 110, 125, 150, 175, 200, 225
	FD6	65	35	18	FD	H/V	70, 80, 90, 100, 110, 125, 150, 175, 200, 225
	FXD6	65	35	18	FX	H/V	70, 80, 90, 100, 110, 125, 150, 175, 200, 225
	HFD6	100	65	25	HF	H/V	70, 80, 90, 100, 110, 125, 150, 175, 200, 225
	HFXD6	100	65	25	H2	H/V	70, 80, 90, 100, 110, 125, 150, 175, 200, 225
250	CFD6 ^②	200	200	100	CF	H/V	70, 80, 90, 100, 110, 125, 150, 175, 200, 225
	FD6	65	35	18	FD	H/V	70, 80, 90, 100, 110, 125, 150, 175, 200, 225, 250
	FXD6	65	35	18	FX	H/V	70, 80, 90, 100, 110, 125, 150, 175, 200, 225, 250
	HFD6	100	65	35	HF	H/V	70, 80, 90, 100, 110, 125, 150, 175, 200, 225, 250
400	HFXD6	65	35	25	H2	H/V	70, 80, 90, 100, 110, 125, 150, 175, 200, 225, 250
	JXD6 ^②	65	35	25	JX	V	200, 225, 250, 300, 350, 400
	JD6 ^②	65	35	35	J6	V	200, 225, 250, 300, 350, 400
	HJXD6 ^②	100	65	35	H6	V	200, 225, 250, 300, 350, 400
	HJD6 ^②	100	65	35	H5	V	200, 225, 250, 300, 350, 400
	SJD6 ^②	65	35	25	SJ	V	200, 300, 400
	SHJD6 ^②	100	65	35	S2	V	200, 300, 400
	CJD6 ^②	200	200	100	CJ	V	200, 300, 400
	SCJD6 ^②	200	200	100	SC	V	200, 300, 400
600	LXD6 ^②	65	35	25	LX	V	450, 500, 600
	LD6 ^②	65	35	25	L6	V	250, 300, 350, 400, 450, 500, 600
	HLXD6 ^②	100	65	35	HL	V	250, 300, 350, 400, 450, 500, 600
	HLD6 ^②	100	65	35	HO	V	250, 300, 350, 400, 450, 500, 600
	SLD6 ^②	65	35	25	SL	V	300, 400, 500, 600
	SHLD6 ^②	100	65	35	S6	V	300, 400, 500, 600
	CLD6 ^②	200	150	100	CL	V	300, 400, 500, 600
	SCLD6	200	150	100	C6	V	300, 400, 500, 600

When an ED4, ED6, HED4, HHED6, QR2, QRH2, HQR2, HQR2H, FD6, HFD6, or FXD6 frame main breaker is required to be vertically mounted, pricing will typically be higher.

Vertically Mounted Main Breaker (available in 2-pole or 3-pole)

Ampere Rating	Breaker Type(s)	Additional Unit Space (in.)
125	ED4, ED6 ^③ , HED4, HHED6	6
225	QR2, QRH2, HQR2, HQR2H	6
250	FXD6, FD6, HFD6	6

Subfeed Breakers (available in 2-pole or 3-pole)

Breaker Type	Mounting Position When Used as Subfeed Breaker	Ampere Ratings For Load	Maximum Interrupting Rating (kA) Symmetrical		
	Vertical		240V AC	480V AC	600V AC
FD6 ^③ , FXD6	Twin	70–250	65	35	22
HFD6 ^③ , HFXD6	Twin	70–250	100	65	25
JD6 ^④ , JXD6	Single	200–400	65	35	25
HJD6 ^④ , HJXD6	Single	200–400	100	65	35

① Interchangeable trip main breakers are mounted at top of panel only.
② Vertically mounted.

③ Twin mounted subfeed breakers are mounted at the bottom of panelboard only and adds 24" to the panel height.

④ Subfeed breaker is mounted at bottom of panelboard only. 400 amp subfeed breaker adds 24" to the panel height. (Only for use with MLO)
⑤ ED6/CED6 2-pole limited amps available (20-50A)

Panelboards

Type P2 Panelboards

Selection

P2 Branch Circuit Breakers

P2 Branch Circuit Breakers																		S = Single Mount				
				1-Pole					2-Pole and 3-Pole													
Amp Rating	Trip Type	Breaker Family	Breaker Type	Max IR (kA) at				Amp Ratings Avail.	Max IR (kA) at								Amp Ratings Avail.	T = Twin mount				
				120V	277V	347V	125V DC		120/240V	240V	480Y/277V	480V	600Y/347V	600V	125/250V DC	250V DC		Unit Space per Kit (in.)	Max 1-pole Circuits per Kit			
100	Thermal Magnetic	BL	BL	10	—	—	—	15-70	10	10	—	—	—	—	—	—	15-100	—	T	3.00	6	
			BLH	22	—	—	—	15-70	22	22	—	—	—	—	—	—	15-100	—	T	3.00	6	
			HBL	65	—	—	—	15-50	65	65	—	—	—	—	—	—	15-100	—	T	3.00	6	
	Special Application	BLG BL	BLG ^①	10	—	—	—	15-20	10	—	—	—	—	—	—	30	—	T	3.00	6		
			BL (HID)	10	—	—	—	15-30	10	—	—	—	—	—	—	15-30	—	T	3.00	6		
	Thermal Magnetic	BQD	BQD ^⑤	65	14	—	14	15-100	—	65	14	—	—	—	14	—	15-100	—	T	3.00	6	
			BQD6 ^⑥	65	—	—	14	15-70	—	65	—	—	10	—	14	—	15-70	—	T	3.00	6	
xx	Electronic and misc.	BL	AFCI/ GFCI & Dual Function	x	—	—	—	see special table page 11-13	x	—	—	—	—	—	—	—	see special table page 11-13	—	T	3.00	6	
125	Thermal Magnetic	GB	NGB	100	25	14	14	15-125	—	100	25	—	14	—	14	—	15-125	—	T	3.00	6	
			HGB	100	35	14	14	15-125	—	100	35	—	14	—	14	—	15-125	—	T	3.00	6	
			LGB	100	65	14	14	15-125	—	100	65	—	14	—	14	—	15-125	—	T	3.00	6	
		Sentron	ED4	65	22	—	30	15-100	—	65	—	18	—	—	—	30	15-125	—	T	3.00	6	
			ED6 ^⑦	—	—	—	—	15-100	—	65	—	25	—	18	—	30	20-125	—	T	3.00	6	
			HED4 ^②	100	25 ^②	—	30	15-100	—	65	—	18 ^②	—	—	—	30	15-125	—	T	3.00	6	
			HHED6	—	—	—	—	—	—	100	—	65	—	18	—	—	15-50	—	T	3.00	6	
		GB2	NGB2	100	25	14	14 ^④	15-125	—	100	—	25	14	—	14 ^④	—	15-125	—	T	3.00	6	
			HGB2	100	35	22	14 ^④	15-125	—	100	—	35	22	—	14 ^④	—	15-125	—	T	3.00	6	
			LGB2	100	65	25	14 ^④	15-125	—	100	—	65	25	—	14 ^④	—	15-125	—	T	3.00	6	
		3VA41 ^③	info not yet avail-able	x	x	x	x		x	x	x	—	x	—	—	x			—	T	3.00	6
				x	x	x	x		x	x	x	—	x	—	—	x			—	T	3.00	6
	x		x	x	x		x	x	x	—	x	—	—	x			—	T	3.00	6		
225	Thermal Magnetic	QR	QR2	—	—	—	—	—	—	10	—	—	—	—	—	—	100-225	—	T	6.00	3	
			QRH2	—	—	—	—	—	—	25	—	—	—	—	—	—	100-225	—	T	6.00	3	
			HQR2	—	—	—	—	—	—	65	—	—	—	—	—	—	100-225	—	T	6.00	3	
			HQR2H	—	—	—	—	—	—	100	—	—	—	—	—	—	100-225	—	T	6.00	3	
				—	—	—	—	—	—	—	—	—	—	—	—	—	100-225	—	T	6.00	3	

Branch Neutral Connections

Wire Range	Max. Number of Connections	Max. Amp ^⑧
#14-#6	26	65
#14-1/0	28	125
#6-350 kcmil	3	250
(1) #4-600 kcmil or (2) #6-250 kcmil	1	400

① BLG two-pole breaker is one phase and neutral. Three pole is two phases and neutral - See SpeedFax page 7-31
 ② 1-pole HED4 15-30A rated 65kA; 35-100A rated 25kA; 3-pole HED4 rated 42kA

③ Availability and additional specs tbd, expected late 2019. (COMPAS may allow selection of alternate trip units)
 ④ 2-pole only or two outer poles of 3-pole breaker
 ⑤ Approved for CSA and UL Listed.

⑥ Approved for CSA but not UL Listed.
 ⑦ ED6 2-pole only available in 20A, 25A and 30A. ED6 1-pole not UL listed - See SpeedFAX section 7 for more details.
 ⑧ Based on 75 degree copper.

Panelboards

Type P2 Panelboards

Selection

Main Lugs Only — Examples of basic P2 Panel numbers w/o devices that add to box height.

Max Panel Amp Rating	Max. 1-pole Circuits	Min. Unit space	Standard or Extended Circuit	3Ø4W 208Y/120V	Box Height Inches Min.	1Ø3W 120/240V	Box Height Inches Min.	3Ø4W 480Y/277V	Box Height Inches Min.
				Panel Number		Panel Number		Panel Number	
125	18	9	Standard Circuit Panel	P2C18ML125ATS	26	P2A18ML125ATS	26	P2E18ML125ATS	26
	30	15		P2C30ML125ATS	32	P2A30ML125ATS	32	P2E30ML125ATS	32
	42	21		P2C42ML125ATS	38	P2A42ML125ATS	38	P2E42ML125ATS	38
	54	27		P2C54ML125ATS	44	P2A54ML125ATS	44	P2E54ML125ATS	44
	66	33	Extended Circuit Panel	P2C66ML125ATS	56	P2A66ML125ATS	56	P2E66ML125ATS	56
	78	39		P2C78ML125ATS	62	P2A78ML125ATS	62	P2E78ML125ATS	62
	90	45		P2C90ML125ATS	68	P2A90ML125ATS	68	P2E90ML125ATS	68
250	18	9	Standard Circuit Panel	P2C18ML250ATS	32	P2A18ML250ATS	32	P2E18ML250ATS	32
	30	15		P2C30ML250ATS	38	P2A30ML250ATS	38	P2E30ML250ATS	38
	42	21		P2C42ML250ATS	44	P2A42ML250ATS	44	P2E42ML250ATS	44
	54	27		P2C54ML250ATS	50	P2A54ML250ATS	50	P2E54ML250ATS	50
	66	33	Extended Circuit Panel	P2C66ML250ATS	62	P2A66ML250ATS	62	P2E66ML250ATS	62
	78	39		P2C78ML250ATS	68	P2A78ML250ATS	68	P2E78ML250ATS	68
	90	45		P2C90ML250ATS	74	P2A90ML250ATS	74	P2E90ML250ATS	74
400	18	9	Standard Circuit Panel	P2C18ML400ATS	38	P2A18ML400ATS	38	P2E18ML400ATS	38
	30	15		P2C30ML400ATS	44	P2A30ML400ATS	44	P2E30ML400ATS	44
	42	21		P2C42ML400ATS	50	P2A42ML400ATS	50	P2E42ML400ATS	50
	54	27		P2C54ML400ATS	56	P2A54ML400ATS	56	P2E54ML400ATS	56
	66	33	Extended Circuit Panel	P2C66ML400ATS	62	P2A66ML400ATS	62	P2E66ML400ATS	62
	78	39		P2C78ML400ATS	68	P2A78ML400ATS	68	P2E78ML400ATS	68
	90	45		P2C90ML400ATS	74	P2A90ML400ATS	74	P2E90ML400ATS	74
600	18	9	Standard Circuit Panel	P2C18ML600ATS	38	P2A18ML600ATS	38	P2E18ML600ATS	38
	30	15		P2C30ML600ATS	44	P2A30ML600ATS	44	P2E30ML600ATS	44
	42	21		P2C42ML600ATS	50	P2A42ML600ATS	50	P2E42ML600ATS	50
	54	27		P2C54ML600ATS	56	P2A54ML600ATS	56	P2E54ML600ATS	56
	66	33	Extended Circuit Panel	P2C66ML600ATS	62	P2A66ML600ATS	62	P2E66ML600ATS	62
	78	39		P2C78ML600ATS	68	P2A78ML600ATS	68	P2E78ML600ATS	68
	90	45		P2C90ML600ATS	74	P2A90ML600ATS	74	P2E90ML600ATS	74

Main Circuit Breaker — Examples of Panel numbers w/o options that add to box height.

Max Panel Amp Rating	Main Type ref	Max. 1-pole Circuits	Unit space	Standard or Extended	1Ø3W 120/240V	Box Height Inches Min.	3Ø4W 208Y/120V	Box Height Inches Min.	3Ø4W 480Y/277V	Box Height Inches Min.
					Panel Number		Panel Number		Panel Number	
100	BL/BQD, xGB, ED horiz.	18	9	Standard Circuit Panel	P2A18BL100ATS	26	P2C18BL100ATS	26	P2E18BQ100ATS	26
		30	15		P2A30BL100ATS	32	P2C30BL100ATS	32	P2E30BQ100ATS	32
		42	21		P2A42BL100ATS	38	P2C42BL100ATS	38	P2E42BQ100ATS	38
		54	27		P2A54BL100ATS	44	P2C54BL100ATS	44	P2E54BQ100ATS	44
125	Horiz. Main ^① BQD, xGB, ED	18	9	Standard Circuit Panel	P2A18BQ125ATS	26	P2C18NB125ATS	26	P2E18E4125ATS	26
		30	15		P2A30BQ125ATS	32	P2C30NB125ATS	32	P2E30E4125ATS	32
		42	21		P2A42BQ125ATS	38	P2C42NB125ATS	38	P2E42E4125ATS	38
		54	27		P2A54BQ125ATS	44	P2C54NB125ATS	44	P2E54E4125ATS	56
		66	33	Extended Circuit Panel	P2A66BQ125ATS	56	P2C66NB125ATS	56	P2E66E4125ATS	56
		78	39		P2A78BQ125ATS	62	P2C78NB125ATS	62	P2E78E4125ATS	62
		90	45		P2A90BQ125ATS	68	P2C90NB125ATS	68	P2E90E4125ATS	68
225	Horiz. Main ^② QR, FD (225A max.)	18	9	Standard Circuit Panel	P2A18QR225ATS	32	P2C18QR225ATS	32	P2E18FX225ATS	38
		30	15		P2A30QR225ATS	38	P2C30QR225ATS	38	P2E30FX225ATS	44
		42	21		P2A42QR225ATS	44	P2C42QR225ATS	44	P2E42FX225ATS	50
		54	27		P2A54QR225ATS	50	P2C54QR225ATS	50	P2E54FX225ATS	56
		66	33	Extended Circuit Panel	P2A66QR225ATS	56	P2C66QR225ATS	56	P2E66FX225ATS	68
		78	39		P2A78QR225ATS	62	P2C78QR225ATS	62	P2E78FX225ATS	74
		90	45		P2A90QR225ATS	68	P2C90QR225ATS	68	n/a	n/a
250	Horiz. Main ^③ FD	18	9	Standard Circuit Panel	P2A18FX250ATS	38	P2C18FX250ATS	38	P2E18FX250ATS	38
		30	15		P2A30FX250ATS	44	P2C30FX250ATS	44	P2E30FX250ATS	44
		42	21		P2A42FX250ATS	50	P2C42FX250ATS	50	P2E42FX250ATS	50
		54	27		P2A54FX250ATS	56	P2C54FX250ATS	56	P2E54FX250ATS	56
		66	33	Extended Circuit Panel	P2A66FX250ATS	68	P2C66FX250ATS	68	P2E66FX250ATS	68
		78	39		P2A78FX250ATS	74	P2C78FX250ATS	74	P2E78FX250ATS	74
		90	45		n/a	n/a	n/a	n/a	n/a	n/a
400	Vert. JD Main ^④	18	9	Standard Circuit Panel	P2A18JX400ATS	50	P2C18JX400ATS	50	P2E18JX400ATS	50
		30	15		P2A30JX400ATS	56	P2C30JX400ATS	56	P2E30JX400ATS	56
		42	21		P2A42JX400ATS	62	P2C42JX400ATS	62	P2E42JX400ATS	62
		54	27		P2A54JX400ATS	68	P2C54JX400ATS	68	P2E54JX400ATS	68
		66	33	Extended Circuit Panel	P2A66JX400ATS	74	P2C66JX400ATS	74	P2E66JX400ATS	74
600	Vert. LD Main ^⑤	18	9	Standard Circuit Panel	P2A18LX600ATS	56	P2C18LX600ATS	56	P2E18LX600ATS	56
		30	15		P2A30LX600ATS	62	P2C30LX600ATS	62	P2E30LX600ATS	62
		42	21		P2A42LX600ATS	68	P2C42LX600ATS	68	P2E42LX600ATS	68
		54	27		P2A54LX600ATS	74	P2C54LX600ATS	74	P2E54LX600ATS	74

General Note: Panel numbers and box sizes are for reference only - COMPAS will configure proper box size needed based on all options.

① 125A: for vert ED & horiz. CED add 6" of box height for both Standard and Extended Circuit.
 ② 225A: for vert QR & FD add 6" of box height for Standard Circuit. Add 12" of box height for Extended Circuit FD Horizontal.

③ 250A: for vert FD add 6" of box height; for vert CFD add 12" of box height. (Standard Circuit- see chart for Extended Circuit)
 ④ 400A: for CLD add 12" of box height for Standard Circuit.
 ⑤ 600A: for CLD add 6" of box height for Standard Circuit.

Panelboards

Type P2 Panelboard Modifications and Additions

Selection

Enclosures

Extra Gutter to Sides or Ends of the Can (Type 1 Only)

Description
6" end gutter
2" side gutter
Barrier in gutter (add to extra gutter price – min 4" required)
24" wide
Hinged trims
Piano hinged trims
Door-in-door trims
Screw to the box trims
Trim mounted devices See page 11-119
• Pilot lights
• Toggle switches
• Push buttons
Painted boxes See page 11-119
Custom colors See painted boxes
Increase gauge trims and boxes See page 11-119
Stainless steel trims and boxes, Type 1 See page 11-119

Meters

(Contact sales for pricing and application engineering for space requirements)

Panel Skirts

See page 11-120

Special Locks

TEY
TEU1
Cat 60
LL803
LL806
Yale 47 (NYC)
National C413A
Best Lock 7-pin tumbler
Southco 1/4 Fastener
Corbin 1001 FAB7

Panel Bus Modifications

Main Bus	Catalog Number Addition Amperes Ratings			
	125A	250A	400A	600A
750 A/SI AL.	B	B	B	B
Copper (tin pltd.)	F	F	F	F
Copper (silver pltd.)	E	E	E	E
1000 A/SI Copper (tin pltd.)	G	G	G	G
1000 A/SI Copper (silver pltd.)	H	H	H	H

Subfeed, Feed-Thru and Split Bus (for 2-pole or 3-pole)

Ampere Rating	Connector Cu/Al Wire Range	Unit Space (inches)
---------------	-------------------------------	------------------------

Subfeed (Double) Lugs for Main Lug Panelboards Only (400 max)

100/125	(2)—#12 AWG-2/0 kcmil	6
225/250	(2)—#6 AWG-350 kcmil (custom)	6
400	(4)—250 kcmil (custom) (2)—600 kcmil	6

Feed-Thru Lugs — Cannot Be Used in Conjunction with TVSS or Subfeed Breakers (200% Neutral not available)

100/125	(1)—#12 AWG-2/0 kcmil	6
225/250	(1)—#6 AWG-350 kcmil	6
400	(2)—250 kcmil (1)—600 kcmil	9
600	(2)—250-500 kcmil	12

Split Bus (1 per interior)

Requires feed thru lugs also to feed sub panel section and for space requirements.

100/125	(1)—#12 AWG-2/0 kcmil	6
225/250	(1)—#6 AWG-350 kcmil	6
400	(2)—250 kcmil (1)—600 kcmil	6
600	(2)—250-500 kcmil	6

Contactor Mains or Submain*

See Page 11-118

• Asco 920 through 225 amps – adds 12" unit space as main, 15" unit space as submain
• External with manufacture supplied enclosure
• Siemens LEN through 30 amps - adds 6" as main; 18" for up to 100A submain and 21" for 200A. 7.75" depth cans for up to 100A and 10" depth cans for 200A.

* Call plant for correct can size.

Branch and Main Breaker Accessories

See breaker section of this catalog.
• Handle blocks
• Handle locks
• Aux. Contacts ^①
• UVR ^①

Increase Capacity Neutral up to 200% (N/A on Feed Thru Lugs & Subfeed Lugs)

Main Bus Amps
125
250
400
600

See page 11-51 for unit space adders and compatibility with other options.

(Devices mounted and wired to the trim should also have hinged trim specified)

Copper MLO Only

Main Bus Amps			
125	250	400	600

Bus mounted SPD See Section 10

Service Entrance Label

Type P2 Panelboards are factory labeled suitable for use as service entrance equipment when NEC requirements are met. A panelboard cannot have more than six main disconnects, unless it is a lighting and appliance branch panelboard. Lighting and appliance branch panelboards are limited to two main disconnects. Factory installed and field installable Service Entrance Barrier kits are now available as required by UL67 (In COMPAS, you must select Service Entrance Required).

Grounding of Panelboards

Ground Bars except for brazed to box are shipped with the panel interior not factory mounted.

- Non-Insulated Equipment Ground Bar
- Copper Non-Insulated Ground Bar
- Al Insulated Equipment Ground Bar
- Cu Insulated Equipment Ground Bar
- Ground Bar Brazed to Box (Not recommended for painted or NEMA 3R enclosures)

Shunt Trip on Main or Branch

BL, BLH, HBL, NGB, HGB, LGB, NGB2, HGB2, LGB2, ED4, HED4, HHED6 uses 1" unit space for shunt trip. All others may be used on mains or subfeeds. See breaker section for list price adders.

Time Clocks

Time clocks may be mounted in a 23" enclosure to be cable connected to the panel. Sangamo, Tork or Paragon time clock can be supplied and mounted in panelboard cabinet. Adds 12" to panel height. Mounts in Sub-area.

Description
Time Clock (1 or 2-pole, single or double throw contacts; 3-pole, single throw) 277V maximum with plain dial
Astronomical dial
An omitting device
Reserve power or carryover
Space and mounting provisions only

① Accessories on 1" pole breakers (BL, BQD, ED) will take unit space.

Panelboards

Embedded Micro Metering Module (Type P2 Panelboard)


Selection

SEM3™ System configured in Panelboards

The Siemens SEM3 system can be configured for factory installation in branch circuit monitoring applications using the Siemens COMPAS configuration tool. This option can lower the installation time of the system for the installer while providing a factory warranted solution.

The SEM3 system can be factory installed in unit space in type P2, P4, & P5 Siemens panel boards and SB1, SB2, & SB3 type Siemens switchboards. Please note P1 and P3 configurations are not available at this time and the amount of unit space needed varies depending upon the application. Please note that lead time adders will apply and may vary depending upon the configuration of the system.

SEM3 for use in Siemens Panelboards



Type P2: Enclosure

- Available in a NEMA 1, 3R, or 12 rated enclosure.
- Minimum width & depth: 24" width x 5.75" depth
- Height: Up to 74" depending on branch breaker selection
 - Addition of monitoring on some mains (primary and subfeed) may require additional box length. In these cases the box will be increased to the next size available as a standard design.
 - In cases where enclosure size is increased all multi-section panels will be increased to match the largest section.



Controller

SEM3 controller is mounted in unit space opposite of the feed location specified in COMPAS (i.e., bottom mount for top feed) and will require 3" of unit space. Each controller will be powered by direct tap connection to the panel section bus. Each controller can monitor up to 45 circuits. Applications that require monitoring more than 45 circuits will require additional controllers.



Current Transformers (CTs)

Five sizes of CTs are available for use in the P2 panel: 50, 125, 250, 400 & 600 amp. All CTs are pre-mounted to a support bracket that attaches to the base rail of the interior of the panel board. Each bracket supports a maximum of 3 CTs and is designed for the breaker selected (brackets are not interchangeable between breaker frames). Each CT will be attached to a data module that is placed in the meter racks.



Meter Racks

Each meter rack requires 3" of unit space. All meter racks will be installed next to the SEM3 controller in unit space. The COMPAS configuration tool will select the appropriate meter rack configuration according to the user's application and will use the 21 space meter rack as a default option where possible. Only one meter rack (regardless of number of positions) can be installed in 3" of unit space.

NOTE: Monitoring of 45 circuits will require 9" of unit space: two 21 position racks and one 3 position rack

Panelboards

Embedded Micro Metering Module (Type P2 Panelboard)

Selection


PANELBOARDS
11

P2 Devices Enclosure sizes

Example P2 Panel with SEM3 Type 1 Enclosure (24" Wide x 5.75" Deep)

Enclosure heights are in 6" increments from 26" thru 74".
Enclosure heights: 26", 32", 38", 44", 50", 56", 62", 68", 74"

The COMPAS configuration tool can provide actual dimensions based on the configuration.
Example below is largest standard P2 enclosure for factory assembled panel with all small (1") branch breakers installed.



**Main Breaker / Main Lug space
varies based on selected options**

Unit space varies
based on selected options

Note: All circuits do not have to be monitored by SEM3 - user can select any circuits in this space to be monitored.

Based on smallest branch breakers and a 3-phase main being monitored. There is a maximum of 63 circuits that can be monitored with the configuration shown. Some selections of main breakers and other subfeed options could limit this further.

In this situation there is 30" of unit space available - so 60 branch circuits could be monitored. If monitoring the main three additional circuits could be monitored with a total of 63 circuits.

This requires two controllers and three 21 position racks using 15" of unit space. - see below -

SEM3 space varies by number of circuits monitored - this uses unit space.

- == > 6" of space for up to 21 circuits monitored one controller and one 21-pos rack
- == > 9" of space for up to 42 circuits monitored one controller and two 21-pos racks
- == > 12" of space for up to 45 circuits monitored one controller and two 21-pos racks plus one 3-pos rack
- == > 15" of space for up to 63 circuits monitored two controllers and three 21-pos racks

Note: If subfeed space is needed - it will take away from available unit space.

Panelboards

Type P2 Panelboard Standard Modifications and Additions

Selection

Box Size Additions for Optional Features

Options	Main Lugs				Main Breakers											
	125A	250A	400A	600A	125A Horiz. BL, BQD, ED, xGB	125A Horiz. CED	125A Vert. ED	225A Horiz. QR	225A Vert. QR	225A Horiz. FD	250A Vert. FD	250A Vert. CFD	400A Vert. JD	400A Vert. CJD	600A Vert. LD	600A Vert. CLD
*Min. Box Size	26"	32"	38"	38"	26"	32"	32"	32"	38"	38"	44"	50"	50"	62"	56"	62"
200% Neutral (lug type)	0	0	6 (all)	6 (all)	0	0	0	N/A	0	N/A	0	0	0	0	0	0
Std. Lugs (100% Neut. PNL)	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
CU Lugs (100% Neut. PNL)	6	6	6	0	N/A	N/A	0	N/A	0	N/A	0	0	0	0	0	0
Comp Lugs (100% Neut. PNL)	6	6	6	6	N/A	N/A	0	N/A	0	N/A	0	0	0	0	0	0
Feed-thru Standard Lugs	6	6	12	12	6	6	6	N/A	6	N/A	6	6	12	12	12	12
Feed-thru Cu Lugs	6	6	12	N/A	N/A	N/A	6	N/A	6	N/A	6	6	12	12	N/A	N/A
Feed-thru Comp Lugs	6	12	12	N/A	N/A	N/A	6	N/A	6	N/A	12	12	12	12	N/A	N/A
Subfeed Standard Lugs	0	6	6	N/A	—	—	—	—	—	—	—	—	N/A	—	—	—
Split Bus	6	6	6	6	6	6	6	N/A	6	N/A	6	6	6	6	6	6
(1) FD Subfeed (Horizontal Mtg.)	N/A	12	12	12	N/A	N/A	N/A	N/A	N/A	12	12	12	12	12	12	12
(2) FD Subfeed (Vertical Mtg.)	N/A	24	24	24	N/A	N/A	N/A	N/A	N/A	24	24	24	24	N/A	N/A	N/A
SPD	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12	12

Split bus is paired with feed-thru lugs by default. Feed-thru lugs are to feed the section after the split.

NOTE: N/A = OPTION NOT AVAILABLE

*Min. Box Size, corresponding to 9" of Unit Space.

Compression Lugs (Aluminum body except where not Al)

Style	Amp Rating	Breaker Type	Compression Connectors	Box Height Addition
MLO	125	N/A	(1)#6 - 350 kcmil Al/Cu	6
	250	N/A	(1)#6 - 350 kcmil Al/Cu	6
	400	N/A	(1) 400-600 Kcmil AL or (1) 400-500 Kcmil CU or (2) #6 - 350 Kcmil Al/Cu	6
	600	N/A	(2)#6 - 350 kcmil Cu or Cu/Al or 400 - 600 kcmil Al/Cu	6
Main Breaker	100	ED4, ED6, HED4 HHED6, CED6 ^①	(1)#14-2/0 AWG Cu or Al	Box must go to 24" wide on CED6 breaker only Add 6" to box height for NØ
	225	QR2, QRH2, HQR2, HQR2H	(1)#6 AWG - 350 kcmil Cu or Al	Box must go to 24" wide
	250	FXD6, HFD6, CFD6	(1)#6 AWG - 350 kcmil Cu or Al	Box must go to 24" wide for all breakers Requires an additional 6.0" box height
	400	JD6, JXD6, HJD6, CJD6, SJD6, SHJD6, SCJD6	(2)#1/0 AWG - 500 kcmil Cu or Al	9
	600	LD6, LXD6, HLD6, CJD6, SLD6, SHLD6, SCLD6	(2)#2/0 AWG - 500 kcmil Cu or Al	6

Alternate Lugs

Style	Amp Rating	Breaker Type	Standard AL Connectors	Box Height Addition
MLO	400	N/A	(1) 250 - 750 kcmil or (2)#3/0 AWG - 250 kcmil Cu or Al	6
Main Breaker	400	JD6, JXD6, HJD6, CJD6, SJD6, SHJD6, SCJD6	(1)#4/0 AWG - 750 kcmil Cu or Al	6

① Not available for feed thru lug.

Panelboards

Type P2 Panelboard Connector Modifications

Selection

Enclosure Modifications

Description
20" Panel Width NEMA 3R enclosures NEMA 3R/12 enclosures Gasket between trim and box (Type 1)
24" Panel Width NEMA 3R enclosures NEMA 3R/12 enclosures ^① Gasket between trim and box (Type 1)

NEMA-4—Water Tight, Dust Tight, Steel Enclosure[®] (Actual NEMA-4 enclosure is larger than standard Type 1 enclosure. See chart below for reference to approximate actual size.)

Standard Box Height (in inches)	Actual NEMA 4 Enclosure Size ^②		
	H	W	D
32	32	20	8
38	42	30	8
44	48	36	8
56	60	36	10

NOTE: Larger NEMA 4 enclosures are not available.

NEMA-4X—Water Tight, Dust Tight and Corrosion Resistant^③
(consult plant for actual enclosure size)

Catalog Number	Enclosure – Stainless Steel Size (inches) (304SS is standard)			Enclosure – Fiberglass Size (inches)		
	H	W	D	H	D	W
B4X26	26	20	5.75	36	30	8
B4X32	32	20	5.75	36	30	8
B4X38	38	20	5.75	48	36	12
B4X44	44	20	5.75	48	36	12
B4X50	50	20	5.75	60	36	12
B4X56	56	20	5.75	60	36	12
B4X62	62	20	5.75			
B4X68	68	20	5.75			
B4X74	74	20	5.75			

NOTE: 316SS is available as an option - must be specified.

① 16 Gauge Cans w/ 14 Gauge Front)

② 14 Gauge only

③ 14 Gauge only - 304SS Std., 316SS Optional)

Gauge Steel of Boxes/Fronts, Surface and Flush (see pgs. 11-6 & 11-7)

Dimensions in Inches (mm)		Gauge Steel		
H	W	Box	Front/Door	Type
26-74 (660-1880)	20 (508)	16 ^①	14 ^②	Type 1
26-74 (660-1880)	20 (508)	16 ^②	16/14 ^②	Type 3R/12
32-60 (813-1524)	20-36 (508-914)	14 ^③	14 ^③	Type 4
26-74 (660-1879)	20 (508)	14 ^④	14 ^④	Type 4X
36-60 (914-1524)	30-36 (762-914)	N/A ^⑤	N/A ^⑤	Type 4X Non-Metallic

① 16 Gauge is Standard (14 Gauge & 12 Gauge are optional)

② 15 Gauge Steel Can with 14 Gauge Door or Similar Approved Construction

③ No Optional Gauge available

④ 304SS 14 Gauge Std., 316SS 14 Gauge optional

⑤ Sizes do not match Standard Enclosure Sizes - See Table P1-21 - material is non-metallic - No Gauge Specified.

⑥ FAS-Latch is 14 GA only.

Screw-to-Box, Hinge-to-Box, Door-in-Door (14 GA Std./12 GA Std. or 10 GA Optional)

STB/HTB/DND with Piano Hinge (14 GA Std./12 GA Optional) (14 GA Stainless 304 Optional)

Panelboards

Type P2 Panelboard Kits and Accessories

Selection

Standard Enclosures

Box Height Inches	Catalog Number				
	Type 1 Standard Trim			Type 3R	Type 3R/12 ①
	Box	Surface	Flush		
26	B26	S26B	F26B	NR26	WP26
32	B32	S32B	F32B	NR32	WP32
38	B38	S38B	F38B	NR38	WP38
44	B44	S44B	F44B	NR44	WP44
50	B50	S50B	F50B	NR50	WP50
56	B56	S56B	F56B	NR56	WP56
62	B62	S62B	F62B	NR62	WP62
68	B68	S68B	F68B	NR68	WP68
74	B74	S74B	F74B	NR74	WP74

① Same as Type 3R with Gasket added for Type 12 Spec.

Options For Type 1 Trims

Items must be ordered as manual line item on Spartanburg

- Hinged trim – Replace “B” suffix with “H”
- Door-in-door – Replace “B” suffix with “D”
- Screw to Box - Replace “B” suffix with “C”
- Metal card holder - Add “M” suffix on all trims
- Stainless Steel – 304 Stainless only with piano hinge

Option For 24" Wide Enclosures with Equal Gutter on Both Sides (Excludes NEMA 3R)

- 24" wide with equal gutter on both sides - Add “24” as prefix

Breaker Kits and Accessories

Kit Number	Description	Contents
BBKB32 (P2/P3)	BL/BQD 6-pole 3" branch breaker kit	Kit contains top barrier, (3) A/C connectors, (1) B connector, hardware
BBKED32 (P2/P3)	ED 6-pole 3" branch breaker kit	Kit contains breaker support, inter-phase barriers, (3) A/C connectors, (1) B connector, hardware
BBKNB32 (P2/P3)	xGB 6-pole 3" branch breaker kit	Kit contains top barrier, (3) A/C connectors, (1) B connector, hardware
BBKGB32 (P2/P3)	xGB2 6-pole 3" branch breaker kit	Kit contains top barrier, (3) A/C connectors, (1) B connector, hardware
BBKQ1 (P2)	QJ branch breaker kit for 2 and 3-pole single mount	Kit to contain all connectors and cover plates necessary to mount both 2 and 3-pole QJ breakers
BBKQR1 (P2)①	P2 branch BKR strap kit for single QR 1-phase/3-phase.	Kit to contain all connectors and cover plates necessary to mount both 2 and 3-pole breakers
DFK1 (P2)	BL, BQD, ED deadfront kit for 1" pole breakers	Center strips 3", 6", 9", 12", 15", 18", 21" plus mounting hardware
DFFP3	Deadfront filler 3"	3" empty space filler and hardware
DFFP6	Deadfront filler 6"	6" empty space filler and hardware
BNK2	Branch neutral (P2)	Three tier lug with mounting hardware to increase neutral capacity
P2BK1	P2 250A max. Bonding Kit	Bonding strap and hardware
P2BK2	P2 400A max. Bonding Kit	Bonding strap and hardware
P2BK3	P2 600A max. Bonding Kit	Bonding strap and hardware
BBKQRP1FK	P2 Filler for QR. Horizontal or vertical mount. 1-phase/3-phase.	Kit contains all cover plates necessary to change from QJ to QR both 2 and 3-pole breakers.
SEBKP2V1③	BL, BQD Main Service Entrance Barrier (P2 only)	Kit contains barrier, mounting brackets, and hardware
SEBKP2V2③	xGB Main Service Entrance Barrier (P2 only)	Kit contains barrier, mounting brackets, and hardware
SEBKP2V3③	FD, QJ, QR Horizontal Main Service Entrance Barrier (P2, P2 with SEM3, P3)	Kit contains barrier, mounting brackets, and hardware
SEBKP2V4③	FD, QJ, QR Vertical Main Service Entrance Barrier (P2, P2 with SEM3)	Kit contains barrier, mounting brackets, and hardware
SEBKP2V5③	ED Horizontal Main Service Entrance Barrier (P2, P2 with SEM3)	Kit contains barrier, mounting brackets, and hardware
SEBKP2V6②③	ED Vertical Main Service Entrance Barrier (P2, P2 with SEM3)	Kit contains barrier, mounting brackets, and hardware
SEBKP1P2P3V1③	JD, LD Service Entrance Barrier Kit (RP1, P1, P2, P3)	Kit contains barrier, mounting brackets, and hardware

① Although QR is rated 250A, it is limited to 225A in panelboard.

② Two kits required for P2 Extended circuit Panels

③ Factory installed and Field installable Service Entrance Barrier kits are now available as required by UL67. (In COMPAS, you must select Service Entrance Required.)

Type P1, P2, and P3 Panelboards

Miscellaneous Parts and Accessories

Catalog No.	Description	Catalog No.	Description
EGK	Al Ground Bus 44 Connections	NBK6	Number Strips 86-168 (snap-in type, P2/P3 panels)
P2BK1	P2 250A Max Horiz. Main Breaker	NBK7	Number Strips 169-210 (snap-in type, P2/P3 panels)
P2BK2	P2 125A Main Lug Bonding Kit	NBK8	Number Strips 211-252 (snap-in type, P2/P3 panels)
P2BK3	P2 250-600A Main Lug and all Vert. Main Breaker Bonding Kit	ECGK	Cu Ground Bus 44 Connections
IMK1	Interior Adjusting Kit	IGK	Insulated Al Ground Bus
LPDC01	Directory Card (Pack of 10; ref. 12-1110-01)	ICGK	Insulated Cu Ground Bus
LPDC02	Directory Card Holder (Pack of 10; ref. 11-1824-01)	EWK1	End Wall Kit with Knockouts (20" W x 5.75" DP)
ANSI/NEMA PB 1.1-2013	General Instructions for Proper Installation, Operation, and Maintenance of Panelboards Rated 600 V or Less (O&M Manual)①	EWK2	End Wall Kit with Knockouts (24" W x 7.75" DP)
NBK3	Number Strips 1-42 (snap-in type, P2/P3 panels)	DFFP1	1" Filler Plate – (used for BL/BQD/xGB/xGB2/ED blank positions) (suitable for replacing QF3 in P1 thru P5 Panelboards and Switchboards)
NBK4	Number Strips 43-84 (snap-in type, P2/P3 panels)	EBF1	NEB/HEB Filler Plate
NBK5	Number Strips 85-126 (snap-in type, P2/P3 panels)		

① PDF can be downloaded (at no cost) and printed at this location: <http://www.nema.org/standards/pages/Panelboards.aspx>


Panelboards

Type P2 Panelboards


Dimensions

Type 1 Box

Box is symmetrical




(UL approved construction. 16 Gage Steel or equivalent alternate Construction.
14 or 12 Gage is available as an optional special order.)
A60 Galvannealed is standard without paint.



Flush Mounting

Type 3R and 3R/12 Box



① Dimensions are interior of the box. Add 5/8" to width for absolute dimension. Add 1/8" to height for absolute dimension.

Dimensions shown in inches and millimeters [].

(UL approved construction. 16 Gage Steel Can with
14 Gage front or similar approved construction.)
A60 Galvannealed with ANSI 61 light gray paint is standard.

Panelboards

Type P3 Panelboards

General

Features

Another innovation from Siemens is the P3 panel. It is a smaller, footprint distribution panel to fit a large number of applications that require more (or larger) branch devices than the lighting panel class offer. This panel offers a wide array of factory-assembled options, and has the ability to mix breaker frames in unit space up to 250 amps. Bussing options for the P3 vary from the standard temperature aluminum to temperature rated copper, 750 A/Si aluminum, and 1000A/Si copper designs. All bussing in the P3 panel is tin-plated as a standard. Silver-plated copper is offered as an option on a copper bus. Integrated time clocks, bus mounted contactors, as mains or sub mains, split bus and subfeed lugs (up to 400 amp) are just a few of the options of this unique panel.

The P3 panel configurations, defined by the unit space, allow for a given amperage, main device, and box height. The P3 panel starts with a 56" high box. Breaker unit space can be mixed and matched to meet customer requirements. All 1" pole breakers (BL, BQD, xGB, xGB2, ED frames) are mounted in 3" or 6" pole increments. Breakers frames, above 125 amps, are mounted in 6" single or twin breaker mountings. QR (225A max) and 3VA52 (250A max) breakers are twin mounted in 6" unit space. A max of 6 total large frame breakers are allowed in unit space. Any subfeed breakers do not reduce this. For example, FD 250 amp and JD 400 amp breakers are mounted as subfeed breakers outside of unit space.

Like other distribution panels, the P3 panel can have blank space added into the panel to allow for future expansions or modifications. Any expansions or modifications must be in 3" increments. BL, BQD, xGB, xGB2, and ED frame breakers have 3" or 6-pole kits and can be mixed in unit space by these increments. Breakers of the same frame can cross from one mounting to another if contiguous. xGB frame breakers cannot be mixed with other frame types. Any expansion or modification must be in 3" increments also. QR frame breakers are mounted in 6" increments for two and three pole single and twin mounted units. Changes in the unit space length for BL, BQD, xGB, xGB2, or ED frame breakers require an additional deadfront center strip kit. Check with sales or the factory for additional unit space kits.

Main Lug/Main Breaker

Enclosure – Standard Type 1 enclosure is 24" wide x 7.75" deep. X Box Height is determined by main device and unit space. See charts for box height.

Voltage – 600V AC max.
250V DC max.

Amperage – 800 amp max.

Short Circuit Rating – 200 Kaic max. symmetrical or equal to the lowest rated device installed unless a series rating is indicated. Panels with subfeed or feed-thru lugs without a main device, circuit breaker or fusible unit, are limited to a three-cycle rating. The three-cycle rating for the P3 panel is limited to 22 Kaic. Note that the main device may be mounted remote from the panel.

Bussing – The P3 panel has more options to meet market requirements. The standard bussing is temperature rated aluminum. The rating is per the requirements of UL 67 – the standard for panelboards. All aluminum bussing is tin-plated. Optional bussing for the P3 panel is: 750 A/si aluminum, temperature rated copper, and 1000 A/si copper. The copper bus option for this panel is tin-plated.

Weight – Approximate

Total panelboard weight when filled with a normal quantity of breakers and accessories is about 5 lbs. (1 kg) per inch (54g per mm) of box height.

Gauge Steel of Boxes Fronts, Surface & Flush

Dimensions in inches (mm)		Gauge Steel	
Width	Height	Box	Front
24" (610)	56 - 80" (1422, 2032)	#16	#14

Panelboards

Type P3 Panelboards

Selection/Dimensions

Panel Unit Space To Box Height Requirements

"B" Dimension Box Height	P3 Panels With Standard Line Lugs. Unit Space (starting with 9" and adding 6" increments) "A" Dimension										
	Main Lugs				Main Breakers						
	250A	400A	600A	800A	250A Horiz. FD	250A Vert. FD	250A Vert. CFD	400A Vert. JD	400A Vert. CJD	600A Vert. LD	600A Vert. CLD
56	27	21	21	21	21	15	9	9	—	9	—
62	33	27	27	27	27	21	15	15	9	15	9
68	39	33	33	33	33	27	21	21	15	21	15
74	45	39	39	39	39	33	27	27	21	27	21
80	45	45	45	45	45	39	33	33	27	33	27

Main Breaker Wire Bending

Breaker Frame	C	E	F
FD Horiz.	7.25	—	20.13
FD Vert.	—	12.25	25.38
CFD	—	13.63	31.38
JD	—	15.63	29.38
CJD	—	14.75	35.38
LD	—	14.75	29.38
CLD	—	14.00	35.38


Main Lug Wire Bending

Panel Amps	Standard Connectors	C	D
250	(1) #6 AWG - 350 kcmil	10.75 ^①	13.50
400	(2) #3/0 AWG - 250 kcmil or (1) 600 kcmil	16.00	17.88
600	(2) #3/0 AWG - 500 kcmil	16.00	17.88
800 ^②	(2) 600 kcmil	16.00	17.88

① This lug is removable.


② CU wire Required for 800A with 2 cables. See Alternate Lugs page 11-47 for 3 cables CU or AL options.

Main Breaker Wire Bending Diagram



Main Breaker Wire Bending

Main Lug Wire Bending Diagram



Main Lug Wire Bending


Branch Breaker Side Gutters Inches (mm)

Reference Letter	Panel Width 24" (609)
A	7.750 (197)
B	7.125 (181)
C	6.000 (152)
D ^①	7.000 (178)
E	5.000 (127)
F	6.625 (168)
G	5.500 (140)

① Single branch mounting construction.

② BQD6 is not UL Listed. Only for CUL and CSA panels.

Branch Breaker Wire Bending Diagram



Branch Breaker Side Gutters

Panelboards

Type P3 Panelboards

Selection

Alternate Main Breakers

Ampere Rating	Breaker Type	Max. Interrupting Rating (kA)			Ref. Type Code	Horizontal or Vertical	Available Configurations ^②			Available Trip Values
		240V	480V	600V			240V AC	480V AC	600V AC	
250	FD6	65	35	18	FD	H/V	STD	STD	STD	70, 80, 90, 100, 110, 125, 150, 200, 225, 250
	FXD6	65	35	18	FX	H/V	STD	STD	STD	70, 80, 90, 100, 110, 125, 150, 200, 225, 250
	HFD6	100	65	25	HF	H/V	ADD	ADD	ADD	70, 80, 90, 100, 110, 125, 150, 200, 225, 250
	HFXD6	100	65	25	H2	H/V	ADD	ADD	ADD	70, 80, 90, 100, 110, 125, 150, 200, 225, 250
	CFD6 ^①	200	150	100	CF	V	ADD	ADD	ADD	70, 80, 90, 100, 110, 125, 150, 200, 225, 250
400	JXD6 ^①	65	35	25	JX	V	STD	STD	STD	200, 225, 250, 300, 350, 400
	JD6 ^①	65	35	25	J6	V	STD	STD	STD	200, 225, 250, 300, 350, 400
	HJXD6 ^①	100	65	35	H6	V	ADD	ADD	ADD	200, 225, 250, 300, 350, 400
	HJD6 ^①	100	65	35	H5	V	ADD	ADD	ADD	200, 225, 250, 300, 350, 400
	SJD6 ^①	65	35	25	SJ	V	ADD	ADD	ADD	200, 300, 400
	SHJD6 ^①	100	65	35	S2	V	ADD	ADD	ADD	200, 300, 400
	CJD6 ^①	200	200	100	CJ	V	ADD	ADD	ADD	200, 300, 400
	SCJD6 ^①	200	200	100	SC	V	ADD	ADD	ADD	200, 300, 400
600	LXD6 ^①	65	35	25	LX	V	STD	STD	STD	450, 500, 600
	LD6 ^①	65	35	25	L6	V	STD	STD	STD	250, 300, 350, 400, 450, 500, 600
	HLXD6 ^①	100	65	35	HL	V	ADD	ADD	ADD	250, 300, 350, 400, 450, 500, 600
	HLD6 ^①	100	65	35	HO	V	ADD	ADD	ADD	250, 300, 350, 400, 450, 500, 600
	SLD6 ^①	65	35	25	SL	V	ADD	ADD	ADD	300, 400, 500, 600
	SHLD6 ^①	100	65	35	S6	V	ADD	ADD	ADD	300, 400, 500, 600
	CLD6 ^①	200	150	100	CL	V	ADD	ADD	ADD	300, 400, 500, 600
	SCLD6	200	150	100	C6	V	ADD	ADD	ADD	300, 400, 500, 600

① Vertically mounted

② STD = Standard configuration. ADD = Additional cost.

Panelboards

Type P3 Panelboards

Selection

P3 Branch Circuit Breakers

P3 Branch Circuit Breakers																		S = Single Mount					
				1-Pole					2-Pole and 3-Pole										T = Twin mount				
Amp Rating	Trip Type	Breaker Family	Breaker Type	Max IR (kA) at				Amp Ratings Avail.	Max IR (kA) at								Amp Ratings Avail.	S	T	Unit Space per Kit (in.)	Max 1-pole Circuits per Kit		
				120V	277V	347V	125V DC		120/240V	240V	480Y/277V	480V	600Y/347V	600V	125/250V DC	250V DC							
100	Thermal Magnetic	BL	BL	10	—	—	—	15-70	10	10	—	—	—	—	—	—	15-100 ^④	—	T	3.00	6		
			BLH	22	—	—	—	15-70	22	22	—	—	—	—	—	—	15-100 ^④	—	T	3.00	6		
			HBL	65	—	—	—	15-50	65	65	—	—	—	—	—	—	15-100	—	T	3.00	6		
	Special Application	BLG BL	BLG ^①	10	—	—	—	15-20	10	—	—	—	—	—	—	—	30	—	T	3.00	6		
			BL (HID)	10	—	—	—	15-30	10	—	—	—	—	—	—	—	15-30	—	T	3.00	6		
	Thermal Magnetic	BQD	BQD ^⑥	65	14	—	14	15-100	—	65	14	—	—	—	14	—	15-100	—	T	3.00	6		
			BQD6 ^⑦	65	—	—	14	15-70	—	65	—	10	—	14	—	15-70	—	T	3.00	6			
xx	Electronic and misc.	BL	AFCI/GFCI & Dual Function	x	—	—	—	see special table page 11-13	x	—	—	—	—	—	—	—	see special table page 11-13	—	T	3.00	6		
125	Thermal Magnetic	GB	NGB	100	25	14	14	15-125	—	100	25	—	14	—	14	—	15-125	—	T	3.00	6		
			HGB	100	35	14	14	15-125	—	100	35	—	14	—	14	—	15-125	—	T	3.00	6		
			LGB	100	65	14	14	15-125	—	100	65	—	14	—	14	—	15-125	—	T	3.00	6		
		Sentron	ED4	—	22	—	30	15-100	—	65	—	18	—	—	—	30	15-125	—	T	3.00	6		
			ED6	—	—	—	—	—	—	65	—	25	—	18	—	30	20-125	—	T	3.00	6		
			HED4 ^②	—	—	—	—	—	—	65	—	18 ^②	—	—	—	30	15-125	—	T	3.00	6		
			HHED6	—	—	—	—	—	—	100	—	65	—	18	—	—	15-50	—	T	3.00	6		
		GB2	NGB2	100	25	14	14 ^④	15-125	—	100	—	25	14	—	14 ^⑤	—	15-125	—	T	3.00	6		
			HGB2	100	35	22	14 ^④	15-125	—	100	—	35	22	—	14 ^⑤	—	15-125	—	T	3.00	6		
			LGB2	100	65	25	14 ^④	15-125	—	100	—	65	25	—	14 ^⑤	—	15-125	—	T	3.00	6		
		3VA41 ^③	info not yet avail-able	x	x	x	x		x	x	x	—	x	—	—	x			—	T	3.00	6	
				x	x	x	x		x	x	x	—	x	—	—	x			—	T	3.00	6	
				x	x	x	x		x	x	x	—	x	—	—	x			—	T	3.00	6	
		225	Thermal Magnetic	QR	QR2	—	—	—	—	—	—	10	—	—	—	—	—	—	100-225	—	T	6.00	6
					QRH2	—	—	—	—	—	—	25	—	—	—	—	—	—	100-225	—	T	6.00	6
HQR2	—				—	—	—	—	—	65	—	—	—	—	—	—	100-225	—	T	6.00	6		
HQR2H	—				—	—	—	—	—	100	—	—	—	—	—	—	100-225	—	T	6.00	6		
250	Thermal Magnetic	3VA52 ^④ (W/TM230 trip)	MFAS	—	—	—	—	—	85	85	—	35	—	18	—	—	100-250	—	T	6.00	6		
			HFAS	—	—	—	—	—	—	100	100	—	65	—	25	—	—	100-250	—	T	6.00	6	
			CFAS	—	—	—	—	—	—	200	200	—	100	—	35	—	—	100-250	—	T	6.00	6	

Subfeed Breakers (available in 2-pole or 3-pole)

Breaker Type	Mounting Position When Used as Subfeed Breaker	Ampere Ratings For Load	Maximum Interrupting Rating (kA) Symmetrical		
			240V AC	480V AC	600V AC
FD6 ^⑥ , FXD6	Twin (Vertical)	70–250	65	35	18
HFD6 ^⑥ , HFXD6	Twin (Vertical)	70–250	100	65	25
JD6 ^⑥ , JXD6	Single (Horizontal)	200–400	65	35	25
HJD6 ^⑥ , HJXD6	Single (Horizontal)	200–400	100	65	35

Neutral Connectors

Wire Range	Max. Number of Connections	Max. Amps
#14-#1/0	44	125
#4 - 350 kcmil	6	250
(1)#4 - 600 kcmil or (2)#6 - 250 kcmil	1	400

① BLG two-pole breaker is one phase and neutral. Three pole is two phases and neutral - See SpeedFax page 7-31
 ② 1-pole HED 15-30A rated 65kA; 35-100A rated 25kA; 3-pole HED rated 42kA
 ③ Availability and additional specs tbd, expected late 2019. (COMPAS may allow selection of alternate trip units)

④ Twin Mount 3VA52 available 2018 with Thermal Magnetic Trip (TMTU), 3VA62 with Electronic Trip (ETU) availability tbd.
 ⑤ 2-pole only or two outer poles of 3-pole breaker
 ⑥ Approved for CSA and UL Listed.
 ⑦ Approved for CSA but not UL Listed.

⑧ Twin mounted subfeed breakers are mounted at bottom of panelboard only and adds 24" to the panel height.
 ⑨ Subfeed breaker is mounted at bottom of panelboard only. 400 amp subfeed breaker adds 30" to the panel height.

Panelboards

Type P3 Panelboards

Selection

Typical Catalog Numbers

Main Lugs Only – Examples of Panel numbers w/o options that add to box height.
– Shown with Aluminum bus, Top fed, and Surface Trims

Max. Panel Amp Rating	Max. Unit Space (inches)	120/240V 1-Phase, 3-Wire	208Y/120V 3-Phase, 4-Wire	240/120V Delta 3Ø4W BØ High Leg	Box Height Inches
		Catalog Number	Catalog Number	Catalog Number	
250	27	P3A56ML250ATS	P3C56ML250ATS	P3B56ML250ATS	56
	33	P3A62ML250ATS	P3C62ML250ATS	P3B62ML250ATS	62
	39	P3A68ML250ATS	P3C68ML250ATS	P3B68ML250ATS	68
	45	P3A74ML250ATS	P3C74ML250ATS	P3B74ML250ATS	74
	45	P3A80ML250ATS	P3C80ML250ATS	P3B80ML250ATS	80
400	21	P3A56ML400ATS	P3C56ML400ATS	P3B56ML400ATS	56
	27	P3A62ML400ATS	P3C62ML400ATS	P3B62ML400ATS	62
	33	P3A68ML400ATS	P3C68ML400ATS	P3B68ML400ATS	68
	39	P3A74ML400ATS	P3C74ML400ATS	P3B74ML400ATS	74
	45	P3A80ML400ATS	P3C80ML400ATS	P3B80ML400ATS	80
600	21	P3A56ML600ATS	P3C56ML600ATS	P3B56ML600ATS	56
	27	P3A62ML600ATS	P3C62ML600ATS	P3B62ML600ATS	62
	33	P3A68ML600ATS	P3C68ML600ATS	P3B68ML600ATS	68
	39	P3A74ML600ATS	P3C74ML600ATS	P3B74ML600ATS	74
	45	P3A80ML600ATS	P3C80ML600ATS	P3B80ML600ATS	80
800	21	P3A56ML800ATS	P3C56ML800ATS	P3B56ML800ATS	56
	27	P3A62ML800ATS	P3C62ML800ATS	P3B62ML800ATS	62
	33	P3A68ML800ATS	P3C68ML800ATS	P3B68ML800ATS	68
	39	P3A74ML800ATS	P3C74ML800ATS	P3B74ML800ATS	74
	45	P3A80ML800ATS	P3C80ML800ATS	P3B80ML800ATS	80

Max. Panel Amp Rating	Max. Unit Space (inches)	480V Delta 3-Phase, 3-Wire	240V Delta 3-Phase, 3-Wire	480Y/277V 3-Phase, 4-Wire	Box Height Inches
		Catalog Number	Catalog Number	Catalog Number	
250	27	P3F56ML250ATS	P3D56ML250ATS	P3E56ML250ATS	56
	33	P3F62ML250ATS	P3D62ML250ATS	P3E62ML250ATS	62
	39	P3F68ML250ATS	P3D68ML250ATS	P3E68ML250ATS	68
	45	P3F74ML250ATS	P3D74ML250ATS	P3E74ML250ATS	74
	45	P3F80ML250ATS	P3D80ML250ATS	P3E80ML250ATS	80
400	21	P3F56ML400ATS	P3D56ML400ATS	P3E56ML400ATS	56
	27	P3F62ML400ATS	P3D62ML400ATS	P3E62ML400ATS	62
	33	P3F68ML400ATS	P3D68ML400ATS	P3E68ML400ATS	68
	39	P3F74ML400ATS	P3D74ML400ATS	P3E74ML400ATS	74
	45	P3F80ML400ATS	P3D80ML400ATS	P3E80ML400ATS	80
600	21	P3F56ML600ATS	P3D56ML600ATS	P3E56ML600ATS	56
	27	P3F62ML600ATS	P3D62ML600ATS	P3E62ML600ATS	62
	33	P3F68ML600ATS	P3D68ML600ATS	P3E68ML600ATS	68
	39	P3F74ML600ATS	P3D74ML600ATS	P3E74ML600ATS	74
	45	P3F80ML600ATS	P3D80ML600ATS	P3E80ML600ATS	80
800	21	P3F56ML800ATS	P3D56ML800ATS	P3E56ML800ATS	56
	27	P3F62ML800ATS	P3D62ML800ATS	P3E62ML800ATS	62
	33	P3F68ML800ATS	P3D68ML800ATS	P3E68ML800ATS	68
	39	P3F74ML800ATS	P3D74ML800ATS	P3E74ML800ATS	74
	45	P3F80ML800ATS	P3D80ML800ATS	P3E80ML800ATS	80

General Note: Panel numbers and box sizes are for reference only - COMPAS will configure proper Box size needed.

Panelboards

Type P3 Panelboards

Selection

Typical Catalog Numbers

Main Circuit Breaker – Examples of Panel numbers w/o options that add to box height.
– Shown with Aluminum bus, Top fed, and Surface Trims

Max. Panel Amp Rating	Max. Unit Space (inches)	120/240V 1-Phase, 3-Wire	208Y/120V 3-Phase, 4-Wire	240/120V Delta 3Ø4W BØ High Leg	Box Height Inches
		Catalog Number	Catalog Number	Catalog Number	
250 ^①	21	P3A56FD250ATS	P3B56FD250ATS	P3C56FD250ATS	56
	27	P3A62FD250ATS	P3B62FD250ATS	P3C62FD250ATS	62
	33	P3A68FD250ATS	P3B68FD250ATS	P3C68FD250ATS	68
	39	P3A74FD250ATS	P3B74FD250ATS	P3C74FD250ATS	74
	45	P3A80FD250ATS	P3B80FD250ATS	P3C80FD250ATS	80
400 ^②	9	P3A56JD400ATS	P3B56JD400ATS	P3C56JD400ATS	56
	15	P3A62JD400ATS	P3B62JD400ATS	P3C62JD400ATS	62
	21	P3A68JD400ATS	P3B68JD400ATS	P3C68JD400ATS	68
	27	P3A74JD400ATS	P3B74JD400ATS	P3C74JD400ATS	74
	33	P3A80JD400ATS	P3B80JD400ATS	P3C80JD400ATS	80
600 ^③	9	P3A56LD600ATS	P3B56LD600ATS	P3C56LD600ATS	56
	15	P3A62LD600ATS	P3B62LD600ATS	P3C62LD600ATS	62
	21	P3A68LD600ATS	P3B68LD600ATS	P3C68LD600ATS	68
	27	P3A74LD600ATS	P3B74LD600ATS	P3C74LD600ATS	74
	33	P3A80LD600ATS	P3B80LD600ATS	P3C80LD600ATS	80

Max. Panel Amp Rating	Max. Unit Space (inches)	480V Delta 3-Phase, 3-Wire	240V Delta 3-Phase, 3-Wire	480Y/277V 3-Phase, 4-Wire	Box Height Inches
		Catalog Number	Catalog Number	Catalog Number	
250 ^①	21	P3F56FD250ATS	P3D56FD250ATS	P3E56FD250ATS	56
	27	P3F62FD250ATS	P3D62FD250ATS	P3E62FD250ATS	62
	33	P3F68FD250ATS	P3D68FD250ATS	P3E68FD250ATS	68
	39	P3F74FD250ATS	P3D74FD250ATS	P3E74FD250ATS	74
	45	P3F80FD250ATS	P3D80FD250ATS	P3E80FD250ATS	80
400 ^②	9	P3F56JD400ATS	P3D56JD400ATS	P3E56JD400ATS	56
	15	P3F62JD400ATS	P3D62JD400ATS	P3E62JD400ATS	62
	21	P3F68JD400ATS	P3D68JD400ATS	P3E68JD400ATS	68
	27	P3F74JD400ATS	P3D74JD400ATS	P3E74JD400ATS	74
	33	P3F80JD400ATS	P3D80JD400ATS	P3E80JD400ATS	80
600 ^③	9	P3F56LD600ATS	P3D56LD600ATS	P3E56LD600ATS	56
	15	P3F62LD600ATS	P3D62LD600ATS	P3E62LD600ATS	62
	21	P3F68LD600ATS	P3D68LD600ATS	P3E68LD600ATS	68
	27	P3F74LD600ATS	P3D74LD600ATS	P3E74LD600ATS	74
	33	P3F80LD600ATS	P3D80LD600ATS	P3E80LD600ATS	80

General Note: Panel numbers and box sizes are for reference only - COMPAS will configure proper Box size needed.

① 250A: for Vert. FD subtract 6" of unit space; for CFD subtract 12" of unit space

② 400A: for CJD box height 56 does not exist, subtract 6" from unit space for all others

③ 600A: for CLD box height 56 does not exist, subtract 6" from unit space for all others

Panelboards

Type P3 Panelboard Modifications and Additions

Selection

Enclosures

Extra Gutter to Sides or Ends of the Can (Type 1 Only)

Description
6" end gutter 2" side gutter Barrier in gutter (add to extra gutter price – min 4" required)
Hinged trims Piano hinged trims Door-in-door trims Screw to the box trims
Trim mounted devices See page 11-119 • Pilot lights • Toggle switches • Push buttons
Painted boxes See page 11-119 Custom colors See painted boxes
Increase gauge trims and boxes See page 11-119 Stainless steel trims, Type 1 See page 11-119

Meters

(Contact sales for pricing and application engineering for space requirements)

Panel Skirts

See page 11-120

Special Locks (see page 11-38)

TEY TEU1 Cat 60 LL803 LL806 Yale 47 (NYC) National C413A Best Lock 7-pin tumbler Southco 1/4" Fastener Corbin 1001 FAB7
--

Panel Bus Modifications

Main Bus	Catalog Number Addition Amperes Ratings			
	125A	250A	400A	600A
750 A/SI AL.	B	B	B	B
Copper (tin pltd.)	F	F	F	F
Copper (silver pltd.)	E	E	E	E
1000 A/SI Copper (tin pltd.)	G	G	G	G
1000 A/SI Copper (silver pltd.)	H	H	H	H

Subfeed, Feed-Thru and Split Bus (for 2-pole or 3-pole)

Ampere Rating	Connector Cu/Al Wire Range	Unit Space (inches)
---------------	-------------------------------	---------------------

Subfeed (Double) Lugs for Main Lug Panelboards Only (400 max)

225/250	(2)—#6 AWG-350 kcmil	6
400	(4)—250 kcmil (2)—600 kcmil	6

Feed-Thru Lugs — Cannot Be Used in Conjunction with TVSS or Subfeed Breakers

See page 11-62 for unit space adders and compatibility with other options.

225/250	(1)—#6 AWG-350 kcmil	6
400	(2)—250 kcmil (1)—600 kcmil	6
600	(2)—250-500 kcmil	9
800	(2)—600 kcmil	12

Split Bus (1 per interior)

225/250	(1)—#6 AWG-350 kcmil	6
400	(2)—250 kcmil (1)—600 kcmil	6
600	(2)—250-500 kcmil	6
800	(2)—600 kcmil	6

Branch and Main Breaker Accessories

See page 11-117 and Breaker Section • Handle blocks • Handle locks • Aux. Contacts[Ⓢ] • UVR[Ⓢ]

Increase capacity neutral up to 200%

Main Bus Amps
125
250
400
600

See page 11-62 for unit space adders and compatibility with other options.

Copper MLO Only

Main Bus Amps
125
250
400
600

(Devices mounted and wired to the trim should also have hinge-to-box trim specified)

Bus mounted SPD

See Section 10 for TPS1

Service Entrance Label

Type P3 Panelboards are factory labeled suitable for use as service entrance equipment when NEC requirements are met. A panelboard cannot have more than six main disconnects, unless it is a lighting and appliance branch panelboard. Lighting and appliance branch panelboards are limited to two main disconnects. Factory installed and field installable Service Entrance Barrier kits are now available as required by UL67 (In COMPAS, you must select Service Entrance Required).

Grounding of Panelboards

Ground Bars except for brazed to box are shipped with the panel interior not factory mounted.

- Non-Insulated Equipment Ground Bar
- Copper Non-Insulated Ground Bar
- Al Insulated Equipment Ground Bar
- Cu Insulated Equipment Ground Bar
- Ground Bar Brazed to Box (Not recommended for painted or NEMA 3R enclosures)

Shunt Trip on Main or Branch

BL, BLH, HBL, BQD, ED4, HED4, ED6, HHED6, QR2, QRH2, HQR2, HQR2H as branch only. BL, BLH, HBL, NGB, HGB, LGB, ED4, HED4, ED6, HHED6 uses 1" unit space for shunt trip. All others may be used on mains or subfeeds.

Time Clocks

Time clocks may be mounted in a 23" enclosure to be cable connected to the panel. Sangamo, Tork or Paragon time clock can be supplied and mounted in panelboard cabinet. Adds 12" to panel height. Mounts in Sub-area.

Description
Time Clock (1 or 2-pole, single or double throw contacts; 3-pole, single throw) 277V maximum with plain dial
Astronomical dial
An omitting device
Reserve power or carryover
Space and mounting provisions only

[Ⓢ] Accessories on 1" pole breakers (BL, BQD, ED) will take unit space.

Panelboards

Type P3 Panelboard Standard Modifications

Selection

Option Combinations

Amps	Incoming	Subfeed Lugs	Feed-thru Lugs	FD ^① Subfeed	JD ^① Subfeed	FD ^② Subfeeds	200% Neutral	Min. Box Size (in.)	Unit Space (in.)
250	Main Lug Only	—	• — —	— • —	— — —	— — •	• • •	56 56 56	27 15 9
	Main Lugs w/Subfeed Lugs	•	• — —	— • —	— — —	— — •	• • •	56 56 62	21 21 9
	Main Breaker (Horiz. FD)	—	• —	— •	— —	— —	• •	56 56	21 9
	Main Breaker (Vert. FD)	None Std.	• —	— •	— —	— —	• •	56 68	15 9 9
	Main Breaker (CFD)	None Std.	• —	— •	— —	— —	• •	56 68	9 9
400 ^{②③}	Main Lug Only	• — — — —	— • — — —	— — • — —	— — — • —	— — — — •	• • • • •	56 56 56 56 62	21 15 9 9 9
	Main Breaker (JD)	None Std.	— • — — —	— — • — —	— — — • —	— — — — •	• • • • •	56 62 68 68 74	9 9 9 9 9
	Main Breaker (CJD)	None Std.	— • — — —	— — • — —	— — — • —	— — — — •	• • • • •	62 74 74 74 80	9 9 9 9 9
	Main Lug Only	—	• — — — —	— — • — —	— — — • —	— — — — •	• • • — •	56 56 56 56 62	21 15 9 9 9
	Main Breaker LD	—	• — — — —	— — • — —	— — — • —	— — — — •	• • • — •	56 62 68 68 74	9 9 9 9 9
600 ^{②③}	Main Breaker CLD	—	• — — — —	— — • — —	— — — • —	— — — — •	• • • — •	62 68 74 74 80	9 9 9 9 9
	Main Lug Only	—	• — — — —	— — • — —	— — — • —	— — — — •	• • • — •	56 56 56 56 62	21 15 9 9 9
	Main Breaker LD	—	• — — — —	— — • — —	— — — • —	— — — — •	• • • — •	56 62 68 68 74	9 9 9 9 9
	Main Breaker CLD	—	• — — — —	— — • — —	— — — • —	— — — — •	• • • — •	62 68 74 74 80	9 9 9 9 9
	Main Lug Only	—	• — — — —	— — • — —	— — — • —	— — — — •	• • • — •	56 56 56 56 62	21 15 9 9 9
800 ^{②③}	Main Lug Only	—	• — — — —	— — • — —	— — — • —	— — — — •	• • • — •	56 56 56 56 62	21 15 9 9 9

① Subfed lugs are currently not offered as standard with main circuit breakers.

② Subfed lugs on panels above 400A are not standard.

③ 200% neutral cannot be provided along with a 400A subfeed breaker because the breaker blocks the 4th lug site.

Panelboards

Type P3 Panelboard Modifications and Additions

Selection

Compression Lugs

Style	Amp Rating	Breaker Type	Compression Connectors	Box Height Addition
MLO	250	N/A	(1)#6 AWG - 350 kcmil	—
	400	N/A	(1) 250 - 500 kcmil or (2)# 1/0 AWG - 250 kcmil	—
	600	N/A	(2)#3/0 AWG - 500 kcmil	—
	800	N/A	(2) 400-750 kcmil Cu only	—
Main Breaker	250	FXD6, HFD6, CFD6	(1)#6 AWG - 350 kcmil Cu or Al	CFD6 requires an additional 6.0" box height
	400	JD6, JXD6, HJD6, CJD6, SJD6, SHJD6, SCJD6	(2)#1/0 AWG - 500 kcmil Cu or Al	—
	600	LD6, LXD6, HLD6, CJD6, SLD6, SHLD6, SCLD6	(2)#2/0 AWG - 500 kcmil Cu or Al	—

Alternate Lugs

Style	Amp Rating	Breaker Type	Standard AL Connectors	Box Height Addition
MLO	400	N/A	(1) 250 - 750 kcmil or (2)#3/0 AWG - 250 kcmil Cu or Al	6
	800	N/A	(3)#4-500 Kcmil CU or Al capacity	6
Main Breaker	400	JD6, JXD6, HJD6, CJD6, SJD6, SHJD6, SCJD6	(1)#4/0 AWG - 750 kcmil Cu or Al	6

Enclosure Modifications

24" Panel Width Description
NEMA 3R enclosures
NEMA 3R/12 enclosures ^①
Gasket between trim and box (Type 1)

NEMA-4X For Type P3^③

Water Tight, Dust Tight and Corrosion Resistant
(consult plant for actual enclosure size and for NEMA 4^② enclosures)

Box Height Inches	Enclosure – Stainless Steel		
	H	W	D
56	56	24	7.75
62	62	24	7.75
68	68	24	7.75
74	74	24	7.75
80	80	24	7.75

① 16 Gauge Cans w/ 14 Gauge Front)

② 14 Gauge only

③ 14 Gauge only - 304SS Std, 316SS Optional)

Panelboards

Type P3 Panelboard Kits and Accessories

Selection

Standard Enclosures

Box Height (in.)	Catalog Number				
	Type 1 Standard Trim			Type 3R	Type 3R/12
	Box	Surface	Flush		
56	24WD56	P3S56	P3F56	24NRD56	24WPD56
62	24WD62	P3S62	P3F62	24NRD62	24WPD62
68	24WD68	P3S68	P3F68	24NRD68	24WPD68
74	24WD74	P3S74	P3F74	24NRD74	24WPD74
80	24WD80	P3S80	P3F80	24NRD80	24WPD80

Options For Type 1 Trims

Items must be ordered as manual line item on factory

Hinged trim – Add “H” suffix

Door-in-door – Add “D” suffix

Metal card holder – Add “M” suffix

Breaker Kits and Accessories

Kit Number	Description	Contents
BBKB32 (P2/P3)	BL/BQD 6-pole 3" branch breaker kit	Kit contains top barrier, (3) A/C connectors, (1) B connector, hardware
BBKNB32 (P2/P3)	NGB, HGB, LGB 6-pole 3" branch breaker kit	Kit contains top barrier, (3) A/C connectors, (1) B connector, hardware
BBKGB32 (P2/P3)	NGB2, HGB2, LGB2 6-pole 3" branch breaker kit	Kit contains top barrier, (3) A/C connectors, (1) B connector, hardware
BBKEB32 (P3)	NEB/HEB 6-pole 3" branch breaker kit	Kit contains top barrier, (3) A/C connectors, (1) B connector, hardware
BBKED32 (P2/P3)	ED 6-pole 3" branch breaker kit	Kit contains breaker support, inter-phase barriers, (3) A/C connectors, (1) B connector, hardware
BBKQ2 (P3)	Branch breaker kit for 2 and 3-pole QJ twin mount	Kit contains all connectors and cover plates necessary to mount both 2 and 3-pole breakers
BBKQR2 ^{①③}	P3 twin BKR mounting kit for QR 1-phase/3-phase	Kit contains all connectors and cover plates necessary to mount both 2 and 3-pole breakers (limit 6 QR per panel)
BBKVA52P3T ^②	P3 strap kit; twin mount 3VA52 branch	Uses 6" of unit space. Includes 2x BBKVA52P3HW, barrier, straps, & mounting hardware.
BBKA52P3HW	P3 branch breaker hardware kit	Includes screw retainers & mounting screws.
DFFP3	Deadfront filler 3"	3" empty space filler and hardware
DFFP6	Deadfront filler 6"	6" empty space filler and hardware
P3BK1	P3 bonding kit 800A max MLO+MB	Bonding strap and hardware. For all MLO+MB configurations.
EBF1	HEB/NEB Filler Plate	Filler Plate
BBKQRP2FK	P3 Filler for QR. Dual mount horizontal. 1-phase/3-phase.	Kit contains all cover plates necessary to change from QJ to QR both 2 and 3-pole breakers. For 1-phase panel, both breakers must change from QJ to QR, cannot have one of each installed.
SEBK3P3V1 ^②	Service entrance barrier kit CFD, FD (P3 only)	Kit contains barrier, mounting brackets, and hardware
SEBK1P2P3V1 ^②	JD, LD Service Entrance Barrier Kit (RP1, P1, P2, P3)	Kit contains barrier, mounting brackets, and hardware
SEBK2P3V3	FD, QJ, QR Horizontal Main Service Entrance Barrier (P2, P2 with SEM3, P3)	Kit contains barrier, mounting brackets, and hardware

① Although QR is rated 250A, it is limited to 225A in panelboard.

② Factory installed and Field installable Service Entrance Barrier kits are now available as required by UL67. (In COMPAS, you must select Service Entrance Required.)

③ Maximum 6 large frame breakers in unit space. (QR + 3VA52)

Type P1, P2, and P3 Panelboards

Miscellaneous Parts and Accessories

Catalog Number	Description
EGK	Al Ground Bus 44 Connections
BK1	Bonding kit for 250A max. and all P1 panels
IMK1	Interior Adjusting Kit
LPDC01	Directory Card (Pack of 10; ref. 12-1110-01)
LPDC02	Directory Card Holder (Pack of 10; ref. 11-1824-01)
NBK3	Number Strips 1-42. Snap-in type; Use w/P2 & P3 series Panels
NBK4	Number Strips 43-84. Snap-in type; Use w/P2 & P3 series Panels
NBK5	Number Strips 85-126. Snap-in type; Use w/P2 & P3 series Panels
NBK6	Number Strips 127-168. Snap-in type; Use w/P2 & P3 series Panels
NBK7	Number Strips 169-210. Snap-in type; Use w/P2 & P3 series Panels
NBK8	Number Strips 211-252. Snap-in type; Use w/P2 & P3 series Panels
ECGK	Cu Ground Bus 44 Connections
IGK	Insulated Al Ground Bus
ICGK	Insulated Cu Ground Bus
EWK2	End Wall Kit with Knockouts (24" W x 7.75" DP)
DFFP1	1" Filler Plate (used for BL/BQD/xGB/xGB2/ED blank positions) (Suitable for replacing QF3 in P1 thru P5 Panelboards and Switchboards)
ANSI/NEMA PB 1.1-2013	General Instructions for Proper Installation, Operation, and Maintenance of Panelboards Rated 600 Volts or Less (O&M Manual) ^①

① PDF can be downloaded (at no cost) and printed at this location: <http://www.nema.org/standards/pages/Panelboards.aspx>


Panelboards

Type P3 Panelboards

Dimensions


Type 1 Box

Box is symmetrical



(UL approved construction. 16 gage steel or equivalent alternate construction.
14 or 12 gage is available as an optional special order.)
G60 Galvanized is standard without paint.

Type 3R and 3R/12 Box



(UL approved construction. 16 gage steel can with
14 gage front or similar approved construction.)
A60 Galvannealed with ANSI 61 light gray paint is standard.

① Dimensions are interior of the box. Add 5/8" to width for absolute dimension. Add 1/8" to height for absolute dimension.
Dimensions shown in inches and millimeters [].

3VA Breaker Configuration Information in Panelboards

3VA breaker Accessories Information

Selection

Panelboard Specific 3VA Accessories Available in Panelboards

3VA Series Accessories

There are 4 positions on each side of the trip handle of the 3VA52 breaker. Accessories can be 1, 2 or 3 positions wide and fit in specific locations as shown on charts and on the inside cover of each breaker.

Accessory types:

3VA breaker auxiliary releases allow remote electrical tripping of the circuit breaker

- **STL** – Shunt Trip Left
- **STF** – Shunt Trip Flexible
- **UVR** – Undervoltage Releases Trip
- **UNI** – Universal Release - Shunt Trip and an Undervoltage Release are Combined

All Auxiliary and Alarm Switches for 3VA breakers belong to an integrated range of accessories

- **AUX_HQ / AUX_HP** – Auxiliary Switches
- **LCS_HQ / LCS_HP** – Leading Changeover Switches
- **TAS_HQ / TAS_HP** – Trip Alarm Switches
- **EAS_HQ / EAS_HP** – Electrical alarm switches

3VA Auxiliary and Alarm Switches have standard (HQ) and high capacity (HP) types as well as "electronic" versions for example: **AUX_HQ_el**


* Padlock accessory will be available in a future release.

3VA52 Breaker Features

3VA Internal Breaker Accessories configurations		Accessory Slots	
TMTU Thermal-Magnetic trip	Frame width	Amp range	
3VA41 - 1-pole	1p	15-125	0
3VA41 - 1-pole in 2p frame	2p	15-125	3
3VA41 - 2-pole			3
3VA41 - 3-pole	3p	15-125	6
3VA51 - 1-pole	1p	15-125	0
3VA51 - 1 pole in 2p frame	2p	15-125	3
3VA51 - 2 pole in 3p frame	3p	15-125	6
3VA51 - 3-pole			6
3VA51 - 3-pole MCS	3p	100	6
3VA52 - 2-pole in 3p frame	3p	100-250	8
3VA52 - 3-pole			8
3VA52 - 3-pole MCS	3p	100-250	8
3VA53 - 3-pole	3p	200-400	10
ETU - Electronic Trip*			
3VA61 - 3 pole	3p	16-150	8
3VA62 - 3-pole	3p	40-250	8
3VA63 - 3-pole	3p	100-400	10
3VA64 - 3-pole	3p	160-600	10

* 100% rated may have reduced ranges

3VA6 ETU only



3VA accessories install easily.
Special Hardware kit for P3 Twin Mount aligns screw for easy installation.

3VA Breaker Configuration Information in Panelboards


P1 Lighting Panel General information

Minimum enclosure size: 20" wide x 5.75" deep

P1 Lighting Panelboard

P1 interiors have unit space setup for either:

- A) BL/BQD type of breakers only
- or
- B) xGB and 3VA41 breakers only in same interior (no BL/BQD allowed)



P1 Lighting Panel

P1 Main Space can include:

Main Lugs: 250A or 400A max

Main Breaker Types:

- 100A max BL/BQD & 125A max. xGB or ED (horiz. mount)
 - 125A max. 3VA41 (TMTU) (horiz. mount)
 - 225A max. QR series (horizontal mount)
 - 250A max. 3VA52/62 (TMTU/ETU) (horiz. mount)
 - 250A max. FD series (horizontal mount)
 - 400A max. 3VA53/63 (TMTU/ETU) (vertical mount)
- (ETU = Electronic Trip Unit)
(TMTU = Thermal Magnetic Trip Unit)
- 400A max. JD series (vertical mount)

P1 Branch Breakers — Small Frame only:

- a) 100A max BL series
- b) 100A max BQD series
- c) 125A max xGB or 3VA41 series after 3/1/2020 (Cannot Mix with BL/BQD)

Note: always check dead front labels for allowed breakers

P1 Subfeed Space offering:

Feed-thru Lugs:

A) 250A or 400A

B) Surge Protection Devices (SPD)

C) Subfeed Breakers: (Horizontal only):

- 250A max. 3VA52 TMTU
- 250A max. 3VA61/62 ETU
- 250A max. FD
- 225A max. QR
- 100A max. BL/BQD
- 125A max. xGB/3VA41/ED

3VA Breaker Configuration Information in Panelboards

P2 Lighting Panel General information

Minimum enclosure size: 20" wide x 5.75" deep

P2 Lighting Panelboard

P2 interiors have flexible unit space setup for Multiple Branch Breaker Types and many different Main/Subfeed options.


Neutral Cross Strap
– positions for mounting Neutral lugs
– many different configurations are used.

Neutral Strips:
1/0 max. cable size
"Step lugs" and other varieties depending on the configuration
– factory assembled only
– optional field installable kits may be added in near future to include 2/0 capability.

Various Branch Breaker Strap Kits installed

Field installable Neutral Extension can be added for AFCI/GFCI when needed due to short pigtails. It can be positioned anywhere along the base rail on either side.
kit # **BNKP2EX1**

Bus Bars:
250A - CU or AL
400A - CU or AL
600A - CU or AL



P2 Lighting Panel

P2 Main Space can include:

Main Lugs: 125A, 250A, 400A or 600A
==> also Subfeed Lugs: 125A, 250A or 400A

Main Breaker Types:

- 100A max. BL/BQD or 125A max. xGB or ED
- 250A max. 3VA52/62 (TMTU/ETU) (horiz. mount)
- 250A max. FD series (horizontal mount)
- 400A max. 3VA53/63 (TMTU/ETU) (vertical mount)
- 400A max. JD series (vertical mount)
- 600A max. 3VA54/64 (TMTU/ETU) (vertical mount)
- 600A max. LD series (vertical mount)

(ETU = Electronic Trip Unit)

(TMTU = Thermal Magnetic Trip Unit)

P2 Branch Breakers — Small Frame:

- a) 100A max BL series
- b) 100A max BQD series
- c) Various AFCI/GFCI series
- d) 125A max ED series (480V delta capable)
- e) 125A max xGB series
- f) 125A max GB2 series (480V delta capable)
- g) 125A max. 3VA41 TMTU (480V delta capable)

P2 Branch Breakers — Large Frame (6 max.)

- 1) 225A max QR series (total 225A/250A frame, four per panel limit)
- 2) 150A max 3VA61 ETU single mount
- 3) 250A max 3VA52/62 TMTU/ETU single mount

Subfeed Space offering:

Feed-thru Lugs:

- A) 125A, 250A, 400A, or 600A
- B) Surge Protection Devices (SPD)

C Subfeed Breakers:

- 250A max. FD twin mount vertical
- 400A max. JD single mount vertical
- 400A max. 3VA53/63 (TMTU/ETU) (vertical single mount)


3VA Breaker Configuration Information in Panelboards

P3 Lighting Panel General information

Minimum enclosure size: 24" wide x 7.75" deep

P3 Lighting Panelboard

P3 interiors have flexible unit space setup for Multiple Branch Breaker Types and many different Main/Subfeed options.



P3 Lighting Panel

P3 Main Space can include:

Main Lugs: 250A, 400A, 600A or 800A
==> also Subfeed Lugs: 250A or 400A

Main Breaker Types:

- 250A max. 3VA52/62 (TMTU/ETU) (horizontal mount)
- 250A max. FD series (horizontal mount)
- 400A max. 3VA53/63 (TMTU/ETU) (vertical mount)
- 400A max. JD series (vertical mount)
- 600A max. 3VA54/64 (TMTU/ETU) (vertical mount)
- 600A max. LD series (vertical mount)

(ETU = Electronic Trip Unit)

(TMTU = Thermal Magnetic Trip Unit)

P3 Branch Breakers — Small Frame:

- a) 100A max BL series
- b) 100A max BQD series
- c) Various AFCI/GFCI series
- d) 125A max ED series (480V delta capable)
- e) 125A max xGB series
- f) 125A max GB2 series (480V delta capable)
- g) 125A max. 3VA41 TMTU (480V delta capable)

P3 Branch Breakers — Large Frame (6 max.)

- 1) 225A max QR series (twin mount)
- 2) 250A max 3VA52 Series (twin Mount) (total 225A/250A frame, 6 per panel limit)
- 3) 250A max 3VA62/3VA61 ETU single mount

New 3VA offering has many field installable accessories available.

P3 Subfeed Space offering:

Feed-thru Lugs:

A) 225A/250A, 400A, 600A or 800A

B) Surge Protection Devices (SPD)

C) Subfeed Breakers:

- 250A max. FD twin mount vertical
- 400A max. JD single mount vertical
- 250A max. 3VA52/62 (TMTU/ETU) (vertical twin mount)
- 400A max. 3VA53/63 (TMTU/ETU) (vertical single mount)


3VA Breaker Configuration Information in Panelboards

P4 Power Panel General information

Minimum enclosure size: 32" wide x 10" deep

P4 Power Panel

P4 interiors have unit space setup for Multiple Branch Breaker Types and many different Main Breaker options.



P4 Power Panel

P4 Main Space can include:

Main Lugs: 400A, 600A, 800A, 1000A or 1200A

Main Breaker Types: (horizontal mount)

- 100A max. BL/BQD or 125A max. xGB or ED
- 400A max. JD and VL-JG series
- 600A max. LD and VL-LG series
- 800A max. LM and VL-MG series

Future 3VA offering in development:

- 400A max. 3VA53/63 (TMTU/ETU)
- 600A max. 3VA54/64 (TMTU/ETU)
- 800A max. 3VA55/65 (TMTU/ETU)

(ETU = Electronic Trip Unit)

(TMTU = Thermal Magnetic Trip Unit)

P4 Branch Breakers — Small Frame:

- a) 100A max BL series (10, 22, 65 kaic @ 240V)
- b) 100A max BQD series (14 kaic @ 480/277V)
- c) Various AFCI/GFCI series
- d) 125A max ED series (480V delta capable)
- e) 125A max xGB seriesf) 125A max GB2 series (480V delta capable)
- g) 125A max. 3VA41 TMTU (480V delta capable)

P4 Branch Breakers — Large Frame (6 max.)

- 1) 150A max VL-DG series
- 2) 150A 3VA61 ETU Series
- 3) 225A max QR series
- 4) 250A max FD or VL-FG series
- 5) 250A max 3VA52/62 TMTU/ETU
- 6) 400A max JD and VL-JG series
- 7) 600A max. LD and VL-LG series
- 8) 800A max. MD and VL-MG series

Future 3VA offering in development:

- 9) 400A max. 3VA53/63 (TMTU/ETU)
- 10) 600A max. 3VA54/64 (TMTU/ETU)
- 11) 800A max. 3VA55/65 (TMTU/ETU)

New 3VA offerings have many field installable accessories available including strap kits.

(See Strap Kit Table page 11-92).

P4 Standard Box Width is 32" W


3VA Breaker Configuration Information in Panelboards

P5 Power Panel General information

Minimum enclosure size: 38" wide x 10" deep

P5 Power Panel

P5 interiors have unit space setup for Multiple Branch Breaker Types and many different Main Breaker options.



3VA Breaker Configuration Information in Panelboards

3VA Electronic Trip Units

Selection

3VA6 ETU – "Electronic Trip" versions of 3VA Breakers used in Panelboards

- See following pages for internal accessory pocket locations available in TMTU & ETU versions
- Standard part number shown for base trip unit - other variations available shown in lower chart
- Breakers shown do not include lugs - lugs are ordered separately as needed per application
- COMPAS will allow various Lug configurations based on Panel Type and mounting location

Connector Kits for 3 Pole 3VA6 series Breakers

For Accessories and positions see tables on pages 11-79 and 11-83

Description note: Use 3-pole for 2-pole applications	One Connector Kit required for each breaker when panel mounted.	Connector Kits	AL	CU
		3VA61/62	3VA9243-0JB12	3VA9243-0JD12
		3VA63	1-port version 3VA9373-0JB13 or 2-port version 3VA9473-0JJ23	1-port version 3VA9373-0JD13 or 2-port version 3VA9473-0JE23
		3VA64		

3 Pole 3VA6 series Breakers without connectors

Standard in COMPAS includes ETU350 LSI Trip (I _r and I _i are adjustable)			ETU350 LSI included	ETU350 LSI included	ETU350 LSI included	ETU350 LSI included	ETU350 LSI included
kA ratings @ 50/60 Hz			3-pole	3-pole	3-pole	3-pole	3-pole
240 VAC kAIC rating ==>			100	100	200	200	200
480Y / 277 VAC kAIC rating ==>			35	65	100	150	150
480 VAC kAIC rating ==>			35	65	100	150	150
600Y / 347 VAC kAIC rating ==>			18	22	35	50	50
600 VAC kAIC rating ==>			18	22	35	50	50
250 VDC kAIC rating ==>			na	na	na	na	na
amps	Adj. I _r	code					
3VA61			UL Type Code / MB code ==>	MDAE / W2	HDAE / W3	CDAE / W4	LDAE [®] / W5
40	16-40	40	3VA61 3P breaker w/trip	3VA6140-5HN31-0AA0	3VA6140-6HN31-0AA0	3VA6140-7HN31-0AA0	3VA6140-8HN31-0AA0
100	40-100	10	3VA61 3P breaker w/trip	3VA6110-5HN31-0AA0	3VA6110-6HN31-0AA0	3VA6110-7HN31-0AA0	3VA6110-8HN31-0AA0
150	60-150	15	3VA61 3P breaker w/trip	3VA6115-5HN31-0AA0	3VA6115-6HN31-0AA0	3VA6115-7HN31-0AA0	3VA6115-8HN31-0AA0
3VA62			UL Type Code / MB code ==>	MFAE / WA	HFAE / WB	CFAE / WC	LF [®] AE / WD
100	40-100	10	3VA62 3P breaker w/trip	3VA6210-5HN31-0AA0	3VA6210-6HN31-0AA0	3VA6210-7HN31-0AA0	3VA6210-8HN31-0AA0
250	100-250	25	3VA62 3P breaker w/trip	3VA6225-5HN31-0AA0	3VA6225-6HN31-0AA0	3VA6225-7HN31-0AA0	3VA6225-8HN31-0AA0
3VA63			UL Type Code / MB code ==>	MJAE / WE	HJAE / WF	CJAE / WG	LJAE [®] / WH
250	100-250	25	3VA63 3P breaker w/trip	3VA6325-5HN31-0AA0	3VA6325-6HN31-0AA0	3VA6325-7HN31-0AA0	3VA6325-8HN31-0AA0
400	160-400	40	3VA63 3P breaker w/trip	3VA6340-5HN31-0AA0	3VA6340-6HN31-0AA0	3VA6340-7HN31-0AA0	3VA6340-8HN31-0AA0
3VA63 MCS			UL Type Code / MB code ==>	na	na	CJAE / WG	na
400	na	40	3VA63 3P Molded Case Sw	non adj. short circuit release I _i ==>		3VA6340-1BB31-0AA0	na
3VA64			UL Type Code / MB code ==>	MLAE / WJ	HLAE / WK	CLAE / WL	LLAE [®] / WM
400	160-400	40	3VA64 3P breaker w/trip	3VA6440-5HN31-0AA0	3VA6440-6HN31-0AA0	3VA6440-7HN31-0AA0	3VA6440-8HN31-0AA0
600	240-600	60	3VA64 3P breaker w/trip	3VA6460-5HN31-0AA0	3VA6460-6HN31-0AA0	3VA6460-7HN31-0AA0	3VA6460-8HN31-0AA0
3VA64 MCS			UL Type Code / MB code ==>	na	na	CLAE / WL	na
600	na	60	3VA64 3P Molded Case Sw	non adj. short circuit release I _i ==>		3VA6460-1BB31-0AA0	na

Electronic Trip Units available for 3VA61/62/63/64 series

(COMPAS may require special Mod for some options)

Part # Differences	Alternate Trips available	I _r	I _i	I _{sd}	I _g	Ground Fault type	Display and/or Metering Included
...HL31-0AA0	ETU320 LI	I _r	I _i	—	—	na	no
...HM31-0AA0	ETU330 LIG	I _r	I _i	—	I _g	Adjustable Protection (b)	no
...JP31-0AA0	ETU550 LSI with Display only	I _r	I _i	I _{sd}	—	na	yes - Display only
...JT31-0AA0	ETU556 LSI(G) with Display only	I _r	I _i	I _{sd}	I _g	Adjustable Alarm (a)	yes - Display only
...JQ31-0AA0	ETU560 LSI(G) with Display only	I _r	I _i	I _{sd}	I _g	Adjustable Protection (b)	yes - Display only
...KL31-0AA0	ETU820 LI w/Display & Metering	I _r	I _i	—	—	na	yes - both
...KM31-0AA0	ETU830 LIG w/Display & Metering	I _r	I _i	—	I _g	Adjustable Protection (b)	yes - both
...KP31-0AA0	ETU850 LSI w/Display & Metering	I _r	I _i	I _{sd}	—	na	yes - both
...KT31-0AA0	ETU856 LSI(G) w/Display & Metering	I _r	I _i	I _{sd}	I _g	Adjustable Alarm (a)	yes - both
...KQ31-0AA0	ETU860 LSI(G) w/Display & Metering	I _r	I _i	I _{sd}	I _g	Adjustable Protection (b)	yes - both

Trip Unit Feature description and notes	
I _r	Adjustable Overload Protection
I _i	Adjustable Instantaneous Short-Circuit Protection
I _{sd}	Adjustable Delayed Short-Circuit Protection
I _g	Either (a) Adjustable Ground-Fault Alarm or (b) Adjustable Ground-Fault Protection (not both)

⑥ The "L" series of UL type codes may not be available for use in all Panelboard types - check COMPAS for verification.

3VA Breaker Configuration Information in Panelboards

3VA Electronic Trip Units — 100% Rated

Selection

3VA6 100% rated ETU – "Electronic Trip" versions of 3VA Breakers in Panelboards

- See following pages for internal accessory pocket locations available in TMTU & ETU versions
- Breakers shown do not include lugs - lugs are ordered separately as needed per application
- COMPAS will allow various Lug configurations based on Panel Type and mounting location

Connector Kits for 3 Pole 3VA6 series Breakers – 100% rated (Requires CU Connectors)

For Accessories
and positions see
tables on pages
11-79 and 11-83

Description note: Use 3-pole for 2-pole applications	One Connector Kit required for each breaker when panel mounted.	Connector Kits	AL	CU
		3VA61/62	not allowed	3VA9243-0JD12
		3VA63	not allowed	1-port version 3VA9373-0JD13 or 2-port version 3VA9473-0JE23
		3VA64		

3 Pole 3VA6 series Breakers – 100% rated – without connectors

Standard in COMPAS includes ETU350 LSI Trip (I _r and I _i are adjustable)			ETU350 LSI included	ETU350 LSI included	ETU350 LSI included	ETU350 LSI included	ETU350 LSI included
kA ratings @ 50/60 Hz			3-pole	3-pole	3-pole	3-pole	3-pole
240 VAC kAIC rating ==>			100	100	200	200	200
480Y / 277 VAC kAIC rating ==>			35	65	100	150	150
480 VAC kAIC rating ==>			35	65	100	150	150
600Y / 347 VAC kAIC rating ==>			18	22	35	50	50
600 VAC kAIC rating ==>			18	22	35	50	50
250 VDC kAIC rating ==>			na	na	na	na	na
amps	Adj. I _r	code					
3VA61			UL Type Code / MB code ==>	MDAE / W2	HDAE / W3	CDAE / W4	LDAE ^① / W5
40	16-40	40	3VA61 3P breaker w/trip	3VA6140-5HN31-2AA0	3VA6140-6HN31-2AA0	3VA6140-7HN31-2AA0	3VA6140-8HN31-2AA0
100	40-100	10	3VA61 3P breaker w/trip	3VA6110-5HN31-2AA0	3VA6110-6HN31-2AA0	3VA6110-7HN31-2AA0	3VA6110-8HN31-2AA0
150	60-150	15	3VA61 3P breaker w/trip	3VA6115-5HN31-2AA0	3VA6115-6HN31-2AA0	3VA6115-7HN31-2AA0	3VA6115-8HN31-2AA0
3VA62			UL Type Code / MB code ==>	MFAE / WA	HFAE / WB	CFAE / WC	LF ^① AE / WD
100	40-100	10	3VA62 3P breaker w/trip	3VA6210-5HN31-2AA0	3VA6210-6HN31-2AA0	3VA6210-7HN31-2AA0	3VA6210-8HN31-2AA0
250	100-250	25	3VA62 3P breaker w/trip	3VA6225-5HN31-2AA0	3VA6225-6HN31-2AA0	3VA6225-7HN31-2AA0	3VA6225-8HN31-2AA0
3VA63			UL Type Code / MB code ==>	MJAE / WE	HJAE / WF	CJAE / WG	LJAE ^① / WH
250	100-250	25	3VA63 3P breaker w/trip	3VA6325-5HN31-2AA0	3VA6325-6HN31-2AA0	3VA6325-7HN31-2AA0	3VA6325-8HN31-2AA0
3VA64			UL Type Code / MB code ==>	MLAE / WJ	HLAE / WK	CLAE / WL	LLAE ^① / WM
400	160-400	40	3VA64 3P breaker w/trip	3VA6440-5HN31-2AA0	3VA6440-6HN31-2AA0	3VA6440-7HN31-2AA0	3VA6440-8HN31-2AA0

Electronic Trip Units available for 3VA61/62/63/64 series

(COMPAS may require special Mods for some options)

Part # Differences	Alternate Trips available	I _r	I _i	I _{sd}	I _g	Ground Fault type	Display and/or Metering Included
...HL31-0AA0	ETU320 LI	I _r	I _i	—	—	na	no
...HM31-0AA0	ETU330 LIG	I _r	I _i	—	I _g	Adjustable Protection (b)	no
...JP31-0AA0	ETU550 LSI with Display only	I _r	I _i	I _{sd}	—	na	yes - Display only
...JT31-0AA0	ETU556 LSI(G) with Display only	I _r	I _i	I _{sd}	I _g	Adjustable Alarm (a)	yes - Display only
...JQ31-0AA0	ETU560 LSI(G) with Display only	I _r	I _i	I _{sd}	I _g	Adjustable Protection (b)	yes - Display only
...KL31-0AA0	ETU820 LI w/Display & Metering	I _r	I _i	—	—	na	yes - both
...KM31-0AA0	ETU830 LIG w/Display & Metering	I _r	I _i	—	I _g	Adjustable Protection (b)	yes - both
...KP31-0AA0	ETU850 LSI w/Display & Metering	I _r	I _i	I _{sd}	—	na	yes - both
...KT31-0AA0	ETU856 LSI(G) w/Display & Metering	I _r	I _i	I _{sd}	I _g	Adjustable Alarm (a)	yes - both
...KQ31-0AA0	ETU860 LSI(G) w/Display & Metering	I _r	I _i	I _{sd}	I _g	Adjustable Protection (b)	yes - both

Trip Unit Feature description and notes	
I _r	Adjustable Overload Protection
I _i	Adjustable Instantaneous Short-Circuit Protection
I _{sd}	Adjustable Delayed Short-Circuit Protection
I _g	Either (a) Adjustable Ground-Fault Alarm or (b) Adjustable Ground-Fault Protection (not both)

① The "L" series of UL type codes may not be available for use in all Panelboard types - check COMPAS for verification.

3VA Breaker Configuration Information in Panelboards

Communications Modules

Selection

3VA6 Communications modules and related accessories for field installation^①

- COMPAS may not allow some of these kits for selection - Special Mod may be required.
- Some items may not be installed in panels and may be shipped separate from Panels even if Configured in COMPAS

Description	Quick reference code	Voltage AC max or range	Voltage DC max or range	Accessory Catalog Number ^②	Qty of slots in breaker req'd	Max. Qty. per Brkr	Position to install for 3VA61/62 and 3VA63/64 only															
							Left side pocket					Right side pocket										
Group ^②							Pocket reference # ==>						25	24	23	22	21	11	12	13	14	15
COM Modules and Cables																						
Communications Module - 3VA61/62	COM060	n/a	24VDC	3VA9177-0TB10	4	1												X				
Communications Module - 3VA63/64	COM060	n/a	24VDC	3VA9377-0TB10	4	1												X				
COM060-to-T-Connector ext. cable 0.4 m	COM060-to-T	n/a	n/a	3VA9987-0TF20	n/a	n/a	External															
COM060-to-T-Connector ext. cable 0.8 m	COM060-to-T	n/a	n/a	3VA9987-0TF10	n/a	n/a	External															
COM060 T-Connector (spare part)	T-Connector	n/a	n/a	3VA9987-0TG10	n/a	n/a	External															
Terminal Resistor	TermRes	n/a	n/a	3VA9987-0TE10	n/a	n/a	External															
COM800 Breaker Data Server = max 8	COM800	n/a	n/a	3VA9977-0TA10	n/a	n/a	P4/P5 only and SWBD															
COM100 Breaker Data Server = max 1	COM100	n/a	n/a	3VA9977-0TA20	n/a	n/a	P4/P5 only and SWBD															
COM100-800 extension cable 0.4 m	COM ext Cable	n/a	n/a	3VA9987-0TC10	n/a	n/a	P4/P5 only and SWBD															
COM100-800 extension cable 1 m	COM ext Cable	n/a	n/a	3VA9987-0TC20	n/a	n/a	P4/P5 only and SWBD															
COM100-800 extension cable 2 m	COM ext Cable	n/a	n/a	3VA9987-0TC30	n/a	n/a	P4/P5 only and SWBD															
COM100-800 extension cable 4 m	COM ext Cable	n/a	n/a	3VA9987-0TC40	n/a	n/a	P4/P5 only and SWBD															
7KM Pac Profibus DP Expansion Module	7KMAB	n/a	n/a	7KM9300-0AB01-0AA0	n/a	n/a	P4/P5 only and SWBD															
7KM PAC Switched Ethernet Profinet Expansion Module	7KMAE	n/a	n/a	7KM9300-0AE01-0AA0	n/a	n/a	P4/P5 only and SWBD															
7KM PAC RS485 Modbus RTU Exp. Module	7KMAM	n/a	n/a	7KM9300-0AM00-0AA0	n/a	n/a	P4/P5 only and SWBD															
DAS, Displays and Related Components																						
DAS Module "Maintenance Mode Box"	MMB300	n/a	n/a	3VA9977-0UF10	n/a	n/a	P4/P5 only and SWBD															
EFB300 - External function box	EFB300	n/a	n/a	3VA9977-0UA10	n/a	n/a	P4/P5 only and SWBD															
Display - DSP800	DSP800	n/a	n/a	3VA9977-0TD10	n/a	n/a	P4/P5 only and SWBD															
1.5m Connecting cable for MMB300/EFB300	MMB/EFB 1.5m	n/a	n/a	3VA9987-UB10	n/a	n/a	P4/P5 only and SWBD															
3.0m Connecting cable for MMB300/EFB300	MMB/EFB 3.0m	n/a	n/a	3VA9987-UB20	n/a	n/a	P4/P5 only and SWBD															
Motor Operators																						
M0320 Motor Operator - 24-60V DC	M0320	n/a	24-60V	3VA9447-0HA10	n/a	1	P4/P5 only and SWBD															
M0320 Motor Operator - 110-230V AC or 110-250V DC	EFB300	n/a	n/a	3VA9977-0UA10	n/a	1	P4/P5 only and SWBD															
Misc. External Components and Cables																						
Neutral Current Transformer, In = 25-150A	NCT150	n/a	n/a	3VA9077-0NA10	n/a	n/a	P4/P5 only and SWBD															
Neutral Current Transformer, In= 160-350A	NCT350	n/a	n/a	3VA9177-0NA10	n/a	n/a	P4/P5 only and SWBD															
Neutral Current Transformer, In = 400-630A	NCT630	n/a	n/a	3VA9377-0NA10	n/a	n/a	P4/P5 only and SWBD															
TD300 - Activation & Trip Box	TD300	n/a	n/a	3VA9977-0MA10	n/a	n/a	P4/P5 only and SWBD															
TD500 - Test device	TD500	n/a	n/a	3VA9977-0MB10	n/a	n/a	P4/P5 only and SWBD															
TD500 External Power Supply	TD500EX	n/a	n/a	3VA9987-0MX10	n/a	n/a	P4/P5 only and SWBD															
Cable to connect to TD500 from 3VA6	TD500CBL	n/a	n/a	3VA9977-0MY10	n/a	n/a	P4/P5 only and SWBD															
Special Connector Lugs with Control Wire Tap																						
#14-3/0 AL wire connector Kit ^③ w/con-tap	AL-lug	3VA51		3VA9133-0JG11	125A TMTU only		Line or Load end as needed															
#14-2/0 CU wire connector Kit ^③ w/con-tap	CU-lug	3VA51		3VA9133-0JK11	125A TMTU only		Line or Load end as needed															
#6-350 kcmil AL wire conn. Kit ^③ w/con-tap	AL-lug	3VA52		3VA9233-0JG12	250A TMTU only		Line or Load end as needed															
#6-350 kcmil CU wire conn. Kit ^③ w/con-tap	CU-lug	3VA52		3VA9233-0JK12	250A TMTU only		Line or Load end as needed															
#14-1/0 AL wire connector Kit ^③ w/con-tap	AL-lug	3VA61		3VA9143-0JG11	150A ETU only		Line or Load end as needed															
#6-350 kcmil AL wire conn. Kit ^③ w/con-tap	AL-lug	3VA61/62		3VA9243-0JG12	150/250A ETU only		Line or Load end as needed															
#14-1/0 CU wire connector Kit ^③ w/con-tap	CU-lug	3VA61		3VA9143-0JK11	150A ETU only		Line or Load end as needed															
#6-350 kcmil CU wire conn. Kit ^③ w/con-tap	CU-lug	3VA61/62		3VA9243-0JK12	150/250A ETU only		Line or Load end as needed															
#1-600 kcmil AL wire conn. Kit ^③ w/con-tap	AL-lug	3VA53/63		3VA9373-0JG13	400A TMTU or ETU		Line or Load end as needed															
#1-600 kcmil CU wire conn. Kit ^③ w/con-tap	CU-lug	3VA53/63		3VA9373-0JK13	400A TMTU or ETU		Line or Load end as needed															
2/0-600 kcmil AL 2 port conn. Kit ^③ w/con-tap	AL-2lug	3VA54/64		3VA9473-0JC23	600A TMTU or ETU		Line or Load end as needed															

① Some accessories may be "field install only" if not available in COMPAS, or not available for use in Panelboards
 ② Many accessories available for the 3VA5 and 3VA6 breakers may not be suitable for use in Lighting Panelboards.
 - COMPAS allows only options that are available for factory assembly.

Some accessories listed above may not be available for all Panelboard configurations.
 ③ Lugs are NOT supplied with loose breaker as standard - must order separately or configure in COMPAS to include lugs.
 - Factory assembled panels include AL lugs as standard without control wire tap, CU lugs are optional. These kits include 3 connectors and hardware.

3VA Breaker Configuration Information in Panelboards

3VA41 Breakers – 1 Pole and 1 Pole in 2-Pole Frame

Selection

3VA41 1 Pole Breakers

3VA41 TMTU 125A max. - breakers include AL lugs installed

TMTU frame	Type	kA code	Type ref	MB code
3VA41	SEAB	S	EAB	V1
3VA41	MEAB	M	EAB	V2
3VA41	HEAB	H	EAB	V3

1 Pole 3VA41

with AL connectors included – for 14 AWG to 3/0 - CU/AL cable

For copper, order kit 3VA9133-0JD10 (15A-40A) or 3VA9133-0JD11 (45A-125A)

Note: No accessory pockets available – see 1-pole in 2-pole frame

3VA41

1-Pole Description

UL Type Code ==>	SEAB	MEAB	HEAB
Panelboard MB codes ==>	V1	V2	V3
120 VAC kAIC rating ==>	65	85	150 ^①
277 VAC kAIC rating ==>	25	35	65
347 VAC kAIC rating ==>	14	18	25
125 VDC kAIC rating ^② ==>	14	25	30
IC family @ 277 VAC ==>	25kA	35kA	65kA
FTFM Trip included ==>	TM210	TM210	TM210

Amps	Code	Description	Catalog Number	Catalog Number	Catalog Number
			1-pole	1-pole	1-pole
15	95	3VA41 1P breaker w/TM210	3VA4195-4ED14-0AA0	3VA4195-5ED14-0AA0	3VA4195-6ED14-0AA0
20	20	3VA41 1P breaker w/TM210	3VA4120-4ED14-0AA0	3VA4120-5ED14-0AA0	3VA4120-6ED14-0AA0
25	25	3VA41 1P breaker w/TM210	3VA4125-4ED14-0AA0	3VA4125-5ED14-0AA0	3VA4125-6ED14-0AA0
30	30	3VA41 1P breaker w/TM210	3VA4130-4ED14-0AA0	3VA4130-5ED14-0AA0	3VA4130-6ED14-0AA0
35	35	3VA41 1P breaker w/TM210	3VA4135-4ED14-0AA0	3VA4135-5ED14-0AA0	3VA4135-6ED14-0AA0
40	40	3VA41 1P breaker w/TM210	3VA4140-4ED14-0AA0	3VA4140-5ED14-0AA0	3VA4140-6ED14-0AA0
45	45	3VA41 1P breaker w/TM210	3VA4145-4ED14-0AA0	3VA4145-5ED14-0AA0	3VA4145-6ED14-0AA0
50	50	3VA41 1P breaker w/TM210	3VA4150-4ED14-0AA0	3VA4150-5ED14-0AA0	3VA4150-6ED14-0AA0
60	60	3VA41 1P breaker w/TM210	3VA4160-4ED14-0AA0	3VA4160-5ED14-0AA0	3VA4160-6ED14-0AA0
70	70	3VA41 1P breaker w/TM210	3VA4170-4ED14-0AA0	3VA4170-5ED14-0AA0	3VA4170-6ED14-0AA0
80	80	3VA41 1P breaker w/TM210	3VA4180-4ED14-0AA0	3VA4180-5ED14-0AA0	3VA4180-6ED14-0AA0
90	90	3VA41 1P breaker w/TM210	3VA4190-4ED14-0AA0	3VA4190-5ED14-0AA0	3VA4190-6ED14-0AA0
100	10	3VA41 1P breaker w/TM210	3VA4110-4ED14-0AA0	3VA4110-5ED14-0AA0	3VA4110-6ED14-0AA0
110	11	3VA41 1P breaker w/TM210	3VA4111-4ED14-0AA0	3VA4111-5ED14-0AA0	3VA4111-6ED14-0AA0
125	12	3VA41 1P breaker w/TM210	3VA4112-4ED14-0AA0	3VA4112-5ED14-0AA0	3VA4112-6ED14-0AA0

1 Pole in 2-Pole Frame 3VA41

with AL connectors included

For copper, order kit 3VA9133-0JD10 (15A-40A) or 3VA9133-0JD11 (45A-125A)

Note: Only 3 Left side Accessory pockets available

3VA41

1-Pole in 2-Pole Description

amps	code	Description	Catalog Number	Catalog Number	Catalog Number
			1-Pole in 2-Pole Frame	1-Pole in 2-Pole Frame	1-Pole in 2-Pole Frame
15	95	3VA41 1P breaker w/TM210	3VA4195-4ED54-0AA0	3VA4195-5ED54-0AA0	3VA4195-6ED54-0AA0
20	20	3VA41 1P breaker w/TM210	3VA4120-4ED54-0AA0	3VA4120-5ED54-0AA0	3VA4120-6ED54-0AA0
25	25	3VA41 1P breaker w/TM210	3VA4125-4ED54-0AA0	3VA4125-5ED54-0AA0	3VA4125-6ED54-0AA0
30	30	3VA41 1P breaker w/TM210	3VA4130-4ED54-0AA0	3VA4130-5ED54-0AA0	3VA4130-6ED54-0AA0
35	35	3VA41 1P breaker w/TM210	3VA4135-4ED54-0AA0	3VA4135-5ED54-0AA0	3VA4135-6ED54-0AA0
40	40	3VA41 1P breaker w/TM210	3VA4140-4ED54-0AA0	3VA4140-5ED54-0AA0	3VA4140-6ED54-0AA0
45	45	3VA41 1P breaker w/TM210	3VA4145-4ED54-0AA0	3VA4145-5ED54-0AA0	3VA4145-6ED54-0AA0
50	50	3VA41 1P breaker w/TM210	3VA4150-4ED54-0AA0	3VA4150-5ED54-0AA0	3VA4150-6ED54-0AA0
60	60	3VA41 1P breaker w/TM210	3VA4160-4ED54-0AA0	3VA4160-5ED54-0AA0	3VA4160-6ED54-0AA0
70	70	3VA41 1P breaker w/TM210	3VA4170-4ED54-0AA0	3VA4170-5ED54-0AA0	3VA4170-6ED54-0AA0
80	80	3VA41 1P breaker w/TM210	3VA4180-4ED54-0AA0	3VA4180-5ED54-0AA0	3VA4180-6ED54-0AA0
90	90	3VA41 1P breaker w/TM210	3VA4190-4ED54-0AA0	3VA4190-5ED54-0AA0	3VA4190-6ED54-0AA0
100	10	3VA41 1P breaker w/TM210	3VA4110-4ED54-0AA0	3VA4110-5ED54-0AA0	3VA4110-6ED54-0AA0
110	11	3VA41 1P breaker w/TM210	3VA4111-4ED54-0AA0	3VA4111-5ED54-0AA0	3VA4111-6ED54-0AA0
125	12	3VA41 1P breaker w/TM210	3VA4112-4ED54-0AA0	3VA4112-5ED54-0AA0	3VA4112-6ED54-0AA0

① Although some breakers have a kAIC rating above 100 kAIC – many panels are limited to 100 kAIC or less.

② DC Voltage panels are limited by various factors. These DC ratings apply to the Breaker only.

3VA Breaker Configuration Information in Panelboards

3VA41 Breakers – 2 Pole and 3 Pole

Selection

3VA41 2 and 3 Pole Breakers

3VA41 TMTU 125A max. - breakers include AL lugs installed

TMTU frame	Type	kA code	Type ref	MB code
3VA41	SEAB	S	EAB	V1
3VA41	MEAB	M	EAB	V2
3VA41	HEAB	H	EAB	V3

3 Pole 3VA41

3VA41

3-Pole Description

with AL connectors included – for 14 AWG to 3/0 - CU/AL cable

For copper, order kit 3VA9133-0JD10 (15A-40A) or 3VA9133-0JD11 (45A-125A)

UL Type Code ==>	SEAB	MEAB	HEAB
Panelboard MB codes ==>	V1	V2	V3
Ratings	3-pole 2-pole	3-pole 2-pole	3-pole 2-pole
240 VAC kAIC rating ==>	65 65	85 85	150 ^① 150 ^①
480Y / 277 VAC kAIC rating ==>	25 25	35 35	65 65
480 VAC kAIC rating ==>	25 25	35 35	65 65
600Y / 347 VAC kAIC rating ==>	14 14	18 18	25 25
600 VAC kAIC rating ==>	na na	na na	na na
250 VDC kAIC rating ^② ==>	na 50	na 85	na 100
IC family @ 277 VAC ==>	25kA	35kA	65kA
FTFM Trip included ==>	TM210	TM210	TM210

Amps	Code	Description	Catalog Number 3-pole	Catalog Number 3-pole	Catalog Number 3-pole
15	95	3VA41 3P breaker w/TM210	3VA4195-4ED34-0AA0	3VA4195-5ED34-0AA0	3VA4195-6ED34-0AA0
20	20	3VA41 3P breaker w/TM210	3VA4120-4ED34-0AA0	3VA4120-5ED34-0AA0	3VA4120-6ED34-0AA0
25	25	3VA41 3P breaker w/TM210	3VA4125-4ED34-0AA0	3VA4125-5ED34-0AA0	3VA4125-6ED34-0AA0
30	30	3VA41 3P breaker w/TM210	3VA4130-4ED34-0AA0	3VA4130-5ED34-0AA0	3VA4130-6ED34-0AA0
35	35	3VA41 3P breaker w/TM210	3VA4135-4ED34-0AA0	3VA4135-5ED34-0AA0	3VA4135-6ED34-0AA0
40	40	3VA41 3P breaker w/TM210	3VA4140-4ED34-0AA0	3VA4140-5ED34-0AA0	3VA4140-6ED34-0AA0
45	45	3VA41 3P breaker w/TM210	3VA4145-4ED34-0AA0	3VA4145-5ED34-0AA0	3VA4145-6ED34-0AA0
50	50	3VA41 3P breaker w/TM210	3VA4150-4ED34-0AA0	3VA4150-5ED34-0AA0	3VA4150-6ED34-0AA0
60	60	3VA41 3P breaker w/TM210	3VA4160-4ED34-0AA0	3VA4160-5ED34-0AA0	3VA4160-6ED34-0AA0
70	70	3VA41 3P breaker w/TM210	3VA4170-4ED34-0AA0	3VA4170-5ED34-0AA0	3VA4170-6ED34-0AA0
80	80	3VA41 3P breaker w/TM210	3VA4180-4ED34-0AA0	3VA4180-5ED34-0AA0	3VA4180-6ED34-0AA0
90	90	3VA41 3P breaker w/TM210	3VA4190-4ED34-0AA0	3VA4190-5ED34-0AA0	3VA4190-6ED34-0AA0
100	10	3VA41 3P breaker w/TM210	3VA4110-4ED34-0AA0	3VA4110-5ED34-0AA0	3VA4110-6ED34-0AA0
110	11	3VA41 3P breaker w/TM210	3VA4111-4ED34-0AA0	3VA4111-5ED34-0AA0	3VA4111-6ED34-0AA0
125	12	3VA41 3P breaker w/TM210	3VA4112-4ED34-0AA0	3VA4112-5ED34-0AA0	3VA4112-6ED34-0AA0
Molded Case Switch					
100	10	3VA41 3P MCS 65 kA	na	na	3VA4110-1BB31-0AA0

2 Pole 3VA41 with AL connectors included

3VA41

2-Pole Description

For copper, order kit 3VA9133-0JD10 (15A-40A) or 3VA9133-0JD11 (45A-125A)

Note: Only 3 Left side Accessory pockets available

Amps	Code	Description	Catalog Number 2-pole	Catalog Number 2-pole	Catalog Number 2-pole
15	95	3VA41 2P breaker w/TM210	3VA4195-4ED24-0AA0	3VA4195-5ED24-0AA0	3VA4195-6ED24-0AA0
20	20	3VA41 2P breaker w/TM210	3VA4120-4ED24-0AA0	3VA4120-5ED24-0AA0	3VA4120-6ED24-0AA0
25	25	3VA41 2P breaker w/TM210	3VA4125-4ED24-0AA0	3VA4125-5ED24-0AA0	3VA4125-6ED24-0AA0
30	30	3VA41 2P breaker w/TM210	3VA4130-4ED24-0AA0	3VA4130-5ED24-0AA0	3VA4130-6ED24-0AA0
35	35	3VA41 2P breaker w/TM210	3VA4135-4ED24-0AA0	3VA4135-5ED24-0AA0	3VA4135-6ED24-0AA0
40	40	3VA41 2P breaker w/TM210	3VA4140-4ED24-0AA0	3VA4140-5ED24-0AA0	3VA4140-6ED24-0AA0
45	45	3VA41 2P breaker w/TM210	3VA4145-4ED24-0AA0	3VA4145-5ED24-0AA0	3VA4145-6ED24-0AA0
50	50	3VA41 2P breaker w/TM210	3VA4150-4ED24-0AA0	3VA4150-5ED24-0AA0	3VA4150-6ED24-0AA0
60	60	3VA41 2P breaker w/TM210	3VA4160-4ED24-0AA0	3VA4160-5ED24-0AA0	3VA4160-6ED24-0AA0
70	70	3VA41 2P breaker w/TM210	3VA4170-4ED24-0AA0	3VA4170-5ED24-0AA0	3VA4170-6ED24-0AA0
80	80	3VA41 2P breaker w/TM210	3VA4180-4ED24-0AA0	3VA4180-5ED24-0AA0	3VA4180-6ED24-0AA0
90	90	3VA41 2P breaker w/TM210	3VA4190-4ED24-0AA0	3VA4190-5ED24-0AA0	3VA4190-6ED24-0AA0
100	10	3VA41 2P breaker w/TM210	3VA4110-4ED24-0AA0	3VA4110-5ED24-0AA0	3VA4110-6ED24-0AA0
110	11	3VA41 2P breaker w/TM210	3VA4111-4ED24-0AA0	3VA4111-5ED24-0AA0	3VA4111-6ED24-0AA0
125	12	3VA41 2P breaker w/TM210	3VA4112-4ED24-0AA0	3VA4112-5ED24-0AA0	3VA4112-6ED24-0AA0

① Although some breakers have a kAIC rating above 100 kAIC – many panels are limited to 100 kAIC or less.

② DC Voltage panels are limited by various factors. These DC ratings apply to the Breaker only.

3VA Breaker Configuration Information in Panelboards

Internal and External Accessories for 125A 3VA Breakers

Selection

Accessories for 3VA41/51 TMTU 125A max.

- 6 slots max. are available - 3 on each side of trip handle.\
- COMPAS will allow only modules that will be allowed in panel being configured.
- Note: 3VA41/51 2-pole and "1-pole in 2-pole frame" have only 3 Left side Accessory pockets available.

Description	Quick reference code	Voltage AC max or range	Voltage DC max or range	Accessory Catalog Number ^②	Qty of slots in breaker req'd	Max. Qty. per Brkr	Position to install for 3VA41/51 only					
-------------	----------------------	-------------------------	-------------------------	---------------------------------------	-------------------------------	--------------------	---------------------------------------	--	--	--	--	--

Accessories

							Left side			Right side		
							23	22	21	11	12	13
Internal Accessories Left side only Only one per breaker allowed	Shunt trip left -10	STL-10	n/a	12	3VA9978-0BL10	3	1	X				
	Shunt trip left -20	STL-20	380...600	n/a	3VA9978-0BL20	3	1	X				
	Shunt trip left -30	STL-30	24	24...30	3VA9978-0BL30	3	1	X				
	Shunt trip left -31	STL-31	48...60	n/a	3VA9978-0BL31	3	1	X				
	Shunt trip left -32	STL-32	110...127	110...127	3VA9978-0BL32	3	1	X				
	Shunt trip left -33	STL-33	208...277	220...250	3VA9978-0BL33	3	1	X				
	Shunt trip flexible -20	STF-20	24	n/a	3VA9978-0BA20	3	1	X				
	Shunt trip flexible -21	STF-21	48...60	n/a	3VA9978-0BA21	3	1	X				
	Shunt trip flexible -22	STF-22	110...127	n/a	3VA9978-0BA22	3	1	X				
	Shunt trip flexible -23	STF-23	208...277	n/a	3VA9978-0BA23	3	1	X				
	Shunt trip flexible -24	STF-24	380...500	n/a	3VA9978-0BA24	3	1	X				
	Shunt trip flexible -25	STF-25	600	n/a	3VA9978-0BA25	3	1	X				
	Undervoltage release -10	UVR-10	n/a	12	3VA9978-0BB10	3	1	X				
	Undervoltage release -11	UVR-11	n/a	24	3VA9978-0BB11	3	1	X				
	Undervoltage release -12	UVR-12	n/a	48	3VA9978-0BB12	3	1	X				
	Undervoltage release -14	UVR-14	n/a	125...127	3VA9978-0BB14	3	1	X				
	Undervoltage release -16	UVR-16	n/a	250	3VA9978-0BB16	3	1	X				
	Undervoltage release -20	UVR-20	24	n/a	3VA9978-0BB20	3	1	X				
	Undervoltage release -24	UVR-24	120...127	n/a	3VA9978-0BB24	3	1	X				
	Undervoltage release -25	UVR-25	208...230	n/a	3VA9978-0BB25	3	1	X				
	Undervoltage release -27	UVR-27	440...480	n/a	3VA9978-0BB27	3	1	X				
	Universal release	UNI-11	n/a	12vdc	3VA9978-0BD11	3	1	X				
	Universal release	UNI-12	n/a	24vdc	3VA9978-0BD12	3	1	X				
	Universal release	UNI-13	n/a	48vdc	3VA9978-0BD13	3	1	X				
Internal Accessories Right side or left side options	Auxiliary switch - standard	AUX_HQ	240VAC	n/a	3VA9978-0AA12	1	6	X	X	X	X	X
	Leading Chg-over SW - standard	LCS_HQ	240VAC	n/a	3VA9978-0AA22	1	1				X	
	Trip alarm (bell alarm) - standard	TAS_HQ	240VAC	250VDC	3VA9978-0AB12	1	4		X	X	X	X
	Auxiliary switch - High capacity ^①	AUX_HP	600VAC	n/a	3VA9978-0AA11	2	2		X		X	
								X			X	
	Leading Chg-over SW - High Cap ^①	LCS_HP	600VAC	250VDC	3VA9978-0AA21	1	1				X	
	Trip alarm (bell alarm) - High Cap ^①	TAS_HP	600VAC	250VDC	3VA9978-0AB11	2	2		X		X	
	Auxiliary switch - electronic ^④	AUX_HQ_el	24VAC	24VDC	3VA9978-0AA13	1	6	X	X	X	X	X
	Leading Chg-over SW - electronic ^④	LCS_HQ_el	24VAC	n/a	3VA9978-0AA23	1	1				X	
	Trip alarm (bell alarm) - electronic ^④	TAS_HQ_el	24VAC	24VDC	3VA9978-0AB13	1	4		X	X	X	X
External ^③ Accessories and field kits	#14-3/0 AL wire connector Kit ^③	AL-lug	n/a	n/a	3VA9133-0JB11	n/a	n/a	Included w/ 3VA41 only				
	#14-2/0 CU wire connector Kit ^③	CU-lug	n/a	n/a	3VA9133-0JD11	n/a	n/a	Load end as required				
	Compression Lugs (future offering - details tbd)	tbd	n/a	n/a	tbd	n/a	n/a	availability and usage locations tbd				
	3VA41 only Padlock Device	tbd	n/a	n/a	3VA9038-0LB11	n/a	n/a	for 1p, 2p or 3p				
	3VA41 2" Handle tie Device	tbd	n/a	n/a	3VA9032-0LB20	n/a	n/a	2" wide for 1p only				
	3VA41 3" Handle tie Device	tbd	n/a	n/a	3VA9033-0LB20	n/a	n/a	3" wide for 1p only				

① High capacity/power (HP) max. Amps load capacity is higher than standard module (.55A up to 6.0A) depends on Voltage and AC/DC requirements - see SpeedFax section 7 or 3VA documentation for more information.

② Many accessories available for the 3VA4, 3VA5 and 3VA6 breakers may not be suitable for use in Lighting Panelboards.
- COMPAS allows options that are available. All accessories listed above can be used with Panelboards in general, but there will be exceptions.

③ Lugs are NOT supplied with loose breaker - must order separately or configured in COMPAS to include lugs. 3VA41 is an exception - AL connectors are included as standard - Factory assembled panels include AL lugs as standard, CU lugs are optional. These kits include 3 connectors and hardware

④ Special electronically-compatible (el) variants are available for applications that require the auxiliary switch signals to be linked to low voltage systems.
- May need special Mod in COMPAS.

3VA Breaker Configuration Information in Panelboards

3VA52 Breakers – 2 Pole and 3 Pole

Selection

3VA52 2 and 3 Pole Breakers

3VA52 TMTU 250A max.

- Part numbers shown are without Lugs.
- Standard Lug kits used in Panelboards are shown in tables below.

TMTU frame	Type	kA code	Type ref	MB code
3VA52	MFAS	M	FAS	VA
3VA52	HFAS	H	FAS	VB
3VA52	CFAS	C	FAS	VC

3 Pole 3VA52 without connectors

The default for Panelboard in COMPAS will be AL 1-conductor connectors:
for AL order one 3VA9233-0JB12 (accepts (1) #6 AWG-350kcmil AL/CU conductor)
for CU order one 3VA9233-0JD12 (accepts (1) #6 AWG-350kcmil CU only conductor)

3VA52

3-Pole Description

UL Type Code ==>	MFAS	HFAS	CFAS
Panelboard MB codes ==>	VA	VB	VC
Ratings	3-pole 2-pole	3-pole 2-pole	3-pole 2-pole
240 VAC kAIC rating ==>	85 85	100 100	200 ^① 200 ^①
480Y / 277 VAC kAIC rating ==>	35 35	65 65	100 100
480 VAC kAIC rating ==>	35 35	65 65	100 100
600Y / 347 VAC kAIC rating ==>	18 18	25 25	35 35
600 VAC kAIC rating ==>	18 18	25 25	35 35
250 VDC kAIC rating ==>	na 50	na 85	na 100
IC family @ 480 VAC ==>	35kA	65kA	100kA
FTAM Trip included ==>	TM230	TM230	TM230

Amps	Code	Description	Catalog Number	Catalog Number	Catalog Number
			3-pole	3-pole	3-pole
100	10	3VA52 3P breaker w/TM230	3VA5210-5EC31-0AA0	3VA5210-6EC31-0AA0	3VA5210-7EC31-0AA0
110	11	3VA52 3P breaker w/TM230	3VA5211-5EC31-0AA0	3VA5211-6EC31-0AA0	3VA5211-7EC31-0AA0
125	12	3VA52 3P breaker w/TM230	3VA5212-5EC31-0AA0	3VA5212-6EC31-0AA0	3VA5212-7EC31-0AA0
150	15	3VA52 3P breaker w/TM230	3VA5215-5EC31-0AA0	3VA5215-6EC31-0AA0	3VA5215-7EC31-0AA0
175	17	3VA52 3P breaker w/TM230	3VA5217-5EC31-0AA0	3VA5217-6EC31-0AA0	3VA5217-7EC31-0AA0
200	20	3VA52 3P breaker w/TM230	3VA5220-5EC31-0AA0	3VA5220-6EC31-0AA0	3VA5220-7EC31-0AA0
225	22	3VA52 3P breaker w/TM230	3VA5222-5EC31-0AA0	3VA5222-6EC31-0AA0	3VA5222-7EC31-0AA0
250	25	3VA52 3P breaker w/TM230	3VA5225-5EC31-0AA0	3VA5225-6EC31-0AA0	3VA5225-7EC31-0AA0
Molded Case Switch				HFAS	CFAS
100	10	3VA52 3P MCS 100kA	na	na	3VA5210-1BB31-0AA0
150	15	3VA52 3P MCS 65kA/100kA	na	3VA5215-0BB31-0AA0	3VA5215-1BB31-0AA0
250	25	3VA52 3P MCS 65kA/100kA	na	3VA5225-0BB31-0AA0	3VA5225-1BB31-0AA0

2 Pole 3VA52 (in 3-Pole frame) without connectors

The default for Panelboard in COMPAS will be AL 1-conductor connectors:
for AL order one 3VA9233-0JB12 (accepts (1) #6 AWG-350kcmil AL/CU conductor)
for CU order one 3VA9233-0JD12 (accepts (1) #6 AWG-350kcmil CU only conductor)

3VA52

2-Pole Description

Amps	Code	Description	Catalog Number	Catalog Number	Catalog Number
			2-pole	2-pole	2-pole
100	10	3VA52 2P breaker w/TM230	3VA5210-5EC61-0AA0	3VA5210-6EC61-0AA0	3VA5210-7EC61-0AA0
110	11	3VA52 2P breaker w/TM230	3VA5211-5EC61-0AA0	3VA5211-6EC61-0AA0	3VA5211-7EC61-0AA0
125	12	3VA52 2P breaker w/TM230	3VA5212-5EC61-0AA0	3VA5212-6EC61-0AA0	3VA5212-7EC61-0AA0
150	15	3VA52 2P breaker w/TM230	3VA5215-5EC61-0AA0	3VA5215-6EC61-0AA0	3VA5215-7EC61-0AA0
175	17	3VA52 2P breaker w/TM230	3VA5217-5EC61-0AA0	3VA5217-6EC61-0AA0	3VA5217-7EC61-0AA0
200	20	3VA52 2P breaker w/TM230	3VA5220-5EC61-0AA0	3VA5220-6EC61-0AA0	3VA5220-7EC61-0AA0
225	22	3VA52 2P breaker w/TM230	3VA5222-5EC61-0AA0	3VA5222-6EC61-0AA0	3VA5222-7EC61-0AA0
250	25	3VA52 2P breaker w/TM230	3VA5225-5EC61-0AA0	3VA5225-6EC61-0AA0	3VA5225-7EC61-0AA0
Molded Case Switch				HFAS	CFAS
100	10	3VA52 2P MCS 100kA	na	na	3VA5210-1BB61-0AA0
150	15	3VA52 2P MCS 65kA/100kA	na	3VA5215-0BB61-0AA0	3VA5215-1BB61-0AA0
250	25	3VA52 2P MCS 65kA/100kA	na	3VA5225-0BB61-0AA0	3VA5225-1BB61-0AA0

① Although some breakers have a kAIC rating above 100 kAIC – many panels are limited to 100 kAIC or less.

② DC Voltage panels are limited by various factors. These DC ratings apply to the Breaker only.

3VA Breaker Configuration Information in Panelboards

Internal and External Accessories for 150-250A 3VA Breakers

Selection

Accessories for 3VA52, 3VA61 and 3VA62 breakers

- 3VA52 TMTU 250A max. and 3VA61 ETU 150A max. and 3VA62 ETU 250A max.
- 6 - 8 slots max. are available – 4 on each side of trip handle.
- COMPAS will allow only modules that will be allowed in panel being configured.

Description	Quick reference code	Voltage AC max or range	Voltage DC max or range	Accessory Catalog Number ²	Qty of slots in breaker req'd	Max. Qty. per Brkr	Position to install for 3VA52/61/62 only							
-------------	----------------------	-------------------------	-------------------------	---------------------------------------	-------------------------------	--------------------	--	--	--	--	--	--	--	--

Accessories

							Left side pocket				Left side pocket			
							24	23	22	21	11	12	13	14
Internal Accessories Left side only Only one per breaker allowed	Shunt trip left -10	STL-10	n/a	12	3VA9978-0BL10	3	1			X				
	Shunt trip left -20	STL-20	380...600	n/a	3VA9978-0BL20	3	1			X				
	Shunt trip left -30	STL-30	24	24...30	3VA9978-0BL30	3	1			X				
	Shunt trip left -31	STL-31	48...60	n/a	3VA9978-0BL31	3	1			X				
	Shunt trip left -32	STL-32	110...127	110...127	3VA9978-0BL32	3	1			X				
	Shunt trip left -33	STL-33	208...277	220...250	3VA9978-0BL33	3	1			X				
	Shunt trip flexible -20	STF-20	24	n/a	3VA9978-0BA20	3	1			X				
	Shunt trip flexible -21	STF-21	48...60	n/a	3VA9978-0BA21	3	1			X				
	Shunt trip flexible -22	STF-22	110...127	n/a	3VA9978-0BA22	3	1			X				
	Shunt trip flexible -23	STF-23	208...277	n/a	3VA9978-0BA23	3	1			X				
	Shunt trip flexible -24	STF-24	380...500	n/a	3VA9978-0BA24	3	1			X				
	Shunt trip flexible -25	STF-25	600	n/a	3VA9978-0BA25	3	1			X				
	Undervoltage release -10	UVR-10	n/a	12	3VA9978-0BB10	3	1			X				
	Undervoltage release -11	UVR-11	n/a	24	3VA9978-0BB11	3	1			X				
	Undervoltage release -12	UVR-12	n/a	48	3VA9978-0BB12	3	1			X				
	Undervoltage release -14	UVR-14	n/a	125...127	3VA9978-0BB14	3	1			X				
	Undervoltage release -16	UVR-16	n/a	250	3VA9978-0BB16	3	1			X				
	Undervoltage release -20	UVR-20	24	n/a	3VA9978-0BB20	3	1			X				
	Undervoltage release -24	UVR-24	120...127	n/a	3VA9978-0BB24	3	1			X				
	Undervoltage release -25	UVR-25	208...230	n/a	3VA9978-0BB25	3	1			X				
	Undervoltage release -27	UVR-27	440...480	n/a	3VA9978-0BB27	3	1			X				
	Universal release	UNI-11	n/a	12vdc	3VA9978-0BD11	3	1			X				
	Universal release	UNI-12	n/a	24vdc	3VA9978-0BD12	3	1			X				
	Universal release	UNI-13	n/a	48vdc	3VA9978-0BD13	3	1			X				

Internal Accessories Right or left side options 3VA52, and 3VA61, 3VA62 (ETU)	Auxiliary switch - standard	AUX_HQ	240VAC	n/a	3VA9978-0AA12	1	6	X	X	X	X	X	X	X
	Leading Chg-over SW - standard	LCS_HQ	240VAC	n/a	3VA9978-0AA22	1	1					X		
	Trip alarm (bell alarm) - standard	TAS_HQ	240VAC	250VDC	3VA9978-0AB12	1	4			X	X	X	X	
	Electrical Alarm Switch std. (ETU Only)	EAS_HQ	240VAC	250VDC	3VA9978-0AB22	1	1							X
	Auxiliary switch - high capacity ¹	AUX_HP	600VAC	n/a	3VA9978-0AA11	2	2		X		X		X	X
	Leading Chg-over SW - High Cap ¹	LCS_HP	600VAC	250VDC	3VA9978-0AA21	1	1					X		
	Trip alarm (bell alarm) - High Cap ¹	TAS_HP	600VAC	250VDC	3VA9978-0AB11	2	2			X		X		
	Auxiliary switch - electronic ⁴	AUX_HQ_el	24VAC	24VDC	3VA9978-0AA13	1	6	X	X	X	X	X	X	X
	Leading Chg-over SW - electronic ⁴	LCS_HQ_el	24VAC	n/a	3VA9978-0AA23	1	1					X		
	Trip alarm (bell alarm) - electronic ⁴	TAS_HQ_el	24VAC	24VDC	3VA9978-0AB13	1	4			X	X	X	X	
	Electrical Alarm Switch electronic ⁴ (ETU Only)	EAS_HQ_el	24VAC	24VDC	3VA9978-0AB23	1	1							X
	Ronis adapter FOR 3VA63/64	Ronis Adapter	n/a	n/a	3VA9347-0LF10	4	1						X	
	Cylinder Lock (type Ronis) Key 1	Ronis Key 1	n/a	n/a	3VA9980-0VL10	one per adapt-er	one per adapt-er							
	Cylinder Lock (type Ronis) Key 2	Ronis Key 2	n/a	n/a	3VA9980-0VL20									
	Cylinder Lock (type Ronis) Key 3	Ronis Key 3	n/a	n/a	3VA9980-0VL30									
	Cylinder Lock (type Ronis) Key 4	Ronis Key 4	n/a	n/a	3VA9980-0VL40									

¹ High capacity/power (HP) max. Amps load capacity is higher than standard module (.55A up to 6.0A) depends on Voltage and AC/DC requirements - see SpeedFax section 7 or 3VA documentation for more information.

² Many accessories available for the 3VA5 and 3VA6 breakers may not be suitable for use in Lighting Panelboards.

– COMPAS allows options that are available. All accessories listed above can be used with Panelboards in general, but there will be exceptions."

³ Lugs are NOT supplied with loose breaker as standard - must order separately or configure in COMPAS to include lugs.

– Factory assembled panels include AL lugs as standard, CU lugs are optional. These kits include 3 connectors and hardware.

⁴ Special electronically-compatible (el) variants are available for applications that require the auxiliary switch signals to be linked to low voltage systems.

– May need special Mod in COMPAS.

3VA Breaker Configuration Information in Panelboards

Internal and External Accessories for 150-250A 3VA Breakers

Selection

Description	Quick reference code	Voltage AC max or range	Voltage DC max or range	Accessory Catalog Number ^②	Qty of slots in breaker req'd	Max. Qty. per Brkr	Position to install for 3VA52/61/62 only							
-------------	----------------------	-------------------------	-------------------------	---------------------------------------	-------------------------------	--------------------	--	--	--	--	--	--	--	--

Accessories (continued)

Internal Accessories 3VA61/62 (ETU) only					Pocket reference # ==>			Left side pkt				Left side pkt			
								24	23	22	21	11	12	13	14
	Communications Module - 3VA61/62	COM060	n/a	24VDC	3VA9177-0TB10	4	1							X	
	COM060-to-T-Connector ext. cable 0.4 m	COM060-to-T	n/a	n/a	3VA9987-0TF20	n/a	n/a								
	COM060-to-T-Connector ext. cable 0.8 m	COM060-to-T	n/a	n/a	3VA9987-0TF10	n/a	n/a								
	COM060 T-Connector (spare part)	T-Connector	n/a	n/a	3VA9987-0TG10	n/a	n/a								

External ^② Accessories and Field Kits	#6-350 kcmil AL wire connector Kit ^③	AL-lug	n/a	n/a	3VA9233-0JB12	TMTU only		3VA52 Load end as required
	#6-350 kcmil CU wire connector Kit ^③	CU-lug	n/a	n/a	3VA9233-0JD12	TMTU only		3VA52 Load end as required
	#14-1/0 AL wire connector Kit ^③	AL-lug	n/a	n/a	3VA9143-0JB11	ETU only		3VA61/62 Load end as required
	#6-350 kcmil AL wire connector Kit ^③	AL-lug	n/a	n/a	3VA9243-0JB12	ETU only		3VA61/62 Load end as required
	#14-1/0 CU wire connector Kit ^③	CU-lug	n/a	n/a	3VA9143-0JD11	ETU only		3VA61/62 Load end as required
	#6-350 kcmil CU wire connector Kit ^③	CU-lug	n/a	n/a	3VA9243-0JD12	ETU only		3VA61/62 Load end as required
	Compression Lugs (future offering - details tbd)	tbd	n/a	n/a	tbd	n/a	n/a	availability and usage locations tbd
	3VA52/61/62 PadLock Device	tbd	n/a	n/a	3VA9138-0LB11	n/a	n/a	
M0320 Motor Operator - 24-60V DC	M0320	n/a	24-60V	3VA9277-0HA10	n/a	1	P4/P5 and SWBD only	
M0320 Motor Operator - 110-230V AC or 110-250V DC	M0320	110-230V	110-250V	3VA9277-0HA20	n/a	1	P4/P5 and SWBD only	
COM100 and COM800 modules and cables can be found on Communications Tables with ETU Breakers earlier in this section.								

① High capacity/power (HP) max. Amps load capacity is higher than standed module (.55A up to 6.0A) depends on Voltage and AC/DC requirements - see SpeedFax section 7 or 3VA documentation for more information.

② Many accessories available for the 3VA5 and 3VA6 breakers may not be suitable for use in Lighting Panelboards.
- COMPAS allows options that are available. All accessories listed above can be used with Panelboards in general, but there will be exceptions."

③ Lugs are NOT supplied with loose breaker as standard - must order separately or configure in COMPAS to include lugs.

- Factory assembled panels include AL lugs as standard, CU lugs are optional. These kits include 3 connectors and hardware.

④ Special electronically-compatible (el) variants are available for applications that require the auxiliary switch signals to be linked to low voltage systems.
- May need special Mod in COMPAS.

3VA Breaker Configuration Information in Panelboards

3VA53 Breakers – 2 Pole and 3 Pole

Selection

3VA53 Breakers

3VA53 TMTU 400A max.

- Part numbers shown are without Lugs.
- Standard Lug kits used in Panelboards are shown in tables below.

TMTU frame	Type	kA code	Type ref	MB code
3VA53	MJAS	M	JAS	VE
3VA53	HJAS	H	JAS	VF
3VA53	CJAS	C	JAS	VG

3 Pole 3VA53 without connectors

The default for Panelboard in COMPAS will be AL 2-conductor connectors:
 for AL order one 3VA9473-0JJ23 (accepts (2) 2/0-600kcmil AL/CU conductors)
 for CU order one 3VA9473-0JE23 (accepts (2) 2/0-600kcmil CU only conductors)
Alternate single conductor lugs are available:
 for AL order one 3VA9473-0JB13 (accepts (1) #1 AWG-600kcmil AL/CU conductors)
 for CU order one 3VA9473-0JD13 (accepts (1) #1 AWG-600kcmil CU only conductors)

3VA53

3-Pole Description

UL Type Code ==>	MJAS	HJAS	CJAS
Panelboard MB codes ==>	VE	VF	VG
Ratings	3-pole 2-pole	3-pole 2-pole	3-pole 2-pole
240 VAC kAIC rating ==>	85 85	100 100	200 ^① 200 ^①
480Y / 277 VAC kAIC rating ==>	35 35	65 65	100 100
480 VAC kAIC rating ==>	35 35	65 65	100 100
600Y / 347 VAC kAIC rating ==>	18 18	25 25	35 35
600 VAC kAIC rating ==>	18 18	25 25	35 35
250 VDC kAIC rating ^② ==>	na 50	na 85	na 100
IC family @ 480 VAC ==>	35kA	65kA	100kA
FTAM Trip included ==>	TM230	TM230	TM230

Amps	Code	Description	Catalog Number	Catalog Number	Catalog Number
			3-pole	3-pole	3-pole
200	20	3VA53 3P breaker w/TM230	3VA5320-5EC31-0AA0	3VA5320-6EC31-0AA0	3VA5320-7EC31-0AA0
225	22	3VA53 3P breaker w/TM230	3VA5322-5EC31-0AA0	3VA5322-6EC31-0AA0	3VA5322-7EC31-0AA0
250	25	3VA53 3P breaker w/TM230	3VA5325-5EC31-0AA0	3VA5325-6EC31-0AA0	3VA5325-7EC31-0AA0
300	30	3VA53 3P breaker w/TM230	3VA5330-5EC31-0AA0	3VA5330-6EC31-0AA0	3VA5330-7EC31-0AA0
350	35	3VA53 3P breaker w/TM230	3VA5335-5EC31-0AA0	3VA5335-6EC31-0AA0	3VA5335-7EC31-0AA0
400	40	3VA53 3P breaker w/TM230	3VA5340-5EC31-0AA0	3VA5340-6EC31-0AA0	3VA5340-7EC31-0AA0

2 Pole 3VA53 (in 3-Pole frame) without connectors

The default for Panelboard in COMPAS will be AL 2-conductor connectors:
 for AL order one 3VA9473-0JJ23 (accepts (2) 2/0-600kcmil AL/CU conductors)
 for CU order one 3VA9473-0JE23 (accepts (2) 2/0-600kcmil CU only conductors)
Alternate single conductor lugs are available:
 for AL order one 3VA9473-0JB13 (accepts (1) #1 AWG-600kcmil AL/CU conductors)
 for CU order one 3VA9473-0JD13 (accepts (1) #1 AWG-600kcmil CU only conductors)

3VA53

2-Pole Description

Amps	Code	Description	Catalog Number	Catalog Number	Catalog Number
			2-pole	2-pole	2-pole
200	20	3VA53 2P breaker w/TM230	3VA5320-5EC61-0AA0	3VA5320-6EC61-0AA0	3VA5320-7EC61-0AA0
225	22	3VA53 2P breaker w/TM230	3VA5322-5EC61-0AA0	3VA5322-6EC61-0AA0	3VA5322-7EC61-0AA0
250	25	3VA53 2P breaker w/TM230	3VA5325-5EC61-0AA0	3VA5325-6EC61-0AA0	3VA5325-7EC61-0AA0
300	30	3VA53 2P breaker w/TM230	3VA5330-5EC61-0AA0	3VA5330-6EC61-0AA0	3VA5330-7EC61-0AA0
350	35	3VA53 2P breaker w/TM230	3VA5335-5EC61-0AA0	3VA5335-6EC61-0AA0	3VA5335-7EC61-0AA0
400	40	3VA53 2P breaker w/TM230	3VA5340-5EC61-0AA0	3VA5340-6EC61-0AA0	3VA5340-7EC61-0AA0

① Although some breakers have a kAIC rating above 100 kAIC – many panels are limited to 100 kAIC or less.

② DC Voltage panels are limited by various factors. These DC ratings apply to the Breaker only.

3VA Breaker Configuration Information in Panelboards

3VA54 Breakers – 2 Pole and 3 Pole

Selection

3VA54 Breakers

3VA54 TMTU 600A max.

- Part numbers shown are without Lugs.
- Standard Lug kits used in Panelboards are shown in tables below.

TMTU frame	Type	kA code	Type ref	MB code
3VA54	MLAS	M	LAS	VJ
3VA54	HLAS	H	LAS	VK
3VA54	CLAS	C	LAS	VL

3 Pole 3VA54 without connectors

The default for Panelboard in COMPAS will be AL 2-conductor connectors:
 for AL order one 3VA9473-0JJ23 (accepts (2) 2/0-600kcmil AL/CU conductors)
 for CU order one 3VA9473-0JE23 (accepts (2) 2/0-600kcmil CU only conductors)
Alternate single conductor lugs are available:
 for AL order one 3VA9473-0JB13 (accepts (1) #1 AWG-600kcmil AL/CU conductors)
 for CU order one 3VA9473-0JD13 (accepts (1) #1 AWG-600kcmil CU only conductors)

3VA54

3-Pole Description

UL Type Code ==>	MLAS	HLAS	CLAS
Panelboard MB codes ==>	VJ	VK	VL
Ratings	3-pole 2-pole	3-pole 2-pole	3-pole 2-pole
240 VAC kAIC rating ==>	85 85	100 100	200 ^① 200 ^①
480Y / 277 VAC kAIC rating ==>	35 35	65 65	100 100
480 VAC kAIC rating ==>	35 35	65 65	100 100
600Y / 347 VAC kAIC rating ==>	18 18	25 25	35 35
600 VAC kAIC rating ==>	18 18	25 25	35 35
250 VDC kAIC rating ^② ==>	na 50	na 85	na 100
IC family @ 480 VAC ==>	35kA	65kA	100kA
FTAM Trip included ==>	TM230	TM230	TM230

Amps	Code	Description	Catalog Number	Catalog Number	Catalog Number
			3-pole	3-pole	3-pole
450	45	3VA54 3P breaker w/TM230	3VA5445-5EC31-0AA0	3VA5445-6EC31-0AA0	3VA5445-7EC31-0AA0
500	50	3VA54 3P breaker w/TM230	3VA5450-5EC31-0AA0	3VA5450-6EC31-0AA0	3VA5450-7EC31-0AA0
600	60	3VA54 3P breaker w/TM230	3VA5460-5EC31-0AA0	3VA5460-6EC31-0AA0	3VA5460-7EC31-0AA0

2 Pole 3VA54 (in 3-Pole frame) without connectors

The default for Panelboard in COMPAS will be AL 2-conductor connectors:
 for AL order one 3VA9473-0JJ23 (accepts (2) 2/0-600kcmil AL/CU conductors)
 for CU order one 3VA9473-0JE23 (accepts (2) 2/0-600kcmil CU only conductors)
Alternate single conductor lugs are available:
 for AL order one 3VA9473-0JB13 (accepts (1) #1 AWG-600kcmil AL/CU conductors)
 for CU order one 3VA9473-0JD13 (accepts (1) #1 AWG-600kcmil CU only conductors)

3VA54

2-Pole Description

Amps	Code	Description	Catalog Number	Catalog Number	Catalog Number
			2-pole	2-pole	2-pole
450	45	3VA54 2P breaker w/TM230	3VA5445-5EC61-0AA0	3VA5445-6EC61-0AA0	3VA5445-7EC61-0AA0
500	50	3VA54 2P breaker w/TM230	3VA5450-5EC61-0AA0	3VA5450-6EC61-0AA0	3VA5450-7EC61-0AA0
600	60	3VA54 2P breaker w/TM230	3VA5460-5EC61-0AA0	3VA5460-6EC61-0AA0	3VA5460-7EC61-0AA0

① Although some breakers have a kAIC rating above 100 kAIC – many panels are limited to 100 kAIC or less.

② DC Voltage panels are limited by various factors. These DC ratings apply to the Breaker only.

3VA Breaker Configuration Information in Panelboards

Internal and External Accessories for 400-600A 3VA Breakers

Selection

Accessories for 3VA53, 3VA63, 3VA54 and 3VA64 breakers

- 3VA53 TMTU 400A max. and 3VA63 ETU 400A max. 3VA54 TMTU 600A max. and 3VA64 ETU 600A max.
- 10 slots max. are available - 5 on each side of trip handle.
- COMPAS will allow only modules that will be allowed in panel being configured.

Description	Quick reference code	Voltage AC max or range	Voltage DC max or range	Accessory Catalog Number ^②	Qty of slots in breaker req'd	Max. Qty. per Brkr	Position to install for 3VA53/63 and 3VA54/64 only									
							Left side pocket					Right side pocket				
							25	24	23	22	21	11	12	13	14	15

Accessories

Internal Accessories Left side preferred Only one per breaker allowed	Shunt trip left -10	STL-10	n/a	12	3VA9978-0BL10	3	1			X						
	Shunt trip left -20	STL-20	380...600	n/a	3VA9978-0BL20	3	1			X						
	Shunt trip left -30	STL-30	24	24...30	3VA9978-0BL30	3	1			X						
	Shunt trip left -31	STL-31	48...60	n/a	3VA9978-0BL31	3	1			X						
	Shunt trip left -32	STL-32	110...127	110...127	3VA9978-0BL32	3	1			X						
	Shunt trip left -33	STL-33	208...277	220...250	3VA9978-0BL33	3	1			X						
	Shunt trip flexible -20	STF-20	24	n/a	3VA9978-0BA20	3	1			X	Right side opt. 3VA6 only					
	Shunt trip flexible -21	STF-21	48...60	n/a	3VA9978-0BA21	3	1			X						
	Shunt trip flexible -22	STF-22	110...127	n/a	3VA9978-0BA22	3	1			X						
	Shunt trip flexible -23	STF-23	208...277	n/a	3VA9978-0BA23	3	1			X						
	Shunt trip flexible -24	STF-24	380...500	n/a	3VA9978-0BA24	3	1			X						
	Shunt trip flexible -25	STF-25	600	n/a	3VA9978-0BA25	3	1			X						
	Undervoltage release -10	UVR-10	n/a	12	3VA9978-0BB10	3	1			X						
	Undervoltage release -11	UVR-11	n/a	24	3VA9978-0BB11	3	1			X						
	Undervoltage release -12	UVR-12	n/a	48	3VA9978-0BB12	3	1			X						
	Undervoltage release -14	UVR-14	n/a	125...127	3VA9978-0BB14	3	1			X						
	Undervoltage release -16	UVR-16	n/a	250	3VA9978-0BB16	3	1			X						
	Undervoltage release -20	UVR-20	24	n/a	3VA9978-0BB20	3	1			X						
	Undervoltage release -24	UVR-24	120...127	n/a	3VA9978-0BB24	3	1			X						
	Undervoltage release -25	UVR-25	208...230	n/a	3VA9978-0BB25	3	1			X						
	Undervoltage release -27	UVR-27	440...480	n/a	3VA9978-0BB27	3	1			X						
Universal release	UNI-11	n/a	12vdc	3VA9978-0BD11	3	1			X							
Universal release	UNI-12	n/a	24vdc	3VA9978-0BD12	3	1			X							
Universal release	UNI-13	n/a	48vdc	3VA9978-0BD13	3	1			X							

Internal Accessories Right or left side options 3VA53/54 and 3VA63/64 (ETU)	Auxiliary switch - standard	AUX_HQ	240VAC	n/a	3VA9978-0AA12	1	6	X	X	X	X	X	X	X	X	X	
	Leading Chg-over SW - standard	LCS_HQ	240VAC	n/a	3VA9978-0AA22	1	1							X			
	Trip alarm (bell alarm) - standard	TAS_HQ	240VAC	250VDC	3VA9978-0AB12	1	4				X	X	X	X			
	Electrical Alarm Switch std. (ETU Only)	EAS_HQ	240VAC	250VDC	3VA9978-0AB22	1	1									X	
	Auxiliary switch - high capacity ^①	AUX_HP	600VAC	n/a	3VA9978-0AA11	2	2		X		X			X	X		
								X		X					X	X	
	Leading Chg-over SW - High Cap ^①	LCS_HP	600VAC	250VDC	3VA9978-0AA21	1	1							X			
	Trip alarm (bell alarm) - High Cap ^①	TAS_HP	600VAC	250VDC	3VA9978-0AB11	2	2					X		X			
	Auxiliary switch - electronic ^④	AUX_HQ_el	24VAC	24VDC	3VA9978-0AA13	1	6	X	X	X	X	X	X	X	X	X	X
	Leading Chg-over SW - electronic ^④	LCS_HQ_el	24VAC	n/a	3VA9978-0AA23	1	1								X		
	Trip alarm (bell alarm) - electronic ^④	TAS_HQ_el	24VAC	24VDC	3VA9978-0AB13	1	4					X	X	X	X		
	Electrical Alarm Switch electronic ^④ (ETU Only)	EAS_HQ_el	24VAC	24VDC	3VA9978-0AB23	1	1										X
	Ronis adapter FOR 3VA63/64	Ronis Adapter	n/a	n/a	3VA9347-0LF10	4	1									X	
Cylinder Lock (type Ronis) Key 1	Ronis Key 1	n/a	n/a	3VA9980-0VL10	one per adapt- er	one per adapt- er									installs in adapter above		
Cylinder Lock (type Ronis) Key 2	Ronis Key 2	n/a	n/a	3VA9980-0VL20													
Cylinder Lock (type Ronis) Key 3	Ronis Key 3	n/a	n/a	3VA9980-0VL30													
Cylinder Lock (type Ronis) Key 4	Ronis Key 4	n/a	n/a	3VA9980-0VL40													

- ① High capacity/power (HP) max. Amps load capacity is higher than standard module (.55A up to 6.0A) depends on Voltage and AC/DC requirements - see SpeedFax section 7 or 3VA documentation for more information.
- ② Many accessories available for the 3VA5 and 3VA6 breakers may not be suitable for use in Lighting Panelboards.
- COMPAS allows options that are available. All accessories listed above can be used with Panelboards in general, but there will be exceptions.

- ③ Lugs are NOT supplied with loose breaker as standard - must order separately or configure in COMPAS to include lugs.
- Factory assembled panels include AL lugs as standard, CU lugs are optional. These kits include 3 connectors and hardware.
- ④ Special electronically-compatible (el) variants are available for applications that require the auxiliary switch signals to be linked to low voltage systems.
- May need special Mod in COMPAS.

3VA Breaker Configuration Information in Panelboards

Internal and External Accessories for 400-600A 3VA Breakers

Selection

Description	Quick reference code	Voltage AC max or range	Voltage DC max or range	Accessory Catalog Number ^②	Qty of slots in breaker req'd	Max. Qty. per Brkr	Position to install for 3VA53/63 and 3VA54/64 only									
							Left side pocket					Right side pocket				
							25	24	23	22	21	11	12	13	14	15

Accessories (continued)

Internal Accessories 3VA63/64 (ETU) only	Pocket reference # ==>							Left side pocket					Right side pocket				
								25	24	23	22	21	11	12	13	14	15
	Communications Module - 3VA63/64	COM060	n/a	24VDC	3VA9377-0TB10	4	1										
	COM060-to-T-Connector ext. cable 0.4 m	COM060-to-T	n/a	n/a	3VA9987-0TF20	n/a	n/a										
	COM060-to-T-Connector ext. cable 0.8 m	COM060-to-T	n/a	n/a	3VA9987-0TF10	n/a	n/a										

External [®] Accessories and Field Kits	#1-600 kcmil AL wire connector Kit [®]	AL-lug	n/a	n/a	3VA9373-0JB13	TMTU or ETU 600A max.		Line or Load end as needed
	#1-600 kcmil CU wire connector Kit [®]	CU-lug	n/a	n/a	3VA9373-0JD13			
	2/0-600 kcmil AL 2 port connector Kit [®]	AL-2lug	n/a	n/a	3VA9473-0JJ23			
	2/0-600 kcmil CU 2 port connector Kit [®]	CU-2lug	n/a	n/a	3VA9473-0JE23			
	Compression Lugs (future offering - details tbd)	tbd	n/a	n/a	tbd	n/a	n/a	availability and usage locations tbd
	3VA53/63 or 54/64 PadLock Device	tbd	n/a	n/a	3VA9338-0LB11	n/a	n/a	
	M0320 Motor Operator - 24-60V DC	M0320	n/a	24-60V	3VA9277-0HA10	n/a	1	P4/P5 only
	M0320 Motor Operator - 110-230V AC or 110-250V DC	M0320	110-230V	110-250V	3VA9277-0HA20	n/a	1	P4/P5 only
	COM100 and COM800 modules and cables can be found on Communications Tables with ETU Breakers earlier in this section.							

① High capacity/power (HP) max. Amps load capacity is higher than standed module (.55A up to 6.0A) depends on Voltage and AC/DC requirements - see SpeedFax section 7 or 3VA documentation for more information.

② Many accessories available for the 3VA5 and 3VA6 breakers may not be suitable for use in Lighting Panelboards.

– COMPAS allows options that are available. All accessories listed above can be used with Panelboards in general, but there will be exceptions."

③ Lugs are NOT supplied with loose breaker as standard - must order separately or configure in COMPAS to include lugs.

– Factory assembled panels include AL lugs as standard, CU lugs are optional. These kits include 3 connectors and hardware.

④ Special electronically-compatible (el) variants are available for applications that require the auxiliary switch signals to be linked to low voltage systems.

– May need special Mod in COMPAS.

Panelboards

Type P4 Panelboards

General

Features

The P4 panel has a medium sized footprint and fits a larger number of applications that require larger branch devices and higher amp ratings than what the lighting panel class offers. Even with the increased capacity, this panel is a space saver with its 32" width and 10" depth. The P4 panel offers a wide array of factory-assembled options and has the ability to mix breaker frames in unit space up to 800 amps and fusible switches up to 200 amps. Bussing options for the P4 vary from the standard temperature rated aluminum to temperature rated copper and 750A/SI aluminum and 1000A/SI copper designs. All aluminum bussing in the P4 panel is tin-plated as a standard. Silver-plated is offered as the default for copper bus and tin as an option. Integrated time clocks, bus mounted contactors as mains or submains, split bus and subfeed lugs (up to 600 amp) are just a few of the options of this flexible panel.

The 3 panel configurations defined by the unit space allowed for a given amperage, main device and box height. The P4 panel starts with a 60" high box. All of the branch devices are unit space mounted. Breakers and switches can be mixed and matched to meet customer requirements.

Main Lug / Main Breaker

Enclosure – Standard Type 1 enclosure is 32" wide x 10" deep. The Box Height is determined by main device and unit space. See charts for box height. Voltage – 600V AC max. 250V DC max.

Amperage – 400-800 amp main breaker or 400-1200 amp main lug only.

Short Circuit Rating – 200 KAIC max. symmetrical or equal to the lowest rated device installed unless a series rating is indicated. Panels with subfeed or feed-thru lugs without a main device, circuit breaker or fusible unit, are limited to a three-cycle rating. The three-cycle rating for the P4 panel is limited to 42 KAIC. Note that the main device may be mounted remote from the panel.

Bussing – The P4 panel has more options to meet market requirements. The standard bussing is temperature rated aluminum. The rating is per the requirements of UL 67 – the standard for panelboards. All aluminum bussing is tin-plated. Optional bussing for the P4 panel is: 750 A/SI aluminum, temperature rated copper, and 1000 A/SI copper. The copper bus option for this panel is silver-plated.

Weight – Approximate

Total panelboard weight when filled with a normal quantity of breakers and accessories is about 8 lbs. (1 kg) per inch (54g per mm) of box height.

Main Lugs^①

Ampere Rating	Connectors Suitable for Copper or Aluminum
400	(1) - #3/0 AWG-500 kcmil (2) - #3/0 AWG-250 kcmil
600	(2) - #3/0 AWG-500 kcmil
800	(3) - #3/0 AWG-500 kcmil
1000	(4) - #3/0 AWG-500 kcmil
1200	(4) - #3/0 AWG-500 kcmil

^① Alternate lugs for 750 kcmil cable are available, but result in significant loss of branch unit mounting space. Consult Siemens.

Gauge Steel of Boxes Fronts, Surface and Flush

Dimensions in inches (mm)		Gauge Steel	
Width	Height	Box	Fronts
32" (813)	60 - 75 - 90 (1524, 1905, 2286)	#16 ^①	#14 (1 piece trim) #14 Ga (4 piece trim)
		#12	#12 (1 piece trim, door in door)
		#10	#10 (1 piece door trim in)
		#16	#16 (4 piece trim)


^① Box has 16 gauge side panels, 14 gauge backplates and 12 gauge back support.

Enclosure Selection^①

Enclosure Dimension in Inches (mm)			Available Circuit Space in Inches (mm) Dimension "C"	
H	W	D	Main Lug	Main Breaker
Type 1 and Type 3R/12			400-800A	400-800A
60 (1524)	32 (813)	10 (254)	30 (762)	21.25 (540)
75 (1905)	32 (813)	10 (254)	45 (1143)	36.25 (921)
90 (2286)	32 (813)	10 (254)	60 (1524)	51.25 (1302)

Main Breaker Unit Space Dimensions

Ampere Rating	Breaker Type	Breaker Family	Dimensions in Inches (mm)	
			A	B
400	JXD6, JD6, HJXD6, HJD6, HHJXD6, HHJD6	Sentron	10.425 (265)	13.125 (333)
400	NJ, HJ, LJ ^②	VL	12.500 (318)	
400	SJD6, SHJD6	Sentron	10.425 (265)	
400	CJD6, SCJD6	Sentron	8.250 (210)	
600	LXD6, LD6, HLXD6, HLD6, HHLXD6, HHLD6	Sentron	10.425 (265)	
600	NL, HL, LL ^②	VL	11.250 (286)	
600	SLD6, SHLD6	Sentron	10.425 (265)	
600	CLD6, SCLD6	Sentron	8.250 (210)	
800	NM, HM, LM	VL	10.500 (267)	



^① Standard trim is four piece without door. Surface or flush one piece trim is available for 32 in. (813 mm) wide circuit breaker panel.

^② Solid state (electronic) trip units only.

Panelboards

Type P4 Panelboards


Dimensions

Main Breaker Selection

Ampere Rating	Trip Type	Breaker Family	Frame Type	Maximum Interruption Rating (KAIC)			Unit Space Requirements in Inches (mm)	Trip Amperage
				240V	480V	600V		
400	Thermal Magnetic	Sentron	JXD6, JD6	65,000	35,000	25,000	8.75 (222)	200, 225, 250, 300, 350, 400
			HJXD6, HJD6	100,000	65,000	35,000	8.75 (222)	200, 225, 250, 300, 350, 400
			HHJXD6, HHJD6	200,000	100,000	50,000	8.75 (222)	200, 225, 250, 300, 350, 400
			CJD6	200,000	150,000	100,000	8.75 (222)	200, 225, 250, 300, 350, 400
	Electronic (Solid state)	VL	NJ	65,000	35,000	25,000	6.25 (159)	250, 400
			HJ	100,000	65,000	25,000	6.25 (159)	250, 400
			LJ	200,000	100,000	25,000	6.25 (159)	250, 400
		Sentron	SJD6	65,000	35,000	25,000	8.75 (222)	200, 300, 400
			SHJD6	100,000	65,000	35,000	8.75 (222)	200, 300, 400
			SCJD6	200,000	150,000	100,000	8.75 (222)	200, 300, 400
600	Thermal Magnetic	Sentron	LXD6	65,000	35,000	25,000	8.75 (222)	450, 500, 600
			LD6	65,000	35,000	25,000	8.75 (222)	250, 300, 350, 400, 450, 500, 600
			HLXD6, HLD6	100,000	65,000	35,000	8.75 (222)	250, 300, 350, 400, 450, 500, 600
			HHLXD6, HHL6	200,000	100,000	50,000	8.75 (222)	250, 300, 350, 400, 450, 500, 600
			CLD6	200,000	150,000	100,000	8.75 (222)	250, 300, 350, 400, 450, 500, 600
	Electronic (Solid state)	VL	NL	65,000	35,000	25,000	6.25 (159)	400, 600
			HL	100,000	65,000	25,000	6.25 (159)	400, 600
			LL	200,000	100,000	25,000	6.25 (159)	400, 600
		Sentron	SLD6	65,000	35,000	25,000	8.75 (222)	300, 400, 500, 600
			SHLD6	100,000	65,000	35,000	8.75 (222)	300, 400, 500, 600
			SCLD6	200,000	150,000	100,000	8.75 (222)	300, 400, 500, 600
800	Thermal Magnetic	VL	NM	65,000	35,000	25,000	8.75 (222)	600, 700, 800
			HM	100,000	65,000	35,000	8.75 (222)	600, 700, 800
			LM	200,000	100,000	50,000	8.75 (222)	600, 700, 800
	Electronic (Solid state)	VL	NM	65,000	35,000	25,000	8.75 (222)	600, 800
			HM	100,000	65,000	35,000	8.75 (222)	600, 800
			LM	200,000	100,000	50,000	8.75 (222)	600, 800

Main Lugs Only Wire Bending Space

Lugs	Dimensions in inches (mm)						
	Main Lug					Neutral	
	400A A	600A B	800A C	1000A D	1200A E	400-600A F	800-1200A G
Standard	16.500 (419)	16.750 (419)	15.969 (406)	15.969 (406)	15.969 (406)	13.125 (333)	13.125 (333)
Oversize	16.500 (419)	21.750 (552)	25.969 (660)	25.969 (660)	25.969 (660)	18.125 (460)	23.125 (587)
Crimp	19.187 (487)	18.250 (464)	18.687 (475)	18.250 (464)	18.250 (464)	15.937 (405)	15.937 (405)
Standard w/Subfeed	16.750 (425)	15.969 (406)	—	—	—	13.125 (333)	13.125 (333)
Standard w/Feed-thru	16.500 (419)	16.750 (419)	—	—	—	13.125 (333)	13.125 (333)



Branch Switch Unit Space

Ampere Rating	Number of Poles	Mounting Height in inches (mm)		AC Voltage	Cables Per Connector	Connectors Suitable for Copper or Aluminum
		Twin Mounted	Single Mounted			
30-30	2, 3	2.50 (64)	—	240	1	#14 - #8 AWG (Cu Only)
30-30	2, 3	5.00 (127)	—	240	1	#14 - #4 AWG
30-60	2, 3	5.00 (127)	—	240	1	#14 - #4 AWG
60-60	2, 3	5.00 (127)	—	240	1	#14 - #4 AWG
60-100	2, 3	7.50 (191)	—	240	1	#10 - #1/0 AWG
100-100	2, 3	7.50 (191)	—	240	1	#10 - #1/0 AWG
200-200	3	10.00 (254)	—	240	1	#6 AWG - 350 kcmil
200	2	—	7.50 (191)	240	1	#6 AWG - 350 kcmil
200	3	—	10.00 (254)	240	2	#6 AWG - 350 kcmil
30-30	2, 3	7.5 (191)	—	600	1	#14 - #8 AWG
30-60	2, 3	7.5 (191)	—	600	1	#14 - #4 AWG
60-60	2, 3	7.5 (191)	—	600	1	#14 - #4 AWG
60-100	2, 3	7.5 (191)	—	600	1	#10-#1/0 AWG
100-100	2, 3	7.5 (191)	—	600	1	#10-#1/0 AWG
200-200	3	10.00 (254)	—	600	1	#6 AWG - 250 kcmil
100	2, 3	—	7.50 (191)	600	1	#10-#1/0 AWG
200	2, 3	—	10.00 (254)	600	1	#6 AWG - 250 kcmil

Panelboards

Type P4 Panelboards

Dimensions

Branch Breaker Side Gutter Inches (mm)

Reference Letter	Panel Width 32 Inches Dimensions in inches (mm)
A	11.0 (279)
B	10.98 (279)
C	8.62 (219)
D	7.0 (178)
E	5.75 (146)
F	5.25 (133)
H	4.62 (117)
I	8.76 (223)
J	10.42 (265)
K	10.0 (254)
L	8.25 (210)
M	10.0 (254)
N	7.0 (178)
O	5.0 (127)
P	7.50 (191)
Q	7.9 (200)
R	7.9 (200)
S	12.5 (318)
T	11.25 (286)
AA	7.06 (179)
AB	6.55 (166)
AC	6.55 (166)

← A →	BL, BLH, HBL, BQD, BLE, BLEH, BLR, BLF2, BLHF2, HBLF2, BLFB, BLHFB, BAF, BAHF, BGL, BQD	BL, BLH, HBL, BQD, BLE, BLEH, BLR, BLF2, BLHF2, HBLF2, BLFB, BLHFB, BAF, BAHF, BGL, BQD	← A →
← B →	NGB, HGB, LGB NGB2, HGB2, LGB2	NGB, HGB, LGB NGB2, HGB2, LGB2	← B →
← D →	ED4, ED6, HED4	ED4, ED6, HED4	← D →
← H →	CED	CED	← H →
← E →	QR2, QRH2, HQR2, HQR2H	QR2, QRH2, HQR2, HQR2H	← E →
← F →	FXD6, FD6, HFXD6, HFD6, HHFXD6, HHFD6, SFD6, SHFD6	FXD6, FD6, HFXD6, HFD6, HHFXD6, HHFD6, SFD6, SHFD6	← F →
← AA →	3VA52 – [MFAS, HFAS, CFAS]	3VA52 – [MFAS, HFAS, CFAS]	← AA →
← Q →	ND, HD, LD	ND, HD, LD	← Q →
← AB →	3VA61 – [MDAE, HDAE, CDAE, LDAE]	3VA61 – [MDAE, HDAE, CDAE, LDAE]	← AB →
← R →	NF, HF, LF	NF, HF, LF	← R →
← AC →	3VA62 – [MFAE, HFAE, CFAE, LFAE]	3VA62 – [MFAE, HFAE, CFAE, LFAE]	← AC →
← I →	CFD6, SCFD6		← I →
← J →	JD6, JXD6, SJD6, HJD6, HXJD6, SHJD6, HHJD6, HHJXD6, LD6, LXD6, SLD6, HLD6, HXLD6, SHLD6, HHLD6, HHLXD6		← J →
← L →	CJD6, SCJD6, CLD6, SCLD6		← L →
← S →	NJ, HJ, LJ		← S →
← T →	NL, HL, LL		← T →
← K →	NM, HM, LM		← K →
← M →	VB 30A, VB 60A (5")	VB 30A, VB 60A (5")	← M →
← N →	VB 30A, VB 60A (5")	VB 30A, VB 60A (5")	← N →
← O →	VB 100 - 200A	VB 100 - 200A	← O →
← P →	VB 100 - 200A Single		← P →

Type P4

Shown with Standard Mains, Top Fed and Surface Trim

Catalog number is for aluminum main bus. For optional copper main bus change "A" in position 11 to "E" (silver-plated copper bus).

Panels are top feed, surface mounted. For bottom feed, change "T" in position 12 to "B". For flush mounting, change "S" in position 13 to "F".

Replace fifth and sixth position in panelboard catalog number, with alternate main breaker code. Use price adders from main breaker section table. Horizontally mounted.

Main Lugs Only — shown with aluminum bus, top fed, and surface trims.

Maximum Panel Amps	Unit Space (inches)	208Y/120V	240/120V	120/240V or 250 V DC Max
		3-Phase, 4-Wire Catalog Number	3-Phase, 4-Wire Catalog Number	1-Phase, 3-Wire Catalog Number
400	30	P4C60ML400ATS	P4B60ML400ATS	P4A60ML400ATS
	45	P4C75ML400ATS	P4B75ML400ATS	P4A75ML400ATS
	60	P4C90ML400ATS	P4B90ML400ATS	P4A90ML400ATS
600	30	P4C60ML600ATS	P4B60ML600ATS	P4A60ML600ATS
	45	P4C75ML600ATS	P4B75ML600ATS	P4A75ML600ATS
	60	P4C90ML600ATS	P4B90ML600ATS	P4A90ML600ATS
800	30	P4C60ML800ATS	P4B60ML800ATS	P4A60ML800ATS
	45	P4C75ML800ATS	P4B75ML800ATS	P4A75ML800ATS
	60	P4C90ML800ATS	P4B90ML800ATS	P4A90ML800ATS
1000	30	P4C60ML101ATS	P4B60ML101ATS	P4A60ML101ATS
	45	P4C75ML101ATS	P4B75ML101ATS	P4A75ML101ATS
	60	P4C90ML101ATS	P4B90ML101ATS	P4A90ML101ATS
1200	30	P4C60ML120ATS	P4B60ML120ATS	P4A60ML120ATS
	45	P4C75ML120ATS	P4B75ML120ATS	P4A75ML120ATS
	60	P4C90ML120ATS	P4B90ML120ATS	P4A90ML120ATS
Maximum Panel Amps	Unit Space (inches)	240V	480Y/277V	480V ^①
		3-Phase, 3-Wire Catalog Number	3-Phase, 4-Wire Catalog Number	3-Phase, 3-Wire Catalog Number
400	30	P4D60ML400ATS	P4E60ML400ATS	P4F60ML400ATS
	45	P4D75ML400ATS	P4E75ML400ATS	P4F75ML400ATS
	60	P4D90ML400ATS	P4E90ML400ATS	P4F90ML400ATS
600	30	P4D60ML600ATS	P4E60ML600ATS	P4F60ML600ATS
	45	P4D75ML600ATS	P4E75ML600ATS	P4F75ML600ATS
	60	P4D90ML600ATS	P4E90ML600ATS	P4F90ML600ATS
800	30	P4D60ML800ATS	P4E60ML800ATS	P4F60ML800ATS
	45	P4D75ML800ATS	P4E75ML800ATS	P4F75ML800ATS
	60	P4D90ML800ATS	P4E90ML800ATS	P4F90ML800ATS
1000	30	P4D60ML101ATS	P4E60ML101ATS	P4F60ML101ATS
	45	P4D75ML101ATS	P4E75ML101ATS	P4F75ML101ATS
	60	P4D90ML101ATS	P4E90ML101ATS	P4F90ML101ATS
1200	30	P4D60ML120ATS	P4E60ML120ATS	P4F60ML120ATS
	45	P4D75ML120ATS	P4E75ML120ATS	P4F75ML120ATS
	60	P4D90ML120ATS	P4E90ML120ATS	P4F90ML120ATS

Main Circuit Breaker — shown with standard mains, aluminum bus, top fed, and surface trims.

Maximum Panel Amps	Unit Space (inches)	208Y/120V	240/120V	120/240V or 250 Vdc Max
		3-Phase, 4-Wire Catalog Number	3-Phase, 4-Wire Catalog Number	1-Phase, 3-Wire Catalog Number
400	21.25	P4C60JX400ATS	P4B60JX400ATS	P4A60JX400ATS
	36.25	P4C75JX400ATS	P4B75JX400ATS	P4A75JX400ATS
	51.25	P4C90JX400ATS	P4B90JX400ATS	P4A90JX400ATS
600	21.25	P4C60LX600ATS	P4B60LX600ATS	P4A60LX600ATS
	36.25	P4C75LX600ATS	P4B75LX600ATS	P4A75LX600ATS
	51.25	P4C90LX600ATS	P4B90LX600ATS	P4A90LX600ATS
800	21.25	P4C60M1800ATS	P4B60M1800ATS	P4A60M1800ATS
	36.25	P4C75M1800ATS	P4B75M1800ATS	P4A75M1800ATS
	51.25	P4C90M1800ATS	P4B90M1800ATS	P4A90M1800ATS
Maximum Panel Amps	Unit Space (inches)	240V	480Y/277V	480V ^①
		3-Phase, 3-Wire Catalog Number	3-Phase, 4-Wire Catalog Number	3-Phase, 3-Wire Catalog Number
400	21.25	P4D60JX400ATS	P4E60JX400ATS	P4F60JX400ATS
	36.25	P4D75JX400ATS	P4E75JX400ATS	P4F75JX400ATS
	51.25	P4D90JX400ATS	P4E90JX400ATS	P4F90JX400ATS
600	21.25	P4D60LX600ATS	P4E60LX600ATS	P4F60LX600ATS
	36.25	P4D75LX600ATS	P4E75LX600ATS	P4F75LX600ATS
	51.25	P4D90LX600ATS	P4E90LX600ATS	P4F90LX600ATS
800	21.25	P4D60M1800ATS	P4E60M1800ATS	P4F60M1800ATS
	36.25	P4D75M1800ATS	P4E75M1800ATS	P4F75M1800ATS
	51.25	P4D90M1800ATS	P4E90M1800ATS	P4F90M1800ATS

① For 600V application, change "F" in position 3 to "G". See alternate main breaker table on page 11-89 for 600V rated mains. Change position 5 and 6 and add price from table. Price only 600V rated branch breakers.

Panelboards

Power and Distribution

Selection

Type P4

Alternate Main Breaker Selection

Breaker Frame Rating	Trip Type	Breaker Family	Frame Type	Type Reference Code	Trip Amperage	Unit Space Requirements in Inches	Maximum Interruption Rating (KAIC) Volts AC		
							240	480	600
400	Thermal Magnetic	Sentron	JXD6	JX	200, 225, 250, 300, 350, 400	8.75	65,000	35,000	25,000
			JD6	J6	200, 225, 250, 300, 350, 400	8.75	65,000	35,000	25,000
			HJXD6	H5	200, 225, 250, 300, 350, 400	8.75	100,000	65,000	35,000
			HJD6	H6	200, 225, 250, 300, 350, 400	8.75	100,000	65,000	35,000
			HHJXD6	H9	200, 225, 250, 300, 350, 400	8.75	200,000	100,000	50,000
			HHJD6	6H	200, 225, 250, 300, 350, 400	8.75	200,000	100,000	50,000
			CJD6	CJ	200, 225, 250, 300, 350, 400	8.75	200,000	150,000	100,000
	Electronic (Solid state)	VL	NJ	J1	250, 400	6.25	65,000	35,000	25,000
			HJ	J7	250, 400	6.25	100,000	65,000	25,000
			LJ	J3	250, 400	6.25	200,000	100,000	25,000
		Sentron	SJD6	SJ	200, 300, 400	8.75	65,000	35,000	25,000
			SHJD6	SX	200, 300, 400	8.75	100,000	65,000	35,000
			SCJD6	SC	200, 300, 400	8.75	200,000	150,000	100,000
			LXD6	LX	450, 500, 600	8.75	65,000	35,000	25,000
600	Thermal Magnetic	Sentron	LD6	L6	250, 300, 350, 400, 450, 500, 600	8.75	65,000	35,000	25,000
			HLXD6	HO	250, 300, 350, 400, 450, 500, 600	8.75	100,000	65,000	35,000
			HLD6	HL	250, 300, 350, 400, 450, 500, 600	8.75	100,000	65,000	35,000
			HHLXD6	XH	250, 300, 350, 400, 450, 500, 600	8.75	200,000	100,000	50,000
			HHLD6	HH	250, 300, 350, 400, 450, 500, 600	8.75	200,000	100,000	50,000
			CLD6	CL	250, 300, 350, 400, 450, 500, 600	8.75	200,000	150,000	100,000
			NL	L7	400, 600	6.25	65,000	35,000	25,000
	Electronic (Solid state)	VL	HL	L2	400, 600	6.25	100,000	65,000	25,000
			LL	SL	400, 600	6.25	200,000	100,000	25,000
			SLD6	L6	300, 400, 500, 600	8.75	65,000	35,000	25,000
		Sentron	SHLD6	S2	300, 400, 500, 600	8.75	100,000	65,000	35,000
			SCLD6	SI	300, 400, 500, 600	8.75	200,000	150,000	100,000
			NM	M1	600, 700, 800	8.75	65,000	35,000	25,000
			HM	M2	600, 700, 800	8.75	100,000	65,000	35,000
800	Thermal Magnetic	VL	LM	M3	600, 700, 800	8.75	200,000	100,000	50,000
			LMXD6	LM	500, 600, 700, 800	8.75	65,000	50,000	25,000
			LMD6	L1	500, 600, 700, 800	8.75	65,000	50,000	25,000
		Sentron	HLMXD6	HK	500, 600, 700, 800	8.75	100,000	65,000	50,000
			HLMD6	HJ	500, 600, 700, 800	8.75	100,000	65,000	50,000
			NM	M1	600, 800	8.75	65,000	35,000	25,000
			HM	M2	600, 800	8.75	100,000	65,000	35,000
	Electronic (Solid state)	VL	LM	M3	600, 800	8.75	200,000	100,000	50,000

For inches / millimeters conversion, see Application Data section.

Panelboards

Power and Distribution

Selection

 11
 PANELBOARDS

P4 Branch Circuit Breakers

P4 Branch Circuit Breakers																		S = Single Mount					
Amp Rating	Trip Type	Breaker Family	Breaker Type	1-Pole					2-Pole and 3-Pole										S	T = Twin mount			
				Max IR (kA) at				Amp Ratings Avail.	Max IR (kA) at											Amp Ratings Avail.	T	Unit Space per Kit (in.)	Max 1-pole Circuits per Kit
				120V	277V	347V	125V DC		120/240V	240V	480Y/277V	480V	600Y/347V	600V	125/250V DC	250V DC							
100	Thermal Magnetic	BL	BL	10	—	—	—	15-70	10	10	—	—	—	—	—	—	15-100 ^④	—	T	3.75 ^⑤	6		
			BLH	22	—	—	—	15-70	22	22	—	—	—	—	—	—	15-100 ^④	—	T	3.75 ^⑤	6		
			HBL	65	—	—	—	15-50	65	65	—	—	—	—	—	—	15-100	—	T	3.75 ^⑤	6		
	Special Application	BLG BL	BLG ^①	10	—	—	—	15-20	10	—	—	—	—	—	—	—	30	—	T	3.75 ^⑤	6		
BL (HID)			10	—	—	—	15-30	10	—	—	—	—	—	—	—	15-30	—	T	3.75 ^⑤	6			
	Thermal Magnetic	BQD	BQD ^⑥	65	14	—	14	15-100	—	65	14	—	—	—	14	—	15-100	—	T	3.75 ^⑤	6		
			BQD6 ^⑦	65	—	—	14	15-70	—	65	—	—	10	—	14	—	15-70	—	T	3.75 ^⑤	6		
xx	Electronic and misc.	BL	AFCI/ GFCI & Dual Function	x	—	—	—	see special table page 11-13	x	—	—	—	—	—	—	—	see special table page 11-13	—	T	3.75 ^⑤	6		
125	Thermal Magnetic	GB	NGB	100	25	14	14	15-125	—	100	25	—	14	—	14	—	15-125	—	T	3.75 ^⑤	6		
			HGB	100	35	14	14	15-125	—	100	35	—	14	—	14	—	15-125	—	T	3.75 ^⑤	6		
			LGB	100	65	14	14	15-125	—	100	65	—	14	—	14	—	15-125	—	T	3.75 ^⑤	6		
		Sentron	ED4	—	22	—	30	15-100	—	65	—	18	—	—	—	30	15-125	—	T	3.75 ^⑤	6		
			ED6	—	—	—	—	—	—	65	—	25	—	18	—	30	20-125	—	T	3.75 ^⑤	6		
			HED4 ^②	—	—	—	—	—	—	65	—	42	—	18	—	30	15-125	—	T	3.75 ^⑤	6		
			HHED6	—	—	—	—	—	—	100	—	65	—	18	—	—	15-50	—	T	3.75 ^⑤	6		
		GB2	NGB2	100	25	14	14 ^④	15-125	—	100	—	25	14	—	14 ^④	—	15-125	—	T	3.75 ^⑤	6		
			HGB2	100	35	22	14 ^④	15-125	—	100	—	35	22	—	14 ^④	—	15-125	—	T	3.75 ^⑤	6		
			LGB2	100	65	25	14 ^④	15-125	—	100	—	65	25	—	14 ^④	—	15-125	—	T	3.75 ^⑤	6		
		3VA41 ^③	info not yet avail-able	x	x	x	x	x	x	x	x	x	—	x	—	—	x					6	
				x	x	x	x	x	x	x	x	x	—	x	—	—	x					6	
150	Electronic (Solid state)	VL	ND	—	—	—	—	—	—	65	—	35	18	—	—	—	60-150	—	T	5.00	6		
			HD	—	—	—	—	—	—	100	—	65	20	—	—	—	60-150	—	T	5.00	6		
			LD	—	—	—	—	—	—	200	—	100	25	—	—	—	60-150	—	T	5.00	6		
	Electronic (Solid state)	3VA61 ^③ (ETU350 LSI standard)	MDAE	—	—	—	—	—	—	100	35	35	18	18	—	—	40-150	—	T	5.00	6		
			HDAE	—	—	—	—	—	—	100	65	65	22	22	—	—	40-150	—	T	5.00	6		
			CDAE	—	—	—	—	—	—	200	100	100	35	35	—	—	40-150	—	T	5.00	6		
LDAE	—	—	—	—	—	—	200	150	150	50	50	—	—	40-150	—	T	5.00	6					
225	Thermal Magnetic	General Application	QR2	—	—	—	—	—	—	10	—	—	—	—	—	—	100-225	—	T	5.00	6		
			QRH2	—	—	—	—	—	—	25	—	—	—	—	—	—	100-225	—	T	5.00	6		
			HQR2	—	—	—	—	—	—	65	—	—	—	—	—	—	100-225	—	T	5.00	6		
			HQR2H	—	—	—	—	—	—	100	—	—	—	—	—	—	100-225	—	T	5.00	6		
250	Thermal Magnetic	Sentron	FXD6, FD6	—	—	—	—	—	—	65	—	35	—	22	—	30	70-250	S	T	5.00	3 or 6		
			HFXD6, HFD6	—	—	—	—	—	—	100	—	65	—	25	—	30	70-250	S	T	5.00	3 or 6		
			HHFXD6, HHFD6	—	—	—	—	—	—	200	—	100	—	25	—	—	70-250	S	T	5.00	3 or 6		
			CFD6	—	—	—	—	—	—	200	—	200	—	100	—	30	70-250	S	-	5.00	3		
	Electronic (Solid state)	VL	NF	—	—	—	—	—	—	65	—	35	18	—	—	—	100-250	S	T	5.00	3 or 6		
			HF	—	—	—	—	—	—	100	—	65	20	—	—	—	100-250	S	T	5.00	3 or 6		
			LF	—	—	—	—	—	—	200	—	100	25	—	—	—	100-250	S	T	5.00	3 or 6		
	Thermal Magnetic	3VA52 ^③ (W/TM230 trip)	MFAS	—	—	—	—	—	85	85	—	35	—	18	—	50	100-250	—	T	5.00	6		
			HFAS	—	—	—	—	—	100	100	—	65	—	25	—	85	100-250	—	T	5.00	6		
			CFAS	—	—	—	—	—	200	200	—	100	—	35	—	100	100-250	—	T	5.00	6		
	Electronic (Solid state)	3VA62 ^③ (ETU350 LSI standard)	MFAE	—	—	—	—	—	—	100	35	35	18	—	—	—	100-250	—	T	5.00	6		
			HFAE	—	—	—	—	—	—	100	65	65	22	—	—	—	100-250	—	T	5.00	6		
CFAE			—	—	—	—	—	—	200	100	100	35	—	—	—	100-250	—	T	5.00	6			
LFAE			—	—	—	—	—	—	200	150	150	50	—	—	—	100-250	—	T	5.00	6			

① BLG two-pole breaker is one phase and neutral. Three pole is two phases and neutral - See SpeedFax page 7-31
 ② 1-pole HED 15-30A rated 65kA; 35-100A rated 25kA; 3-pole HED rated 42kA

③ Availability and additional specs tbd, expected late 2019. (COMPAS may allow selection of alternate trip units)
 ④ 2-pole only or two outer poles of 3-pole breaker

⑤ Accessories such as shunt trips on 3 pole breakers require 6.25" of unit space
 ⑥ Approved for CSA and UL Listed.
 ⑦ Approved for CSA but not UL Listed.

Panelboards

Power and Distribution

Selection

P4 Branch Circuit Breakers (cont.)

P4 Branch Circuit Breakers (cont.)				1-Pole		2-Pole and 3-Pole													S = Single Mount			
Amp Rating	Trip Type	Breaker Family	Breaker Type	Max IR (kA) at				Amp Ratings Avail.	Max IR (kA) at								Amp Ratings Avail.	S	T = Twin mount			
				120V	277V	347V	125V DC		120/ 240V	240V	480Y/ 277V	480V	600Y/ 347V	600V	125/ 250V DC	250V DC			Unit Space per Kit (in.)	Max 1-pole Circuits per Kit		
400	Thermal Magnetic	Sentron	JXD6, JD6	—	—	—	—	—	—	65	—	35	—	25	—	30	200-400	S	—	8.75	3	
			HJXD6, HJD6	—	—	—	—	—	—	100	—	65	—	35	—	30	200-400	S	—	8.75	3	
			HHJXD6, HHJD6	—	—	—	—	—	—	200	—	100	—	50	—	—	200-400	S	—	8.75	3	
			CJD6	—	—	—	—	—	—	200	—	150	—	100	—	30	200-400	S	—	8.75	3	
	Electronic (Solid state)	VL	NJ	—	—	—	—	—	—	65	—	35	—	25	—	—	250-400	S	—	6.25	3	
			HJ	—	—	—	—	—	—	100	—	65	—	25	—	—	250-400	S	—	6.25	3	
			LJ	—	—	—	—	—	—	200	—	100	—	25	—	—	250-400	S	—	6.25	3	
		Sentron	SJD6	—	—	—	—	—	—	65	—	35	—	25	—	—	200-400	S	—	8.75	3	
SHJD6	—		—	—	—	—	—	100	—	65	—	35	—	—	200-400	S	—	8.75	3			
SCJD6	—		—	—	—	—	—	200	—	100	—	100	—	—	200-400	S	—	8.75	3			
600	Thermal Magnetic	Sentron	LXD6	—	—	—	—	—	—	65	—	35	—	25	—	30	450-600	S	—	8.75	3	
			LD6	—	—	—	—	—	—	65	—	35	—	25	—	30	250-600	S	—	8.75	3	
			HLXD6, HLD6	—	—	—	—	—	—	100	—	65	—	35	—	30	250-600	S	—	8.75	3	
			HHLXD6, HHL6	—	—	—	—	—	—	200	—	100	—	50	—	—	250-600	S	—	8.75	3	
	Electronic (Solid state)	VL	NL	—	—	—	—	—	—	65	—	35	—	18	—	—	400-600	S	—	6.25	3	
			HL	—	—	—	—	—	—	100	—	65	—	18	—	—	400-600	S	—	6.25	3	
			LL	—	—	—	—	—	—	200	—	100	—	18	—	—	400-600	S	—	6.25	3	
		Sentron	SLD6	—	—	—	—	—	—	65	—	35	—	25	—	—	300-600	S	—	8.75	3	
SHLD6	—		—	—	—	—	—	100	—	65	—	35	—	—	300-600	S	—	8.75	3			
SCLD6	—		—	—	—	—	—	200	—	150	—	100	—	—	300-600	S	—	8.75	3			
800	Thermal Magnetic	VL	NM	—	—	—	—	—	—	65	—	35	—	25	—	22	600-800	S	—	8.75	3	
			HM	—	—	—	—	—	—	100	—	65	—	35	—	25	600-800	S	—	8.75	3	
			LM	—	—	—	—	—	—	200	—	100	—	50	—	42	600-800	S	—	8.75	3	
	Electronic (Solid state)		NM	—	—	—	—	—	—	65	—	35	—	25	—	—	600-800	S	—	8.75	3	
HM		—	—	—	—	—	—	100	—	65	—	35	—	—	600-800	S	—	8.75	3			
LM		—	—	—	—	—	—	200	—	100	—	50	—	—	600-800	S	—	8.75	3			

① BLG two-pole breaker is one phase and neutral. Three pole is two phases and neutral - See SpeedFax page 7-31
 ② 1-pole HED 15-30A rated 65kA; 35-100A rated 25kA: 3-pole HED rated 42kA

③ Availability and additional specs tbd, expected late 2019. (COMPAS may allow selection of alternate trip units)
 ④ 2-pole only or two outer poles of 3-pole breaker

⑤ Accessories such as shunt trips on 3 pole breakers require 6.25" of unit space
 ⑥ Approved for CSA and UL Listed.
 ⑦ Approved for CSA but not UL Listed.

Panelboards

Power and Distribution

Selection

 11
 PANELBOARDS

Type S4/P4/SPP (10" deep) and F1/P4/FPP (10" deep)

Connecting Strap Kits — w/o Circuit Breaker

For use with Type P4, Type S4 or Sentron SPP Shallow depth panelboards					
Max Amp Rating	Breaker Family	Breaker Type	Catalog Number ^{①④}	Unit Height (inches)	Mounting
100	General	BL, BQD	SBL	3.75	Twin
125	3VA	3VA41, xGB	S3VA41T ^⑨	3.75	Twin
	General	xGB2	SGB2	3.75	Twin
	General	ED	SE6	3.75	Twin
	General	CED	SCE	3.75	Twin
150	3VA	3VA61	S3VA52T ^⑨	5.00	Twin
	VL	DG	SDGD	5.00	Twin
225	General	QR	SQR	5.00	Twin
250	3VA	3VA52, 3VA62	S3VA52T ^⑨	5.00	Twin
	VL	FG	SFG	5.00	Twin
	Sentron	FD	SF6	5.00	Twin
	Sentron	CFD	SCF	5.00	Single
400	3VA	3VA53	S3VA53T ^⑨	6.25	Single
	3VA	3VA63	S3VA63T ^⑨	6.25	Single
	VL	JG	SJG	6.25	Single
	Sentron	JD	SJ1	8.75	Single
	Sentron	CJD	SCJ	8.75	Single
	Sentron	SJD	SSJ1	8.75	Single
600	Sentron	SCJD	SSCJ	8.75	Single
	3VA	3VA54	S3VA54T ^⑨	6.25	Single
	3VA	3VA64	S3VA64T ^⑨	6.25	Single
	VL	LG	SLG	6.25	Single
	Sentron	LD	SL6	8.75	Single
	Sentron	CLD	SCL	8.75	Single
800	Sentron	SLD	SSL6	8.75	Single
	Sentron	SCLD	SSCL	8.75	Single
	VL	MG	MG1	8.75	Single

3VA Breaker Provision Kits

Breaker Type	Catalog Number	Description
3VA52, 3VA61 or 3VA62 Breaker	S3VA52PR ^⑨	Only required when installing a 3VA52, 3VA61, or 3VA62 breaker to an existing provision in the field. Parts are included with kit S3VA52T.

Service Entrance Barriers

Field installable Barriers to meet UL 67 service entrance requirements	
Breaker Type	Catalog Number
(S)JD, (S)LD, MG	SEBP4V1
CJD, CLD	SEBP4V2
JG, LG	SEBP4V3

Connecting Strap Kits^④ Fusible

For use with Sentron Shallow Depth or Type SPP/FPP/F1/P4 power panels		
Ampere Rating	Unit Height (inches)	10" Deep Box Catalog Number
30-30	2.5	F602
30-60	5, 7.5	F657
30-60	5, 7.5	F657
60-60	5, 7.5	F657
60-100	5, 7.5	F657
100-100	5, 7.5	F657
100	7.5	F657
200	10	F671
200-200	10	F672

For inches / millimeters conversion, see Application Data section.

- ① Includes housing frame plate without breaker handle opening.
- ② For Class J, R or T fuse clip prices, refer to page 11-93.
- ③ For Class J fuse clips price 600V, 7½" high units.
- ④ NEC fuse clips only.
- ⑤ Normal stock item.

- ⑥ Suitable to replace QF3 in P1 thru P5 Panelboards and Switchboards.
- ⑦ To replace a QJ with a QR only a new cover is needed up to 225A.
- ⑧ Although QR is rated 250A, it is limited to 225A in panelboard.

Branch Switch Selection

Ampere Rating	Mounting Height (inches)
---------------	--------------------------

240V — Twin Mounted	NEC Fuse Clips ^②
30-30	2½ ^③
30-30	5
30-60	5
60-60	5
60-100	7½
100-100	7½
200-200	10

240V — Single Mounted	NEC Fuse Clips ^②
30	7½
60	7½
100	7½
200	10
200	7½

600V — Twin Mounted	NEC Fuse Clips ^②
30-30	7½
30-60	7½
60-60	7½
60-100	7½
100-100	7½
200-200	10

600V — Single Mounted	NEC Fuse Clips ^②
100	7½
200	10

Blank Plates — Circuit Breaker and Vacu-Break

For use with Type P4, Type S4 or Sentron SPP Shallow depth panelboards	
Height (inches)	Catalog Number
1.25	6FPB01
2.5	6FPB02
3.75	6FPB03
5.0	6FPB05
10.0	6FPB10

Filler Plates

For use with Type P4, Type S4 or Sentron SPP Shallow depth panelboards	
Breaker Type	Filler Plate Catalog Number
BL, BLH, HBL ED4, ED6, HED4, HHED6, NGB, HGB, LGB, NGB2, HGB2, LGB2	DFFP1 ^⑤
NEB, HEB	EBF1

Cover Plates

For use with Sentron Shallow Depth or Type SPP/FPP/F1/P4 power panels	
Breaker Type	Catalog Number
QR	SQRC ^⑥

- ⑨ Only required when installing a 3VA52, 3VA61, or 3VA62 breaker to an existing provision in the field. Parts are included with kit S3VA52T.
- ⑩ Strap Kit can also accommodate xGB breakers, reference Installation Instructions
- ⑪ Consult Sales for availability
- ⑫ Kit includes breaker nut keepers & bus extensions

Panelboards

Modifications and Additions

Selection

P4 Panelboards

Devices Mounted on Gutter Cover Includes Device, Mounting – Wired or Unwired

Description
One piece front with door
Hinged Gutter Covers 4 pc front
Toggle Switch — SPST or 3-way
15A, 277V maximum
Pilot Light — General Purpose
Neon or Incandescent
Pushbutton

Increased Capacity Neutral

Ampere Rating	Unit Space (inches)
Phase	Neutral
400	600
400	800
600	1200
800	1200

Subfeed or Feed-Thru Lugs (One Set Per Panel) Subfeed Double Lugs (Main Lug Panels)

Amp Rating	Unit Spaces (Additional inches)
	MLO
400	0
600	0
800	N/A
1200	N/A

Feed-Thru Lugs

Ampere Rating	Unit Space (inches)
400	10
600	10
800	17.5
1200	17.5

Grounding of Panelboards Ground Bars (except for brazed-to-box) are shipped with the panel interior factory mounted.

- Non-Insulated Equipment Ground Bar – Standard
- Copper Non-Insulated Ground Bar
- Al Insulated Equipment Ground Bar
- Cu Insulated Equipment Ground Bar
- Ground Bar Brazed to Box

Fuse Clip Provisions (Add to 250 Volts or 600 Volts Unit Prices Per Switch)

Amp Rating	Class J	Class R	Class T
30		•	•
60		•	•
100		•	•
200		•	•

Spanner Wrenches (for Vacu-Break Switches)

Ground Fault on Main Breaker

Description
Conventional Ground Fault ① Includes: ground fault relay, ground sensor, CPT & shunt trip
Test and Monitor Panel ②
Ground Fault add to Sensitrip III breaker price

Time Clocks ③

Sangamo, Tork or Paragon time clock can be supplied, mounted in panelboard cabinet. For required increase in enclosure dimension, consult local sales office.

Description
Time clock (1- or 2-Pole, Single or Double Throw Contacts; 3-Pole Single Throw)
277V Maximum with Plain Dial
Optional: Astronomical Dial An Omitting Device Reserve Power or Carryover
Space and Mounting Provisions Only

Circuit Breaker Accessories Handle Blocking Device Blocks handle in either the “ON” or “OFF” position.

Padlocking Device – Padlocks in “OFF” position.

Main Bus

Standard main bus and ground bus are tin-plated aluminum. For copper main bus, neutral bus and ground bus, add from the table for each panel.

Lugs – For Main Lug Only Panels

Standard main lugs and neutral lugs are tin-plated aluminum, UL listed for use with aluminum/copper cables. Copper only lugs are an option.

Ampere Rating
400 - 1200

Shunt Trip on Main and Branches ④

Description
BL, BQD, NGB, HGB, LGB, NGB2, HGB2, LGB2 (branch only)
QR2, QRH2, HQR2, HQR2H, ED4, ED6, HED4, HHED6, CED6
All others to 800A

100% Rated Main Circuit Breakers

Ampere Rating	Breaker Type
400A	JXD6H, HJXD6H SCJD6H, SHJD6H NJY, HJY, LJY
600A	LXD6H, HLXD6H NMY®, HMY®, LMY®

① Available in 90" high enclosure only. Unit space is 42 1/2" with Test and Monitor Panel; 45" without Test and Monitor Panel.

② Not available on Sensitrip III.

③ For required unit space, consult local sales office.

④ Shunt Trip on 100A frame breakers increases mounting height to 6.25" for twin mounting.

⑤ The 600A, 100% rated breaker requires the use of an 800A frame breaker.

Panelboards

Embedded Micro Metering Module

Selection

SEM3 System configured in Panelboards

The Siemens SEM3 system can be configured for factory installation in branch circuit monitoring applications using the Siemens COMPAS configuration tool. This option can lower the installation time of the system for the installer while providing a factory warranted solution.

The SEM3 system can be factory installed in unit space in type P2, P4, & P5 Siemens panel boards. Please note P1 and P3 configurations are not available at this time and the amount of unit space needed varies depending upon the application. Please note that lead time adders will apply and may vary depending upon the configuration of the system.

SEM3 for use in Siemens Panelboards

Available in a NEMA 1, 3R, or 12 rated enclosure



Controller

SEM3 controller is mounted in unit space opposite of the feed location specified in COMPAS (i.e., bottom mount for top feed) and will require 3" of unit space. Each controller will be powered by direct tap connection to the panel section bus. Each controller can monitor up to 45 circuits. Applications that require monitoring more than 45 circuits will require additional controllers.



Current Transformers (CTs)

Seven sizes of CTs are available for use in the P4 panel: 50, 125, 250, 400, 600, 800, 1200 amp. All CTs are pre-mounted to a support bracket that attaches to the base rail of the interior of the panel board. Each bracket supports a maximum of 3 CTs and is designed for the breaker selected (brackets are not interchangeable between breaker frames). Each CT will be attached to a data module that is placed in the meter racks.



Meter Racks

Each meter rack requires 3" of unit space. All meter racks will be installed next to the SEM3 controller in unit space. The COMPAS configuration tool will select the appropriate meter rack configuration according to the user's application and will use the 21 space meter rack as a default option where possible. Only one meter rack (regardless of number of positions) can be installed in 3" of unit space.

NOTE: Monitoring of 45 circuits will require 9" of unit space: two 21 position racks and one 3 position rack

Other Considerations

Configuration: Data modules from CTs monitoring a circuit breaker must be mounted adjacent to one another in the meter rack. Any field changes to the factory configuration must take this into account.

Start-up & Commissioning: Siemens can provide these services. Contact your local SIEMENS PDS Power Solutions Business Developer for more details.


Billing Services for sub billing applications: Billing services are available. Contact your local SIEMENS PDS Power Solutions Business Developer for more details.

Panelboards

Embedded Micro Metering Module

Selection

P4 Devices Enclosure sizes



Example P4 Panel with SEM3 Type 1 Enclosure P4 = (32" Wide x 10" Deep)

Enclosure heights are in 15" increments from 60" thru 90".
Enclosure heights: 60", 75", 90" (there are optional depths also)

The COMPAS configuration tool can provide actual dimensions based on the configuration. Example below is largest standard P4 enclosure for factory assembled panel - unit space is in 3.75" increments - up to 6 circuits can occupy each 3.75" of unit space.

← 32" std. width for P4 →

**Main Breaker / Main Lug space
varies based on selected options**

**Unit space varies
based on selected options**

Note: All circuits do not have to be monitored by SEM3 - user can select any circuits in this space to be monitored.

Based on smallest branch breakers and a 3-phase main being monitored. There is a maximum of 63 circuits that can be monitored with the configuration shown. Some selections of main breakers and other subfeed options could limit this further.

In this situation there is 37.5" of unit space available - so 60 branch circuits could be monitored.
If monitoring the main three additional circuits could be monitored with a total of 63 circuits.

This requires two controllers and three 21 position racks using 18.75" of unit space.
- see below -

SEM3 space varies by number of circuits monitored - this uses unit space.

- == > 7.5" of space for up to 21 circuits monitored
one controller and one 21-pos rack
- == > 11.25" of space for up to 42 circuits monitored
one controller and two 21-pos racks
- == > 15" of space for up to 45 circuits monitored
one controller and two 21-pos racks plus one 3-pos rack
- == > 18.75" of space for up to 63 circuits monitored
two controllers and three 21-pos racks

Note: If subfeed space is needed - it will take away from available unit space.

Due to gutter space limitations, SEM3 is not available in a P4 Powerpanel for 3VA52, 3VA61, or 3VA62 breakers.

Panelboards

Modifications and Additions

Selection

PANELBOARDS
11

Lug Modifications

Compression Lugs

Style	Amp Rating	Breaker Type	Compression Connectors	Available Unit Space Reduction
MLO	400	N/A	All compression lugs	Deduct 5.0" of Unit Space
	600	N/A	All compression lugs	
	800	N/A	All compression lugs	
	1000	N/A	All compression lugs	
	1200	N/A	All compression lugs	
Main Breaker	400	JD6, JXD6, HJD6, HJXD6, HHJD6, HHJXD6, CJD6, SJD6, SHJD6, SCJD6, LD6, LXD6, HLD6, HLXD6, NL, HL, LL	(2)#2/0 AWG - 500 Kcmil Cu or Al	Deduct 0" of Unit Space
			(1)#6 - 350 Kcmil Cu or Al	
Main Breaker	600	HHLD6, HHLXD6, CLD6, SLD6, SHLD6, SCLD6	(2)#2/0 AWG - 500 Kcmil Cu or Al	Deduct 0" of Unit Space
		NJ, HJ, LJ	(2)#6 - 350 Kcmil Cu or Al	

Alternate Lugs

Amp Rating	Breaker Type	Compression Connectors	Available Unit Space Reduction
400	N/A	(1)#3/0 AWG - 750 Kcmil or (2)#3/0 AWG 250 Kcmil Cu or Al	Deduct 0" of Unit Space
600	N/A	(2)#3/0 AWG - 750 Kcmil	Deduct 5" of Unit Space
800	N/A	(3)#3/0 AWG - 750 Kcmil Cu or Al	Deduct 10" of Unit Space
1200	N/A	(4)#3/0 AWG - 600 Kcmil Cu or Al (4)#3/0 AWG - 750 Kcmil Cu or Al	Deduct 10" of Unit Space

Panelboards

Kits and Accessories

Selection

P4 Enclosures

Description	Catalog number
P4 Type 1 32" W x 10" D x 60" H	PB60
P4 Type 1 32" W x 10" D x 75" H	PB75
P4 Type 1 32" W x 10" D x 90" H	PB90
P4 Type 3R/12 60" H	WP260
P4 Type 3R/12 75" H	WP275
P4 Type 3R/12 90" H	WP290

P4 Trims

Description	Catalog number
P4 Std (4 piece trim) vented 60"	P460V
P4 Std (4 piece trim) vented 75"	P475V
P4 Std (4 piece trim) vented 90"	P490V
P4 VBS Std (4 Piece trim) vented 60"	P460VV
P4 VBS Std (4 Piece trim) vented 75"	P475VV
P4 VBS Std (4 Piece trim) vented 90"	P490VV
P4 Std (4 piece trim) unvented 60"	P460NV
P4 Std (4 piece trim) unvented 75"	P475NV
P4 Std (4 piece trim) unvented 90"	P490NV
P4 VBS Std (4 Piece trim) unvented 60"	P460NVV
P4 VBS Std (4 Piece trim) unvented 75"	P475NVV
P4 VBS Std (4 Piece trim) unvented 90"	P490NVV
P4 Std (4 piece trim) vented 60" with hinged gutter covers	P460VHG
P4 Std (4 piece trim) vented 75" with hinged gutter covers	P475VHG
P4 Std (4 piece trim) vented 90" with hinged gutter covers	P490VHG
P4 VBS Std (4 piece trim) vented 60" w/Hinged gutter covers	P460VVHG
P4 VBS Std (4 piece trim) vented 75" w/Hinged gutter covers	P475VVHG
P4 VBS Std (4 piece trim) vented 90" w/Hinged gutter covers	P490VVHG
P4 Std (4 piece trim) unvented 60" with hinged gutter covers	P460NVHG
P4 Std (4 piece trim) unvented 75" with hinged gutter covers	P475NVHG
P4 Std (4 piece trim) unvented 90" with hinged gutter covers	P490NVHG
P4 VBS Std (4 piece trim) unvented 60" w/Hinged gutter covers	P460NVVHG
P4 VBS Std (4 piece trim) unvented 75" w/Hinged gutter covers	P475NVVHG
P4 VBS Std (4 piece trim) unvented 90" w/Hinged gutter covers	P490NVVHG
P4 Std (1 PC Door) vented 60"	P460VD
P4 Std (1 PC Door) vented 75"	P475VD
P4 Std (1 PC Door) vented 90"	P490VD
P4 Std (1 PC Door) unvented 60"	P460NVD
P4 Std (1 PC Door) unvented 75"	P475NVD
P4 Std (1 PC Door) unvented 90"	P490NVD
P4 Std (1 PC Door-in-door) vented 60"	P460VDD
P4 Std (1 PC Door-in-door) vented 75"	P475VDD
P4 Std (1 PC Door-in-door) vented 90"	P490VDD
P4 Std (1 PC Door-in-door) unvented 60"	P460NVDD
P4 Std (1 PC Door-in-door) unvented 75"	P475NVDD
P4 Std (1 PC Door-in-door) unvented 90"	P490NVDD

P4 Flush mounting kits

Description	Catalog number
Flush kit for P4 60" High	F60
Flush kit for P4 75" High	F75
Flush kit for P4 90" High	F90


Panelboards

Type P4 Panelboards


Dimensions

Type 1 Box

Box is symmetrical



Type 3R and 3R/12 Box



Dimensions shown in inches and millimeters [].

Panelboards

Type P5 Panelboards

General

Features

The P5 is the largest distribution panel in the Siemens' panel family. Even with a larger footprint, the P5 is still a space saver with its 38" width and 12.75" depth. The panel offers higher main ratings to fit applications that require larger branch devices.

This panel offers a wide array of factory assembled options and has the ability to mix breaker frames in unit space up to 1200 amps and fusible switches up to 1200 amps. Bussing options for the P5 vary from the standard temperature rated aluminum to temperature rated copper and 750 A/SI aluminum and 1000A/SI copper designs. All aluminum bussing in the P5 panel is tin-plated as a standard. Silver-plated is offered as the default for copper bus and tin as an option. Integrated time clocks, bus mounted contactors as mains or submains, split bus and subfeed lugs (up to 600 amps) are just a few of the options of this flexible panel.

The P5 panel configurations defined by the unit space allowed for a given amperage, main device and box height. The P5 panel starts with a 60" high box. All of the branch devices are unit space mounted. Breakers and switches can be mixed and matched to meet customer requirements.

Main Lug / Main Breaker / Main Switch

Enclosure – Standard Type 1 enclosure is 38" wide x 12.75" deep. X Box Height is determined by main device and unit space. See charts for box height.

Voltage – 600V AC max.
250V DC max.

Amperage – 400-1200 amp main breaker, 400-1200 amp main lug only or 200-1200 amp main switch.

Short Circuit Rating – 200 Kaic max. symmetrical or equal to the lowest rated device installed unless a series rating is indicated. Panels with subfeed or feed-thru lugs without a main device, circuit breaker or fusible unit, are limited to a three-cycle rating. The three-cycle rating for the P5 panel is limited to 42 Kaic. Note that the main device may be mounted remote from the panel.

Bussing – The P5 panel has more options to meet market requirements. The standard bussing is temperature rated aluminum. The rating is per the requirements of UL 67 – the standard for panelboards. All aluminum bussing is tin-plated. Optional bussing for the P5 panel is: 750 A/SI aluminum, temperature rated copper, and 1000 A/SI copper. The copper bus option for this panel is tin-plated.

Weight – Approximate

Total panelboard weight when filled with a normal quantity of breakers and accessories is about 10 lbs. (1 kg) per inch (54g per mm) of box height.

Main Lugs ^①

Ampere Rating	Connectors Suitable for Copper or Aluminum
400	(1) 250-500Kcmil
600	(2) #3/0-500Kcmil
800	(3) #3/0 AWG-500 Kcmil
1000	(4) #3/0 AWG-500 Kcmil
1200	(4) #3/0 AWB-500 Kcmil

^① Alternate lugs for 750 kcmil cable are available, but result in significant loss of branch unit mounting space. Consult Siemens.

Gauge Steel of Boxes Fronts, Surface and Flush

Dimensions in inches (mm)		Gauge Steel	
Width	Height	Box	Fronts
38" (965)	60 - 75 - 90 (1524, 1905, 2286)	#16 ^①	#14 (1 piece trim) #14 (4 piece trim)
	60 - 75 - 90 (1524, 1905, 2286)	#14	#12 (1 piece & door in door) #10 (1 piece & door in door)
	60 - 75 - 90 (1524, 1905, 2286)	#14	#16 (4 piece, top and bottom over) #10 (4 piece, side/ gutter cover)

^① 16 gauge side panels, 12 gauge back support, 14 gauge back panels.

Panelboards

Power and Distribution

Selection/Dimensions


11
PANELBOARDS

Enclosure Selection ^①

Enclosure Dimension in Inches (mm)				Available Unit Space in Inches (mm)					
H	W	D		Main Lug Only	Main Breaker		Main VB Switch		Main HCP Switch
Type 1 or 3R/12		Type 1	Type 3R/12	400 - 1200A	400-800A	1200A	200A	400A-600A	400-1200A
60 (1524)	38 (965)	12.75 (324)	14.25 (362)	30 (762)	21.25 (540)	20 (508)	20 (508)	-	13.75 (349)
75 (1905)	38 (965)	12.75 (324)	14.25 (362)	45 (1143)	36.25 (921)	35 (889)	40 (1016)	25 (889)	28.75 (730)
90 (2286)	38 (965)	12.75 (324)	14.25 (362)	60 (1524)	51.25 (1302)	50 (1270)	55 (1397)	40 (1270)	43.75 (1111)

Main Breaker Unit Space Dimensions

Ampere Rating	Breaker Family	Breaker Type	Dimensions in inches (mm)	
			A	B
400	Sentron	JXD6, JD6, HJXD6, HJD6, HHJXD6, HHJD6	13.425 (265)	13.125 (333)
	VL ^②	NJ, HJ, LJ	15.500 (318)	
	Sentron	SJD6, SHJD6	13.425 (265)	
		CJD6, SCJD6	11.250 (210)	
600	Sentron	LXD6, LD6, HLXD6, LD6, HHLXD6, HHLD6	13.425 (265)	
	VL ^②	NL, HL, LL	14.250 (286)	
	Sentron	SLD6, SHLD6	13.425 (265)	
		CLD6, SCLD6	11.250 (210)	
800	VL	NM, HM, LM	13.425 (265)	
	Sentron	MXD6, MD6, HMXD6, HMD6, CMD6, SMD6, SHMD6, SCMD6	13.00 (330) 10.42 (265)	
1200	VL	NN, HN, LN	13.425 (265)	
	Sentron	NXD6, ND6, HNXD6, HND6, CND6, SND6, SHMD6, SCND6	13.00 (330) 13.00 (330)	



Main Breaker Wire Bending Space Dimensions & Main Switch

Main Switch


Maximum Ampere Rating	A	B
400A/600A VB	9.30 (236)	13.125 (333)
800A/1200A HCP	10.30 (262)	
200A VB	13.425 (265)	

Main Switch Connectors

Ampere Rating	Connectors suitable for Copper or Aluminum
400	(1) #3/0 AWG-500 kcmil (2) #3/0 AWG-250 kcmil
600	(2) #3/0 AWG-500 kcmil
800	(3) #3/0 AWG-500 kcmil
1200	(4) #3/0 AWG-500 kcmil

Main Lugs Only Wire Bending Space

Lugs	Dimensions in inches (mm)					
	Main Lug					Neutral
	400A A	600A B	800A C	1000A D	1200A E	800A G
Standard	16.500 (419)	16.750 (425)	15.969 (406)	15.969 (406)	15.969 (406)	13.125 (333)
Oversize	16.500 (419)	21.750 (552)	25.969 (660)	25.969 (660)	25.969 (660)	23.125 (587)
Crimp	19.187 (487)	18.250 (464)	18.687 (475)	18.250 (464)	18.250 (464)	15.937 (405)
Standard with Subfeed	16.750 (425)	15.969 (406)	—	—	—	13.125 (333)
Standard with Feed-thru	16.500 (419)	16.750 (425)	—	—	—	13.125 (333)



Main Lugs Only Wire Bending Space

① Standard trim is for space without door. Surface flush one piece trim is available for 32" (813mm) wide circuit breaker panel.

② Available with solid state (electronic) trip units only.

Type P5

Shown with Standard Mains, Top Fed and Surface Trim

Catalog number is for aluminum main bus. For optional copper main bus change "A" in position 11 to "E" (silver-plated copper bus).

Panels are top feed, surface mounted. For bottom feed, change "T" in position 12 to "B". For flush mounting, change "S" in position 13 to "F".

Replace fifth and sixth position in panelboard catalog number, with alternate main breaker code. Use price adders from main breaker section table. Horizontally mounted.

Main Lugs Only — shown with aluminum bus, top fed, and surface trims.

Maximum Panel Ampere Rating	Unit Space (inches)	208Y/120V	240/120V	120/240V or 250 Vdc Max
		3-Phase, 4-Wire Catalog Number	3-Phase, 4-Wire Catalog Number	1-Phase, 3-Wire Catalog Number
800 ^②	30	P5C60ML800ATS	P5B60ML800ATS	P5A60ML800ATS
	45	P5C75ML800ATS	P5B75ML800ATS	P5A75ML800ATS
	60	P5C90ML800ATS	P5B90ML800ATS	P5A90ML800ATS
1000	30	P5C60ML101ATS	P5B60ML101ATS	P5A60ML101ATS
	45	P5C75ML101ATS	P5B75ML101ATS	P5A75ML101ATS
	60	P5C90ML101ATS	P5B90ML101ATS	P5A90ML101ATS
1200	30	P5C60ML120ATS	P5B60ML120ATS	P5A60ML120ATS
	45	P5C75ML120ATS	P5B75ML120ATS	P5A75ML120ATS
	60	P5C90ML120ATS	P5B90ML120ATS	P5A90ML120ATS
Maximum Panel Ampere Rating	Unit Space (inches)	240	480Y/277V	480V ^①
		3-Phase, 3-Wire Catalog Number	3-Phase, 4-Wire Catalog Number	1-Phase, 3-Wire Catalog Number
800 ^②	30	P5D60ML800ATS	P5E60ML800ATS	P5F60ML800ATS
	45	P5D75ML800ATS	P5E75ML800ATS	P5F75ML800ATS
	60	P5D90ML800ATS	P5E90ML800ATS	P5F90ML800ATS
1000	30	P5D60ML101ATS	P5E60ML101ATS	P5F60ML101ATS
	45	P5D75ML101ATS	P5E75ML101ATS	P5F75ML101ATS
	60	P5D90ML101ATS	P5E90ML101ATS	P5F90ML101ATS
1200	30	P5D60ML120ATS	P5E60ML120ATS	P5F60ML120ATS
	45	P5D75ML120ATS	P5E75ML120ATS	P5F75ML120ATS
	60	P5D90ML120ATS	P5E90ML120ATS	P5F90ML120ATS

Main Circuit Breaker — shown with aluminum bus, top fed, and surface trims.

Maximum Panel Ampere Rating	Unit Space (inches)	208Y/120V	240/120V	120/240V or 250 Vdc Max
		3-Phase, 4-Wire Catalog Number	3-Phase, 4-Wire Catalog Number	1-Phase, 3-Wire Catalog Number
800 ^②	21.25	P5C60M1800ATS	P5B60M1800ATS	P5A60M1800ATS
	36.25	P5C75M1800ATS	P5B75M1800ATS	P5A75M1800ATS
	51.25	P5C90M1800ATS	P5B90M1800ATS	P5A90M1800ATS
1200	20	P5C60N1120ATS	P5B60N1120ATS	P5A60N1120ATS
	35	P5C75N1120ATS	P5B75N1120ATS	P5A75N1120ATS
	50	P5C90N1120ATS	P5B90N1120ATS	P5A90N1120ATS
Maximum Panel Ampere Rating	Unit Space (inches)	240	480Y/277V	480V ^①
		3-Phase, 4-Wire Catalog Number	3-Phase, 4-Wire Catalog Number	1-Phase, 3-Wire Catalog Number
800 ^②	21.25	P5D60M1800ATS	P5E60M1800ATS	P5F60M1800ATS
	36.25	P5D75M1800ATS	P5E75M1800ATS	P5F75M1800ATS
	51.25	P5D90M1800ATS	P5E90M1800ATS	P5F90M1800ATS
1200	20	P5D60N1120ATS	P5E60N1120ATS	P5F60N1120ATS
	35	P5D75N1120ATS	P5E75N1120ATS	P5F75N1120ATS
	50	P5D90N1120ATS	P5E90N1120ATS	P5F90N1120ATS

For inches / millimeters conversion, see Application Data section.

① For 600V, change "F" in position 3 to "G". Price only branch breakers with 600V ratings.

② Alternate main breaker requires additional 1.25" unit space.

Panelboards

Power and Distribution

Selection

 11
 PANELBOARDS

Main Fusible Switch (fuses not included)

Maximum Panel Ampere Rating	Unit Space (inches)	208Y/120V 3-Phase, 4-Wire Catalog Number	240/120V 3-Phase, 4-Wire Catalog Number	120/240V 1-Phase, 3-Wire Catalog Number	240V 3-Phase, 3-Wire Catalog Number	480Y/277V 3-Phase, 4-Wire Catalog Number	480V ^① 3-Phase, 3-Wire Catalog Number
400	25	P5C75MS400ATS	P5B75MS400ATS	P5A75MS400ATS	P5D75MS400ATS	P5E75MS400ATS	P5F75MS400ATS
	40	P5C90MS400ATS	P5B90MS400ATS	P5A90MS400ATS	P5D90MS400ATS	P5E90MS400ATS	P5F90MS400ATS
600	25	P5C75MS600ATS	P5B75MS600ATS	P5A75MS600ATS	P5D75MS600ATS	P5E75MS600ATS	P5F75MS600ATS
	40	P5C90MS600ATS	P5B90MS600ATS	P5A90MS600ATS	P5D90MS600ATS	P5E90MS600ATS	P5F90MS600ATS
800 ^④	28.75	P5C75MS800ATS	P5B75MS800ATS	P5A75MS800ATS	P5D75MS800ATS	P5E75MS800ATS	P5F75MS800ATS
	43.75	P5C90MS800ATS	P5B90MS800ATS	P5A90MS800ATS	P5D90MS800ATS	P5E90MS800ATS	P5F90MS800ATS
1200 ^④	28.75	P5C75MS120ATS	P5B75MS120ATS	P5A75MS120ATS	P5D75MS120ATS	P5E75MS120ATS	P5F75MS120ATS
	43.75	P5C90MS120ATS	P5B90MS120ATS	P5A90MS120ATS	P5D90MS120ATS	P5E90MS120ATS	P5F90MS120ATS

Alternate Main Breaker Selection^②

Breaker Frame Rating	Trip Type	Breaker Family	Frame Type	Type Ref. Code ^③	Trip Amperage	Unit Space Requirements in Inches	Maximum Interruption Rating (KAIC) Volts AC		
							240	480	600
400	Thermal Magnetic	Sentron	JXD6	JX	200, 225, 250, 300, 350, 400	8.75	65,000	35,000	25,000
			JD6	J6	200, 225, 250, 300, 350, 400	8.75	65,000	35,000	25,000
			HJXD6	H5	200, 225, 250, 300, 350, 400	8.75	100,000	65,000	35,000
			HJD6	H6	200, 225, 250, 300, 350, 400	8.75	100,000	65,000	35,000
			HHJXD6	H9	200, 225, 250, 300, 350, 400	8.75	200,000	100,000	50,000
			HHJD6	6H	200, 225, 250, 300, 350, 400	8.75	200,000	100,000	50,000
			CJD6	CJ	200, 225, 250, 300, 350, 400	8.75	200,000	150,000	100,000
	Electronic (Solid state)	VL	NJ	J1	250, 400	6.25	65,000	35,000	25,000
			HJ	J7	250, 400	6.25	100,000	65,000	25,000
			LJ	J3	250, 400	6.25	200,000	100,000	25,000
		Sentron	SJD6	SJ	200, 300, 400	8.75	65,000	35,000	25,000
			SHJD6	SX	200, 300, 400	8.75	100,000	65,000	35,000
			SCJD6	SC	200, 300, 400	8.75	200,000	150,000	100,000
600	Thermal Magnetic	Sentron	LXD6	LX	450, 500, 600	8.75	65,000	35,000	25,000
			LD6	L6	250, 300, 350, 400, 450, 500, 600	8.75	65,000	35,000	25,000
			HLXD6	HO	250, 300, 350, 400, 450, 500, 600	8.75	100,000	65,000	35,000
			HLD6	HL	250, 300, 350, 400, 450, 500, 600	8.75	100,000	65,000	35,000
			HHLXD6	XH	250, 300, 350, 400, 450, 500, 600	8.75	200,000	100,000	50,000
			HHLD6	HH	250, 300, 350, 400, 450, 500, 600	8.75	200,000	100,000	50,000
			CLD6	CL	250, 300, 350, 400, 450, 500, 600	8.75	200,000	150,000	100,000
	Electronic (Solid state)	VL	NL	L7	400, 600	6.25	65,000	35,000	25,000
			HL	L2	400, 600	6.25	100,000	65,000	25,000
			LL	SL	400, 600	6.25	200,000	100,000	25,000
		Sentron	SLD6	L6	300, 400, 500, 600	8.75	65,000	35,000	25,000
			SHLD6	S2	300, 400, 500, 600	8.75	100,000	65,000	35,000
			SCLD6	SI	300, 400, 500, 600	8.75	200,000	150,000	100,000
			NM	M1	600, 700, 800	8.75	65,000	35,000	25,000
			HM	M2	600, 700, 800	8.75	100,000	65,000	35,000
			LM	M3	600, 700, 800	8.75	200,000	100,000	50,000
			LMXD6	LM	500, 600, 700, 800	8.75	65,000	50,000	25,000
800	Thermal Magnetic	Sentron	LMD6	L1	500, 600, 700, 800	8.75	65,000	50,000	25,000
			HLMXD6	HK	500, 600, 700, 800	8.75	100,000	65,000	50,000
			HLMD6	HJ	500, 600, 700, 800	8.75	100,000	65,000	50,000
			MXD6	MX	500, 600, 700, 800	10.00	65,000	50,000	25,000
			MD6	MD	500, 600, 700, 800	10.00	65,000	50,000	25,000
			HMXD6	HR	500, 600, 700, 800	10.00	100,000	65,000	50,000
			HMD6	HM	500, 600, 700, 800	10.00	100,000	65,000	50,000
			CMD6	CM	500, 600, 700, 800	10.00	200,000	100,000	65,000
	Electronic (Solid state)	VL	NM	M1	600, 800	8.75	65,000	35,000	25,000
			HM	M2	600, 800	8.75	100,000	65,000	35,000
			LM	M3	600, 800	8.75	200,000	100,000	50,000
		Sentron	SMD6	SM	600, 700, 800	10.00	65,000	50,000	25,000
			SHMD6	S5	600, 700, 800	10.00	100,000	65,000	50,000
			SCMD6	SO	600, 700, 800	10.00	200,000	100,000	65,000
1200	Thermal Magnetic	VL	NN	N1	800, 900, 1000, 1200	10.00	65,000	35,000	25,000
			HN	N2	800, 900, 1000, 1200	10.00	100,000	65,000	35,000
			LN	N3	800, 900, 1000, 1200	10.00	200,000	100,000	65,000
		Sentron	NXD6	NX	900, 1000, 1200	10.00	65,000	50,000	25,000
			ND6	ND	900, 1000, 1200	10.00	65,000	50,000	25,000
			HNXD6	HT	900, 1000, 1200	10.00	100,000	65,000	50,000
			HND6	HN	900, 1000, 1200	10.00	100,000	65,000	50,000
			CND6	Cn	900, 1000, 1200	10.00	200,000	100,000	65,000
	Electronic (Solid state)	VL	NN	N1	800, 1000, 1200	10.00	65,000	35,000	25,000
			HN	N2	800, 1000, 1200	10.00	100,000	65,000	35,000
			LN	N3	800, 1000, 1200	10.00	200,000	100,000	65,000
		Sentron	SND6	SN	800, 1000, 1200	10.00	65,000	50,000	25,000
			SHND6	AD	800, 1000, 1200	10.00	100,000	65,000	50,000
			SCND6	SR	800, 1000, 1200	10.00	200,000	100,000	65,000

For inches / millimeters conversion, see Application Data section.

① For 600V, change "F" in position 3 to "G". Price only branch breakers with 600V ratings.
 ② For ground fault, see page 11-107.

③ Replace "MS" in catalog number with code letter. (See Main Fusible Switch Table above)
 ④ 800 and 1200 ampere switches have "L" class fuse provisions (Type HCP).

Panelboards

Power and Distribution

Selection

P5 Branch Circuit Breakers

P5 Branch Circuit Breakers																		S = Single Mount				
				1-Pole					2-Pole and 3-Pole										T = Twin mount			
				Max IR (kA) at				Amp Ratings Avail.	Max IR (kA) at								Amp Ratings Avail.					
Amp Rating	Trip Type	Breaker Family	Breaker Type	120V	277V	347V	125V DC		120/240V	240V	480Y/277V	480V	600Y/347V	600V	125/250V DC	250V DC		S	T	Unit Space per Kit (in.)	Max 1-pole Circuits per Kit	
100	Thermal Magnetic	BL	BL	10	—	—	—	15-70	10	10	—	—	—	—	—	—	15-100 ^④	—	T	3.75 ^⑤	6	
			BLH	22	—	—	—	15-70	22	22	—	—	—	—	—	—	15-100 ^④	—	T	3.75 ^⑤	6	
			HBL	65	—	—	—	15-50	65	65	—	—	—	—	—	—	15-100	—	T	3.75 ^⑤	6	
	Special Application	BLG BL	BLG ^① BL (HID)	10	—	—	—	15-20	10	—	—	—	—	—	—	30	—	T	3.75 ^⑤	6		
				10	—	—	—	15-30	10	—	—	—	—	—	—	15-30	—	T	3.75 ^⑤	6		
	Thermal Magnetic	BQD	BQD ^②	65	14	—	14	15-100	—	65	14	—	—	—	14	—	15-100	—	T	3.75 ^⑤	6	
			BQD6 ^⑦	65	—	—	14	15-70	—	65	—	—	10	—	14	—	15-70	—	T	3.75 ^⑤	6	
xx	Electronic and misc.	BL	AFCI/ GFCI & Dual Function	x	—	—	—	see special table page 11-13	x	—	—	—	—	—	—	see special table page 11-13	—	T	3.75 ^⑤	6		
125	Thermal Magnetic	GB	NGB	100	25	14	14	15-125	—	100	25	—	14	—	14	—	15-125	—	T	3.75 ^⑤	6	
			HGB	100	35	14	14	15-125	—	100	35	—	14	—	14	—	15-125	—	T	3.75 ^⑤	6	
			LGB	100	65	14	14	15-125	—	100	65	—	14	—	14	—	15-125	—	T	3.75 ^⑤	6	
		Sentron	ED4	—	22	—	30	15-100	—	65	—	18	—	—	—	30	15-125	—	T	3.75 ^⑤	6	
			ED6	—	—	—	—	—	—	65	—	25	—	18	—	30	20-125	—	T	3.75 ^⑤	6	
			HED4 ^②	—	—	—	—	—	—	65	—	42	—	18	—	30	15-125	—	T	3.75 ^⑤	6	
			HHED6	—	—	—	—	—	—	100	—	65	—	18	—	—	15-50	—	T	3.75 ^⑤	6	
		GB2	NGB2	100	25	14	14 ^④	15-125	—	100	—	25	14	—	14 ^④	—	15-125	—	T	3.75 ^⑤	6	
			HGB2	100	35	22	14 ^④	15-125	—	100	—	35	22	—	14 ^④	—	15-125	—	T	3.75 ^⑤	6	
			LGB2	100	65	25	14 ^④	15-125	—	100	—	65	25	—	14 ^④	—	15-125	—	T	3.75 ^⑤	6	
		3VA41 ^③	info not yet avail-able	x	x	x	x	x	—	x	x	x	—	x	—	—	x	—	—	—	6	
				x	x	x	x	x	—	x	x	x	—	x	—	—	x	—	—	6		
				x	x	x	x	x	—	x	x	x	—	x	—	—	x	—	—	6		
150	Electronic (Solid state)	VL	ND	—	—	—	—	—	—	65	—	35	18	—	—	—	60-150	—	T	5.00	6	
			HD	—	—	—	—	—	—	100	—	65	20	—	—	—	60-150	—	T	5.00	6	
			LD	—	—	—	—	—	—	200	—	100	25	—	—	—	60-150	—	T	5.00	6	
	Electronic (Solid state)	3VA61 ^③ (ETU350 LSI standard)	MDAE	—	—	—	—	—	—	100	35	35	18	18	—	—	40-150	—	T	5.00	6	
			HDAE	—	—	—	—	—	—	100	65	65	22	22	—	—	40-150	—	T	5.00	6	
			CDAE	—	—	—	—	—	—	200	100	100	35	35	—	—	40-150	—	T	5.00	6	
	LDAE	—	—	—	—	—	—	200	150	150	50	50	—	—	40-150	—	T	5.00	6			
225	Thermal Magnetic	QR	QR2	—	—	—	—	—	—	10	—	—	—	—	—	100-225	—	T	5.00	6		
			QRH2	—	—	—	—	—	—	25	—	—	—	—	—	100-225	—	T	5.00	6		
			HQR2	—	—	—	—	—	—	65	—	—	—	—	—	100-225	—	T	5.00	6		
			HQR2H	—	—	—	—	—	—	100	—	—	—	—	—	100-225	—	T	5.00	6		
250	Thermal Magnetic	Sentron	FXD6-A, FD6-A	—	—	—	—	—	—	65	—	35	—	22	—	30	70-250	S	T	5.00	3 or 6	
			HFXD6, HFD6	—	—	—	—	—	—	100	—	65	—	25	—	30	70-250	S	T	5.00	3 or 6	
			HHFXD6, HHFD6	—	—	—	—	—	—	200	—	100	—	25	—	—	70-250	S	—	5.00	3	
			CFD6-A	—	—	—	—	—	—	200	—	200	—	100	—	30	70-250	S	—	5.00	3	
	Electronic (Solid state)	VL	NF	—	—	—	—	—	—	65	—	35	—	18	—	—	100-250	—	T	5.00	6	
			HF	—	—	—	—	—	—	100	—	65	—	20	—	—	100-250	—	T	5.00	6	
			LF	—	—	—	—	—	—	200	—	100	—	25	—	—	100-250	—	T	5.00	6	
	Thermal Magnetic	3VA52 ^③ (W/TM230 trip)	MFAS	—	—	—	—	—	85	85	—	35	—	18	—	50	100-250	—	T	5.00	6	
			HFAS	—	—	—	—	—	100	100	—	65	—	25	—	85	100-250	—	T	5.00	6	
			CFAS	—	—	—	—	—	200	200	—	100	—	35	—	100	100-250	—	T	5.00	6	
				—	—	—	—	—	—	—	100	35	35	18	—	—	—	100-250	—	T	5.00	6
	Electronic (Solid state)	3VA62 ^③ (ETU350 LSI standard)	HFAE	—	—	—	—	—	—	100	65	65	22	—	—	—	100-250	—	T	5.00	6	
CFAE			—	—	—	—	—	—	200	100	100	35	—	—	—	100-250	—	T	5.00	6		
LFAE			—	—	—	—	—	—	200	150	150	50	—	—	—	100-250	—	T	5.00	6		
			—	—	—	—	—	—	—	—	—	—	—	—	—	—	100-250	—	T	5.00	6	

① BLG two-pole breaker is one phase and neutral. Three pole is two phases and neutral - See SpeedFax page 7-31
 ② 1-pole HED 15-30A rated 65kA; 35-100A rated 25kA; 3-pole HED rated 42kA

③ Availability and additional specs tbd, expected late 2019. (COMPAS may allow selection of alternate trip units)
 ④ 2-pole only or two outer poles of 3-pole breaker

⑤ Accessories such as shunt trips on 3 pole breakers require 6.25" of unit space
 ⑥ Approved for CSA and UL Listed.
 ⑦ Approved for CSA but not UL Listed.

Panelboards

Power and Distribution

Selection

P5 Branch Circuit Breakers

cont.

P5 Branch Circuit Breakers																			S = Single Mount			
cont.				1-Pole					2-Pole and 3-Pole										T = Twin mount			
Amp Rating	Trip Type	Breaker Family	Breaker Type	Max IR (kA) at				Amp Ratings Avail.	Max IR (kA) at													
				120V	277V	347V	125V DC		120/240V	240V	480Y/277V	480V	600Y/347V	600V	125/250V DC	250V DC						
400	Thermal Magnetic	Sentron	JXD6-A, JD6-A	—	—	—	—	—	—	65	—	35	—	25	—	30	200-400	S	T	8.75	3 or 6	
			HJXD6-A, HJD6-A	—	—	—	—	—	—	100	—	65	—	35	—	30	200-400	S	T	8.75	3 or 6	
			HHJXD6, HHJD6	—	—	—	—	—	—	200	—	100	—	50	—	—	200-400	S	T	8.75	3 or 6	
			CJD6-A	—	—	—	—	—	—	200	—	150	—	100	—	30	200-400	S	—	8.75	3	
	Electronic (Solid state)	VL	NJ	—	—	—	—	—	—	65	—	35	—	25	—	—	250-400	S	T	6.25	3 or 6	
			HJ	—	—	—	—	—	—	100	—	65	—	25	—	—	250-400	S	T	6.25	3 or 6	
			LJ	—	—	—	—	—	—	200	—	100	—	25	—	—	250-400	S	T	6.25	3 or 6	
		Sentron	SJD6-B	—	—	—	—	—	—	65	—	35	—	25	—	—	200-400	S	—	8.75	3	
			SHJD6-B	—	—	—	—	—	—	100	—	65	—	35	—	—	200-400	S	—	8.75	3	
	SCJD6-B	—	—	—	—	—	—	200	—	100	—	100	—	—	200-400	S	—	8.75	3			
600	Thermal Magnetic	Sentron	LXD6	—	—	—	—	—	—	65	—	35	—	25	—	30	450-600	S	—	8.75	3	
			LD6	—	—	—	—	—	—	65	—	35	—	25	—	30	250-600	S	—	8.75	3	
			HLXD6, HLD6	—	—	—	—	—	—	100	—	65	—	35	—	30	250-600	S	—	8.75	3	
			HHLXD6, HHL6	—	—	—	—	—	—	200	—	100	—	50	—	—	250-600	S	—	8.75	3	
			CLD6	—	—	—	—	—	—	200	—	150	—	100	—	—	250-600	S	—	8.75	3	
	Electronic (Solid state)	VL	NL	—	—	—	—	—	—	65	—	35	—	18	—	—	400-600	S	—	6.25	3	
			HL	—	—	—	—	—	—	100	—	65	—	18	—	—	400-600	S	—	6.25	3	
			LL	—	—	—	—	—	—	200	—	100	—	18	—	—	400-600	S	—	6.25	3	
		Sentron	SLD6	—	—	—	—	—	—	65	—	35	—	25	—	—	300-600	S	—	8.75	3	
			SHLD6	—	—	—	—	—	—	100	—	65	—	35	—	—	300-600	S	—	8.75	3	
			SCLD6	—	—	—	—	—	—	200	—	150	—	100	—	—	300-600	S	—	8.75	3	
800	Thermal Magnetic	VL	NM	—	—	—	—	—	—	65	—	35	—	25	—	22	600-800	S	—	8.75	3	
			HM	—	—	—	—	—	—	100	—	65	—	35	—	25	600-800	S	—	8.75	3	
			LM	—	—	—	—	—	—	200	—	100	—	50	—	42	600-800	S	—	8.75	3	
		Sentron	MXD6	—	—	—	—	—	—	65	—	50	—	25	—	30	600-800	S	—	10.00	3	
			MD6	—	—	—	—	—	—	65	—	50	—	25	—	30	500-800	S	—	10.00	3	
			HMXD6	—	—	—	—	—	—	100	—	65	—	50	—	30	600-800	S	—	10.00	3	
	Electronic (Solid state)	VL	HMD6	—	—	—	—	—	—	100	—	65	—	50	—	30	500-800	S	—	10.00	3	
			CMD6	—	—	—	—	—	—	200	—	100	—	65	—	—	600-800	S	—	10.00	3	
		Sentron	SMD6	—	—	—	—	—	—	65	—	50	—	25	—	—	600-800	S	—	10.00	3	
			SHMD6	—	—	—	—	—	—	100	—	65	—	50	—	—	600-800	S	—	10.00	3	
			SCMD6	—	—	—	—	—	—	200	—	100	—	65	—	—	600-800	S	—	10.00	3	
1200	Thermal Magnetic	VL	NN	—	—	—	—	—	—	65	—	35	—	25	—	22	800-1200	S	—	10.00	3	
			HN	—	—	—	—	—	—	100	—	65	—	35	—	25	800-1200	S	—	10.00	3	
			LN	—	—	—	—	—	—	200	—	100	—	50	—	42	800-1200	S	—	10.00	3	
		Sentron	NXD6	—	—	—	—	—	—	65	—	50	—	25	—	30	900-1200	S	—	10.00	3	
			ND6	—	—	—	—	—	—	65	—	50	—	25	—	30	800-1200	S	—	10.00	3	
			HNXD6	—	—	—	—	—	—	100	—	65	—	50	—	30	900-1200	S	—	10.00	3	
	Electronic (Solid state)	VL	HND6	—	—	—	—	—	—	100	—	65	—	50	—	30	800-1200	S	—	10.00	3	
			CND6	—	—	—	—	—	—	200	—	100	—	65	—	—	900-1200	S	—	10.00	3	
		Sentron	SND6	—	—	—	—	—	—	65	—	50	—	25	—	—	800-1200	S	—	10.00	3	
			SHND6	—	—	—	—	—	—	100	—	65	—	50	—	—	800-1200	S	—	10.00	3	
			SCND6	—	—	—	—	—	—	200	—	100	—	65	—	—	800-1200	S	—	10.00	3	

① BLG two-pole breaker is one phase and neutral. Three pole is two phases and neutral - See SpeedFax page 7-31
 ② 1-pole HED 15-30A rated 65kA; 35-100A rated 25kA; 3-pole HED rated 42kA

③ Availability and additional specs tbd, expected late 2019. (COMPAS may allow selection of alternate trip units)
 ④ 2-pole only or two outer poles of 3-pole breaker

⑤ Accessories such as shunt trips on 3 pole breakers require 6.25" of unit space
 ⑥ Approved for CSA and UL Listed.
 ⑦ Approved for CSA but not UL Listed.

Panelboards

Power and Distribution

Selection/Dimensions

Ampere Rating	Mounting Height (inches)
---------------	--------------------------

240V — Twin Mounted NEC Fuse Clips ^①	
30-30	2½ ^②
30-30	5
30-60	5
60-60	5
60-100	7½
100-100	7½
200-200	10

240V — Single Mounted NEC Fuse Clips ^①	
30	7½
60	7½
100	7½
200	10
200	7½
400	10
400	15
600	15
800 (HCP)	16¼
1200 (HCP)	16¼

Ampere Rating	Mounting Height (inches)
---------------	--------------------------

600V — Twin Mounted NEC Fuse Clips ^①	
30-30	7½
30-60	7½
60-60	7½
60-100	7½
100-100	7½
200-200	10

600V — Single Mounted NEC Fuse Clips ^①	
100	7½
200	10
400	10
400	15
400 (HCP)	15
600	15
600	15
800 ^③ (HCP)	16¼
1200 ^③ (HCP)	16¼

Branch Breaker Side Gutter Inches (mm)

Reference Letter	Panel Width 38 Inches Dimensions in inches (mm)
A	14.00 (356)
B	13.98 (355)
C	11.62 (295)
D	10.00 (254)
E	7.61 (193)
F	8.75 (222)
G	8.25 (210)
H	10.90 (276)
I	10.90 (276)
J	11.76 (299)
K	7.92 (201)
L	8.00 (203)
M	13.42 (341)
N	12.00 (305)
O	15.50 (393)
P	14.25 (362)
Q	13.42 (341)
R	13.42 (341)
S	10.00 (254)
T	8.00 (203)
U	10.50 (267)
V	10.50 (267)
W	9.30 (236)
X	10.30 (262)
Y	9.30 (236)
Z	10.30 (262)
AA	10.10 (257)
AB	9.59 (244)
AC	9.59 (244)

← A →	BL, BLH, HBL, BQD	BL, BLH, HBL, BQD	← A →
← B →	NGB, HGB, LGB NGB2, HGB2, LGB2	NGB, HGB, LGB NGB2, HGB2, LGB2	← B →
← D →	ED4, ED6, HED4, HHED6	ED4, ED6, HED4, HHED6	← D →
← E →	CED6	CED6	← E →
← F →	QR2, QRH2, HQR2, HQR2H	QR2, QRH2, HQR2, HQR2H	← F →
← G →	FD6, FXD6, HFD6, HHFD6	FD6, FXD6, HFD6, HHFD6	← G →
← AA →	3VA52 – [MFAS, HFAS, CFAS]	3VA52 – [MFAS, HFAS, CFAS]	← AA →
← H →	ND, HD, LD	ND, HD, LD	← H →
← AB →	3VA61 – [MDAE, HDAE, CDAE, LDAE]	3VA61 – [MDAE, HDAE, CDAE, LDAE]	← AB →
← I →	NF, HF, LF	NF, HF, LF	← I →
← AC →	3VA62 – [MFAE, HFAE, CFAE, LFAE]	3VA62 – [MFAE, HFAE, CFAE, LFAE]	← AC →
← J →	CFD		← J →
← K →	JD6, JXD6, HJD6, HHJD6	JD6, JXD6, HJD6, HHJD6	← K →
← L →	NJ, HJ, LJ	NJ, HJ, LJ	← L →
← M →	SJD6, SHJD6, LD6, LXD6, HLD6, HHLD6, SLD6, SHLD6		← M →
← N →	CJD6, SCJD6, CLD6, SCLD6		← N →
← O →	NJ, HJ, LJ		← O →
← P →	NL, HL, LL		← P →
← Q →	NM, HM, LM		← Q →
← R →	NN, HN, LN		← R →
← S →	VB 30 A	VB 30 A	← S →
← T →	VB 30 - 60A	VB 30 - 60A	← T →
← U →	VB 60 -100A	VB 60 -100A	← U →
← V →	VB 200A	VB 200A	← V →
← W →	VB 100A Single		← W →
← X →	VB 200A Single		← X →
← Y →	VB 400 – 600A Single		← Y →
← Z →	HCP 400 – 1200A Single		← Z →

For inches / millimeters conversion,
see Application Data section.

① For Class J, R or T fuse clip prices, refer to page 11-107.

② NEC fuse clips only.

③ 800 and 1200 ampere switches have class "L" fuse provisions. (Type HCP).

Panelboards

Power and Distribution

Selection/Dimensions

Types P5 and SPP/FPP, F2 (12 3/4" deep)

Connecting Strap Kits^{①②③} Circuit Breaker

For use with P5, Sentron Deep or Type S5 Power Panels					
Max Amp Rating	Breaker Family	Breaker Type	Catalog Number	Unit Height (inches)	Mounting
100	General	BL, BQD	SBLBD	3.75	Twin
125	3VA	3VA41, xGB	S3VA41TD ^④	3.75	Twin
	3VA	3VA41, xGB	S3VA41TDHD ^{④⑤}	7.50	Twin, High Density
	General	XGB2	SGB2D	3.75	Twin
	General	ED	SE6D	3.75	Twin
	General	CED	6CLE2	3.75	Twin
150	3VA	3VA61	S3VA52TD ^④	5.00	Twin
	VL	DG	SDGD	5.00	Twin
225	General	QR	6QR2	5.00	Twin
250	3VA	3VA52, 3VA62	S3VA52TD ^④	5.00	Twin
	VL	FG	SFGD	5.00	Twin
	Sentron	FD	SF6D	5.00	Twin
	Sentron	CFD	SCFD	5.00	Single
400	3VA	3VA53	S3VA53TD ^④	6.25	Single
	3VA	3VA63	S3VA63TD ^④	6.25	Single
	VL	JG	SJG2D	6.25	Twin
	VL	JG	SJG1D	6.25	Single
	Sentron	JD	SJ1D	8.75	Single
	Sentron	JD	SJ2D	8.75	Twin
	Sentron	CJD	SCJD	8.75	Single
	Sentron	SJD	SCJD	8.75	Single
600	3VA	3VA54	S3VA54TD ^④	6.25	Single
	3VA	3VA64	S3VA64TD ^④	6.25	Single
	VL	LG	SLGD	6.25	Single
	Sentron	LD	SL6D	8.75	Single
	Sentron	CLD	SCLD	8.75	Single
	Sentron	SLD	SSL6D	8.75	Single
800	VL	SCLD	SSCLD	8.75	Single
	VL	MG	MG1D	8.75	Single
	Sentron	LMD	SLM1D	8.75	Single
	Sentron	MD, CMD	SMND	10.00	Single
1200	Sentron	SMD	SSMND	10.00	Single
	VL	NG	NG1D	10.00	Single
	Sentron	ND	SMND	10.00	Single
	Sentron	SND	SSMND	10.00	Single

3VA Breaker Provision Kits

Breaker Type	Catalog Number	Description
3VA52, 3VA61 or 3VA62 Breaker	S3VA52PR ^⑥	Only required when installing a 3VA52, 3VA61, or 3VA62 breaker to an existing provision in the field. Parts are included with kit S3VA52TD.

Service Entrance Barriers

Field installable Barriers to meet UL 67 service entrance requirements	
Breaker Type	Catalog Number
(S)JD, (S)LD, MG	SEBP4V1
CJD, CLD	SEBP4V2
JG, LG	SEBP4V3
(S)MD, (S)ND without shield	SEBP5V1
(S)MD, (S)ND with shield	SEBP5V2
Vacu-Break Switches	SEBP5V3
HCP Switches	SEBP5V4

For inches / millimeters conversion, see Application Data section.

- ① Normal stock item.
- ② Includes cover plate and mounting hardware, less circuit breaker.
- ③ Also fits Types FCI, FCII, SB1 and SB2 switchboards.
- ④ 800–1200 amp units are HCP switch.

- ⑤ Suitable to replace QF3 in P1 thru P5 Panelboards and Switchboards
- ⑥ To replace a QJ with a QR only a new cover is needed up to 225A
- ⑦ Although QR is rated 250A, it is limited to 225A in panelboard.
- ⑧ Only required when installing a 3VA52, 3VA61, or 3VA62 breaker to an existing provision in the field. Parts are included with kit S3VA52TD.

Connecting Strap Kits^③ Fusible

For use with P5, Sentron FPP Deep or Type F2 power panels		
Ampere Rating	Unit Height (inches)	12. 75" Deep Box Catalog Number
30–30	2.5	F602D
30–30	5, 7.5	F657D
30–60	5, 7.5	F657D
60–60	5, 7.5	F657D
60–100	5, 7.5	F657D
100–100	5, 7.5	F657D
100	7.5	F657D
200	7.5	F657D
200	10	F671D
200–200	10	F672D
400–600	15	F6150D
800–1200 ^④	16.25	F6162D

Blank Plates

Circuit Breaker and Vacu-Break^①

For use with P5, Sentron SPP and Type S5 power panels	
Height (inches)	Catalog Number
1.25	6FPB01
2.5	6FPB02
3.75	6FPB03
5.0	6FPB05
10.0	6FPB10

Filler Plates

For use with P5, Sentron SPP and Type S5 power panels	
Breaker Type	Filler Plate Catalog Number
BL, BLH, HBL, BQD, ED4, ED6, HED4, HHED6, NGB, HGB, LGB, NGB2, HGB2, LGB2,	DFFP1 ^⑧
NEB, HEB	EBF1

Note: When a front filler plate is not completely filled with breakers, the openings in the unused space must be closed with filler plates selected from this table.

Cover Plates

For use with P5, Sentron SPP and Type S5 power panels	
Breaker Type	Catalog Number
QR	SQRC ^⑨

- ⑧ Strap Kit can also accommodate xGB breakers, reference Installation Instructions
- ⑨ High Density Kit, requires 7.5" Unit Space to fit QTY (6) 2 Pole breakers
- ⑩ Consult Sales for availability
- ⑪ Kit includes breaker nut keepers & bus extensions

Panelboards

Modifications and Additions

Selection

Type P5 Panelboards

Devices Mounted on Gutter Cover Includes Device, Mounting – Wired or Unwired

Description
One piece front with door
(Depth increases to 14.25")
Hinged Gutter Covers 4 pc front
Toggle Switch — SPST or 3-way
15A, 277V maximum
Pilot Light — General Purpose
Neon or Incandescent
Pushbutton

Feed-Thru Lugs

Ampere Rating	Unit Space (inches)
400	10
600	10
800	17.5
1200	17.5

Grounding of Panelboards

Ground Bars except for brazed to box are shipped with the panel interior factory mounted.

- Non-Insulated Equipment Ground Bar – Standard
- Copper Non-Insulated Ground Bar
- Al Insulated Equipment Ground Bar
- Cu Insulated Equipment Ground Bar
- Ground Bar Brazed to Box

Fuse Clip Provisions (Add to 250 Volts or 600 Volts Unit Prices Per Switch)

Amp Rating	Class J	Class R	Class T
30	•	•	N/A
60	•	•	N/A
100	•	•	•
200 ^①	•	•	•
400	N/A	•	•
600	•	•	•

• Indicates available

Ground Fault on Main Breaker

Description	Amp Rating
Conventional Ground Fault ^② Includes:	
Ground Fault Relay, Ground Sensor, CPT and Shunt Trip	800-1200
Test and Monitor Panel ^③	
Ground Fault add to Sensitrip III breaker price (takes 5" of unit space)	800-1200

Time Clocks^④

Sangamo, Tork or Paragon time clock can be supplied, mounted in panel-board cabinet. For required increase in enclosure dimension, consult local sales office.

Description
Time clock (1- or 2-Pole, Single or Double Throw Contacts; 3-Pole Single Throw)
277V Maximum with Plain Dial
Optional: Astronomical Dial An Omitting Device Reserve Power or Carryover
Space and Mounting Provisions Only

Circuit Breaker Accessories Handle Blocking Device Blocks handle in either the "ON" or "OFF" position.

Padlocking Device – Padlocks in "OFF" position.

Main Bus

Standard main bus and ground bus are tin-plated aluminum. For copper main bus, neutral bus and ground bus, add from the table for each panel.

Lugs – For Main Lug Only Panels

Standard main lugs and neutral lugs are tin-plated aluminum, UL listed for use with aluminum/copper cables. Copper only lugs are an option.

Ampere Rating
400 - 1200

Shunt Trip on Main and Branches^⑤

Description
BL, BQD, NGB, HGB, LGB, NGB2, HGB2, LGB2 (branch only)
QR2, QRH2, HQR2, HQR2H ED4, HED4, HHED6, CED6 (branch only)
All others to 1200A

100% Rated Main Circuit Breakers

Ampere Rating	Breaker Type
400	JXD6H, HJXD6H NJY, HJY, LJY
600	LXD6H, HLXD6H
600 ^⑥	NMY, HMY, LMY
800 ^⑦	NNY, HNY, LNY MXD6H, HMXD6U, SMD6, SHMD6, SND6, SHND6, NXD6H, HNXD6H
1200	NNY, HNY, LNY NXD6H, HNXDH,

① For use on main lug, main breaker or main switch panels without subfeed breakers.

② Available in 90" high enclosure only. Unit space is 42½" with Test and Monitor Panel; 45" without Test Monitor Panel.

③ Not available on Sensitrip III.

④ For required unit space, consult local sales office.

⑤ Shunt Trip on 100A frame breakers increases mounting height to 6.25" for twin mounting.

⑥ The 600A, 100% rated breaker application requires the use of an 800A frame breaker.

⑦ The 800A, 100% rated breaker application requires the use of a 1200A frame breaker.

Panelboards

Embedded Micro Metering Module™

Selection

SEM3 System configured in Panelboards

The Siemens SEM3 system can be configured for factory installation in branch circuit monitoring applications using the Siemens COMPAS configuration tool. This option can lower the installation time of the system for the installer while providing a factory warranted solution.

The SEM3 system can be factory installed in unit space in type P2, P4, & P5 Siemens panel boards. Please note P1 and P3 configurations are not available at this time and the amount of unit space needed varies depending upon the application. Please note that lead time adders will apply and may vary depending upon the configuration of the system.

SEM3 for use in Siemens Panelboards

Available in a NEMA 1, 3R, or 12 rated enclosure



Controller

SEM3 controller is mounted in unit space opposite of the feed location specified in COMPAS (i.e., bottom mount for top feed) and will require 3" of unit space. Each controller will be powered by direct tap connection to the panel section bus. Each controller can monitor up to 45 circuits. Applications that require monitoring more than 45 circuits will require additional controllers.



Current Transformers (CTs)

Seven sizes of CTs are available for use in the P5 panel: 50, 125, 250, 400, 600, 800, 1200 amp. All CTs are pre-mounted to a support bracket that attaches to the base rail of the interior of the panel board. Each bracket supports a maximum of 3 CTs and is designed for the breaker selected (brackets are not interchangeable between breaker frames). Each CT will be attached to a data module that is placed in the meter racks.



Meter Racks

Each meter rack requires 3" of unit space. All meter racks will be installed next to the SEM3 controller in unit space. The COMPAS configuration tool will select the appropriate meter rack configuration according to the user's application and will use the 21 space meter rack as a default option where possible. Only one meter rack (regardless of number of positions) can be installed in 3" of unit space.

NOTE: Monitoring of 45 circuits will require 9" of unit space: two 21 position racks and one 3 position rack

Other Considerations

Configuration: Data modules from CTs monitoring a circuit breaker must be mounted adjacent to one another in the meter rack. Any field changes to the factory configuration must take this into account.

Start-up & Commissioning: Siemens can provide these services. Contact your local SIEMENS PDS Power Solutions Business Developer for more details.

Billing Services for sub billing applications: Billing services are available. Contact your local SIEMENS PDS Power Solutions Business Developer for more details.

Panelboards

Embedded Micro Metering Module™


Selection

P5 Devices Enclosure sizes

Example P5 Panel with SEM3 Type 1 Enclosure P5 = (38" or 46" Wide x 10" Deep)

Enclosure heights are in 15" increments from 60" thru 90".
Enclosure heights: 60", 75", 90" (there are optional depths also)

The COMPAS configuration tool can provide actual dimensions based on the configuration. Example below is largest standard P4 enclosure for factory assembled panel - unit space is in 3.75" increments - up to 6 circuits can occupy each 3.75" of unit space.



38" std. width for P5

**Main Breaker / Main Lug space
varies based on selected options**

**Unit space varies
based on selected options**

Note: All circuits do not have to be monitored by SEM3 - user can select any circuits in this space to be monitored.

Based on smallest branch breakers and a 3-phase main being monitored. There is a maximum of 63 circuits that can be monitored with the configuration shown. Some selections of main breakers and other subfeed options could limit this further.

In this situation there is 37.5" of unit space available - so 60 branch circuits could be monitored. If monitoring the main three additional circuits could be monitored with a total of 63 circuits.

This requires two controllers and three 21 position racks using 18.75" of unit space.
- see below -

SEM3 space varies by number of circuits monitored - this uses unit space.

- == > 7.5" of space for up to 21 circuits monitored
one controller and one 21-pos rack
- == > 11.25" of space for up to 42 circuits monitored
one controller and two 21-pos racks
- == > 15" of space for up to 45 circuits monitored
one controller and two 21-pos racks plus one 3-pos rack
- == > 18.75" of space for up to 63 circuits monitored
two controllers and three 21-pos racks

Note: If subfeed space is needed - it will take away from available unit space.

Panelboards

Modifications and Additions

Selection

Type P5 Panelboards

Vacu-Break Fusible Switches

For Branch Circuit Use with AC Combination Full Voltage Starters ^①

Amp Rating	Horsepower Ratings				Mounting Height in Inches (mm)				Min. Section Width Inches (mm)
	240V AC		480V AC		240V AC		480V AC		
	With NEC Fuse	With Dual-Element Fuse	With NEC Fuse	With Dual-Element Fuse	Twin	Single	Twin	Single	
30-30	3	7.5	—	—	2.50 ② (64)	—	—	—	32 (813)
30-30	3	7.5	5	10	5.00 (127)	—	7.50 (191)	—	32 (813)
30-60	3-7.5	7.5-15	5-15	25	5.00 (127)	—	7.50 (191)	—	32 (813)
60-60	7.5	15	15	25	5.00 (127)	—	7.50 (191)	—	32 (813)
60-100	7.5-15	15-30	15-25	25-50	7.50 (191)	—	7.50 (191)	—	32 (813)
100-100	15	30	25	50	7.50 (191)	—	7.50 (191)	—	32 (813)
100	—	—	25	50	—	—	—	7.50 (191)	32 (813)
200	25	50	50	100	—	10.00 (254)	—	10.00 (254)	32 (813)
200-200	—	50	—	100	10.00 (254)	—	10.00 (254)	—	32 (813)
400	50	100	100	—	—	10.00 (254)	—	10.00 (254)	38 (965)
400	50	100	100	—	—	15.00 (381)	—	15.00 (381)	38 (965)
600	75	100	—	—	—	15.00 (381)	—	15.00 (381)	38 (965)

Connector Modifications

Compression Lugs

Style	Amp Rating	Breaker Type	Compression Connectors	Available Unit Space Reduction
MLO	800	N/A	All compression lugs	Deduct 5.0" Unit Space
	1000	N/A	All compression lugs	Deduct 5.0" Unit Space
	1200	N/A	All compression lugs	Deduct 5.0" Unit Space
Main Breaker	800	MD6, HMD6, CMD6, SMD6, SHMD6, SCMD6	(3)#2/0 AWG - 500 Kcmil Cu or Al	0
	1200	ND6, HND6, CND6, SND6, SHND6, SCND6	(4)#250 - 500 Kcmil Cu or Al	0

Alternate Lugs

Style	Amp Rating	Breaker Type	Compression Connectors	Available Unit Space Reduction
MLO	800	N/A	(3)#3/0 AWG - 750 Kcmil Cu or Al	Deduct 10" Unit Space
	1000	N/A	(4)#3/0 - 600 Kcmil Cu or Al (4)#3/0 AWG - 750 Kcmil Cu or Al	Deduct 10" Unit Space
	1200	N/A	(4)#3/0 AWG - 600 Kcmil Cu or Al (4)#3/0 AWG - 750 Kcmil Cu or Al	Deduct 10" Unit Space

① 100,000 kA at 480V with Class J or Class RK5 fuses.

② The 2.50 inch (64mm) high unit is suitable for NEC Class H and K5 fuses only. Class R rejection type fuse holders are not available.

Panelboards

Kits and Accessories

Selection

Type P5 Panelboards

Enclosures

Description	Catalog number
P5 Type 1 36" W x 12.75" D x 60" H	PB860
P5 Type 1 36" W x 12.75" D x 75" H	PB875
P5 Type 1 36" W x 12.75" D x 90" H	PB890
P5 Type 1 36" W x 14.75" D x 60" H	PBD860 ^①
P5 Type 1 36" W x 14.75" D x 75" H	PBD875 ^①
P5 Type 1 36" W x 14.75" D x 90" H	PBD890 ^①
P5 Type 3R/12 60" H	WP860
P5 Type 3R/12 75" H	WP875
P5 Type 3R/12 90" H	WP890

Trims

Description	Catalog number
P5 Std (4 piece trim) vented 60"	P560V
P5 Std (4 piece trim) vented 75"	P575V
P5 Std (4 piece trim) vented 90"	P590V
P5 Std (4 piece trim) unvented 60"	P560NV ^②
P5 Std (4 piece trim) unvented 75"	P575NV ^②
P5 Std (4 piece trim) unvented 90"	P575NV ^②
P5 Std (4 piece trim) vented 60" with hinged gutter covers	P560VHG
P5 Std (4 piece trim) vented 75" with hinged gutter covers	P575VHG
P5 Std (4 piece trim) vented 90" with hinged gutter covers	P590VHG
P5 Std (4 piece trim) unvented 60" with hinged gutter covers	P560NVHG
P5 Std (4 piece trim) unvented 75" with hinged gutter covers	P575NVHG
P5 Std (4 piece trim) unvented 90" with hinged gutter covers	P590NVHG
P5 Std (1 PC Door) vented 60"	P560VD ^③
P5 Std (1 PC Door) vented 75"	P575VD ^③
P5 Std (1 PC Door) vented 90"	P590VD ^③
P5 Std (1 PC Door) unvented 60"	P560NVD ^③
P5 Std (1 PC Door) unvented 75"	P575NVD ^③
P5 Std (1 PC Door) unvented 90"	P590NVD ^③
P5 Std (1 PC Door-in-door) vented 60"	P560VDD ^③
P5 Std (1 PC Door-in-door) vented 75"	P575VDD ^③
P5 Std (1 PC Door-in-door) vented 90"	P590VDD ^③
P5 Std (1 PC Door-in-door) unvented 60"	P560NVDD ^③
P5 Std (1 PC Door-in-door) unvented 75"	P575NVDD ^③
P5 Std (1 PC Door-in-door) unvented 90"	P590NVDD ^③

Flush mounting kits

Description	Catalog number
Flush kit to P5 60" High	F860
Flush kit to P5 75" High	F875
Flush kit to P5 90" High	F890

^① Required with door over breaker handles.

^③ Requires 14.5" deep box.

^② Unvented trims require amps per square inch bussing.


Panelboards

Type P5 Panelboards


Dimensions

Type 1 Box

Box is symmetrical



Type 3R and 3R/12 Box



Dimensions shown in inches and millimeters [].

Panelboards

Circuit Breaker / Column Type

General

Type C1

240 Volts AC Maximum

250 Ampere Mains

250 Ampere Maximum Branch

UL Short Circuit Rating —

200,000 IR Maximum

**Branch Breaker Symmetrical
Interrupting Rating**

Based on Underwriters' Test Procedure

Type C2

480Y/277 Volts AC Maximum

250 Ampere Mains

250 Ampere Maximum Branch

UL Short Circuit Rating —

100,000 IR Maximum

Meets NEC wire bending requirement,
section 312-6.

Panelboards

Listed by Underwriter's Laboratories,
Inc., under "Panelboards" File #E2269.

Meets Federal Specification
W-C375B/Gen.

Service

240 Volts Maximum. 1-Phase, 3-Wire, or
3-Phase, 4-Wire.

Panelboards Fronts and Doors

Standard panelboards are furnished with
trim with a flush door lock. All are factory
assembled for ease of installation. Fronts
are fabricated from code gauge steel and
finished ANSI-61.

Main Breakers C1

BL, BLH and HBL frame breakers are
mounted horizontally. All other frames
are mounted vertically.

Main Breakers C2

BQD frame breakers are mounted
horizontally. All other frames are
mounted vertically.

Boxes

C1 — 7 $\frac{5}{8}$ " wide, 5 $\frac{3}{4}$ " deep.

C2 — 8 $\frac{1}{2}$ " wide, 5 $\frac{3}{4}$ " deep.

Branch Breaker Side Gutters

Type	Circuit Breaker	Side Gutter (inches)
C1	BL, BLH, HBL	3.505
C2	BQD	3.5

Weight—Approximate

Total panelboard weight when filled with
a normal quantity of breakers and
accessories is:

*About 3 lbs. per inch of box height.

Gauge Steel Boxes

Type	Width	Height	Gauge Steel
C1	7 $\frac{5}{8}$ "	48", 73", 85"	#14
C2	8 $\frac{1}{2}$ "	48", 73", 85"	#14

Fronts

C1	7 $\frac{5}{8}$ "	48", 73", 85"*	#14
C2	8 $\frac{1}{2}$ "	48", 73", 85"*	#14

*Note: Feed thru lugs and subfeed breaker not available
for this height.

Main Breaker Connectors

Ampere Rating	Connectors suitable for Cu or Al
100	(1) #14-1/0 AWG
125	(1) #4-1/0 AWG
225	(1) #6 AWG-300 kcmil
250	(1) #4 AWG-350 kcmil Al (1) #6 AWG-350 kcmil Cu

Main Lugs

125	(1) #6 AWG-350 kcmil
250	(1) #6 AWG-350 kcmil

For inches / millimeters conversion,
see Application Data section.

① Connector ranges indicated do not apply to all main breaker types. Refer to
molded case circuit breaker standard pressure wire connectors in the breaker
section of this catalog for the wire ranges for a specific breaker frame.

Panelboards

Circuit Breaker / Column Type

Selection

11
PANELBOARDS

Main Lugs Only C1

240 Volts Maximum

Maximum Panel Ampere Rating	Maximum 1-Pole Circuits	Box Height (inches)	208Y/120V	120/240V
			3-Phase, 4-Wire Catalog Number	1-Phase, 3-Wire Catalog Number
125	18	48	C1C18ML125CTS	C1A18ML125CTS
	30	73	C1C30ML125CTS	C1A30ML125CTS
	42	85	C1C42ML125CTS	C1A42ML125CTS
250	18	48	C1C18ML250CTS	C1A18ML250CTS
	30	73	C1C30ML250CTS	C1A30ML250CTS
	42	85	C1C42ML250CTS	C1A42ML250CTS

Main Circuit Breaker^{①②} C1

240 Volts Maximum

100	18	48	C1C18BL100CTS	C1A18BL100CTS
	30	73	C1C30BL100CTS	C1A30BL100CTS
	42	85	C1C42BL100CTS	C1A42BL100CTS
125	18	48	C1C18E4125CTS	C1A18E4125CTS
	30	73	C1C30E4125CTS	C1A30E4125CTS
	42	85	C1C42E4125CTS	C1A42E4125CTS
225	18	48	C1C18QR225CTS	C1A18QR225CTS
	30	73	C1C30QR225CTS	C1A30QR225CTS
	42	85	C1C42QR225CTS	C1A42QR225CTS
250	18	48	C1C18FX250CTS	C1A18FX250CTS
	30	73	C1C30FX250CTS	C1A30FX250CTS
	42	85	C1C42FX250CTS	C1A42FX250CTS

Main Lugs Only C2

480Y/277 Volts Maximum

Maximum Panel Ampere Rating	Maximum 1-Pole Circuits	Box Height (inches)	480Y/277V
			3-Phase, 4-Wire Catalog Number
125	18	48	C2E18ML125CTS
	30	73	C2E30ML125CTS
	42	85	C2E42ML125CTS
250	18	48	C2E18ML250CTS
	30	73	C2E30ML250CTS
	42	85	C2E42ML250CTS

Main Circuit Breaker^{①②} C2

480Y/277 Volts Maximum

100	18	48	C2E18BD100CTS
	30	73	C2E30BD100CTS
	42	85	C2E42BD100CTS
125	18	48	C2E18E4125CTS
	30	73	C2E30E4125CTS
	42	85	C2E42E4125CTS
225	18	48	C2E18FX225CTS
	30	73	C2E30FX225CTS
	42	85	C2E42FX225CTS
250	18	48	C2E18FX250CTS
	30	73	C2E30FX250CTS
	42	85	C2E42FX250CTS

Alternate Main Breaker Selection^{①②} C1

Ampere Rating	Breaker Type	Maximum Interrupting Rating (KA)	Catalog Number	Available Trip Values
100	BL	10	BL	50, 60, 70, 80, 90, 100
	BLH	22	LH	50, 60, 70, 80, 90, 100
	HBL	65	HL	50, 60, 70, 80, 90, 100
125	ED4	65	E4	50, 60, 70, 80, 90, 100, 110, 125
	HED4	100	H4	50, 60, 70, 80, 90, 100, 110, 125
	HHED6	100	HA	50 (3-pole only)
225	QR2	10	QR	100, 110, 125, 150, 175, 200, 225
225	FXD6	65	FX	70, 80, 90, 100, 110, 125, 150, 175, 200, 225
	HFD6 ^②	100	HF	70, 80, 90, 100, 110, 125, 150, 175, 200, 225
250	FXD6	65	FX	250
	HFD6 ^②	100	HF	250

For inches / millimeters conversion, see Application Data section.

① BL, BLH, HBL and BQD are horizontally mounted. All others vertically mounted.

② Interchangeable trip breakers such as FD6 and HFD6 cannot be back fed. Must be top feed only.

Panelboards

Circuit Breaker / Column Type

Selection

Branch Breaker Selection C1

Breaker Type	Available Ampere Rating	Availability			Maximum Interrupting Rating (kA)		
		1-Pole	2-Pole	3-Pole	120V	120/240V	240V
BL (120V)	15, 20, 30, 40, 50, 60	✓	✓	✓	—	10	—
	70	✓	✓	✓	—	10	—
	70, 80, 90, 100	—	✓	✓	—	10	—
BL (HID)	15, 20, 30	✓	✓	—	—	—	—
BLF (GFCI)	15, 20, 30	✓	✓	—	10	—	—
	40, 50, 60	—	✓	—	10	—	—
BLE (EQGFI)	15, 20, 30	✓	✓	—	10	—	—
BGL (SWN)	15, 20, 30	—	✓	✓	10	—	—
BLR (240V)	15, 20, 30, 40, 50, 60	—	✓	—	—	—	10
	70, 80, 90, 100	—	✓	—	—	—	10
BLH (120V)	15, 20, 30, 40, 50, 60	✓	✓	✓	—	22	—
	70	✓	✓	✓	—	22	—
	70, 80, 90, 100	—	✓	✓	—	22	—
BLHF (GFCI)	15, 20, 30	✓	✓	—	—	22	—
	40, 50, 60	—	✓	—	—	22	—
HBL	15, 20, 30, 40, 50	✓	✓	✓	—	65	65
	60, 70, 80, 90, 100	—	✓	✓	—	65	65

Subfeed Breakers — Limit One Per Panel^① C1 (Not available for 42 circuit panels)

ED4	15, 20, 30, 40, 50, 60, 70, 80, 90, 100	—	✓	✓	—	—	65
	110, 125	—	✓	✓	—	—	65
HED4	15, 20, 30, 40, 50, 60, 70, 80, 90, 100	—	✓	✓	—	—	65
	110, 125	—	✓	✓	—	—	100
HHED6	15, 20, 30, 40, 50 (3-pole only)	—	—	✓	—	—	100
QR2	100, 110, 125, 150, 175, 200, 225	—	✓	✓	—	—	10
FXD6	70, 80, 90, 100, 110, 125, 150, 175, 200, 225, 250	—	✓	✓	—	—	65
	70, 80, 90, 100, 110, 125, 150, 175, 200, 225, 250	—	✓	✓	—	—	100

Alternate Main Breaker Selection^{①②③} C2

Ampere Rating	Breaker Type	IR	Catalog Number	Available Trip Values
100	BQD	14	BD	50, 60, 70, 80, 90, 100
125	ED4	18	E4	50, 60, 70, 80, 90, 100, 110, 125
	ED6	25	E6	50, 60, 70, 80, 90, 100, 110, 125
	HED4	42	H4	50, 60, 70, 80, 90, 100, 110, 125
	HHED6	65	HA	50 (3-pole only)
225	FXD6	35	FX	70, 80, 90, 100, 110, 125, 150, 175, 200, 225
	HFD6	65	HF	170, 80, 90, 100, 110, 125, 150, 175, 200, 225
250	FXD6	35	FX	250
	HFD6	65	HF	250

Branch Circuit Breakers C2

Breaker Type	Available Ampere Rating	Availability			Maximum Interrupting Rating (kA)		
		1-Pole	2-Pole	3-Pole	277V	480/277V	480V
BQD	15, 20, 30, 40, 50, 60	✓	✓	✓	14	14	—
	70, 80, 90, 100	✓	✓	✓	14	14	—

Subfeed Breakers — Limit One Per Panel^{①②} C2 (Not available for 42 circuit panels)

ED4	15, 20, 30, 40, 50, 60, 70, 80, 90, 100	—	✓	✓	—	18	18
	110, 125	—	✓	✓	—	18	18
ED6 ^④	15, 20, 30, 40, 50, 60, 70, 80, 90, 100	—	✓	✓	—	—	25
	110, 125	—	✓	✓	—	—	25
HED4	15, 20, 30, 40, 50, 60, 70, 80, 90, 100	—	✓	✓	—	—	42
	110, 125	—	✓	✓	—	—	42
FXD6	70, 80, 90, 100, 110, 125, 150, 175, 200, 225, 250	—	✓	✓	—	—	35
HFD6	70, 80, 90, 100, 110, 125, 150, 175, 200, 225, 250	—	✓	✓	—	—	65

① No increase in box height. Space is already built into C1 panel.

② BL, BLH, HBL and BQD are horizontally mounted. All others vertically mounted.

③ Interchangeable trip breakers such as FD6 and HFD6 cannot be back fed. Must be top feed only.

④ ED6/CED6 2-pole limited amps available (20-50A)

Panelboards

Circuit Breaker / Column Type, Modifications and Additions

Selection

PANELBOARDS
11

Type C1/C2

When required, special constructions or additions to standard panelboards may be specified for factory-assembled column panelboards.

Box Modifications

Description
Gasketed
Metal Card Holder
Welded Metal Card Holder
Nameplate
Al Ground Bar
Cu Ground Bar
Insulated Al Ground Bar
Insulated Cu Ground Bar

Interior Modifications

Description
Feed-Thru Lugs
Cu Neutral Lugs
Cu main Lugs 125A
Cu main Lugs 250A

Box Sizing Chart

Certain modifications such as subfeed breakers and feed-thru lugs require additional unit space. Use this chart to determine proper enclosure size.

Panel Configuration	Box Height (inches)
All MLO 18 Circuit	48
All MLO 30 Circuit	73
All MLO 42 Circuit	85
All MLO 18 Circuit with feed-thru lugs	73
All MLO 30 Circuit with feed-thru lugs	85
All MLO 18 Circuit with subfeed breaker	73
All MLO 30 Circuit with subfeed breaker	85
All Main Breaker 18 Circuit	48
All Main Breaker 30 Circuit	73
All Main Breaker 42 Circuit	85
All Main Breaker 18 Circuit with feed-thru lugs	73
All Main Breaker 30 Circuit with feed-thru lugs	85
All Main Breaker 18 Circuit with subfeed breaker	73
All Main Breaker 30 Circuit with subfeed breaker	85

Breaker Kits and Accessories

Kit Number	Description	Contents
MBKQRC1FK	C1 Filler for QR in Main position 1PH or 3PH	Kit contains all cover plates necessary to change from QJ to QR both 2 and 3-pole breakers.

Column Extension

Available in various standard lengths, extensions are 5¼ inches deep and 7 inches wide.

Height (inches)	Catalog Number ^①
14	LXX-14
20	LXX-20
26	LXX-26
32	LXX-32
38	LXX-38
41	LXX-41
44	LXX-44
53	LXX-53
56	LXX-56
62	LXX-62
65	LXX-65
68	LXX-68
74	LXX-74
80	LXX-80
86	LXX-86

Pull Boxes

Two styles of pull boxes are available, top and front mounted. When the panel and its extensions are mounted in a structural WF beam a front mounted pull box is required. When the panels are surface mounted, a top mounted pull box may be used. Provisions are made so that the neutral bar may be mounted in the pull box when required. (Front mounted pull box dimensions are 14" H. X 20" W.)

Description	Catalog Number ^①
Top Mount	LXXP-T
Front Mount ^②	LXX50-F

For inches / millimeters conversion, see Application Data section.

^① Must be ordered as a manual line.
^② Includes 50" extension.

Panelboards

Telephone and Equipment Cabinets

Selection/Dimensions

Telephone and Equipment Cabinets: Conform to requirements of Underwriters' Laboratories, Inc., for all cabinets and boxes bearing their label. Surface and Flush enclosures: box and front constructed of code-gauge steel, box galvanized and front only finished with light gray, ANSI-61. Cabinets provided without backboards.

Boxes: Standard construction has blank end walls, without knockouts.

Fronts: Siemens Fas Latch fronts feature concealed hinges and fastening screws. Match P1 and P2 Panels in appearance. Two locks supplied on doors more than 51 inches high.

Cabinets


Dimensions (inches)			Surface Mount Catalog Number	Flush Mount Catalog Number
Height	Width	Depth		

With FAS Latch Front

29	20	5.75	TCS29B	TCF29B
41	20	5.75	TCS41B	TCF41B
47	20	5.75	TCS47B	TCF47B
59	20	5.75	TCS59B	TCF59B



Dimensions



For inches / millimeters conversion, see Application Data section.

© Add S for Surface, F for Flush.

Panelboards

Enclosure Modifications

Selection

Customer Relay Cabinets

Dimensions			Catalog Number
H	W	D	
23	20	5.75	RC(1)23B ^①
23	24	5.75	RCW(1)23B ^②

Ampere Rating	ASCO #920 Mechanically held		ASCO #911 — Mechanically held remote control switch suitable for all classes of loads (Total system loads). Voltage rated to 480V AC, UL listed.	Siemens LEN Electrically Held	
	2-Pole	3-Pole	3-Pole	2-Pole	3-Pole
20	—	—	—	—	—
30	✓	✓	—	—	✓
60	✓	✓	—	—	✓
75	✓	✓	—	—	—
100	✓	✓	✓	—	✓
150	✓	✓	✓	—	—
200	✓	✓	—	—	✓
225	✓	✓	—	—	—
260	—	—	✓	—	—
300	—	—	✓	—	—
400	—	—	✓	—	—
600	—	—	✓ ^③	—	—
800	—	—	✓	—	—
1000	—	—	✓	—	—
1200	—	—	✓	—	—

✓ = available configurations

Application (See individual panel sections for application information)

Remote Control Switch Modification

Description
Auxiliary Contacts (Mounted Not Wired) Ea.
2-Wire Control (add 6" to panel height.)

Control Power Transformer

Size	VA
0,1	50
2	75
3	150
4	250

① Replace (1) with "S" for surface applications and "F" for flush applications.

② Includes Fas latch trim and steel mounting pan. If 2 or more cabinets are to be stacked in order (no extra charge for connecting hardware).

③ Available in P4 or P5 only.

Panelboards

Modifications and Additions

Selection

Standard Enclosures Made From Special Materials — Type P1, P2, P3

Stainless Steel Options

14GA 304 SS Grade (Brush Front)	Front Front
------------------------------------	----------------

* Stainless available only for Screw-to-Box, Hinge-to-Box, and Door-in-Door.
All have piano hinges only.

**No special sizes. 20" and 24" wide only.

Stainless Steel Additions to Enclosure Size (Type 1 Only)

	Lighting Panel	Distribution Panels
Width	Order in 2" increments (30" max)	Order in 2" increments
Depth	Order in 2" increments (10" max)	Order in 2" increments

Consult factory for dimension limitations.

Miscellaneous

Description.
Conduit Hubs — Up to 1 1/2 in. Each 2 in. to 2 1/2 in. Each 3 in. Each

Painted Finish

Set-up Charge Net Box Only Alternate Color Trim

Front And Door Modifications

Two Panels with Common Trim (14 GA only) ^②

Devices Mounted On Interior-Includes Device, Mounting (Wired or Unwired)^①

Toggle Switch-SPST or 3-way; 15A, 277 V Maximum
Pilot Light-General Purpose, Neon or Incandescent
Pushbutton

Gauge Steel of Boxes/Fronts, Surface and Flush (see pgs. 11-6 & 11-7)

Dimensions in Inches (mm)		Gauge Steel		
H	W	Box	Front/Door	Type
26-74 (660-1880)	20 (508)	16 ^①	14 ^⑥	Type 1
26-74 (660-1880)	20 (508)	16 ^②	16/14 ^②	Type 3R/12
32-60 (813-1524)	20-36 (508-914)	14 ^③	14 ^③	Type 4
26-74 (660-1879)	20 (508)	14 ^④	14 ^④	Type 4X
36-60 (914-1524)	30-36 (762-914)	N/A ^⑤	N/A ^⑤	Type 4X Non-Metallic

① 16 Gauge is Standard (14 Gauge & 12 Gauge are optional)

② 15 Gauge Steel Can with 14 Gauge Door or Similar Approved Construction

③ No Optional Gauge available

④ 304SS 14 Gauge Std., 316SS 14 Gauge optional

⑤ Sizes do not match Standard Enclosure Sizes - See Table P1-21 - material is non-metallic - No Gauge Specified.

⑥ FAS-Latch is 14 GA only.

Screw-to-Box, Hinge-to-Box, Door-in-Door (14 GA Std./12 GA Std. or 10 GA Optional)
STB/HTB/DND with Piano Hinge (14 GA Std./12 GA Optional)

Note: For retro fit interiors and fronts into existing can, retro fit must match or exceed minimum height, width, and depth requirements of standard Type 1 enclosures.

①Panels having doors over 48 in. high, 2 locks are standard.

② Lighting panels only. Field must supply dimensional information and panel orientation.

Panelboards

Circuit Breaker Accessories and Modifications


Selection

Conduit Enclosing Shield (Panel Skirts)

Sheet metal to cover conduits above or below a standard panelboard box.

Skirt Length	Width	Depth
8, 9, 11, 12, 14, 17, 18, 23, 25	20.00	5.75
26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36		
37, 38, 39, 40, 41, 42, 43, 44		
8, 9, 11, 12, 14, 17, 18, 23, 25	24.00	7.75
26, 27, 28, 29, 30, 31, 32, 33, 34, 35, 36		
37, 38, 39, 40, 41, 42, 43, 44		

Panel Skirts Standard Configurations



Notes:

- A) 4-sided skirts have standard Part Numbers (not catalog numbers).
- B) 3-sided skirts are ordered as Custom in COMPAS.
- C) Order in COMPAS with interior when possible.
- D) If ordered separate from interior, use a manual line in COMPAS.
- E) Must note if Top Entry or Bottom Entry required.

Molded Case Switches^①

(Non-Automatic Circuit Interrupters)

When Molded case switches are substituted for thermal breakers deduct from the installed thermal breaker price:

Ampere Rating	Breaker Frame	Availability	
		3-Pole	2-Pole
100	ED2 ED4 ED6	✓ ✓ ✓	✓ ✓ ✓
225	QR2	✓	✓
250	FXD6	✓	✓
400	JXD2 JXD6	✓ ✓	✓ ✓
600	LXD6	✓	✓
800	MD6	✓	✓
1200	ND6	✓	—

^① Available only as a main switch for non-service equipment applications. Not available for branch devices.

QuickShip™


All SQSCP configurations of the standard NEMA 1 enclosure can be specified for shipment within 10 business days of order when specified.



Mains	MLO (Main Lug Only)
	Fused disconnect switch
	Non-fused disconnect switch
Assembly SCCRs	200kA, 100kA or 50kA AC, 100kA or 20kA@125Vdc ^①
Voltage ratings	Applicable on any 600Vac or less, or 125Vdc ^② or less systems
Bus amperages	400A, 225A, 200A, 100A, 60A or 30A
Branch circuits	Circuits: 18, 30 or 42*
	Amps: Up to 100A
	Type: 1-, 2- and 3-Pole
Panels	Feed: top & bottom
	Mounting: surface or flush
	Door/Trim: regular or door-in-door
	NEMA Ratings: 1 & 3R. Other ratings available, consult factory.
Through-lugs & loadside disconnect	Feed-Through: single and double
	Sub-Feed
	Feed/Sub-Through
	Fused loadside disconnect, (up to 1/2 of main amp rating)
Neutrals	200A, 400A and 800A unbonded and bonded
Grounds	Non-isolated or isolated
Enclosure sizes	Standard size panelboard (20" W x 5 3/4" D x 33" - 69" H)*
Spare fuses	Spare fuse compartment holds up to six fuses
Options	Surge protection device (SPD) for high and low energy transients.*

① Depending on configuration.

② 125Vdc rating applicable to only 80 amp or less CCPBs on MLO panels only.



*Factory installed SPD options

System & Voltage	Catalog Number	Discharge Current		Response Time	SCCR	Data Sheet Number
		Nominal (I _n)	Maximum (I _{max})			
Single-phase, 120/240	BSPM2240S3G	20 kA	40 kA	≤25 ns	200 kA	2150
Three-phase Wye, 208/120	BSPM4208WYNG					2152
Three-phase Wye, 480/277	BSPM4480WYNG					2152
Delta, 480	BSPM3480DLG					2151

Catalog Symbol: SQSCP4

Description

Panelboards for commercial/industrial branch or service entrance applications on systems up through 600Vac.

The SQSCP is specifically designed to address the NEC® Selective Coordination Requirements for Emergency, Legally Required Standby, Healthcare Essential Electrical and Critical Operation Power Systems (COPS) per NEC® 700.28, 701.27, 645.27 and 708.54. Not for applications requiring AFCI protected circuits. The SQSCP is configured to order for the application. To confirm availability of options and constructions, contact your Siemens distributor.

Ratings

Volts: 600Vac (or less), 125 Vdc
Amps: 30, 60, 100, 200, 225, 400A
SCCR: 20kA or 100kA @ 125Vdc—See panelboard short circuit ratings table for AC ratings.

Agency information

- UL 67—Standard for panelboards
- UL 50/UL 50E—Enclosures for electrical equipment
- CSA 22.2, No. 29-M1989—Panelboards and encl. panelboards
- UL listed, class CTL panelboard (meets editions of the NEC prior to 2008 with regard to the NEC® 408.15 limit of 42 overcurrent devices per panel)
- UBC and CBC Seismic Qualified and IBC Approved

Main options

- Main lug only (MLO)
- Fused main disconnect
- Non-fused main disconnect

Branch disconnect options

- 1-, 2-, and 3-pole 15, 20, 30, 40, 50, 60, 70, 90, and 100A rejecting branch disconnects (see table for details).
Branch ampacity on 125Vdc panels limited to SCCPB 80A or less.

Branch circuit positions

- 18, 30 and 42

Neutral options

- Unbonded and bonded 200A, 400A and 800A

Ground options

- Isolated and non-isolated

Enclosures

- NEMA 1 and NEMA 3R. Other ratings available. Consult factory.

Spare fuse compartment

- Six space spare fuse compartment standard on all models

Panelboard Short-circuit Current Ratings

SCCR	AC main options				DC
	Main lug only (MLO) ^①	70-200A main disc. no fuses ^① or w/ Class J fuses	225-400A main disc. no fuses ^① or w/ Class J fuses	SCCP_CF main disc. (60A) ^②	Main lug only (MLO) ^①
High	200kA	200kA	100kA	200kA	100kA
Std.	50kA	50kA	50kA	50kA	20kA

① Class J, T or RK1 fuses upstream, max amps = panel amps.


② CUBEFuse® disconnect

Panelboards

SCCPB Branch Disconnects, CUBEFuse®

Replacement parts and performance data

11
PANELBOARDS



I – CCPB Branch Disconnects

Poles	Ampacity	Part No.
1-pole	15A, 20A, 30A, 40A, 50A, 60A, 70A, 90A, 100A	SCCPB-1-(amp)CF
2-pole		SCCPB-2-(amp)CF
3-pole		SCCPB-3-(amp)CF

J – CUBEFuse® Fuses

For CCPB® Part No.	Non-indicating Part No. STCF(amps)RN	Indicating® Part No. STCF(amps)
SCCPB-(# of poles)-15CF	STCF1RN, STCF3RN, STCF6RN, STCF10RN, STCF15RN	STCF6 STCF10 STCF15
SCCPB-(# of poles)-20CF	STCF17-1/2 RN STCF20RN	STCF17-1/2 STCF20
SCCPB-(# of poles)-30CF	STCF25RN STCF30RN	STCF25 STCF30
SCCPB-(# of poles)-40CF	STCF35RN STCF40RN	STCF35 STCF40
SCCPB-(# of poles)-50CF	STCF45RN STCF50RN	STCF45 STCF50
SCCPB-(# of poles)-60CF	STCF60RN	STCF60
SCCPB-(# of poles)-70CF	STCF70RN	STCF70
SCCPB-(# of poles)-90CF	STCF80RN STCF90RN	STCF80 STCF90
SCCPB-(# of poles)-100CF	STCF100RN	STCF100

- ① CCPB disconnect can accept CUBEFuses® with amp ratings less than or equal to the amp rating of the SCCPB disconnect.
 ② 1A indicating CUBEFuse® not available. Correct fit with SCCPB disconnect requires indicating CUBEFuse® with date code R38 or later.

Fuse and disconnect performance data

For details and specifications, access the following data sheets online at www.usa.siemens.com/panelboards

CUBEFuse® Specifications Catalog Symbols

STCF_ (6-100A Indicating version)

STCF_RN (1-100A Non-indicating version)

Description

The CUBEfuse® is a finger-safe, dual-element, time delay UL Class CF power fuse with Class J fuse electrical performance characteristics. 10 Seconds minimum operating time at 500% rated current.

Ratings

Volts: 600Vac/300Vdc
 Amps: 1-100 (non-indicating version)
 6-100 (indicating version)
 IR: 300kA RMS Sym. (UL)
 200kA RMS. Sym (CSA)
 100kA DC (UL & CSA)

Agency Information

- UL Listed Special Purpose Fuse: Guide JFHR, File E56412
- CSA Certified Fuse: Class 1422- 02, File 53787
- CE compliance for the European Union low voltage directive

Other Ratings/Specifications

Watts Loss at rated current: STCF30: 3.99W
 STCF60: 6.23W
 STCF100: 9.51W

Operating and Storage Temperature Range

14 to 149°F (-10 to 65°C)

Material Specifications

- Case: Glass filled PES (Polyethersulfone)
- Terminals: Copper alloy
- Terminal plating: Electroless tin
- Indicator lens: PES (Polyethersulfone) (indicating version only)
- Indicator: Energetic chemical

CUBEFuse®, Low-Peak®, Quik-Spec™, QuickShip™, and easyID™ are valuable trademarks of Cooper Industries in the United States and other countries.

Panelboards

SCCPB Branch Disconnects, CUBEFuse®

Specifications


11
PANELBOARDS

SCCPB Horsepower Ratings

SCCPB Disconnect	Amp Rating	HP Rating @ Vac			
		120	240	480	600
SCCPB-(poles)-15CF	15	0.5	3	5	7.5
SCCPB-(poles)-20CF	20	0.75	3	7.5	10
SCCPB-(poles)-30CF	30	1.5	5	15	10
SCCPB-(poles)-40CF	40	2	7.5	20	10
SCCPB-(poles)-50CF	50	3	7.5	20	10
SCCPB-(poles)-60CF	60	3	7.5	20	10
SCCPB-(poles)-70CF	70	3	15	30	40
SCCPB-(poles)-90CF	80	5	20	40	50
SCCPB-(poles)-100CF	100	5	20	50	50

Branch Disconnects

SCCPB ^① Part No.	Poles	Fuse Amp Range	Max. SCCBP Amp.	Non-indicating Fuses (Standard)	Indicating Fuses (Opt'l) ^②
SCCPB-1-15CF	1	1-15	15	STCF1RN, STCF3RN, STCF6RN, STCF10RN, STCF15RN	STCF6 STCF10 STCF15
SCCPB-2-15CF	2				
SCCPB-3-15CF	3				
SCCPB-1-20CF	1	17.5-20	20	STCF17-1/2 RN STCF20RN	STCF17-1/2 STCF20
SCCPB-2-20CF	2				
SCCPB-3-20CF	3				
SCCPB-1-30CF	1	25-30	30	STCF25RN STCF30RN	STCF25 STCF30
SCCPB-2-30CF	2				
SCCPB-3-30CF	3				
SCCPB-1-40CF	1	35-40	40	STCF35RN STCF40RN	STCF35 STCF40
SCCPB-2-40CF	2				
SCCPB-3-40CF	3				
SCCPB-1-50CF	1	45-50	50	STCF45RN STCF50RN	STCF45 STCF50
SCCPB-2-50CF	2				
SCCPB-3-50CF	3				
SCCPB-1-60CF	1	60	60	STCF60RN	STCF60
SCCPB-2-60CF	2				
SCCPB-3-60CF	3				
SCCPB-1-70CF	1	70	70	STCF70RN	STCF70
SCCPB-2-70CF	2				
SCCPB-3-70CF	3				
SCCPB-1-90CF	1	80-90	90	STCF80RN STCF90RN	STCF80 STCF90
SCCPB-2-90CF	2				
SCCPB-3-90CF	3				
SCCPB-1-100CF	1	100	100	STCF100RN	STCF100
SCCPB-2-100CF	2				
SCCPB-3-100CF	3				



- ① SCCPB disconnect can accept CUBEFuses® with amp ratings less than or equal to the amp rating of the SCCPB disconnect.
② Correct fit with SCCPB disconnect requires indicating CUBEFuses® with date code R38 or later.

Panelboards

Enclosure/System Types, AC & DC Voltages

NEMA 1

- Flush or surface mount.
- Galvanized steel with removable end walls—blank or with knockouts to order.
- Box sizes: 20" W x 5.75" D x 33", 50", 59" or 69" H (510 W x 145 D x 838, 1270, 1500 or 1753mm H). Box can be rotated 180° to accommodate conduit feed.
- Enclosure and chassis mounting instructions are found in supplied literature.
- Chassis mounts directly onto studs in the enclosure.
- Trim finished with gray powder coat paint over phosphatized steel (ANSI 61).
- Door and door-in-door configurations with locks.
- Door locks use key #2A1910-2.
- Circuit directory card is located on the inside of the door.
- Trim screws are concealed.

NEMA 3R


- Surface mount only.
- Finished with gray powder coat paint over phosphatized steel (ANSI 61).
- Bottom feed only, no knockouts
- Box sizes: 20" W x 7.7" D x 34.5", 51.5", 60.5" or 70.5" H (510 W x 195 D x 876, 1310, 1535 or 1791mm H).
- Enclosure and chassis mounting instructions are found in supplied literature
- Chassis mounts directly onto studs in the enclosure.
- Gasketed door has vault handle with lock.
- Door locks use key #2A1910-1.
- Circuit directory card is located on the inside of the door.

Busing


Tin-plated copper with sufficient cross section to meet UL 67 temperature rise requirements.

Distributed 1- & 3-phase busing

All SCCPB branch disconnects can be mounted in any branch circuit position.



Single-phase




Three-phase

AC Voltages


1 phase, 2 wire

- 120V 1 phase, 2 wire
- 240V 1 phase, 2 wire




1 phase, 3 wire

- 120/240V 1 phase, 3 wire




1 phase, 2 wire, Wye

- 277V 1 phase, 2 wire




1 phase, 2 wire, Delta

- 480V 1 phase, 2 wire




1 phase, 3 wire, Delta

- 240/480V 1 phase, 3 wire




3 phase, 4 wire, Wye

- 208Y/120V 3 phase, 4 wire
- 480Y/277V 3 phase, 4 wire
- 600Y/347V 3 phase, 4 wire




3 phase, 4 wire, Delta

- 240/120V 3 phase, 4 wire
- 480/240V 3 phase, 4 wire




3 phase, 3 wire, Delta

- 240V, 3 phase, 3 wire
- 480V, 3 phase, 3 wire
- 600V, 3 phase, 3 wire
- 240V, 3 phase, 3 wire, grounded B
- 480V, 3 phase, 3 wire, grounded B
- 600V, 3 phase, 3 wire, grounded B



1 phase, 3 wire, Wye

- 208Y/120V 1 phase, 3 wire
- 480Y/277V 1 phase, 3 wire




DC voltage

1 phase, 2 wire

- 125Vdc, 2 wire

(Up to 125Vdc, MLO option only, SCCPB 40A or less.)



Panelboards

Dimensions and Panelboard Configurations

NEMA 1 and 3R Enclosure Dimensions

Encl. Type	Encl. Height	Dimensions (inches)			CH	DH	RH	SH	DW	D
		H	HC	MH						
NEMA 1	33	33.0	N/A	29.0	26.0	28.9	25.0	2.0	20.0	5.7
	50	50.0	N/A	43.0	40.0	37.9	39.0	3.5	20.0	5.7
	59	59.0	N/A	52.0	49.0	46.9	48.0	3.5	20.0	5.7
	69	69.0	N/A	62.0	59.0	56.9	58.0	3.5	20.0	5.7
NEMA 3R	33	33.0	34.5	35.5	26.0	28.9	25.0	2.0	20.0	6.3
	50	50.0	51.5	52.5	40.0	37.9	39.0	2.0	20.0	6.3
	59	59.0	60.5	61.5	49.0	46.9	48.0	2.0	20.0	6.3
	69	69.0	70.5	71.5	59.0	56.9	58.0	2.0	20.0	6.3

Available panelboard configurations

Based on enclosure height, panel amp rating and number of branch circuit positions


Encl. height (inches)	Panel amp rating	Branch positions	Available configurations
33"	30–200	18	· Main lug only, with or without feed-through lugs · Non-fused disconnect, no loadside options
		30	· Main lug only, no loadside options
50"	30–60	18	· 30 through 60A fused main disconnect with or without feed-through lugs or TVSS device
		30	· 30 through 60A fused main disconnect with or without feed-through lugs or TVSS device
		42	· 30 through 60A fused main disconnect with or without feed-through lugs or TVSS device
	70–200	18	· 70 through 200A fused main disconnect with or without feed-through lugs or TVSS device
		30	· 70 through 200A fused disconnect with or without feed-through lugs
	30–200	18	· Main lug only with TVSS device · Non-fused disconnect, with feed-through lugs or TVSS device
		30	· Main lugs only, with feed-through lugs or TVSS device · Non-fused disconnect, with or without feed through lugs
		42	· Main lug only, with or without feed-through lugs or TVSS device · Non-fused disconnect, with or without feed-through lugs
	225–400A	18	· Main lug only, with ot without feed through lugs or TVSS device · Non-fused disconnect, with or without feed-through lugs
		30	· Main lug only, with or without feed-through lugs
59"	70–200	30	· 70 through 200A fused main disconnect, with TVSS device
		42	· 70 through 200A fused main disconnect with or without feed-through lugs or TVSS device
	30–200	42	· Non-fused disconnect with TVSS device
	225–400A	18	· Main lug only with loadside disconnect · Non-fused disconnect, with TVSS device · 225 through 400A fused disconnect with or without feed-through lugs or TVSS device
		30	· Main lug only, with TVSS device · 225 through 400A fused disconnect, with no loadside options
		42	· Main lug only, with or without feed-through lugs or TVSS device · Non-fused disconnect, with no loadside options
69"	225–400A	18	· Non-fused disconnect, with loadside disconnect
		30	· Main lug only with loadside disconnect · 225 through 400A fused disconnect with feed-through lugs or TVSS device
		42	· Non-fused disconnect, with or without feed through lugs or TVSS device · 225 through 400A fused main disconnect, with or without feed-through lugs or TVSS device

Panelboards


NEMA 1 and NEMA 3R

Dimensions

NEMA 1 Enclosures and Interior




NEMA 3R Enclosures Interior same as NEMA 1




Panelboards

Fuse Curves



Time-Current Characteristic Curves—Average Melt

Current Limitation Curves



Panelboards

Notes

11

PANELBOARDS