
SIEMENS

Data sheet US2:52PP2A2A



Head Cap Small 1.73" (44 mm) Metal, Anodized Red 2 Position Maintained, Pull-to-Release with 1 N.O. - 1 N.C. Heavy Duty Contacts, A600/P600 UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

30mm Command/52, Chrome Finish Heavy Duty, Watertight/Oiltight Complete Metal Unit Push-Pull Operator Non-Illuminated Mushroom

Enclosure		
Number of command points	1	
Delivery state		
● as a kit	No	
Actuator		
Material of the actuating element	metal	
Number of contact modules	1	
Type of unlocking device	pull-to-unlatch mechanism	
Number of switching positions	2	
Front ring		
Product component front ring	Yes	
Design of the front ring	standard	
Material of the front ring	metal	
General technical data		
Product function		
 positive opening 	Yes	

Figure similar

No	
600 V	
IP66	
IP20	
10 A	
	600 V IP66 IP20

Auxiliary circuit	
Number of NC contacts for auxiliary contacts	1
Number of NO contacts for auxiliary contacts	1
Operating current at AC-15	
• at 110 V rated value	60 A
● at 500 V rated value	12 A

Connections/ Terminals	
Type of electrical connection	screw-type terminals
Tightening torque of the screws in the bracket	20 N·m
Tightening torque [lbf·in]	
with screw-type terminals	8 lbf·in

Ambient conditions		
Ambient temperature		
during operation	-35 +70 °C	
during storage	-40 +85 °C	

Installation/ mounting/ dimensions	
Shape of the installation opening	round

Certificates/ approvals

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

www.siemens.com/sirius/catalogs

Industry Mall (Online ordering system)
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52PP2A2A

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52PP2A2A

Service&Support (Manuals, Certificates, Characteristics, FAQs,...) https://support.industry.siemens.com/cs/ww/en/ps/US2:52PP2A2A

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52PP2A2A&lang=en

11/13/2019 last modified: