

12" x 12" Ceiling Module Size	Neck Size (in.)	Neck Velocity (fpm)	400	500	600	700	800	900	1000	1200	1400	1600
	Velocity Pressure (in. w.g.)	0.010	0.016	0.022	0.031	0.040	0.051	0.062	0.090	0.090	0.122	0.160
6	Total Pressure (in. w.g.)	0.018	0.028	0.041	0.056	0.073	0.094	0.114	0.164	0.223	0.291	
	Air Flow (cfm)	78	98	118	137	157	176	196	235	274	314	
	Throw (ft.)	2-2-5	2-3-6	2-3-7	3-4-8	3-5-9	3-6-9	4-6-10	5-7-11	5-8-12	6-9-13	
	NC (dB)	--	--	--	--	18	25	28	32	37	42	
7	Total Pressure (in. w.g.)	0.020	0.031	0.045	0.062	0.081	0.104	0.126	0.181	0.247	0.322	
	Air Flow (cfm)	107	134	160	187	214	240	267	320	374	427	
	Throw (ft.)	2-3-5	2-3-7	3-4-8	3-5-9	4-5-10	4-6-11	4-7-12	5-8-13	6-9-14	7-10-15	
	NC (dB)	--	--	--	15	20	24	28	34	39	44	
8	Total Pressure (in. w.g.)	0.022	0.035	0.050	0.069	0.090	0.115	0.140	0.202	0.275	0.359	
	Air Flow (cfm)	140	175	209	244	279	314	349	419	489	558	
	Throw (ft.)	2-3-6	3-4-8	3-5-9	4-5-11	4-6-12	4-7-12	5-8-13	6-9-14	7-11-16	8-12-17	
	NC (dB)	--	--	--	18	22	25	29	36	41	46	
24" x 24" Ceiling Module Size	Neck Size (in.)	Neck Velocity (fpm)	400	500	600	700	800	900	1000	1200	1400	1600
	Velocity Pressure (in. w.g.)	0.010	0.016	0.022	0.031	0.040	0.051	0.062	0.090	0.122	0.160	
	Total Pressure (in. w.g.)	0.017	0.025	0.036	0.048	0.063	0.079	0.097	0.138	0.186	0.242	
	Air Flow (cfm)	78	98	117	137	157	176	196	235	274	314	
	Throw (ft.)	1-2-4	1-2-4	2-3-5	2-3-6	2-4-7	3-4-7	3-4-7	4-5-8	4-6-94	5-7-9	
	NC (dB)	--	--	--	--	16	19	22	28	32	36	
	Total Pressure (in. w.g.)	0.018	0.0270	0.039	0.052	0.068	0.085	0.105	0.149	0.202	0.263	
	Air Flow (cfm)	139	174	209	244	279	314	349	419	489	558	
	Throw (ft.)	2-2-5	2-3-6	2-4-7	3-4-8	3-5-9	4-6-9	4-6-10	5-7-11	6-8-12	7-9-12	
	NC (dB)	--	--	--	15	19	23	26	31	36	40	
	Total Pressure (in. w.g.)	0.021	0.032	0.046	0.062	0.081	0.101	0.125	0.178	0.241	0.314	
	Air Flow (cfm)	218	273	327	382	436	491	545	654	763	872	
	Throw (ft.)	2-3-6	3-4-8	3-5-9	4-6-10	4-6-11	5-7-12	5-8-12	6-9-13	8-10-14	9-11-15	
	NC (dB)	--	--	--	18	22	25	29	34	39	43	
	Total Pressure (in. w.g.)	0.025	0.038	0.053	0.072	0.094	0.118	0.145	0.208	0.282	0.367	
	Air Flow (cfm)	314	393	471	549	628	706	785	942	1099	1256	
	Throw (ft.)	3-4-8	3-5-10	4-6-11	5-7-12	5-8-13	6-9-14	7-10-15	8-11-16	9-12-17	11-13-19	
	NC (dB)	--	--	16	21	24	28	31	36	41	45	
	Total Pressure (in. w.g.)	0.028	0.043	0.061	0.082	0.107	0.134	0.165	0.236	0.321	0.418	
	Air Flow (cfm)	428	535	641	748	855	962	1069	1283	1497	1710	
	Throw (ft.)	3-5-10	4-6-12	5-7-13	6-9-14	6-10-15	7-11-16	8-12-17	10-13-19	11-14-20	12-15-22	
	NC (dB)	--	--	18	22	26	27	33	38	43	47	

- Throw data is given for isothermal conditions.
- Throw values are given for the terminal velocities of 150, 100 and 50 fpm.
- NC values are based on room absorption of 10dB re  $10^{-12}$  watts.
- Blanks “—” indicate NC value of less than 15dB.
- If the diffuser is mounted on exposed duct, the throw values are 70% of those listed in the table.
- To obtain static pressure, subtract the velocity pressure from the total pressure.