



A Division of SUPCO®



Thermostat Guide





Climate Technology Corporation (CTC) has been manufacturing thermostats for over 20 years. Specifically focused on the HVAC contractor's needs, we have produced reliable, high quality thermostats at a very competitive price.

We are proud to be in a position to offer three distinct product lines that continue to meet the changing needs of the HVAC marketplace.

I Our new, comprehensive line of thermostats offer three styles for the contractor to choose from:

- **Professional Series** thermostats are ideal for the contractor to install a high quality thermostat with basic functionality
- **Performance Series** thermostats provide a premier thermostat, adding functionality that suits the varying demands of end users
- **Ultimate Series** is a touchscreen thermostat providing the end user with any and all functions found in "top of the line" thermostats

II The 43000 Series thermostats are economically priced and manufactured for quality and reliability. These field proven thermostats include mechanical, digital and programmable thermostats for single stage, conventional systems.

- 43004A/43005A Mechanical Thermostats
- 43054 Digital Thermostat
- 43154 5/2 or 5/1/1 Programmable Thermostat



84210T
Ultimate Series Thermostat



43054
Digital Thermostat

Precise • Quality • Reliable • Innovative

PERFORMANCE SERIES

73200N

Non-Programmable Thermostat

Compatibility:

- Up to 3 Heat / 2 Cool Heat Pump Systems
Up to 2 Heat / 2 Cool Conventional Systems
- 24 VAC Gas, Oil or Electric Systems
- Millivolt
- Hot Water Gravity & Zoned
- Hot Water Motor Valves (3-wire)
- Hot Water Solenoid Valves (2-wire)
- Single Stage Heat Pumps
- Air / Ground / Hydronic Exchanger

Features:

- 3 Square Inch Display with Bright Blue Backlight
- Auto or Manual Changeover
- Adjustable Temperature Limits
- Indoor or Outdoor Remote Sensing
- User Selectable Service Monitors
- Separate User and Installer Reset Buttons
- Permanent Memory Retains Settings
- Adjustable Balance Points
- Auxiliary Heat Fossil Fuel Option
- Hardwire or Battery Powered
- Multi-Level Keypad Lockout
- Set Point Adjustment Limits
- Compressor Short Cycle Protection
- English / Spanish Packaging and Instruction Card

Accessories

- 6390 Remote Indoor Sensor
- 6490 Remote Outdoor Sensor



Actual Size

Specifications

Dimensions	3.86" x 5.11" x 1.42"
Electric Rating	24 Volt AC (18-30 Volt AC) 1 Amp Maximum Load per Terminal 5 Amp Total Maximum Load (All Terminals)
AC Power	18-30 Volt AC
DC Power	3.0 Volts DC (2 AA Alkaline Batteries Included)
Control Range	45°F to 90°F (7°C to 32°C)
Display Range	40°F to 99°F (5°C to 37°C)
Accuracy	+/-1°F (+/-0.5°C)
Storage Temperature	14°F to 140°F (-10°C to 60°C)
Operating Humidity	5% to 95% Relative Humidity
Terminations	G, Rc, Rh, W2, O/B/V3, Y1, Y2, W1/E/W3, C, L, S1, S2



Precise • Quality • Reliable • Innovative

ULTIMATE SERIES

84210T

5/2, 7 Day or Non-Programmable Touchscreen Thermostat

Compatibility:

- Up to 4 Heat / 2 Cool Heat Pump Systems
- Up to 3 Heat / 2 Cool Conventional Systems
- 24 VAC Gas, Oil or Electric Systems
- Millivolt
- Hot Water Gravity & Zoned
- Hot Water Solenoid Valves (2-wire)
- Air / Ground / Hydronic Exchanger

Features:

- 10 Square Inch Touchscreen Display with Bright Blue Backlight
- Residential or Commercial Modes
- Indoor or Outdoor Remote Sensing
- Auto or Manual Changeover
- Adjustable Compressor Protection
- Hardwire or Battery Powered
- Adjustable Temperature Limits
- Separate User and Installer Reset Buttons
- Auxiliary Heat Fossil Fuel Option
- Multi-Level Keypad Lockout
- Economizer Control
- Programmable Fan Mode
- English / Spanish Packaging and Instruction Card

Accessories

- 6390 Remote Indoor Sensor
- 6490 Remote Outdoor Sensor



Actual Size

Specifications

Dimensions	4.13" x 6.13" x 1.38"
Electric Rating	24 Volt AC (18-30 Volt AC) 1 Amp Maximum Load per Terminal 7 Amp Total Maximum Load (All Terminals)
AC Power	18-30 Volt AC
DC Power	3.0 Volts DC (2 AA Alkaline Batteries Included)
Control Range	45°F to 90°F (7°C to 32°C)
Display Range	40°F to 99°F (5°C to 37°C)
Accuracy	+/-1°F (+/- .5°C)
Storage Temperature	14°F to 140°F (-10°C to 60°C)
Operating Humidity	5% to 95% Relative Humidity
Terminations	A, G, Rc, Rh, W2/AUX2, W3/O/B, Y1, Y2, W1/E/AUX1, C, L, S1, S2

Precise • Quality • Reliable • Innovative

MORE THERMOSTAT CHOICES

43004A / 43005A

Mechanical Thermostat

All models offer our “quiet switching” design and require no additional sub-base for heating, cooling or heating/cooling installation. All deliver maximum performance at a value price. All mechanical thermostats have a 1 year warranty.

- **Heat / Cool**
- **For Use with Most 4 or 5 Wire 24 VAC Systems and Single-stage Heat Pumps**
- **Adjustable Heat Anticipator**
- **Mercury Free**
- **Terminations: RC, RH, W, Y, G, O, B**



43004A
Horizontal



43005A
Vertical

**Common Features/Compatibility for
43004A, 43005A, 43054 and 43154**

Features

- **Latching Relays for System Compatibility**
- **Soft Touch Keypad**
- **Low Battery Indicator**
- **Blue Back Light**
- **Easy, Front Load Battery Access**
- **2 AA Batteries Included**
- **°F/°C Selector**
- **3 Year Warranty**

Compatible With:

- **24 VAC Heat/Cool, Heat Only or Cool Only Systems**
- **Gas, Electric or Oil Systems**
- **Millivolt Systems**
- **2 Wire Hydronic Systems**

43054

Digital Thermostat

- **Non-Programmable**
- **Electronic Digital Accuracy**
- **Large, easy-to-read LCD**
- **Filter Change Indicator**
- **No Leveling Required**
- **Bi-Metal Freeze Protection**
- **Terminations: RC/O, RH/B, Y, W, G, R**



43154

5/2 or 5/1 Day Programmable Thermostat

- **For Conventional Heat / Cool or Single-Stage Systems**
- **Pre-Programmed**
- **4 Periods Per Day**
- **Adjustable Cycle Rate**
- **Easy “Front Load” Battery Access**
- **Mechanical Low Temperature Protection**
- **Filter Monitor**
- **Up-Opening Door**
- **Two-Stage Low Battery Warning with Fail Safe Protection**
- **Large, easy-to-read LCD**
- **Terminations: G, RC, RH, Y/O, WB, Y1**



Precise • Quality • Reliable • Innovative

GUARDS & ACCESSORIES

6390

Indoor Remote Sensor

- Simple 2-wire Installation
- Indoor Use Only
- Mounting Hardwire Included
- Accuracy +/- 1°F (+/- .5°C)
- Compatible with CTC Thermostats 71100N, 73200N, 71157P, 73257P, 84210T



6490

Outdoor Remote Sensor

- Simple 2-wire Installation
- Outdoor Use Only
- Mounting Hardwire Included
- Accuracy +/- 1°F (+/- .5°C)
- Compatible with CTC Thermostats 71100N, 73200N, 71157P, 73257P, 84210T



Thermostat Guards

PART NO.	DESCRIPTION
BTG-K	Clear Plastic
BTG-EK	Clear Plastic
BTG-RK	Clear Plastic
BTG-UK2	Clear Plastic
BTG-UN	Clear Plastic
BTG-UM	Metal
BTG-UWM	Metal
BTG-54VL	Metal
BTG-54VLW	Metal



BTG-UN

Magjumpers

- Powerful Magnets
- 20" Wire Length
- Max Voltage: 3VAC/VDC
- Max Current: 5 Amps



MAG1BL



MAG1RD



MAG1GR



MAG1BK



MAG1YL

Precise • Quality • Reliable • Innovative



Climate Technology Corp.
A Division of SUPCO®
PO Box 21, 2230 Landmark Place
Allenwood, NJ 08720 USA
www.supco.com