

# FORCED AIR DIESEL & KEROSENE

Model #	Description
F170250	HS50K 50,000 BTU/HR
F170275	HS75KT 75,000BTU/HR

## FEATURES:

- Heavy-Duty Construction - Illuminated On-Off Switch - 115 V 60Hz
- 25% Heavier Gauge Steel for Durability
- Motor 25% More Horsepower
- Flame Safety/Overheat Safety Shutoff
- Enclosed Motor - Fuel Gauge
- Continuous Ignition
- Cord Wrap (HS75KT only) - High Output Fan
- Larger "Glove-Friendly" Controls
- CSA Certified



## LARGE JOBSITES

Model #	Description
F170325	HS125KT 125,000 BTU/HR
F170375	HS175KT 175,000 BRU/HR
F170380	HS210KT 210,000 BTU/HR

## FEATURES:

- Heavy-Duty Construction - Illuminated On-Off Switch -115 V 60Hz
- 25% Heavier Gauge Steel for Durability
- Motor 25% More Horsepower
- Flame Safety/Overheat Safety Shutoff
- Enclosed Motor - Fuel Gauge - High Output Fan
- Continuous Ignition
- Large Heavy-Duty Handles w/cord wrap
- 10" Solid foam filled tires
- Larger "Glove-Friendly" Controls
- CSA Certified



Part #	HS50K	HS75KT	HS125KT	HS175KT	HS210KT
Model #	F170250	F170275	F170325	F170375	F170380
Output (BTU/HR)	50,000	75,000	125,000	175,000	210,000
Heating Area (SQ. FT.)	1,200	1,750	3,000	4,250	6,000
CFM Output	165	240	275	400	400
Fuel Consumption (GAL H/HR-L/HR)	.38/1.43	.56/2.11	.77/2.91	1.15/4.35	1.60/6.05
Tank Capacity (GAL-L)	4/15	6/22	14/52	14/52	14/52
Tires/Wheels	NA	NA	Solid Foam Filled	Solid Foam Filled	Solid Foam Filled
Operating Hours On Full Tank	11	11	15	10	8
Shipping Size	32" x 14" x 14.5"	32" x 14.25" x 17"	42" x 18" x 22"	42" x 18" x 22"	42" x 18" x 22"
Weight	43 lbs.	43 lbs.	74 lbs.	81 lbs.	87 lbs.
Multi-Fuel (No. 1 Or No. 2 Diesel Oil, Kerosene, JP-8 Or Jet A)	Yes	Yes	Yes	Yes	Yes

